FLOW MEASUREMENTS>>					Reviewers Initials	
AN-Code				**Date**		**WQ Sample ID**

Stream Discharge Measurement (Calculated In Cubic Feet Per Second – cfs)						
Measurer				**Time**		**Flow Meter ID**

IMPORTANT: The flow rod is calibrated for readings to be taken at 0.4 (60%) depth.
To set the flow rod to read at 0.2 depth, divide the depth by 2 and then set the rod to that value.
To set the flow rod to read at 0.8 depth, multiply the depth by 2 and then set the rod to that value.

Measurement	Location Description (e.g., LDB, RDB, EEF, Left Channel LDB, Left Channel EEF, Left Channel RDB)	Distance (ft)	Depth (ft)	Velocity (ft/s) at X distance from bottom (or % from top)			Measurement Notes
				0.2 (80%)	0.4 (60%)	0.8 (20%)	
1			0	0	0	0	
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							
25							
26							
27							
28							
29							
30							

Final Discharge Reading (cfs) =		

Do you think that this flow measurement is comparable?	☐Yes ☐No	**If Not, Why?**

U.S.G.S. Gage Name:		**U.S.G.S. Gage Number:**		**Gage Height or Control:**	

Reviewers Initials		ADDITIONAL MEASUREMENTS >>						
Measurement	**Location Description (e.g., LDB, RDB, EEF, Left Channel LDB, Left Channel EEF, Left Channel RDB)**	**Distance (ft)**	**Depth (ft)**	**Velocity (ft/s) at X distance from bottom (or % from top)**			**Measurement Notes**
				0.2 (80%)	**0.4 (60%)**	**0.8 (20%)**	
31							
32							
33							
34							
35							
36							
37							
38							
39							
40							
41							
42							
43							
44							
45							
46							
47							
48							
49							
50							
51							
52							
53							
54							
55							
56							
57							
58							
59							
60							

Additional Notes	