



---

west virginia department of environmental protection

---

**STATE OF WEST VIRGINIA  
DEPARTMENT OF ENVIRONMENTAL PROTECTION  
DIVISION OF WATER AND WASTE MANAGEMENT  
601 57th STREET SE  
CHARLESTON, WV 25304-2345  
GENERAL WATER POLLUTION CONTROL PERMIT**

Permit No. WV0116815

Issue Date: XXX XX, 2025  
Effective Date: XXX XX, 2025  
Expiration Date: XXX XX, 2030

Subject: Stormwater Associated with Oil and Gas related Construction Activities

To Whom It May Concern:

This is to certify that any discharge of stormwater runoff from oil and gas field construction activities or operations such as exploration, production, processing or treatment operations or transmission facilities, disturbing one acre or greater of land area are agreeing to be regulated under the terms and conditions of this General Water Pollution Control Permit (General Permit), except for;

1. Activities that result in the disturbance of less than one acre of total land area, Which are not part of a larger common plan of development;
2. Stormwater discharges associated with land disturbing activities that may reasonably be expected to be causing or contributing to a violation of a water quality standard as determined by the Director;
3. Activities occurring within the limit of disturbance authorized by an active permit or certification issued by the Department of Environmental Protection's Office of Oil and Gas (OOG).

is hereby granted coverage under this General Water Pollution Control Permit to allow stormwater discharges into the surface waters of the State. This General Permit is subject to the following terms and conditions:

Promoting a healthy environment.

There are two separate application forms, one is for between one to less than three acres, Notice of Intent (NOI) and the second is for Site Registration Application (SRA) form for projects that disturb three acres and greater.

Submittal of the application shall be made using the online Electronic Submission System. The information submitted with the registration application form will hereby be made terms and conditions of the General Permit with like effect as if all such information were set forth herein, and other pertinent terms and conditions set forth in Sections A, B, C, D, E, F, G, H, I and J.

Applicants authorized to discharge stormwater associated with oil and gas construction activities under the 2013 version of Permit WV0116815 shall be authorized to complete and/or modify such activities (*e.g.* SWPPP, GPP, Limits of Disturbance (LOD), Plan Sheets) under the terms and conditions of the 2013 Permit. This authorization, granted in order to allow for an efficient transition of existing projects to this Permit, will allow existing projects authorized under the 2013 Permit 180 days from the effective date of this permit to complete remaining authorized construction activities, and grants authorization to complete and/or modify activities (*e.g.* SWPPP, GPP, Limits of Disturbance) under the 2013 Permit terms and conditions, including final site stabilization and obtaining termination of the 2013 Permit terms and conditions.

All such work under the 2013 Permit terms and conditions is expected to be completed on or before 180 days from the effective date of this permit. Existing construction projects that will not be completed within the time allowed in the previous paragraphs must submit a new application to continue coverage under this newly issued permit within 90 days from the effective date of this permit.

Extension of coverage for projects with expired registrations under the General Permit. -

Projects whose registration under the General Permit has expired and have not yet achieved stabilization may be granted an extension of coverage for a period not exceeding one (1) year, upon written request by the facility. Such an extension shall only be considered if all land disturbance activities have been completed and the project requires additional time solely for the purpose of achieving final stabilization. Facilities granted an extension under this provision shall be permitted to conduct seeding, vegetative stabilization activities, and proper operation and maintenance of required BMPs. Any facility requesting an extension must submit a certification through the Electronic Submission System, demonstrating completion of land disturbance activities. The certification must include: a narrative explanation detailing the reasons permanent stabilization has not yet been achieved, photographic evidence of the affected areas; and an updated Progress Map clearly identifying the areas requiring stabilization.

Applications for extension shall be reviewed and approved on a case-by-case basis at the sole discretion of the Director.

### TABLE OF CONTENTS

SECTION A. TERMS OF PERMIT.....	4
SECTION B. SCHEDULE OF COMPLIANCE.....	4
SECTION C. MANAGEMENT CONDITIONS.....	4
C.1. Duty to Comply.....	4
C.2. Permit Continuance.....	4
C.3. Duty to Mitigate.....	5
C.4. Permit Actions.....	5
C.5. Property Rights.....	5
C.6. Signatory Requirements .....	5
C.7. Transferability.....	5
C.8. Duty to Provide Information. ....	5
C.9. Other Information.....	6
C.10. Inspections and Entry.....	6
C.11. Permit Modification.....	6
C.12. Water Quality .....	6
C.13. Liabilities.....	6
SECTION D. OPERATION AND MAINTENANCE .....	7
D.1. Proper Operation and Maintenance.....	7
D.2. Need to Halt or Reduce Activity Not a Defense.....	7
D.3. Bypass.....	7
D.4. Upset .....	8
D.5. Removed Substances.....	8
SECTION E. DEFINITIONS.....	9
SECTION F. MONITORING AND REPORTING.....	13
SECTION G. OTHER REQUIREMENTS.....	14
G.1. Requiring an Individual Permit.....	14
G.2. Prohibition of Non-Stormwater Discharges.....	14
G.3. Releases in Excess of Reportable Quantities.....	14
G.4. Stormwater Pollution Prevention Plans (SWPPP).....	14
G.5. Groundwater Protection Plans (GPP).....	15
SECTION H. REOPENER CLAUSE.....	26
SECTION I. GENERAL PERMIT REISSUANCE .....	26
SECTION J. SATISFACTORY STABILIZATION .....	26
DIRECTORS SIGNATURE PAGE.....	27

## SECTION A. TERMS OF PERMIT

Discharges covered under this General Permit shall not cause or contribute to a violation of the Legislative rules governing water quality or groundwater protection, namely Requirements Governing Water Quality Standards (47 C.S.R. 2) and Requirements Governing Groundwater Standards (47 C.S.R. 12), in accordance with W. Va. Code §§ 22- 11-8 and 22-12-4. For purposes of this General Permit, the West Virginia Water Pollution Control Act, W. Va. Code § 22-11-1, et seq., shall be referred to as the WPCA and the West Virginia Groundwater Protection Act, W. Va. Code § 22-12-1, et seq., shall be referred to as the GWPA. Discharges that are not in compliance with these standards are not authorized. Properly designed, installed / constructed, and maintained BMPs contained in this Permit are designed to protect water quality and the existing uses and designations by minimizing impacts to receiving waters. Full compliance with all BMPs shall be considered protective of and in compliance with water quality standards and groundwater quality standards

## SECTION B. SCHEDULE OF COMPLIANCE

Compliance with this General Permit and the approved Stormwater Pollution Prevention Plan (SWPPP) is required at the start of the construction project.

## SECTION C. MANAGEMENT CONDITIONS

### C.1. Duty to Comply.

The permittee must comply with all terms and conditions of this General Permit. Permit noncompliance constitutes a violation of the WPCA and/or the GWPA and is grounds for enforcement action; permit modification, suspension or revocation; or denial of a permit renewal application. See, W. Va. Code §§ 22-11-12, 22-11-22, 22-11-24, and 22-12-10.

### C.2. Permit Continuance

If this General Permit is not reissued or replaced prior to the expiration date it will be administratively continued in accordance with 47CSR10 and will remain in full force and effect. If a permittee were authorized to discharge under this General Permit prior to the expiration date, any discharges authorized under this permit will automatically remain covered by this General Permit until the earliest of these actions:

C.2.a. Authorization for coverage under a reissued General Permit or a replacement of this General Permit following submittal of a timely and complete application requesting authorization to discharge under a new General Permit; or a

C.2.b. Submittal of notification that the activity has ceased; or issuance or denial of an individual permit for the activities discharge; or

C.2.c. A formal permit decision by the DWWM not to reissue this General Permit, at which time the DWWM will identify a reasonable time for covered dischargers to seek coverage under an alternative General Permit or an individual permit. Coverage under this General Permit will then cease.

C.3. Duty to Mitigate

The permittee shall take all reasonable steps to minimize or prevent any discharge in violation of this permit, which has a reasonable likelihood of adversely affecting human health or the environment.

C.4. Permit Actions

This permit may be modified, revoked and reissued, suspended, or revoked for cause. The filing of a request by the permittee for permit modification, revocation and reissuance, or revocation, or a notification of a planned change or anticipated noncompliance, does not stay any permit condition.

C.5. Property Rights

This permit does not convey any property rights of any sort, or any exclusive privilege.

C.6. Signatory Requirements

All applications, reports or information submitted to the Director shall be signed and certified by an authorized representative as required by 47 C.S.R. 10 § 4.6. If an authorization becomes inaccurate because a different individual or position has responsibility for the overall operation of the project, a new authorization must be submitted to the Director prior to, or together with any reports, information, or applications to be signed by an authorized representative.

C.7. Transferability

The Director may require modification or revocation and reissuance of a permit registration to change the name of the permittee and incorporate such other requirements as may be necessary.

C.8. Duty to Provide Information

The permittee shall furnish to the Director, within a reasonably specified time, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, suspending, or revoking this permit, or to determine compliance with this permit. This information may include water quality information as specified by the Director. The permittee shall also furnish to the Director, upon request, copies of records required to be kept by this permit.

C.9. Other Information

Where the permittee becomes aware that it failed to submit any relevant facts in a permit application or submitted incorrect information in a permit application or in any report to the Director, it shall immediately submit such facts or information.

C.10. Inspections and Entry

The permittee shall allow the Director or designated representative upon the presentation of credentials and such other documents as may be required by law:

C.10.a. To enter upon the permittee's premises at all reasonable times in which a discharge or activity is located, or where records must be kept under the conditions of this permit;

C.10.b. To have access to and copy at reasonable times any records that must be kept under the conditions of this permit;

C.10.c. To inspect at reasonable times any activities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit;

C.10.d. To sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by the WPCA,

C.11. Modification

C.11.a. This permit may be modified, suspended, or revoked in whole or in part during its term in accordance with the provisions of W. Va. Code § 22-11-12 and 47 C.S.R. 10- 9. Any permittee wishing to modify coverage under this permit shall submit such a request at least 45 days prior to the commencement of the proposed action for modification if no public notice period is required. A modification that will have a public notice period must be submitted at least 90 days prior to construction to allow for the public notice procedure. Provided that upon approval of a request for modification by the Director, the permittee may immediately commence the proposed action.

C.11.b. Registrations covered under this General Permit may be modified, suspended, or revoked in whole or in part during its term in accordance with the provisions of W. Va. Code § 22-11-12 and 47 C.S.R. 10- 9. Any permittee wishing to modify coverage under this permit shall submit such a request at least 45 days prior to the commencement of the proposed action for modification if no public notice period is required. A modification that will have a public notice period must be submitted at least 90 days prior to construction to allow for the public notice procedure. Provided that upon approval of a request for modification by the Director, the permittee may immediately commence the proposed action.

C.12. Water Quality

The permittee shall protect water quality and the existing uses and designations of receiving waters by implementing erosion and sediment control BMPs. Properly designed, installed / constructed, and maintained BMPs contained in this Permit are designed to protect water quality and the existing uses and designations by minimizing impacts to receiving waters. Full compliance with all BMPs shall be considered protective of and in compliance with water quality standards and groundwater quality standards. The Director reserves authority to impose additional terms and conditions as necessary on a case-by-case basis upon demonstration that such terms and conditions are necessary to protect water quality and the existing uses and designations of receiving streams.

Compliance with the requirements of this Permit, including the use of appropriate BMPs (regular or enhanced) at construction sites, satisfies the antidegradation requirements of 47 CSR 2 and 60 CSR 5.

C.13. Liabilities.

C.13.a. Any person who violates a permit condition is subject to a civil penalty not to exceed \$25,000 per day of such violation as provided in W. Va. Code § 22-11-22. Any person who willfully or negligently violates permit conditions is subject to a fine of not less than \$2,500 nor more than \$25,000 per day of violation, or by imprisonment for not more than one year, or both, as provided in W. Va. Code § 22- 11-24.

C.13.b. Any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including reports of compliance or noncompliance shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by imprisonment for not more than six months per violation, or by both, in accordance with W. Va. Code § 22-11-24.

C.14 Outlet Markers. An outlet marker shall be posted during the term of General Permit coverage in accordance with the Special Rules of the DWWM, 47 C.S.R. 11 § 9.

SECTION D. OPERATION AND MAINTENANCE

D.1. Proper Operation and Maintenance

The permittee shall at all times properly operate and maintain all activities and systems of treatment and control which are installed or used by the permittee to achieve compliance with the terms and conditions of the permit.

D.2. Need to Halt or Reduce Activity Not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

D.3. Bypass

D.3.a. Definitions

D.3.a.1. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility; and

D.3.a.2. "Severe property damage" means substantial physical damage to property, damage to the treatment facility which causes them to become inoperable, or substantial and permanent loss of natural resources that can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.

D.3.b. Bypass not exceeding limitations. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of D.3.c. and D.3.d. of this permit.

D.3.c. Notification of bypass

D.3.c. 1. If the permittee knows in advance of the need for a bypass, it shall submit prior notice, if possible, at least 10 days before the date of the bypass.

D.3.c.2. If the permittee does not know in advance of the need for bypass, notice shall be submitted as required in F.2.a. of this permit.

D.3.d. Prohibition of bypass

D.3.d.1. Bypass is permitted only under the following conditions, and the Director may take enforcement action against a permittee for bypass, unless;

D.3.d.1.A. Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;

D.3.d.1.B. There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated sediment, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate backup equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass that occurred during normal periods of equipment downtime or preventive maintenance. This condition is not satisfied if the sediment and erosion control structures were not installed in the proper sequence; and



D.3.d.1.C. The permittee submitted notices as required under D.3.c. of this permit.

D.3.d.2. The Director may approve an anticipated bypass, after considering its adverse effects, if the Director determines that it will meet the three conditions listed in D.3.d.1. of this permit.

D.4. Upset

D.4.a. "Upset" means an exceptional incident in which there is unintentional and temporary noncompliance with the terms and conditions of the permit and the Stormwater Pollution Prevention Plan because of factors beyond the reasonable control of the permittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.

D.4.b. Effect of an upset. An upset constitutes an affirmative defense to an action brought for temporary noncompliance with the terms and conditions of the permit and the Stormwater Pollution Prevention Plan if the requirements of D.4.c. are met. No determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is final administrative action subject to judicial review.

D.4.c. Conditions necessary for a demonstration of upset. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:

D.4.c.1. An upset occurred and that the permittee can identify the cause(s) of the upset.

D.4.c.2. The permitted activity was at the time being properly operated.

D.4.c.3. The permittee submitted notice of the upset as required in F.2.a. of this permit.

D.4.c.4. The permittee complied with any remedial measures required under C.3. of this permit.

D.4.d. Burden of proof

In any enforcement proceedings the permittee seeking to establish the occurrence of an upset has the burden of proof.

D.5. Removed Substances

Occasionally incidents occur on construction sites that cause materials to be removed. Soil or stormwater affected by fuel spills or other substances may require special handling and disposal. Such handling and disposal shall be done in accordance with the requirements of the Solid Waste Management Rule, 33 C.S.R. 1.

Sediment removed from a trapping device or from waters of the State after deposition by stormwater runoff from a construction related activity shall be removed in a manner consistent with local, state and federal guidelines and placed upland behind appropriate controls in a manner that prevents erosion.

#### SECTION E. DEFINITIONS

"10-year, 24-hour precipitation" means the maximum 24-hour precipitation event with a probable recurrence interval of once in 10 years. Used for calculating sediment traps with drainage areas less than five acres, clean water, dirty water and access road drainage ditches.

"2-year, 24-hour precipitation" means the maximum 24-hour precipitation event with a probable recurrence interval of once in 2 years. Used for calculating access road culverts.

"25-year, 24-hour precipitation" means the maximum 24-hour precipitation event with a probable recurrence interval of once in 25 years. Used for calculating sediment basins with drainage areas greater than five acres and stream crossings.

"Access Road" means surface right-of-way for purposes of travel by land vehicles and/or equipment used in Construction activities. A road consists of the entire area within the right-of-way, including the roadbed, shoulders, parking and side areas, approaches, ditches, and other related structures.

"Application" is the form to be submitted to register a construction project that discharges to Waters of the State.

"ATV (All-Terrain Vehicle) Trails" refers to a trail the landowner deems desirable as a post-construction accessway to portions of the released site.

"Best management practices" (BMPs) means schedules of activities, prohibitions of practices, maintenance procedures, other management practices and various structural practices such as but not limited to silt fence, sediment traps, seeding and mulching, and riprap used to prevent or reduce erosion and sediment runoff and the pollution of surface waters of the State. BMPs also include treatment requirements, operating procedures and practices to control site runoff, spillage or leaks, sludge or waste disposal, or drainage from raw material storage.

"Buffer zone" means the region near the border of a protected area; a transition zone between areas managed for different objectives.

"Clearing" means cutting and removing vegetation with chain saws, brush axes, brush hogs and other mechanical means where there is little or no soil disturbance.

"Common plan of development" is a contiguous construction project where multiple separate and distinct construction activities may be taking place at different times on different schedules but under one plan. The "plan" is broadly defined as any announcement or piece of documentation or physical demarcation indicating construction activities may occur on a specific plot.

"Control" is a best management practice such as erosion control or sediment control that will reduce sedimentation on a construction project.

"Construction Activity" means land disturbance operations such as grubbing, grading, filling, and excavating during site development for residential, commercial or industrial purposes. This includes, but is not limited to, access roads, borrow and spoil areas and equipment lay down or staging areas where such land disturbance activity will take place.

"Director" means the Director of the Division of Water and Waste Management, Department of Environmental Protection, or his or her designated representative.

"Disturbed area" is the total area of land disturbing activity that will take place during all phases of a construction project, including, but not limited to, waste and borrow sites, equipment lay down or staging areas where such land disturbance activity will take place, utility installation, road building, mass grading, and site development.

"Diversion" means a berm or excavated channel, or combination berm and channel constructed across sloping land on a predetermined grade. This includes but is not limited to protecting work areas from upslope runoff and reducing the size of the drainage going to sediment trapping structures (clean water diversion), transporting runoff across a project to minimize erosion and diverting sediment-laden water to an appropriate sediment-trapping structure.

"Erosion" means the displacement of solids (soil, mud, rock, and other particles) by the agents of wind, water, and ice in response to gravity.

"Establishment" means an industrial establishment, mill, factory, tannery, paper and pulp mill, mine, colliery, breaker or mineral processing operation, quarry, refinery, well and each and every industry or plant or works in the operation or process of which industrial wastes, sewage or other wastes are produced.

"Estimate" means to be based on a technical evaluation of the sources contributing to the discharge.

"Excavating" means large scale grading accomplished usually with heavy machinery.

"Final stabilization" means disturbed areas shall be covered by permanent protection. Final stabilization includes pavement, buildings, stable waterways (riprap, concrete, grass or pipe), a healthy, vigorous stand of perennial grass that uniformly covers at least 70 percent of the ground,

stable outlet channels with velocity dissipation that directs site runoff to a natural watercourse, and any other approved structure or material.

"Grading" means changing surface contours by removing soil and stone from one place and building it up in another.

"Groundwater" means the water occurring in the zone of saturation beneath the seasonal high-water table or any perched water zones.

"Groundwater Protection Plan" (GPP) means groundwater protection practices developed and implemented in accordance with the Groundwater Protection Rule, 47 C.S.R. 58.

"Grubbing" means physically removing vegetative stumps and roots from the ground and disturbing the earth, usually by heavy machinery.

"Karst" means a type of topography formed over limestone, dolomite, or gypsum resulting in dissolving or solution of the underlying calcareous rock.

"Notice of Intent" (NOI) is the form to be submitted by the applicant to register a minor construction project (one that disturbs one to less than three acres) under the General Water Pollution Control Permit for Stormwater Associated with Oil and Gas related Construction Activities.

"Notice of Termination" (NOT) is the form to be submitted by the permittee to terminate coverage under the General Water Pollution Control Permit, after final stabilization has been completed. See Final Stabilization.

"Permanent detention/retention facility" means: Detention- The process of reducing offsite stormwater discharge rates by temporarily holding the water in a storage basin and then releasing it slowly over a period of time. The objective of a detention facility is to regulate the runoff from a given rainfall event and to control discharge rates to reduce the impact on downstream stormwater systems. Retention- The prevention of stormwater runoff from being discharged into receiving waters by storing it in a storage area. Water is retained and stored until it is lost through percolation, removed by evapotranspiration by plants, or through evaporation from the free water surface. Retention systems are designed to not have any offsite discharges.

"Point source" is any discernible, confined and discrete conveyance, including but not limited to, any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, and container from which pollutants are or may be discharged to surface waters of the state.

"Pollutant" means industrial waste, sewage or other wastes.

"Post-development" means the anticipated final conditions of the project, including rooftops, parking lots, streets, drainage systems, vegetation, and any other structure planned.

"Pre-development" means the condition of the land, the amount and health of the ground cover and vegetation prior to development.

"Qualified Person" means a person who is knowledgeable in the principles and practices of sediment and erosion controls, pollution prevention, and possesses the education and/or experience and abilities to assess conditions at the proposed site that could impact stormwater quality and to assess the effectiveness of proposed stormwater controls to meet the requirements of this permit.

"Sediment" means any particulate matter that can be transported by fluid flow, and which eventually is deposited as a layer of solid particles on the bed or bottom of a body of water or other liquid.

"Sedimentation" means the deposition by settling of a suspended material.

"Sediment trap" means a temporary ponding area formed by constructing an embankment or excavation and embankment that will trap the flow of sediment-laden runoff. Sediment traps have a properly stabilized outlet/weir or riser and pipe to detain sediment-laden runoff from small, disturbed areas of five acres or less. Outlets must be designed to extend the detention time and allow the majority of the sediment to settle out.

"Sediment basin" means a temporary structure consisting of an earthen embankment, or embankment and excavated area, located in a suitable area to capture sediment-laden runoff detention (48 to 72 hours) to settle out the majority of the suspended solids and sediment and prevent sedimentation in waterways, culverts, streams and rivers. Sediment basins have both wet and dry storage space to enhance the trapping efficiency and are appropriate in drainage areas of five acres and greater.

"Sinkhole" means a depression in the land surface formed by solution or collapse that directs surface runoff into subsurface or to an underground drainage flow.

"Site Registration Application forms" means the forms designed by the Director for the purpose of registering for coverage under a general permit. Under the General Water Pollution Control Permit for Stormwater Associated with Oil and Gas related Construction Activities there will be two separate forms, one for one to less than three acres (Notice of Intent) and the Site Registration Application form for projects that disturb three acres and greater. -

"Stormwater" means stormwater runoff, snowmelt runoff, and surface runoff and drainage.

"Stormwater management facilities" means structures such as ponds, basins, outlets, ditches, velocity dissipaters, infiltration trenches and basins, extended detention basins and ponds, and any other structure used to control the quality and quantity of stormwater from a development project.

"Stormwater Pollution Prevention Plan" (SWPPP) means the erosion and sediment control plan and the post development plan submitted as part of the Site Registration Application form.

"Tier 3 Waters" means waters that meet the definition of "outstanding national resource waters" as that term is defined at 47 C.S.R. 2 § 2.10 and discussed at 47 C.S.R. 2 § 4.1.c.

"Trout Streams" means any waters which meet the definition of "trout waters" as that term is defined at 47 C.S.R. 2 § 2.19.

#### SECTION F. MONITORING AND REPORTING

Monitoring of discharges is not required for construction activities unless directed by the Director.

##### F.1. Reporting Spill and Accidental Discharges.

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to the Special Rules of the DWWM regarding reporting spills and accidental discharges as set forth at 47 C.S.R. 11 § 2.

##### F.2. Immediate Reporting

F.2.a. The permittee shall report any spill or release of pollutants to waters of the state which may endanger health or the environment immediately after becoming aware of the circumstances by using the Department's designated spill alert telephone number ((800) 642-3074). A written submission shall be provided within five days of the time the permittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause; the period of noncompliance, including exact dates and time, and if, the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.

#### SECTION G. OTHER REQUIREMENTS

##### G.1. Requiring an Individual Permit

The Director may require any person otherwise eligible for this permit to apply for and obtain an Individual Permit in the event that the proposed project will involve land disturbance across a very significant area or other unique impacts that the Director determines require the imposition of special conditions beyond those contained in this General Permit. Any interested person may petition the Director to take action under this paragraph. The Director may require any owner or operator authorized by this permit to apply for an Individual Permit only if the owner or operator has been notified in writing that such a permit application is required.

##### G.2. Prohibition of Non-Stormwater Discharges

All discharges authorized by this General Permit shall be composed entirely of stormwater, except as follows:

discharges from emergency firefighting activities, fire hydrant flushing; waters used to wash vehicles, provided there is no discharge of soaps, solvents, or detergents used for that purpose; waters used to control dust; potable water sources, including uncontaminated waterline flushing; landscape irrigation; lawn watering; routine external building washdown which does not use detergents; pavement wash water provided spills or leaks of toxic or hazardous materials have not occurred (unless all spilled material has been removed) and where detergents are not used, provided that such pavement wash waters may not be discharged directly into any surface water, storm drain inlet, or stormwater conveyance, unless the conveyance is connected to a sediment basin, sediment trap, or similarly effective control; uncontaminated air conditioning condensate; uncontaminated, non-turbid discharges of groundwater or springs; foundation or footing drains where flows are not contaminated with process materials such as solvents that are combined with stormwater discharges associated with industrial activity; and other construction dewatering activities that are treated by an appropriate control.

This permit does not authorize the conveyance, diversion, channeling, directing or otherwise allowing the discharge of stormwater into a sinkhole without an Underground Injection Control Permit.

G.3. Releases in Excess of Reportable Quantities.

This permit does not relieve the permittee of the reporting requirements of 40 C.F.R. Part 117, Determination of Reportable Quantities for Hazardous Substances, or 40 C.F.R. Part 302, Designation, Reportable Quantities, and Notification. The discharge of hazardous substances in the stormwater discharge(s) from a project is not authorized by this General Permit, and in no case shall the discharge(s) contain a hazardous substance equal to or in excess of reporting quantities.

G.4. Stormwater Pollution Prevention Plans and Groundwater Protection Plans (SWPPP/GPP)

Stormwater Pollution Prevention Plans (SWPPP) shall be prepared in accordance with good engineering practices. The SWPPP shall identify all pollutants and potential sources of pollution that may reasonably be expected to affect the quality of stormwater discharges associated with construction activity. In addition, the SWPPP shall describe and ensure the implementation of practices that are to be used to reduce the pollutants in stormwater discharges associated with construction activity and to assure compliance with the terms and conditions of this permit. The SWPPP shall be prepared by a Qualified Person.

Groundwater Protection Plans (GPP) shall be prepared in accordance with the requirements of the Groundwater Protection Rule, 47 C.S.R. 58 § 4.11. The GPP shall

identify all operations that may reasonably be expected to contaminate the groundwater resources with an indication of the potential for soil and groundwater contamination from those operations. In addition, the GPP shall provide a thorough and detailed description of procedures designed to protect groundwater from the identified potential contamination sources. The GPP is not required to be submitted to the Division of Water and Waste Management for review. Guidance in the completion of a GPP is available from the Division of Water and Waste Management.

G.4.a. The SWPPP and the GPP shall be signed in accordance with Section C.6. and available onsite.

G.4.b. The application and SWPPP shall be submitted to the Division of Water and Waste Management at least 45 days before construction activity is to begin, except as noted in G.4.b.3. and G.4.b.4. As the plans are evaluated by the Director or designated representative, the Director or designated representative may notify the permittee during the 45-day review period that the plan does not meet one or more of the minimum requirements of this section. After such notification from the Director or designated representative, the permittee shall make changes to the plan in accordance with the time frames established below and shall submit to the Director a written certification that the requested changes have been made.

G.4.b.1. Except as provided in G.4.b.2., the permittee shall have 30 days after such notification to make the changes necessary.

G.4.b.2. The permittee shall have 24 hours after such notification to make changes relating to sediment and erosion controls to prevent loss of sediment from an active construction site, unless additional time is provided by the Director or an designated representative.

G.4.b.3. Projects disturbing one to less than three acres that do not discharge to or upstream of Tier 3 Waters shall submit only the Notice of Intent (NOI) Form and detailed site map 10 days prior to initiating construction. Projects disturbing one to less than three acres that discharge upstream of a Tier 3 Water shall submit the NOI Form, site plan, and Storm Water Pollution Prevention Plan (SWPPP) at least 45 days prior to initiating construction.

G.4.b.4. Projects that will discharge to Tier 3 waters or that will disturb 100 or more acres, shall submit the application and SWPPP at least 90 days prior to construction to allow for the public notice procedure.

G.4.b.5. Within 72 hours of receiving the permit registration number, the applicant shall display a sign for the duration of the construction project near the entrance of the project or, for linear projects, at a location near an active part of the project that is accessible by the public, containing the following information:

- The applicant's name and emergency telephone number;



- Project Reference ID;
- For info on this stormwater permit Call: 800-654-5227 or [DEP.  
Comments@wv.gov](mailto:Comments@wv.gov);
- Permit Registration Number.

The sign shall be a minimum of two feet by two feet and at least three feet above ground level, clearly visible and legible from a public roadway or right-of-way. If it is not feasible to display a sign at or near the project, the registrant, with prior approval from the DWWM, may post a notice containing the foregoing information at a local public building, including, but not limited to, a town hall or public library.

G.4.c. The permittee shall modify, using forms provided by DWWM, the SWPPP whenever there is a change in design, construction, scope of operation, or maintenance, which has the potential to adversely impact the surface waters of the State, or if the SWPPP proves to be ineffective in achieving the general objectives of controlling pollutants in stormwater discharges associated with construction activities. Should conditions warrant, the Director, or the Director's representative, may request changes to the SWPPP during a field inspection. The Director may review changes or modifications to the SWPPP in the same manner as above.

The permittee shall amend the GPP whenever there is a change in design, construction, operation, or maintenance which could reasonably be expected to have an impact on the potential contamination of groundwater.

G.4.d. In addition to the requirements of G.4.e, the SWPPP shall also include, at a minimum, the following items:

G.4.d.1. General management controls

G.4.d.1.A. Preventive maintenance

A preventive maintenance program shall involve inspection and maintenance of sediment and erosion control best management practices to identify and address conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters.

G.4.d.1.B. Good housekeeping

Good housekeeping requires the maintenance of a clean and orderly project.

G.4.d.1.C. Spill prevention and response procedures

Promoting a healthy environment.

Areas where potential spills may occur, and their accompanying drainage points, shall be identified clearly in the SWPPP/GPP. Where appropriate, specify material handling procedures and storage requirements in the SWPPP/GPP. Procedures for cleaning up spills shall be identified in the plan and made available to the appropriate personnel. The necessary equipment to implement a cleanup shall be available to personnel, including spill kits.

#### G.4.d.2. Consistency with other plans

Stormwater Pollution Prevention Plans may reflect requirements for Spill Prevention Control and Countermeasure (SPCC) plans or any BMPs or GPPs implemented in accordance with the Groundwater Protection Rule, 47 C.S.R. 58 and may incorporate any part of such plans into the SWPPP by reference.

#### G.4.e. Requirements for construction activities

Construction activity disturbing one or more acres that discharge stormwater are not only subject to the requirements of Section G.4.d. of this permit but are also subject to the following requirements. The SWPPP shall include, at a minimum, the following items.

##### G.4.e. 1. Site description

Each plan shall, at a minimum, provide a description of the following:

G.4.e. 1.A. A description of the nature of the construction activity, including a proposed timetable for major activities;

G.4.e. 1.B. Estimates of the following: total area of the site, the part of the site that is expected to undergo excavation or grading, and the total amount of excavation by cut and fill;

G.4.e.1.C. Site maps indicating the Limits of areas to be Disturbed (LOD), with a minimum of five-foot contours, drainage patterns and slopes prior to construction and anticipated conditions after grading activities, topsoil stockpiles, waste areas, borrow sites, locations of sediment control structures identified in the narrative, the location of impervious areas after construction is complete, final stormwater routing including all ditches and pipe systems, property boundaries and easements, nearest receiving stream, access roads, legend and springs, surface waters and any other information necessary to describe the project in detail.

G.4.e.1.D. A description and detail of the proposed construction entrance(s). Each site shall have stone access entrance and exit drives and parking areas to reduce the tracking of sediment onto public or private roads. Except for haul roads, all unpaved roads on the site carrying more than 25 vehicles per day shall be graveled.

#### G.4.e.1.E. Access Roads

Maintenance activities for access roads as outlined in 47 CSR 10 Section 2.8. do not meet the definition of "Construction Activities."

Each newly constructed access road or upgraded existing access road (outside of routine maintenance activities; such as, ditch and culvert cleaning and activities to maintain the original line and grade of the road) whose drainage is not directed to a sediment basin or trap shall be designed with the following specifications:

- A ditch shall be provided for hillside runoff;
- Ditch lines shall be capable of passing a 10-year, 24-hour precipitation event;
- Culverts shall be capable of passing a 2-year, 24-hour precipitation event and shall have a minimum of one foot of cover or one half the diameter of the pipe, whichever is greater;;
- Culverts or water bars with appropriate spacing of  $400/\%grade + 75'$ ;
- All unpaved roads on the site shall have a durable surface;
- Culvert / water bar outlets protected by appropriate erosion controls;
- Sediment control provided by sumps or equivalent controls;

Alternative design criteria for access road drainage may be used if approved by the Director.

G.4.e.1.F. The project LOD shall be illustrated in an ArcGIS Shapefile (.shp).

G.4.e.1.G. The application for registration shall identify existing All-Terrain Vehicle (ATV) trails to be retained by the landowner upon termination of the permit registration. ATV trails that are not shown with the original application may be identified through a minor modification to the registration. ATV trails shall be maintained by the applicant and stabilized upon conclusion of construction when not identified in the registration as a landowner accepted trail.

#### G.4.e.2. Controls

Each construction activity covered by this permit shall develop a description of controls appropriate for the project and implement such controls. These controls shall be in place and functional prior to land disturbance. For registrations proposed to be completed in multiple phases, controls for each phase must be constructed and functional prior to land disturbance beginning in that phase. Erosion and sediment control BMPs shall be implemented in accordance with standard procedures set forth in the BMP Manual, however, other BMPs may be used if equally protective of water quality. The description of these controls shall address the following minimum components, including a schedule for implementing such controls.

##### G.4.e.2. A. Erosion and sediment controls

###### G.4.e.2.A.i. Vegetative practices

A description of interim and permanent stabilization practices, including site specific implementation schedules of the practices shall be provided. Site plans should ensure that existing vegetation is preserved where attainable and that disturbed portions of the site are stabilized as rapidly as possible. Stabilization practices may include temporary seeding, permanent seeding, mulching, geotextiles, sod stabilization, vegetative buffer strips, protection of trees, preservation of mature vegetation, and other appropriate measures. Also include in the plan seedbed preparation requirements and the type and amount of soil amendments necessary to establish a healthy stand of vegetation. A record of the dates when major grading activities will occur, and when construction activities temporarily or permanently cease on a portion of the site, and when stabilization measures will be initiated shall be included in the plan.

Except as noted below, stabilization measures shall be initiated as soon as practicable in portions of the site where construction activities have temporarily or permanently ceased, but in no case more than seven days after the construction activity in that portion of the site has permanently ceased.

G.4.e.2.A.i.a. Where the initiation of stabilization measures by the seventh day after construction activity temporarily or permanently ceases is precluded by natural causes,

stabilization measures shall be initiated as soon as conditions allow.

G.4.e.2.A.i.b. Where construction activity will resume on a portion of the site within 21 days from when activities ceased, (e.g., the total time period that construction activity is temporarily halted is less than 21 days) then stabilization measures do not have to be initiated on that portion of the site by the seventh day after construction activities have temporarily ceased.

G.4.e.2.A.i.c. Areas where the seed has failed to germinate adequately (uniform perennial vegetative cover with a density of 70%) within 30 days after seeding and mulching must be reseeded immediately, or as soon as weather conditions allow.

G.4.e.2.A.i.d. Clean water diversions must be stabilized prior to becoming functional and shall be capable of passing the peak discharge of a 10-year, 24-hour precipitation event.

#### G.4. e.2.A. ii. Structural practices

A description of the structural practices to be used to divert flows around exposed soils, store flows or otherwise limit runoff from exposed areas and eliminate sediment-laden runoff from the site. Such practices may include but are not limited to: earthen berms, land grading, diversions, drainage swales, check dams, subsurface drains, pipe slope drains, storm drain inlet protection, rock outlet protection, reinforced soil retention systems and geotextiles, gabions and riprap, and permanent and temporary sediment traps/basins.

G.4.e.2.A.ii.a. For locations on a site that have a drainage area of five acres or less, a sediment trap which provides a storage volume equal to 3,600 cubic feet per acre of drainage area shall be installed. Half of the volume of the trap will be in a permanent pool and half will be dry storage.

G.4.e.2.A.ii.b. For drainage areas of greater than five acres, a sediment basin providing 3,600 cubic feet per drainage acre shall be installed. Half of the volume of the basin shall be in a permanent pool and half shall be dry storage.

Sediment basins must be able to dewater the dry storage volume in 48 to 72 hours. A sediment basin must be able to pass through the spillway(s) a 25-year, 24-hour storm event, and still maintain at least one foot of freeboard.

G.4.e.2.A.ii.c. The inlet(s) and outlet(s) for a sediment trapping structure must be protected against erosion by appropriate material such as riprap or other similar media.

G.4.e.2.A.ii.d. If necessary, diversions will be used to direct runoff to the trapping structure. Diversions may need to be stabilized prior to becoming functional.

G.4.e.2.A.ii.e. For locations served by a common drainage where a detention basin providing 3,600 cubic feet of storage is not attainable, additional sediment and erosion controls within the project area are required in lieu of the required sized sediment basin. Justification and a narrative description of the additional measures proposed must be provided for use of any practice(s) other than sediment basins or traps.

G.4.e.2.A.ii.f. Fill slopes must be protected by measures used to divert runoff away from fill slopes to conveyance measures such as pipe slope drains or stable channels.

G.4.e.2.A.ii.g. Sediment trapping structures will be eliminated, and the area properly reclaimed and stabilized when the contributing drainage area is stabilized and the structures are no longer needed, unless the structure is converted into a permanent stormwater detention/retention structure.

G.4.e.2.A.ii.h. All trapped sediments will be disposed of in an upland area where there is no chance of entering nearby streams.

G.4.e.2.A.ii.i. Breaching the embankment to dewater the structure is not permitted. Dewatering and structure removal shall not cause a violation of water quality standards. Provide a description of the procedures that will be used in removing these structures and the time frame.

G.4.e.2.A.ii.j. No sediment-laden water will be allowed to leave the site without going through an appropriate best management practice.

G.4.e.2.A.ii.k. Hay or straw bales are not acceptable stand-alone BMPs; however, use of hay or straw bales may be used in certain BMP dewatering applications as long as they do not promote erosion.

G.4.e.2.A.iii. Presumptive conditions for discharges to Tier 3 waters

Construction activities discharging upstream or to Tier 3 waters will go through the Tier 3.0 anti-degradation review process.

G.4.e.2.B. Stormwater management plan

Projects located in areas that have local government requirements and/or criteria for post development stormwater management must meet those requirements and/or criteria. Compliance with this General Permit does not assure compliance with local codes, regulations, or ordinances. A description of measures that will be installed during construction to control pollutants in stormwater discharges after the project is completed shall be included in the SWPPP.

The permittee shall submit all calculations, watershed mapping, design drawings, and any other information necessary to explain the technical basis for the stormwater management plan. Since development site conditions vary widely, plan preparers will have significant latitude in designing practices to comply with this provision of the permit. However, design procedures shall follow professionally accepted engineering and hydrologic methodologies. Permanent stormwater management structures that will impound water (detention/retention basins or similar structures) shall be designed and certified by a registered professional engineer.

G.4.e.2.C Other controls

G.4.e.2.C.i. All solid waste and construction/demolition material must be disposed of in accordance with the Code of West Virginia and Legislative Rule Title 33 Series 1, (Solid Waste Management Rule).

G.4. e.2.C. ii. Provisions must be made to control fugitive dust.

G.4.e.2.C.iii. Groundwater Protection Plan (GPP) The applicant shall prepare a GPP that will satisfy the requirements of the Groundwater Protection Rule, 47 C.S.R. 58 § 4.11.

G.4. e.2.C. iv. Employee training

Promoting a healthy environment.

Employee training programs shall inform personnel at all levels of responsibility of the components and goals of the SWPPP. Training should address topics such as spill response, good housekeeping and routine inspection. Training shall be on a quarterly basis while construction activities are occurring, and records of the training shall be available on site for review by the Director or designated representative.

#### G.4.e.2.C.v. Visual inspection

A Qualified Person shall be identified to inspect as set forth under G.4.e.2.D. A tracking procedure shall be used to ensure that adequate corrective actions have been taken in response to deficiencies identified during an inspection. Records of inspections shall be available onsite for review by the Director or designated representative.

#### G.4.e.2.C.vi. Recordkeeping and internal reporting procedures

Incidents such as spills, leaks and improper dumping, along with other information describing the quality and quantity of stormwater discharges should be included in the records. Record keeping of quality and quantity of stormwater discharges may be accomplished through documentation of visual observations of stormwater discharges and best management practice installation. Inspection and maintenance records must be available onsite for review by the Director or designated representative.

#### G.4.e.2.C.vii. Slip Prevention Control Procedures

Provide a description of BMPs including water management and passive bleeder drains to prevent soil saturation and protect slopes from slips of slopes 3:1 or greater during pipeline placement.

Surface runoff, seeps, and springs that can percolate into the soil strata during and after pipeline trenching.

#### G.4.e.2.D Maintenance

The permittee shall ensure that all newly installed erosion and sediment control BMPs are inspected by a Qualified Person. A description of procedures to maintain in good and effective condition and promptly repair or restore all grade surfaces, walls, dams and structures, vegetation, erosion and sediment control measures and other protective devices identified in the site plan. At a minimum, procedures in the site plan shall provide that all erosion and sediment controls on the site are inspected at least once every seven calendar days for actively disturbed areas, 14



calendar days for restored areas and within 24 hours after any storm event of greater than 0.5 inches of rain per 24- hour period. To determine if a precipitation event of 0.5 inches or greater has occurred on the site, the permittee must either:

- Keep a properly maintained rain gauge on-site,
- Obtain the precipitation event information from a NOAA weather station that is representative of the location, or
- Utilize another equivalent weather tracking program / system.

G.4.e.2.D.i. All public and private roads adjacent to a construction entrance must be inspected and cleaned of debris originating from the construction site as necessary.

G.4.f. All SWPPPs and GPPs required under this permit are considered reports that shall be available to the public under Section 308(b) of the CWA. The owner or operator of a project with stormwater discharges covered by this permit shall make plans available for review to members of the public upon request. However, the permittee may claim any portion of a SWPPP or GPP as confidential in accordance with 47 CSR 10-12.7. (NPDES Program).

G.4.g Compliance with other laws and statutes

Nothing in this General Permit shall be construed as excusing the permittee from compliance with any applicable federal, state, or local statutes, ordinances, or regulations.

G.4.h Emergency Procedures

When conducting earth-disturbing activities in response to a public emergency (e.g., natural disaster, widespread disruption in essential public services), and the related work requires immediate authorization to avoid imminent endangerment to human health, public safety, or the environment, or to reestablish essential public services, authorization to discharge is conditioned that a complete and accurate application is submitted within 30 calendar days after commencing earth-disturbing activities establishing eligibility under this permit.

G.5. Discharges to Waters with Approved TMDLs

Dischargers located in a watershed area where a Total Maximum Daily Load (TMDL) has been developed and approved may be required to implement additional BMP's as necessary to comply with an applicable waste load allocation.

## SECTION H. REOPENER CLAUSE

If there is evidence indicating reasonable potential or realized impacts on water quality due to any stormwater discharge authorized by this General Permit, the owner or operator of such discharge may be required to obtain an individual permit in accordance with Section G.1. of this permit, or the permit may be modified to include different limitations and/or requirements.

#### SECTION I. GENERAL PERMIT REISSUANCE

The conditions, standards, and limitations of this General Permit will be reviewed at the time of reissuance for possible revisions that may lead to more or less stringent conditions, standards, and limitations.

#### SECTION J. SATISFACTORY STABILIZATION

From the date final stabilization is achieved, the permittee has 30 days to ready the site for submittal of N.O.T and by the 30th day must submit the N.O.T. via electronic notice of termination to the Director. An inspection by a Qualified Person shall be conducted wherein all areas of the project and all off-site areas impacted by the project are inspected for compliance with this permit. The Qualified Person shall conduct a review of the available records to verify compliance with the retention requirements of this permit. The Qualified Person shall issue a report to the permittee outlining any deficiencies to be corrected. The permittee shall correct deficiencies promptly and request a re-inspection by the Qualified Person. Once an inspection identifies no deficiencies, the site may be considered ready for the submittal of the N.O.T. The permittee shall review the fee payment history and pay any unpaid fees during this 30-day period.

After meeting the requirements of the preceding paragraph, the permittee shall apply for termination of permit coverage by submitting an N.O.T., which will serve as a request for final inspection. Upon receipt of the N.O.T., the Director shall inspect the site to determine the appropriateness of ending permit coverage. Final stabilization inspections for 1 to < 3 acres sites shall be conducted within 30 days of receipt of the N.O.T. and for sites 3 acres and larger the final stabilization inspection shall be conducted within 60 days. The permittee has the option of submitting a certification by a registered professional engineer or professional surveyor that the site meets stabilization requirements. Should the Director not inspect within the time frames established in this section, the Stabilization Certificate shall be accepted in lieu of the final inspection by the Director's Staff.

ATV trails accepted by the landowner and identified in the registration, do not require a healthy, vigorous stand of grass or native vegetation that uniformly covers more than 70 percent of the ground in the vehicle lanes of the trail to be considered for termination. No eroded areas of trails that are the source of sediment in stormwater runoff may be deemed stable or eligible for release. A registration modification must be approved by the Director prior to submittal of the Notice of Termination and prior to registration expiration for ATV trails not previously identified by the permittee to be turned over to the landowner.

Permit coverage for construction activities encompassed by this permit expires upon

verification of satisfactory stabilization of the site and payment of all outstanding fees. Satisfactory stabilization means ALL disturbed areas shall be covered by some permanent protection. Stabilize includes pavement, compacted gravel, permeable pavements/pavers, buildings, waterways (riprap, concrete, grass, or pipe), a healthy, vigorous stand of grass or native vegetation that uniformly covers more than 70 percent of the ground, stable outlet channels with velocity dissipation which directs site runoff to a natural watercourse, and any other approved structure or material.

---

The herein-described activity is to be constructed or installed and operated, used and maintained strictly in accordance with the terms and conditions of this permit with any plans, specifications, and information submitted with the individual site registration application form, with any plan of maintenance and method of operation thereof submitted and with any applicable rules and regulations promulgated by the Environmental Quality Board and the Secretary of the Department of Environmental Protection.

Failure to comply with the terms and conditions of this permit; with any plans, specifications or information submitted to the Department; or with any plan of maintenance or method of operation submitted to the Department shall subject the offending individual registrant to suspension or revocation of the registrant's operation from this General Permit and/or to other enforcement action as provided in W. Va. Code §§ 22-11-12, 22-11-22, 22-11-24 or 22-12-10.

This permit is issued in accordance with the provisions of Chapter 22, Article 11 of the Code of West Virginia.

BY: \_\_\_\_\_

Jeremy W. Bandy  
Director