

West Virginia Department of Environmental Protection
Earl Ray Tomblin
Governor

Division of Air Quality

Randy C. Huffman
Cabinet Secretary

Permit to Modify



R13-3070A

This permit is issued in accordance with the West Virginia Air Pollution Control Act (West Virginia Code §§22-5-1 et seq.) and 45 C.S.R. 13 – Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Temporary Permits, General Permits and Procedures for Evaluation. The permittee identified at the above-referenced facility is authorized to construct the stationary sources of air pollutants identified herein in accordance with all terms and conditions of this permit.

Issued to:

Williams Ohio Valley Midstream, LLC
Oak Grove Natural Gas Processing Facility
051-00157

William F. Durham
Director

*Issued: **DRAFT***

This permit will supercede and replace R13-3070 issued on July 12, 2013.

Facility Location: Moundsville, Marshall County, West Virginia
Mailing Address: Park Place Corporate Center 2, 2000 Commerce Drive, Pittsburgh, PA 15275
Facility Description: Natural Gas Processing Facility
SIC Codes: 1321
NAICS Codes: 211112
UTM Coordinates: 525.9 km Easting • 4,414.1 km Northing • Zone 17
Latitude/Longitude: 39.8758/-80.6959
Permit Type: Modification
Description of Change: Modification to make various changes at the facility including (1) increasing the amount of waste-gases combusted at the flare, (2) revising the maximum design heat input (MDHI) of the Hot Oil and Regeneration Heaters, (3) changing the size and model of the standby generator, and (4) increasing the amount of condensate/slop oil stored and loaded out of the facility.

Any person whose interest may be affected, including, but not necessarily limited to, the applicant and any person who participated in the public comment process, by a permit issued, modified or denied by the Secretary may appeal such action of the Secretary to the Air Quality Board pursuant to article one [§§22B-1-1 et seq.], Chapter 22B of the Code of West Virginia. West Virginia Code §§22-5-14.

As a result of this permit, the source is a major source subject to 45CSR30. The Title V (45CSR30) application will be due within twelve (12) months after the commencement date of any operation authorized by this permit.

Table of Contents

1.0.	Emission Units	5
1.1.	Control Devices	6
2.0.	General Conditions	7
2.1.	Definitions	7
2.2.	Acronyms.....	7
2.3.	Authority.....	8
2.4.	Term and Renewal	8
2.5.	Duty to Comply	8
2.6.	Duty to Provide Information.....	8
2.7.	Duty to Supplement and Correct Information.....	8
2.8.	Administrative Update	9
2.9.	Permit Modification.....	9
2.10.	Major Permit Modification	9
2.11.	Inspection and Entry	9
2.12.	Emergency	9
2.13.	Need to Halt or Reduce Activity Not a Defense	10
2.14.	Suspension of Activities	10
2.15.	Property Rights	10
2.16.	Severability	10
2.17.	Transferability.....	10
2.18.	Notification Requirements	11
2.19.	Credible Evidence.....	11
3.0.	Facility-Wide Requirements	12
3.1.	Limitations and Standards	12
3.2.	Monitoring Requirements	12
3.3.	Testing Requirements	12
3.4.	Recordkeeping Requirements	13
3.5.	Reporting Requirements	14
4.0.	Source-Specific Requirements	15
4.1.	Limitations and Standards	15
5.0.	Source-Specific Requirements (Heaters, 1E-7E)	16
5.1.	Limitations and Standards	16
5.2.	Monitoring Requirements	18
5.3.	Testing Requirements	18
5.4.	Recordkeeping Requirements	18
5.5.	Reporting Requirements	19
6.0.	Source-Specific Requirements (Flare Control Device, 8E)	20
6.1.	Limitations and Standards	20
6.2.	Monitoring Requirements	21
6.3.	Testing Requirements	22
6.4.	Recordkeeping Requirements	22
6.5.	Reporting Requirements	22
7.0.	Source-Specific Requirements (Standby Generator, 9E)	24
7.1.	Limitations and Standards	24
7.2.	Recordkeeping Requirements	24

8.0. Source-Specific Requirements (40CFR60 Subpart JJJJ Requirements, Standby Generator, 9E).....	25
8.1. Limitations and Standards	25
9.0. Source-Specific Requirements (Gas Processing Plant, 40 CFR 60 Subpart OOOO Requirements: Piping and Equipment Fugitives (15E) & Reciprocating Compressors (17E)).....	256
9.1. Limitations and Standards	26
9.2. Initial Compliance Demonstration	28
9.3. Continuous Compliance Demonstration	29
9.4. Notification, Recordkeeping and Reporting Requirements	30
9.5. Recordkeeping Requirements	33
10.0. Source-Specific Hazardous Air Pollutant Requirements (Amine Process .. Vent, 16E)	34
10.1. Limitations and Standards	34
11.0. Source-Specific Requirements (Truck Loadout, 14E).....	35
11.1. Limitations and Standards	35
11.2. Recordkeeping Requirements	35
12.0. Source-Specific Requirements (Storage Tanks, 10E-13E).....	36
12.1. Limitations and Standards	36
12.2. Recordkeeping Requirements	36
CERTIFICATION OF DATA ACCURACY	37

1.0. Emission Units

Emission Unit ID	Emission Point ID	Emission Unit Description	Year Installed/Modified	Design Capacity	Control Device
H-01	1E	TXP1 Hot Oil Heater	2013	26.26 MMBTU/hr	None
H-02	2E	TXP1 Regen Gas Heater	2013	9.40 MMBTU/hr	None
H-03	3E	TXP2 Regen Gas Heater	2013	20.30 MMBTU/hr	None
H-04	4E	TXP3 Regen Gas Heater	2013	20.30 MMBTU/hr	None
H-05	5E	DeC2 Hot Oil Heater	2013	68.33 MMBTU/hr	None
H-06	6E	DeC2 Hot Oil Heater	2013	68.33 MMBTU/hr	None
H-07	7E	DeC2 Regen Gas Heater	2013	10.44 MMBTU/hr	None
FL-1	8E	Process Flare	2013	208,000 lb/hr	None
GEN-1	9E	Standby Generator	2013	224 HP	None
TK-1	10E	Slop Oil/Condensate	2013	16,800 gallon	None
TK-2	11E	Slop Oil/Condensate	2013	16,800 gallon	None
TK-3	12E	Slop Oil/Condensate	2013	16,800 gallon	None
TK-4	13E	Slop Oil/Condensate	2013	16,800 gallon	None
TL-1	14E	Truck Loadout	2013	4,000,000 gal/yr	None
FUG-G FUG-L	15E	Piping and Equipment Fugitives (Gas and Liquid Service)	2013	n/a	LDAR
V-01	16E	Amine Process Vent	2013	1,848,000 gal/day	FL-1 ⁽¹⁾
RPC	17E	Rod Packing – Reciprocating Compressors	2013	n/a	None
DGS	18E	Dry Gas Seals – Centrifugal Compressors	2013	n/a	None

(1) The amine unit flash tank offgas is either burned in the flare or used as fuel. The amine unit regenerator overheads are emitted directly to the atmosphere.

1.1. Control Devices

Emission Sources	Pollutant	Control Device	Control Efficiency
<u>Inlet Gas:</u> TXP Blowdowns TXP Start-Up and Dry-out Balance of Plant Volumes Filters Change-Out Compressor Maintenance Amine Unit Flash Gas Gas Pig Trap Blowdown Compressor Dry Gas Seals Other/Miscellaneous	Volatile Organic Compounds	Process Flare (FL-1)	99.0 %
<u>Ethane:</u> Ethane Feed <u>NGL:</u> Liquid Pig Trap Blowdown TXP Tanks Liquid Dry-Out Pump Maintenance: <u>Residue Gas:</u> Purge Gas Pilot Gas	Total HAPS	Process Flare (FL-1)	99.0 %

2.0. General Conditions

2.1. Definitions

- 2.1.1. All references to the “West Virginia Air Pollution Control Act” or the “Air Pollution Control Act” mean those provisions contained in W.Va. Code §§ 22-5-1 to 22-5-18.
- 2.1.2. The “Clean Air Act” means those provisions contained in 42 U.S.C. §§ 7401 to 7671q, and regulations promulgated thereunder.
- 2.1.3. “Secretary” means the Secretary of the Department of Environmental Protection or such other person to whom the Secretary has delegated authority or duties pursuant to W.Va. Code §§ 22-1-6 or 22-1-8 (45CSR§30-2.12.). The Director of the Division of Air Quality is the Secretary’s designated representative for the purposes of this permit.

2.2. Acronyms

CAAA	Clean Air Act Amendments	NO_x	Nitrogen Oxides
CBI	Confidential Business Information	NSPS	New Source Performance Standards
CEM	Continuous Emission Monitor	PM	Particulate Matter
CES	Certified Emission Statement	PM_{2.5}	Particulate Matter less than 2.5 µm in diameter
C.F.R. or CFR	Code of Federal Regulations	PM₁₀	Particulate Matter less than 10µm in diameter
CO	Carbon Monoxide	Ppb	Pounds per Batch
C.S.R. or CSR	Codes of State Rules	Pph	Pounds per Hour
DAQ	Division of Air Quality	Ppm	Parts per Million
DEP	Department of Environmental Protection	Ppm_v or ppmv	Parts per Million by Volume
dscm	Dry Standard Cubic Meter	PSD	Prevention of Significant Deterioration
FOIA	Freedom of Information Act	Psi	Pounds per Square Inch
HAP	Hazardous Air Pollutant	SIC	Standard Industrial Classification
HON	Hazardous Organic NESHAP	SIP	State Implementation Plan
HP	Horsepower	SO₂	Sulfur Dioxide
lbs/hr	Pounds per Hour	TAP	Toxic Air Pollutant
LDAR	Leak Detection and Repair	TPY	Tons per Year
M	Thousand	TRS	Total Reduced Sulfur
MACT	Maximum Achievable Control Technology	TSP	Total Suspended Particulate
MDHI	Maximum Design Heat Input	USEPA	United States Environmental Protection Agency
MM	Million	UTM	Universal Transverse Mercator
MMBtu/hr or mmbtu/hr	Million British Thermal Units per Hour	VEE	Visual Emissions Evaluation
MMCF/hr or mmcf/hr	Million Cubic Feet per Hour	VOC	Volatile Organic Compounds
NA	Not Applicable	VOL	Volatile Organic Liquids
NAAQS	National Ambient Air Quality Standards		
NESHAPS	National Emissions Standards for Hazardous Air Pollutants		

2.3. Authority

This permit is issued in accordance with West Virginia air pollution control law W.Va. Code §§ 22-5-1. et seq. and the following Legislative Rules promulgated thereunder:

- 2.3.1. 45CSR13 – *Permits for Construction, Modification, Relocation and Operation of Stationary Sources of Air Pollutants, Notification Requirements, Temporary Permits, General Permits and Procedures for Evaluation;*

2.4. Term and Renewal

- 2.4.1. This Permit shall remain valid, continuous and in effect unless it is revised, suspended, revoked or otherwise changed under an applicable provision of 45CSR13 or any other applicable legislative rule;

2.5. Duty to Comply

- 2.5.1. The permitted facility shall be constructed and operated in accordance with the plans and specifications filed in Permit Application R13-3070A and any modifications, administrative updates, or amendments thereto. The Secretary may suspend or revoke a permit if the plans and specifications upon which the approval was based are not adhered to;
[45CSR§§13-5.11 and -10.3.]
- 2.5.2. This permit will supercede and replace R13-3070. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the West Virginia Code and the Clean Air Act and is grounds for enforcement action by the Secretary or USEPA;
- 2.5.3. Violations of any of the conditions contained in this permit, or incorporated herein by reference, may subject the permittee to civil and/or criminal penalties for each violation and further action or remedies as provided by West Virginia Code 22-5-6 and 22-5-7;
- 2.5.4. Approval of this permit does not relieve the permittee herein of the responsibility to apply for and obtain all other permits, licenses, and/or approvals from other agencies; i.e., local, state, and federal, which may have jurisdiction over the construction and/or operation of the source(s) and/or facility herein permitted.

2.6. Duty to Provide Information

The permittee shall furnish to the Secretary within a reasonable time any information the Secretary may request in writing to determine whether cause exists for administratively updating, modifying, revoking, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Secretary copies of records to be kept by the permittee. For information claimed to be confidential, the permittee shall furnish such records to the Secretary along with a claim of confidentiality in accordance with 45CSR31. If confidential information is to be sent to USEPA, the permittee shall directly provide such information to USEPA along with a claim of confidentiality in accordance with 40 C.F.R. Part 2.

2.7. Duty to Supplement and Correct Information

Upon becoming aware of a failure to submit any relevant facts or a submittal of incorrect information in any permit application, the permittee shall promptly submit to the Secretary such supplemental facts or corrected information.

2.8. Administrative Update

The permittee may request an administrative update to this permit as defined in and according to the procedures specified in 45CSR13.

[45CSR§13-4.]

2.9. Permit Modification

The permittee may request a minor modification to this permit as defined in and according to the procedures specified in 45CSR13.

[45CSR§13-5.4.]

2.10 Major Permit Modification

The permittee may request a major modification as defined in and according to the procedures specified in 45CSR14 or 45CSR19, as appropriate.

[45CSR§13-5.1]

2.11. Inspection and Entry

The permittee shall allow any authorized representative of the Secretary, upon the presentation of credentials and other documents as may be required by law, to perform the following:

- a. At all reasonable times (including all times in which the facility is in operation) enter upon the permittee's premises where a source is located or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
- c. Inspect at reasonable times (including all times in which the facility is in operation) any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit;
- d. Sample or monitor at reasonable times substances or parameters to determine compliance with the permit or applicable requirements or ascertain the amounts and types of air pollutants discharged.

2.12. Emergency

2.12.1. An "emergency" means any situation arising from sudden and reasonable unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

2.12.2. Effect of any emergency. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions of Section 2.12.3 are met.

2.12.3. The affirmative defense of emergency shall be demonstrated through properly signed, contemporaneous operating logs, or other relevant evidence that:

- a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
 - b. The permitted facility was at the time being properly operated;
 - c. During the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and
 - d. The permittee submitted notice of the emergency to the Secretary within one (1) working day of the time when emission limitations were exceeded due to the emergency and made a request for variance, and as applicable rules provide. This notice must contain a detailed description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.
- 2.12.4. In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.
- 2.12.5 The provisions of this section are in addition to any emergency or upset provision contained in any applicable requirement.

2.13. Need to Halt or Reduce Activity Not a Defense

It shall not be a defense for a permittee in an enforcement action that it should have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. However, nothing in this paragraph shall be construed as precluding consideration of a need to halt or reduce activity as a mitigating factor in determining penalties for noncompliance if the health, safety, or environmental impacts of halting or reducing operations would be more serious than the impacts of continued operations.

2.14. Suspension of Activities

In the event the permittee should deem it necessary to suspend, for a period in excess of sixty (60) consecutive calendar days, the operations authorized by this permit, the permittee shall notify the Secretary, in writing, within two (2) calendar weeks of the passing of the sixtieth (60) day of the suspension period.

2.15. Property Rights

This permit does not convey any property rights of any sort or any exclusive privilege.

2.16. Severability

The provisions of this permit are severable and should any provision(s) be declared by a court of competent jurisdiction to be invalid or unenforceable, all other provisions shall remain in full force and effect.

2.17. Transferability

This permit is transferable in accordance with the requirements outlined in Section 10.1 of 45CSR13. **[45CSR§13-10.1.]**

2.18. Notification Requirements

The permittee shall notify the Secretary, in writing, no later than thirty (30) calendar days after the actual startup of the operations authorized under this permit.

2.19. Credible Evidence

Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defense otherwise available to the permittee including, but not limited to, any challenge to the credible evidence rule in the context of any future proceeding.

3.0. Facility-Wide Requirements

3.1. Limitations and Standards

- 3.1.1. **Open burning.** The open burning of refuse by any person, firm, corporation, association or public agency is prohibited except as noted in 45CSR§6-3.1.
[45CSR§6-3.1.]
- 3.1.2. **Open burning exemptions.** The exemptions listed in 45CSR§6-3.1 are subject to the following stipulation: Upon notification by the Secretary, no person shall cause, suffer, allow or permit any form of open burning during existing or predicted periods of atmospheric stagnation. Notification shall be made by such means as the Secretary may deem necessary and feasible.
[45CSR§6-3.2.]
- 3.1.3. **Asbestos.** The permittee is responsible for thoroughly inspecting the facility, or part of the facility, prior to commencement of demolition or renovation for the presence of asbestos and complying with 40 C.F.R. § 61.145, 40 C.F.R. § 61.148, and 40 C.F.R. § 61.150. The permittee, owner, or operator must notify the Secretary at least ten (10) working days prior to the commencement of any asbestos removal on the forms prescribed by the Secretary if the permittee is subject to the notification requirements of 40 C.F.R. § 61.145(b)(3)(i). The USEPA, the Division of Waste Management, and the Bureau for Public Health - Environmental Health require a copy of this notice to be sent to them.
[40CFR§61.145(b) and 45CSR§34]
- 3.1.4. **Odor.** No person shall cause, suffer, allow or permit the discharge of air pollutants which cause or contribute to an objectionable odor at any location occupied by the public.
[45CSR§4-3.1] *[State Enforceable Only]*
- 3.1.5. **Permanent shutdown.** A source which has not operated at least 500 hours in one 12-month period within the previous five (5) year time period may be considered permanently shutdown, unless such source can provide to the Secretary, with reasonable specificity, information to the contrary. All permits may be modified or revoked and/or reapplication or application for new permits may be required for any source determined to be permanently shutdown.
[45CSR§13-10.5.]
- 3.1.6. **Standby plan for reducing emissions.** When requested by the Secretary, the permittee shall prepare standby plans for reducing the emissions of air pollutants in accordance with the objectives set forth in Tables I, II, and III of 45CSR11.
[45CSR§11-5.2.]

3.2. Monitoring Requirements *[Reserved]*

3.3. Testing Requirements

- 3.3.1. **Stack testing.** As per provisions set forth in this permit or as otherwise required by the Secretary, in accordance with the West Virginia Code, underlying regulations, permits and orders, the permittee shall conduct test(s) to determine compliance with the emission limitations set forth in this permit and/or established or set forth in underlying documents. The Secretary, or his duly authorized representative, may at his option witness or conduct such test(s). Should the Secretary exercise his option to conduct such test(s), the operator shall provide all necessary sampling connections and sampling ports to be located in such manner as the Secretary may require, power for test equipment and the required safety equipment, such as scaffolding, railings and ladders, to

comply with generally accepted good safety practices. Such tests shall be conducted in accordance with the methods and procedures set forth in this permit or as otherwise approved or specified by the Secretary in accordance with the following:

- a. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with 40 C.F.R. Parts 60, 61, and 63 in accordance with the Secretary's delegated authority and any established equivalency determination methods which are applicable. If a testing method is specified or approved which effectively replaces a test method specified in the permit, the permit may be revised in accordance with 45CSR§13-4. or 45CSR§13-5.4 as applicable.
- b. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with applicable requirements which do not involve federal delegation. In specifying or approving such alternative testing to the test methods, the Secretary, to the extent possible, shall utilize the same equivalency criteria as would be used in approving such changes under Section 3.3.1.a. of this permit. If a testing method is specified or approved which effectively replaces a test method specified in the permit, the permit may be revised in accordance with 45CSR§13-4. or 45CSR§13-5.4 as applicable.
- c. All periodic tests to determine mass emission limits from or air pollutant concentrations in discharge stacks and such other tests as specified in this permit shall be conducted in accordance with an approved test protocol. Unless previously approved, such protocols shall be submitted to the Secretary in writing at least thirty (30) days prior to any testing and shall contain the information set forth by the Secretary. In addition, the permittee shall notify the Secretary at least fifteen (15) days prior to any testing so the Secretary may have the opportunity to observe such tests. This notification shall include the actual date and time during which the test will be conducted and, if appropriate, verification that the tests will fully conform to a referenced protocol previously approved by the Secretary.
- d. The permittee shall submit a report of the results of the stack test within sixty (60) days of completion of the test. The test report shall provide the information necessary to document the objectives of the test and to determine whether proper procedures were used to accomplish these objectives. The report shall include the following: the certification described in paragraph 3.5.1.; a statement of compliance status, also signed by a responsible official; and, a summary of conditions which form the basis for the compliance status evaluation. The summary of conditions shall include the following:
 1. The permit or rule evaluated, with the citation number and language;
 2. The result of the test for each permit or rule condition; and,
 3. A statement of compliance or noncompliance with each permit or rule condition.

[WV Code § 22-5-4(a)(14-15) and 45CSR13]

3.4. Recordkeeping Requirements

- 3.4.1. **Retention of records.** The permittee shall maintain records of all information (including monitoring data, support information, reports, and notifications) required by this permit recorded in a form suitable and readily available for expeditious inspection and review. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation. The files shall be maintained for at least five (5) years following the date of each occurrence, measurement, maintenance, corrective action, report, or record. At a minimum, the most recent two (2) years of data shall be maintained on site. The

remaining three (3) years of data may be maintained off site, but must remain accessible within a reasonable time. Where appropriate, the permittee may maintain records electronically (on a computer, on computer floppy disks, CDs, DVDs, or magnetic tape disks), on microfilm, or on microfiche.

- 3.4.2. **Odors.** For the purposes of 45CSR4, the permittee shall maintain a record of all odor complaints received, any investigation performed in response to such a complaint, and any responsive action(s) taken.

[45CSR§4. *State Enforceable Only.*]

3.5. Reporting Requirements

- 3.5.1. **Responsible official.** Any application form, report, or compliance certification required by this permit to be submitted to the DAQ and/or USEPA shall contain a certification by the responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

- 3.5.2. **Confidential information.** A permittee may request confidential treatment for the submission of reporting required by this permit pursuant to the limitations and procedures of W.Va. Code § 22-5-10 and 45CSR31.

- 3.5.3. **Correspondence.** All notices, requests, demands, submissions and other communications required or permitted to be made to the Secretary of DEP and/or USEPA shall be made in writing and shall be deemed to have been duly given when delivered by hand, or mailed first class with postage prepaid to the address(es) set forth below or to such other person or address as the Secretary of the Department of Environmental Protection may designate:

If to the DAQ:

Director
WVDEP
Division of Air Quality
601 57th Street
Charleston, WV 25304-2345

If to the US EPA:

Associate Director
Office of Air Enforcement and Compliance
Assistance
(3AP20)
U.S. Environmental Protection Agency
Region III
1650 Arch Street
Philadelphia, PA 19103-2029

- 3.5.4. **Operating Fee**

- 3.5.4.1. In accordance with 45CSR30 – Operating Permit Program, the permittee shall submit a certified emissions statement and pay fees on an annual basis in accordance with the submittal requirements of the Division of Air Quality. A receipt for the appropriate fee shall be maintained on the premises for which the receipt has been issued, and shall be made immediately available for inspection by the Secretary or his/her duly authorized representative.

- 3.5.5. **Emission inventory.** At such time(s) as the Secretary may designate, the permittee herein shall prepare and submit an emission inventory for the previous year, addressing the emissions from the facility and/or process(es) authorized herein, in accordance with the emission inventory submittal requirements of the Division of Air Quality. After the initial submittal, the Secretary may, based upon the type and quantity of the pollutants emitted, establish a frequency other than on an annual basis.

4.0. Source-Specific Requirements

4.1. Limitations and Standards

- 4.1.1. **Record of Monitoring.** The permittee shall keep records of monitoring information that include the following:
- a. The date, place as defined in this permit, and time of sampling or measurements;
 - b. The date(s) analyses were performed;
 - c. The company or entity that performed the analyses;
 - d. The analytical techniques or methods used;
 - e. The results of the analyses; and
 - f. The operating conditions existing at the time of sampling or measurement.
- 4.1.2. **Minor Source of Hazardous Air Pollutants (HAP).** HAP emissions from the facility shall not exceed 10 tons/year of any single HAP and 25 tons/year of any combination of HAPs. Compliance with this Section shall ensure that the facility is a minor HAP source.
- 4.1.3. **Operation and Maintenance of Air Pollution Control Equipment.** The permittee shall, to the extent practicable, install, maintain, and operate all pollution control equipment listed in Section 1.0 and associated monitoring equipment in a manner consistent with safety and good air pollution control practices for minimizing emissions, or comply with any more stringent limits set forth in this permit or as set forth by any State rule, Federal regulation, or alternative control plan approved by the Secretary.
[45CSR§13-5.11.]
- 4.1.4. **Record of Malfunctions of Air Pollution Control Equipment.** For all air pollution control equipment listed in Section 1.0, the permittee shall maintain records of the occurrence and duration of any malfunction or operational shutdown of the air pollution control equipment during which excess emissions occur. For each such case, the following information shall be recorded:
- a. The equipment involved.
 - b. Steps taken to minimize emissions during the event.
 - c. The duration of the event.
 - d. The estimated increase in emissions during the event.

For each such case associated with an equipment malfunction, the additional information shall also be recorded:

- e. The cause of the malfunction.
- f. Steps taken to correct the malfunction.
- g. Any changes or modifications to equipment or procedures that would help prevent future recurrences of the malfunction.

5.0. Source-Specific Requirements (Heaters, 1E-7E)

5.1. Limitations and Standards

- 5.1.1. Maximum Design Heat Input. The maximum design heat input (MDHI) for Heaters (1E-7E) shall not exceed the values as given under Table 1.0: Emissions Units.
- 5.1.2. Maximum emissions from the 26.26 MMBTU/hr TXP1 Hot Oil Heater (1E) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	2.57	11.28
Carbon Monoxide	2.16	9.47
Volatile Organic Compounds	0.15	0.64

- 5.1.3. The hourly quantity of natural gas that shall be consumed in the 26.26 MMBTU/hr Hot Oil Heater (1E) shall not exceed 25,748 scf/hr.
- 5.1.4. The annual quantity of natural gas that shall be consumed in the 26.26 MMBTU/hr Hot Oil Heater (1E) shall not exceed 226 MMscf/yr.
- 5.1.5. Maximum emissions from the 9.40 MMBTU/hr TXP1 Regen Gas Heater (2E) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	0.92	4.04
Carbon Monoxide	0.77	3.39
Volatile Organic Compounds	0.05	0.23

- 5.1.6. The hourly quantity of natural gas that shall be consumed in the 9.40 MMBTU/hr TXP1 Regen Gas Heater (2E) shall not exceed 9,216 scf/hr.
- 5.1.7. The annual quantity of natural gas that shall be consumed in the 9.40 MMBTU/hr TXP1 Regen Gas Heater (2E) shall not exceed 81 MMscf/yr.
- 5.1.8. *[Reserved]*
- 5.1.9. Maximum emissions from the 20.30 MMBTU/hr TXP2 Regen Gas Heater (3E) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	0.73	3.20
Carbon Monoxide	0.81	3.56
Volatile Organic Compounds	0.39	1.69

- 5.1.10. The hourly quantity of natural gas that shall be consumed in the 20.30 MMBTU/hr TXP2 Regen Gas Heater (3E) shall not exceed 19,902 scf/hr.
- 5.1.11. The annual quantity of natural gas that shall be consumed in the 20.30 MMBTU/hr TXP2 Regen Gas Heater (3E) shall not exceed 175 MMscf/yr.
- 5.1.12. *[Reserved]*
- 5.1.13. Maximum emissions from the 20.30 MMBTU/hr TXP2 Regen Gas Heater (4E) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	0.73	3.20
Carbon Monoxide	0.81	3.56
Volatile Organic Compounds	0.39	1.69

- 5.1.14. The hourly quantity of natural gas that shall be consumed in the 20.30 MMBTU/hr TXP2 Regen Gas Heater (4E) shall not exceed 19,902 scf/hr.
- 5.1.15. The annual quantity of natural gas that shall be consumed in the 20.30 MMBTU/hr TXP2 Regen Gas Heater (4E) shall not exceed 175 MMscf/yr.
- 5.1.16. *[Reserved]*
- 5.1.17. Maximum emissions from each of the 68.33 MMBTU/hr De-Ethanizer Hot Oil Heaters (5E, 6E) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	2.46	10.77
Carbon Monoxide	2.53	11.07
Volatile Organic Compounds	0.38	1.67

- 5.1.18. The hourly quantity of natural gas that shall be consumed in each of the 68.33 MMBTU/hr De-Ethanizer Hot Oil Heaters (5E, 6E) shall not exceed 67,000 scf/hr.
- 5.1.19. The annual quantity of natural gas that shall be consumed in each of the 68.33 MMBTU/hr De-Ethanizer Hot Oil Heaters (5E, 6E) shall not exceed 587 MMscf/yr.
- 5.1.20. Maximum emissions from the 10.44 MMBTU/hr De-Ethanizer Regen Gas Heater (7E) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	1.02	4.48
Carbon Monoxide	0.86	3.77
Volatile Organic Compounds	0.06	0.25

- 5.1.21. The hourly quantity of natural gas that shall be consumed in the 10.44 MMBTU/hr De-Ethanizer Regen Gas Heater (7E) shall not exceed 10,237 standard cubic feet per hour.
- 5.1.22. The annual quantity of natural gas that shall be consumed in the 10.44 MMBTU/hr De-Ethanizer Regen Gas Heater (7E) shall not exceed 89.68×10^6 standard cubic feet per year.
- 5.1.23. *[Reserved]*
- 5.1.24. No person shall cause, suffer, allow or permit emission of smoke and/or particulate matter into the open air from any fuel burning unit which is greater than ten (10) percent opacity based on a six minute block average.
[45CSR§2-3.1.]
- 5.1.25. The permitted facility shall comply with all applicable provisions of 40CFR60 Subpart Dc, provided that compliance with any more stringent limitation set forth under this permit shall also be demonstrated. Recordkeeping and reporting requirements shall be conducted in accordance with §60.48c. These reports shall be submitted in accordance with the time lines and in the order set forth in §60.48c and submitted to the addresses listed in Section 3.5.3.

5.2. Monitoring Requirements

- 5.2.1. At such reasonable times as the Secretary may designate, the permittee shall conduct Method 9 emission observations for the purpose of demonstrating compliance with Section 5.1.24. Method 9 shall be conducted in accordance with 40 CFR 60 Appendix A.

5.3. Testing Requirements

- 5.3.1. Compliance with the visible emission requirements of section 5.1.24 shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9 or by using measurements from continuous opacity monitoring systems approved by the Director. The Director may require the installation, calibration, maintenance and operation of continuous opacity monitoring systems and may establish policies for the evaluation of continuous opacity monitoring results and the determination of compliance with the visible emission requirements of section 5.1.24. Continuous opacity monitors shall not be required on fuel burning units which employ wet scrubbing systems for emission control.
[45CSR§2-3.2.]

5.4. Recordkeeping Requirements

- 5.4.1. To demonstrate compliance with sections 5.1.1-5.1.23, the permittee shall maintain a monthly record of the amount of natural gas consumed and the hours of operation of each of the heaters (1E-7E). Compliance with the maximum throughput limitation shall be determined using a twelve month rolling total. A twelve month rolling total shall mean the sum of the monthly throughput at any given time during the previous twelve consecutive calendar months. Said records shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.
- 5.4.2. Except as provided under paragraphs (g)(2) and (g)(3) of this section, the owner or operator of each affected facility shall record and maintain records of the amount of each fuel combusted during each operating day.
[40CFR§60.48(c)(g)(1)]

5.4.3. As an alternative to meeting the requirements of paragraph (g)(1) of this section, the owner or operator of an affected facility that combusts only natural gas, wood, fuels using fuel certification in §60.48c(f) to demonstrate compliance with the SO₂ standard, fuels not subject to an emissions standard (excluding opacity), or a mixture of these fuels may elect to record and maintain records of the amount of each fuel combusted during each calendar month.

[40CFR§60.48 (c)(g)(2)]

5.4.4. As an alternative to meeting the requirements of paragraph (g)(1) of this section, the owner or operator of an affected facility or multiple affected facilities located on a contiguous property unit where the only fuels combusted in any steam generating unit (including steam generating units not subject to this subpart) at that property are natural gas, wood, distillate oil meeting the most current requirements in §60.42C to use fuel certification to demonstrate compliance with the SO₂ standard, and/or fuels, excluding coal and residual oil, not subject to an emissions standard (excluding opacity) may elect to record and maintain records of the total amount of each steam generating unit fuel delivered to that property during each calendar month.

[40CFR§60.48(c)(g)(3)]

5.5. Reporting Requirements

5.5.1. The owner or operator of each affected facility shall submit notification of the date of construction or reconstruction and actual startup, as provided by §60.7 of this part. This notification shall include:

1. The design heat input capacity of the affected facility and identification of fuels to be combusted in the affected facility.
2. If applicable, a copy of any federally enforceable requirement that limits the annual capacity factor for any fuel or mixture of fuels under §60.42c, or §60.43c.
3. The annual capacity factor at which the owner or operator anticipates operating the affected facility based on all fuels fired and based on each individual fuel fired.
4. Notification if an emerging technology will be used for controlling SO₂ emissions. The Administrator will examine the description of the control device and will determine whether the technology qualifies as an emerging technology. In making this determination, the Administrator may require the owner or operator of the affected facility to submit additional information concerning the control device. The affected facility is subject to the provisions of §60.42c(a) or (b)(1), unless and until this determination is made by the Administrator.

[40CFR§60.48c(a)]

5.5.2. The reporting period for the reports required under this subpart is each six-month period. All reports shall be submitted to the Administrator and shall be postmarked by the 30th day following the end of the reporting period.

[40CFR§60.48c(j)]

6.0. Source-Specific Requirements (Flare Control Device, 8E)

6.1. Limitations and Standards

6.1.1. In accordance with information in permit application R13-3070A, the permittee shall install and operate a Process Flare (8S) designed to achieve, at a minimum, a 99.0% destruction and removal efficiency (DRE) of VOCs and organic HAPS from the sources identified under Control Devices Table 1.1. The maximum aggregate amount of waste gases sent to the Process Flare from these sources shall not exceed 630.19 MMscf/yr based on a rolling 12 month total.

6.1.2. Maximum emissions from the Zeeco flare (8E) shall not exceed the following limits:

- a. The maximum aggregate emissions generated at the Process Flare (8E) from the combustion of waste gases and the pilot light shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxides	638.12	73.27
Carbon Monoxide	1,273.91	146.28

- b. The maximum emissions of VOCs and HAPs at the Process Flare (representing un-combusted pass-through organic vapors that are generated at one of the sources identified under 6.1.1.) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
VOCs	177.30	20.36
<i>Benzene</i>	4.49	0.52
<i>Ethylbenzene</i>	6.09	0.70
<i>n-Hexane</i>	5.48	0.63
<i>Toluene</i>	5.30	0.61
<i>2,2,4-TMP</i>	6.55	0.75
<i>Xylenes</i>	6.11	0.70
Total HAPs	34.38	3.95

6.1.3. The installed Process Flare (8S) shall be a Zeeco Model Number AFTA-24/80, shall have a maximum waste-gas capacity of 208,000 lb/hr, shall have an MDHI of 4,624 mmBtu/hr, and shall be designed and operated in accordance with the following:

- a. Flare shall be air-assisted.
- b. Flare shall be designed for and operated with no visible emissions, except for periods not to exceed a total of 5 minutes during any 2 consecutive hours.
- c. Flare shall be operated, with a flame present at all times whenever emissions may be vented to it, except during SSM (Startup, Shutdown, Malfunctions) events.

- d. A flare shall be used only where the net heating value of the gas being combusted is 11.2 MJ/scm (300 Btu/scf) or greater if the flare is steam-assisted or air-assisted; or where the net heating value of the gas being combusted is 7.45 MJ/scm (200 Btu/scf) or greater if the flares is non-assisted. The net heating value of the gas being combusted in a flare shall be calculated using the following equation:

$$H_T = K \sum_{i=1}^n C_i H_i$$

Where:

H_T =Net heating value of the sample, MJ/scm; where the net enthalpy per mole of off gas is based on combustion at 25 °C and 760 mm Hg, but the standard temperature for determining the volume corresponding to one mole is 20 °C.

K =Constant=

$$1.740 \times 10^{-7} \left(\frac{1}{ppmv} \right) \left(\frac{g\text{-mole}}{scm} \right) \left(\frac{MJ}{kcal} \right)$$

where the standard temperature for (g-mole/scm) is 20 °C.

C_i =Concentration of sample component i in ppmv on a wet basis, which may be measured for organics by Test Method 18, but is not required to be measured using Method 18 (unless designated by the Director).

H_i =Net heat of combustion of sample component i, kcal/g-mole at 25 °C and 760 mm Hg. The heats of combustion may be determined using ASTM D2382–76 or 88 or D4809–95 if published values are not available or cannot be calculated.

n =Number of sample components.

- e. Air-assisted flares shall be designed and operated with an exit velocity less than the velocity V_{max} . The maximum permitted velocity, V_{max} , for air-assisted flares shall be determined by the following equation:

$$V_{max} = 8.71 + 0.708(H_T)$$

Where:

V_{max} =Maximum permitted velocity, m/sec.

8.71=Constant.

0.708=Constant.

H_T =The net heating value as determined in 6.1.3.d.

- 6.1.4. The permittee is not required to conduct a flare compliance assessment for concentration of sample (i.e. Method 18) and tip velocity (i.e. Method 2) until such time as the Director requests a flare compliance assessment to be conducted in accordance with section 6.3.2, but the permittee is required to conduct a flare design evaluation in accordance with section 6.4.2. Alternatively, the permittee may elect to demonstrate compliance with the flare design criteria requirements of section 6.1.3 by complying with the compliance assessment testing requirements of section 6.3.2.

6.2. Monitoring Requirements

- 6.2.1. In order to demonstrate compliance with the requirements of 6.1.3.c, the permittee shall monitor the presence or absence of a flare pilot flame using a thermocouple or any other equivalent device, except during SSM events.
- 6.2.2. In order to determine compliance with 6.1.1., the permittee shall monitor and record the monthly and rolling twelve (12) month total aggregate waste gases, pilot gas, and purge gas sent to the flare (in MMscf) from the sources identified under Control Devices Table 1.1.

6.3. Testing Requirements

- 6.3.1. In order to demonstrate compliance with the flare opacity requirements of 6.1.3.b the permittee shall conduct a Method 22 opacity test for at least two hours. This test shall demonstrate no visible emissions are observed for more than a total of 5 minutes during any 2 consecutive hour period using 40CFR60 Appendix A Method 22. The permittee shall conduct this test within one (1) year of R13-3070 permit issuance or initial startup whichever is later. The visible emission checks shall determine the presence or absence of visible emissions. At a minimum, the observer must be trained and knowledgeable regarding the effects of background contrast, ambient lighting, observer position relative to lighting, wind, and the presence of uncombined water (condensing water vapor) on the visibility of emissions. This training may be obtained from written materials found in the References 1 and 2 from 40 CFR part 60, appendix A, Method 22 or from the lecture portion of 40 CFR part 60, appendix A, Method 9 certification course.
- 6.3.2. The Director may require the permittee to conduct a flare compliance assessment to demonstrate compliance with section 6.1.5. This compliance assessment testing shall be conducted in accordance with appropriate test methods or other equivalent testing as approved in writing by the Director.

6.4. Recordkeeping Requirements

- 6.4.1. For the purpose of demonstrating compliance with section 6.1.3.c and 6.2.1, the permittee shall maintain records of the times and duration of all periods which the pilot flame was absent.
- 6.4.2. For the purpose of demonstrating compliance with section 6.1.3 and 6.3.2, the permittee shall maintain a record of the flare design evaluation. The flare design evaluation shall include, net heat value calculations, exit (tip) velocity calculations, and all supporting concentration calculations and other related information requested by the Director.
- 6.4.3. For the purpose of demonstrating compliance with the requirements set forth in sections 6.1.3, the permittee shall maintain records of testing conducted in accordance with 6.3.2.
- 6.4.4. The permittee shall document and maintain the corresponding records specified by the on-going monitoring requirements of 6.2 and testing requirements of 6.3.
- 6.4.5. For the purpose of demonstrating compliance with section 6.1.3.b, the permittee shall maintain records of the visible emission opacity tests conducted per Section 6.3.1.
- 6.4.6. All records required under Section 6.3 shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

6.5. Reporting Requirements

- 6.5.1. If permittee is required by the Director to demonstrate compliance with section 6.3.2, then the permittee shall submit a testing protocol at least thirty (30) days prior to testing and shall submit a notification of the testing date at least fifteen (15) days prior to testing. The permittee shall submit the testing results within sixty (60) days of testing and provide all supporting calculations and testing data.
- 6.5.2. Any deviation(s) from the allowable visible emission requirement for any emission source discovered during observations using 40CFR Part 60, Appendix A, Method 9 or 22 shall be reported in writing to the Director of the Division of Air Quality as soon as practicable, but in any case within ten (10) calendar days of the occurrence and shall include at least the following

information: the results of the visible determination of opacity of emissions, the cause or suspected cause of the violation(s), and any corrective measures taken or planned.

- 6.5.3. Any deviation(s) from the flare design and operation criteria in Section 6.1.3 shall be reported in writing to the Director of the Division of Air Quality as soon as practicable, but in any case within ten (10) calendar days of discovery of such deviation.

7.0. Source-Specific Requirements (Standby Generator, 9E)

7.1. Limitations and Standards

- 7.1.1. To demonstrate compliance with Section 7.1.2, the quantity of natural gas that shall be consumed in the 224 hp liquid propane gas (LPG)-fired reciprocating engine, an Olympian Model G150LG2 (9E), shall not exceed 878 cubic feet per hour and 440,000 cubic feet per year.
- 7.1.2. Maximum emissions from the 224 hp LPG-fired reciprocating engine, an Olympian Model G150LG2 (9E), shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Nitrogen Oxide	0.99	0.25
Carbon Monoxide	1.98	0.49
VOCs	0.54	0.13
Formaldehyde	0.04	0.01

- 7.1.3. **Maximum Yearly Operation Limitation.** The maximum yearly hours of operation for the 224 hp LPG-fired reciprocating engine, an Olympian Model G150LG2 (9E), shall not exceed 500 hours per year. Compliance with the Maximum Yearly Operation Limitation shall be determined using a twelve month rolling total. A twelve month rolling total shall mean the sum of the hours of operation at any given time during the previous twelve consecutive calendar months.

7.2. Recordkeeping Requirements

- 7.2.1. To demonstrate compliance with sections 7.1.1-7.1.3, the permittee shall maintain records of the hours of operation of the engine (9E). Said records shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

8.0. Source-Specific Requirements (40CFR60 Subpart JJJJ Requirements, Standby Generator, 9E)

8.1. Limitations and Standards

- 8.1.1. Owners and operators of stationary SI ICE with a maximum engine power greater than 19 KW (25 HP) manufactured on or after the applicable date in §60.4230(a)(4) that are rich burn engines that use LPG must comply with the emission standards in §60.4231(c) for their stationary SI ICE.
[40CFR§60.4233(c)]

- 8.1.2. Stationary SI internal combustion engine manufacturers must certify their stationary SI ICE with a maximum engine power greater than 19 KW (25 HP) (except emergency stationary ICE with a maximum engine power greater than 25 HP and less than 130 HP) that are rich burn engines that use LPG and that are manufactured on or after the applicable date in §60.4230(a)(2), or manufactured on or after the applicable date in §60.4230(a)(4) for emergency stationary ICE with a maximum engine power greater than or equal to 130 HP, to the certification emission standards and other requirements for new nonroad SI engines in 40 CFR part 1048. Stationary SI internal combustion engine manufacturers must certify their emergency stationary SI ICE greater than 25 HP and less than 130 HP that are rich burn engines that use LPG and that are manufactured on or after the applicable date in §60.4230(a)(4) to the Phase 1 emission standards in 40 CFR 90.103, applicable to class II engines, and other requirements for new nonroad SI engines in 40 CFR part 90. Stationary SI internal combustion engine manufacturers may certify their stationary SI ICE with a maximum engine power less than or equal to 30 KW (40 HP) with a total displacement less than or equal to 1,000 cc that are rich burn engines that use LPG to the certification emission standards and other requirements for new nonroad SI engines in 40 CFR part 90 or 1054, as appropriate.
[40CFR§60.4231(c)]

9.0. Source-Specific Requirements (Gas Processing Plant, 40CFR60 Subpart OOOO Requirements: Piping and Equipment Fugitives (15E) & Reciprocating Compressors (17E))

9.1. Limitations and Standards

9.1.1. **Maximum Throughput Limitation.** The total maximum wet natural gas throughput through the Gas Processing Plant shall not exceed 660 mmscf/day.

9.1.2. You must comply with the standards in paragraphs (a) through (d) of this section for each reciprocating compressor affected facility.

a. You must replace the reciprocating compressor rod packing according to either paragraph (a)(1) or (2) of this section.

1. Before the compressor has operated for 26,000 hours. The number of hours of operation must be continuously monitored beginning upon initial startup of your reciprocating compressor affected facility, or October 15, 2012, or the date of the most recent reciprocating compressor rod packing replacement, whichever is later.

2. Prior to 36 months from the date of the most recent rod packing replacement, or 36 months from the date of startup for a new reciprocating compressor for which the rod packing has not yet been replaced.

b. You must demonstrate initial compliance with standards that apply to reciprocating compressor affected facilities as required by § 60.5410.

c. You must demonstrate continuous compliance with standards that apply to reciprocating compressor affected facilities as required by § 60.5415.

d. You must perform the required notification, recordkeeping, and reporting as required by § 60.5420.

[40CFR§60.5385, Reciprocating Compressors (17E)]

9.1.3. What equipment leak standards apply to affected facilities at an onshore natural gas processing plant?

This section applies to the group of all equipment, except compressors, within a process unit.

a. You must comply with the requirements of §§ 60.482-1a(a), (b), and (d), 60.482-2a, and 60.482-4a through 60.482-11a, except as provided in § 60.5401.

b. You may elect to comply with the requirements of §§ 60.483-1a and 60.483-2a, as an alternative.

c. You may apply to the Administrator for permission to use an alternative means of emission limitation that achieves a reduction in emissions of VOC at least equivalent to that achieved by the controls required in this subpart according to the requirements of § 60.5402 of this subpart.

d. You must comply with the provisions of § 60.485a of this part except as provided in paragraph (f) of this section.

e. You must comply with the provisions of §§ 60.486a and 60.487a of this part except as provided in §§ 60.5401, 60.5421, and 60.5422 of this part.

- f. You must use the following provision instead of § 60.485a(d)(1): Each piece of equipment is presumed to be in VOC service or in wet gas service unless an owner or operator demonstrates that the piece of equipment is not in VOC service or in wet gas service. For a piece of equipment to be considered not in VOC service, it must be determined that the VOC content can be reasonably expected never to exceed 10.0 percent by weight. For a piece of equipment to be considered in wet gas service, it must be determined that it contains or contacts the field gas before the extraction step in the process. For purposes of determining the percent VOC content of the process fluid that is contained in or contacts a piece of equipment, procedures that conform to the methods described in ASTM E169-93, E168-92, or E260-96 (incorporated by reference as specified in § 60.17) must be used.
[40CFR§60.5400, Onshore Natural Gas Processing Plant]

9.1.4. What are the exceptions to the equipment leak standards for affected facilities at onshore natural gas processing plants?

- a. You may comply with the following exceptions to the provisions of § 60.5400(a) and (b).
- b. 1. Each pressure relief device in gas/vapor service may be monitored quarterly and within 5 days after each pressure release to detect leaks by the methods specified in § 60.485a(b) except as provided in § 60.5400(c) and in paragraph (b)(4) of this section, and § 60.482-4a(a) through (c) of subpart VVa.
2. If an instrument reading of 500 ppm or greater is measured, a leak is detected.
3. i. When a leak is detected, it must be repaired as soon as practicable, but no later than 15 calendar days after it is detected, except as provided in § 60.482-9a.
- ii. A first attempt at repair must be made no later than 5 calendar days after each leak is detected.
4. i. Any pressure relief device that is located in a nonfractionating plant that is monitored only by non-plant personnel may be monitored after a pressure release the next time the monitoring personnel are on-site, instead of within 5 days as specified in paragraph (b)(1) of this section and § 60.482-4a(b)(1) of subpart VVa.
- ii. No pressure relief device described in paragraph (b)(4)(i) of this section must be allowed to operate for more than 30 days after a pressure release without monitoring.
- a. Sampling connection systems are exempt from the requirements of § 60.482-5a.
- b. Pumps in light liquid service, valves in gas/vapor and light liquid service, and pressure relief devices in gas/vapor service that are located at a nonfractionating plant that does not have the design capacity to process 283,200 standard cubic meters per day (scmd) (10 million standard cubic feet per day) or more of field gas are exempt from the routine monitoring requirements of §§ 60.482-2a(a)(1) and 60.482-7a(a), and paragraph (b)(1) of this section.
- c. Pumps in light liquid service, valves in gas/vapor and light liquid service, and pressure relief devices in gas/vapor service within a process unit that is located in the Alaskan North Slope are exempt from the routine monitoring requirements of §§ 60.482-2a(a)(1), 60.482-7a(a), and paragraph (b)(1) of this section.
- d. An owner or operator may use the following provisions instead of § 60.485a(e):
1. Equipment is in heavy liquid service if the weight percent evaporated is 10 percent or less at 150 °C (302 °F) as determined by ASTM Method D86-96 (incorporated by reference as specified in § 60.17).

2. Equipment is in light liquid service if the weight percent evaporated is greater than 10 percent at 150 °C (302 °F) as determined by ASTM Method D86-96 (incorporated by reference as specified in § 60.17).
- e. An owner or operator may use the following provisions instead of § 60.485a(b)(2): A calibration drift assessment shall be performed, at a minimum, at the end of each monitoring day. Check the instrument using the same calibration gas(es) that were used to calibrate the instrument before use. Follow the procedures specified in Method 21 of appendix A-7 of this part, Section 10.1, except do not adjust the meter readout to correspond to the calibration gas value. Record the instrument reading for each scale used as specified in § 60.486a(e)(8). Divide these readings by the initial calibration values for each scale and multiply by 100 to express the calibration drift as a percentage. If any calibration drift assessment shows a negative drift of more than 10 percent from the initial calibration value, then all equipment monitored since the last calibration with instrument readings below the appropriate leak definition and above the leak definition multiplied by (100 minus the percent of negative drift/divided by 100) must be re-monitored. If any calibration drift assessment shows a positive drift of more than 10 percent from the initial calibration value, then, at the owner/operator's discretion, all equipment since the last calibration with instrument readings above the appropriate leak definition and below the leak definition multiplied by (100 plus the percent of positive drift/divided by 100) may be re-monitored.

[40CFR§60.5401, Onshore Natural Gas Processing Plant]

- 9.1.5. What are the alternative emission limitations for equipment leaks from onshore natural gas processing plants?
 - a. If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in VOC emissions at least equivalent to the reduction in VOC emissions achieved under any design, equipment, work practice or operational standard, the Administrator will publish, in the Federal Register, a notice permitting the use of that alternative means for the purpose of compliance with that standard. The notice may condition permission on requirements related to the operation and maintenance of the alternative means.
 - b. Any notice under paragraph (a) of this section must be published only after notice and an opportunity for a public hearing.
 - c. The Administrator will consider applications under this section from either owners or operators of affected facilities, or manufacturers of control equipment.
 - d. The Administrator will treat applications under this section according to the following criteria, except in cases where the Administrator concludes that other criteria are appropriate:
 1. The applicant must collect, verify and submit test data, covering a period of at least 12 months, necessary to support the finding in paragraph (a) of this section.
 2. If the applicant is an owner or operator of an affected facility, the applicant must commit in writing to operate and maintain the alternative means so as to achieve a reduction in VOC emissions at least equivalent to the reduction in VOC emissions achieved under the design, equipment, work practice or operational standard.

[40CFR§60.5402, Onshore Natural Gas Processing Plant]

9.2. Initial Compliance Demonstration

- 9.2.1. You must determine initial compliance with the standards for each affected facility using the requirements in paragraph (c) and (f) of this section. The initial compliance period begins on October 15, 2012 or upon initial startup, whichever is later, and ends no later than one year after the initial startup date for your affected facility or no later than one year after October 15, 2012. The initial compliance period may be less than one full year.

- c. To achieve initial compliance with the standards for each reciprocating compressor affected facility you must comply with paragraphs (c)(1) through (4) of this section.
 - 1. During the initial compliance period, you must continuously monitor the number of hours of operation or track the number of months since the last rod packing replacement.
 - 2. You must submit the notifications required in 60.7(a)(1), (3), and (4).
 - 3. You must submit the initial annual report for your reciprocating compressor as required in § 60.5420(b).
 - 4. You must maintain the records as specified in § 60.5420(c)(3) for each reciprocating compressor affected facility.

- f. For affected facilities at onshore natural gas processing plants, initial compliance with the VOC requirements is demonstrated if you are in compliance with the requirements of § 60.5400.

[40CFR§60.5410, Reciprocating Compressors (17E), Onshore Natural Gas Processing Plant]

9.3. Continuous Compliance Demonstration

- 9.3.1. For each reciprocating compressor affected facility, you must demonstrate continuous compliance according to paragraphs (1) through (3) of this section.
 - 1. You must continuously monitor the number of hours of operation for each reciprocating compressor affected facility or track the number of months since initial startup, or October 15, 2012, or the date of the most recent reciprocating compressor rod packing replacement, whichever is later.
 - 2. You must submit the annual report as required in § 60.5420(b) and maintain records as required in § 60.5420(c)(3).
 - 3. You must replace the reciprocating compressor rod packing before the total number of hours of operation reaches 26,000 hours or the number of months since the most recent rod packing replacement reaches 36 months.

- 9.3.2. For affected facilities at onshore natural gas processing plants, continuous compliance with VOC requirements is demonstrated if you are in compliance with the requirements of § 60.5400.

- 9.3.3. Affirmative defense for violations of emission standards during malfunction. In response to an action to enforce the standards set forth in §§ 60.5375, you may assert an affirmative defense to a claim for civil penalties for violations of such standards that are caused by malfunction, as defined at § 60.2. Appropriate penalties may be assessed, however, if you fail to meet your burden of proving all of the requirements in the affirmative defense. The affirmative defense shall not be available for claims for injunctive relief.

(1) To establish the affirmative defense in any action to enforce such a standard, you must timely meet the reporting requirements in § 60.5420(a), and must prove by a preponderance of evidence that:

(i) The violation:

(A) Was caused by a sudden, infrequent, and unavoidable failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner; and

(B) Could not have been prevented through careful planning, proper design or better operation and maintenance practices; and

(C) Did not stem from any activity or event that could have been foreseen and avoided, or planned for; and

(D) Was not part of a recurring pattern indicative of inadequate design, operation, or maintenance; and

(ii) Repairs were made as expeditiously as possible when a violation occurred. Off-shift and overtime labor were used, to the extent practicable to make these repairs; and

(iii) The frequency, amount and duration of the violation (including any bypass) were minimized to the maximum extent practicable; and

(iv) If the violation resulted from a bypass of control equipment or a process, then the bypass was unavoidable to prevent loss of life, personal injury, or severe property damage; and

(v) All possible steps were taken to minimize the impact of the violation on ambient air quality, the environment and human health; and

(vi) All emissions monitoring and control systems were kept in operation if at all possible, consistent with safety and good air pollution control practices; and

(vii) All of the actions in response to the violation were documented by properly signed, contemporaneous operating logs; and

(viii) At all times, the affected source was operated in a manner consistent with good practices for minimizing emissions; and

(ix) A written root cause analysis has been prepared, the purpose of which is to determine, correct, and eliminate the primary causes of the malfunction and the violation resulting from the malfunction event at issue. The analysis shall also specify, using best monitoring methods and engineering judgment, the amount of any emissions that were the result of the malfunction.

(2) Report. The owner or operator seeking to assert an affirmative defense shall submit a written report to the Administrator with all necessary supporting documentation, that it has met the requirements set forth in paragraph (h)(1) of this section. This affirmative defense report shall be included in the first periodic compliance, deviation report or excess emission report otherwise required after the initial occurrence of the violation of the relevant standard (which may be the end of any applicable averaging period). If such compliance, deviation report or excess emission report is due less than 45 days after the initial occurrence of the violation, the affirmative defense report may be included in the second compliance, deviation report or excess emission report due after the initial occurrence of the violation of the relevant standard.

[40CFR§60.5415]

9.4. Notification, Recordkeeping and Reporting Requirements

9.4.1. You must submit the notifications required in § 60.7(a)(1) and (4), and according to paragraphs (a)(1) and (2) of this section, if you own or operate one or more of the affected facilities specified in § 60.5365 that was constructed, modified, or reconstructed during the reporting period.

(1) If you own or operate a gas well, pneumatic controller or storage vessel affected facility you are not required to submit the notifications required in § 60.7(a)(1), (3), and (4).

(2) (i) If you own or operate a gas well affected facility, you must submit a notification to the Administrator no later than 2 days prior to the commencement of each well completion operation listing the anticipated date of the well completion operation. The notification shall include contact information for the owner or operator; the API well number, the latitude and

longitude coordinates for each well in decimal degrees to an accuracy and precision of five (5) decimals of a degree using the North American Datum of 1983; and the planned date of the beginning of flowback. You may submit the notification in writing or in electronic format.

(ii) If you are subject to state regulations that require advance notification of well completions and you have met those notification requirements, then you are considered to have met the advance notification requirements of paragraph (a)(2)(i) of this section.

9.4.2. Reporting requirements. You must submit annual reports containing the information specified in paragraphs (b)(1) and (b)(4) of this section to the Administrator and performance test reports as specified in paragraph (b)(7) of this section. The initial annual report is due 30 days after the end of the initial compliance period as determined according to § 60.5410. Subsequent annual reports are due on the same date each year as the initial annual report. If you own or operate more than one affected facility, you may submit one report for multiple affected facilities provided the report contains all of the information required as specified in paragraphs (b)(1) through (6) of this section. Annual reports may coincide with title V reports as long as all the required elements of the annual report are included. You may arrange with the Administrator a common schedule on which reports required by this part may be submitted as long as the schedule does not extend the reporting period.

(1) The general information specified in paragraphs (b)(1)(i) through (iv) of this section.

(i) The company name and address of the affected facility.

(ii) An identification of each affected facility being included in the annual report.

(iii) Beginning and ending dates of the reporting period.

(iv) A certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

(4) For each reciprocating compressor affected facility, the information specified in paragraphs (b)(4)(i) through (ii) of this section.

(i) The cumulative number of hours of operation or the number of months since initial startup, October 15, 2012, or since the previous reciprocating compressor rod packing replacement, whichever is later.

(ii) Records of deviations specified in paragraph (c)(3)(iii) of this section that occurred during the reporting period.

(7) (i) Within 60 days after the date of completing each performance test (see § 60.8 of this part) as required by this subpart you must submit the results of the performance tests required by this subpart to EPA's WebFIRE database by using the Compliance and Emissions Data Reporting Interface (CEDRI) that is accessed through EPA's Central Data Exchange (CDX) (www.epa.gov/cdx). Performance test data must be submitted in the file format generated through use of EPA's Electronic Reporting Tool (ERT) (see <http://www.epa.gov/ttn/chief/ert/index.html>). Only data collected using test methods on the ERT Web site are subject to this requirement for submitting reports electronically to WebFIRE. Owners or operators who claim that some of the information being submitted for performance tests is confidential business information (CBI) must submit a complete ERT file including information claimed to be CBI on a compact disk or other commonly used electronic storage media (including, but not limited to, flash drives) to EPA. The electronic media must be clearly marked as CBI and mailed to U.S. EPA/OAPQS/CORE CBI Office, Attention: WebFIRE Administrator, MD C404-02, 4930 Old Page Rd., Durham, NC 27703. The same ERT file with the CBI omitted must be submitted to EPA via CDX as described earlier in this paragraph. At the discretion of the delegated authority, you must also submit

these reports, including the confidential business information, to the delegated authority in the format specified by the delegated authority.

(ii) All reports required by this subpart not subject to the requirements in paragraph (a)(2)(i) of this section must be sent to the Administrator at the appropriate address listed in § 63.13 of this part. The Administrator or the delegated authority may request a report in any form suitable for the specific case (e.g., by commonly used electronic media such as Excel spreadsheet, on CD or hard copy). The Administrator retains the right to require submittal of reports subject to paragraph (a)(2)(i) and (ii) of this section in paper format.

9.4.3. Recordkeeping requirements. You must maintain the records identified as specified in § 60.7(f) and in paragraph (c)(3) of this section. All records must be maintained for at least 5 years.

(3) For each reciprocating compressors affected facility, you must maintain the records in paragraphs (c)(3)(i) through (iii) of this section.

(i) Records of the cumulative number of hours of operation or number of months since initial startup or October 15, 2012, or the previous replacement of the reciprocating compressor rod packing, whichever is later.

(ii) Records of the date and time of each reciprocating compressor rod packing placement.

(iii) Records of deviations in cases where the reciprocating compressor was not operated in compliance with the requirements specified in § 60.5385.

[40CFR§60.5420]

9.4.4. What are my additional recordkeeping requirements for my affected facility subject to VOC requirements for onshore natural gas processing plants?

a. You must comply with the requirements of paragraph (b) of this section in addition to the requirements of § 60.486a.

b. The following recordkeeping requirements apply to pressure relief devices subject to the requirements of § 60.5401(b)(1) of this subpart.

1. When each leak is detected as specified in § 60.5401(b)(2), a weatherproof and readily visible identification, marked with the equipment identification number, must be attached to the leaking equipment. The identification on the pressure relief device may be removed after it has been repaired.

2. When each leak is detected as specified in § 60.5401(b)(2), the following information must be recorded in a log and shall be kept for 2 years in a readily accessible location:

i. The instrument and operator identification numbers and the equipment identification number.

ii. The date the leak was detected and the dates of each attempt to repair the leak.

iii. Repair methods applied in each attempt to repair the leak.

iv. “Above 500 ppm” if the maximum instrument reading measured by the methods specified in paragraph (a) of this section after each repair attempt is 500 ppm or greater.

v. “Repair delayed” and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.

vi. The signature of the owner or operator (or designate) whose decision it was that repair could not be effected without a process shutdown.

- vii. The expected date of successful repair of the leak if a leak is not repaired within 15 days.
- viii. Dates of process unit shutdowns that occur while the equipment is unrepaired.
- ix. The date of successful repair of the leak.
- x. A list of identification numbers for equipment that are designated for no detectable emissions under the provisions of § 60.482-4a(a). The designation of equipment subject to the provisions of § 60.482-4a(a) must be signed by the owner or operator.

[40CFR§60.5421, Onshore Natural Gas Processing Plant]

- 9.4.5. What are my additional reporting requirements for my affected facility subject to VOC requirements for onshore natural gas processing plants?
- a. You must comply with the requirements of paragraphs (b) and (c) of this section in addition to the requirements of § 60.487a(a), (b), (c)(2)(i) through (iv), and (c)(2)(vii) through (viii).
 - b. An owner or operator must include the following information in the initial semiannual report in addition to the information required in § 60.487a(b)(1) through (4): Number of pressure relief devices subject to the requirements of § 60.5401(b) except for those pressure relief devices designated for no detectable emissions under the provisions of § 60.482-4a(a) and those pressure relief devices complying with § 60.482-4a(c).
 - c. An owner or operator must include the following information in all semiannual reports in addition to the information required in § 60.487a(c)(2)(i) through (vi):
 - 1. Number of pressure relief devices for which leaks were detected as required in § 60.5401(b)(2); and
 - 2. Number of pressure relief devices for which leaks were not repaired as required in § 60.5401(b)(3).

[40CFR§60.5422, Onshore Natural Gas Processing Plant]

9.5. Recordkeeping Requirements

- 9.5.1. To demonstrate compliance with section 9.1.1 the permittee shall maintain records of the amount of natural gas processed in the Gas Processing Plant. Said records required shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

10.0. Source-Specific Hazardous Air Pollutant Requirements (Amine Process Vent, 16E)

10.1. Limitations and Standards

10.1.1. **Maximum Throughput Limitation.** The maximum ethane feedstock to the amine system shall not exceed 44,000 barrels/day.

10.1.2. The amine system (16E) shall be designed and operated in accordance with the following:

- a. Carbon dioxide will be removed from the ethane product in an amine contacting system.
- b. The total ethane product shall be contacted with a amine solution in the contactor where the carbon dioxide in the ethane product is removed.
- c. The rich amine from the Contactor is regenerated in the Amine Regenerator where heat input is used to drive the carbon dioxide and water overhead and vented to the atmosphere.
- d. The lean amine from the bottom of the Regenerator is recycled back to the Amine Contactor.

10.1.3. Maximum emissions from the Amine System (16E) shall not exceed the following limits:

Pollutant	Maximum Hourly Emissions (lb/hr)	Maximum Annual Emissions (ton/year)
Volatile Organic Compounds	0.11	0.49

10.2. Monitoring Requirements

10.2.1. The permittee shall monitor the throughput of ethane feedstock fed to the Amine Process (16E) on a monthly basis.

10.3. Recordkeeping Requirements

10.3.1. The permittee shall maintain a record of the ethane product throughput to the Amine Process Vent (16E) to demonstrate compliance with section 10.1.1 of this permit. Said records shall be maintained for a period of five (5) years on site or in a readily accessible off-site location maintained by the permittee. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

11.0. Source-Specific Requirements (Truck Loadout, 14E)

11.1. Limitations and Standards

- 11.1.1. The maximum quantity of slop oil (condensate) that shall be loaded (14E) shall not exceed 4,000,000 gallons per year.
- 11.1.2. The Truck Loadout (14E) shall be operated in accordance with the plans and specifications filed in Permit Application R13-3070A unless the changes do not meet the definition of a modification in 45CFR13.

11.2. Recordkeeping Requirements

- 11.2.1. For the purpose of demonstrating compliance with section 11.1.1, the permittee shall maintain records of the amount of slop oil (condensate) loaded from the Truck Loadout (14E).
- 11.2.2. All records required under Section 11.2 shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

12.0. Source-Specific Requirements (Storage Tanks, 10E-13E)

12.1. Limitations and Standards

12.1.1. The maximum throughput to the storage tanks (10E-13E) shall not exceed the following:

Emission Point ID#	Emission Unit Description	Maximum Annual Throughput (gallons/year)
10E	Slop Oil (Condensate) Tank (00-ST-826)	1,000,000
11E	Slop Oil (Condensate) Tank (00-ST-827)	1,000,000
12E	Slop Oil (Condensate) Tank (00-ST-844)	1,000,000
13E	Slop Oil (Condensate) Tank (00-ST-845)	1,000,000

12.2. Recordkeeping Requirements

12.2.1. For the purpose of demonstrating compliance with section 12.1.1, the permittee shall maintain records of the maximum tank throughput of the storage tanks (10E-13E)

12.2.2. All records required under Section 12.2 shall be maintained on site or in a readily accessible off-site location maintained by the permittee for a period of five (5) years. Said records shall be readily available to the Director of the Division of Air Quality or his/her duly authorized representative for expeditious inspection and review. Any records submitted to the agency pursuant to a requirement of this permit or upon request by the Director shall be certified by a responsible official.

CERTIFICATION OF DATA ACCURACY

I, the undersigned, hereby certify that, based on information and belief formed after reasonable inquiry, all information contained in the attached _____, representing the period beginning _____ and ending _____, and any supporting documents appended hereto, is true, accurate, and complete.

Signature¹ _____
(please use blue ink) Responsible Official or Authorized Representative Date

Name & Title _____
(please print or type) Name Title

Telephone No. _____ Fax No. _____

¹ This form shall be signed by a "Responsible Official." "Responsible Official" means one of the following:

- a. For a corporation: The president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation, or a duly authorized representative of such person if the representative is responsible for the overall operation of one or more manufacturing, production, or operating facilities applying for or subject to a permit and either:
 - (i) the facilities employ more than 250 persons or have a gross annual sales or expenditures exceeding \$25 million (in second quarter 1980 dollars), or
 - (ii) the delegation of authority to such representative is approved in advance by the Director;
- b. For a partnership or sole proprietorship: a general partner or the proprietor, respectively;
- c. For a municipality, State, Federal, or other public entity: either a principal executive officer or ranking elected official. For the purposes of this part, a principal executive officer of a Federal agency includes the chief executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g., a Regional Administrator of U.S. EPA); or
- d. The designated representative delegated with such authority and approved in advance by the Director.