



625 Liberty Ave, Suite 1700
Pittsburgh PA 15222
www.eqt.com

TEL: (412) 395-3699
FAX: (412) 395-2156

Alex Bosiljevac
Environmental Coordinator

April 26, 2016

CERTIFIED MAIL # 7015 1660 0000 9399 6079

Mr. William F. Durham, Director
West Virginia Department of Environmental Protection
Division of Air Quality
601 57th Street, SE
Charleston, West Virginia, 25304

**RE: G70B Permit Application
EQT Production Company
OXF-159 Natural Gas Production Site
Facility ID No. 017-00152**

Dear Mr. Durham,

Enclosed are two electronic copies and one original hard copy of a proposed application for a G70-B General Air Permit for the OXF-159 Natural Gas Production Well Site. The site currently operates under a G70-A General Air Permit (G70-A159). Please note that this application satisfies a requirement in Consent Order CO-R13-E-2016-04, in which EQT Production Company is required to submit an application with the equipment specified in the consent order. A legal advertisement will be published in the next few days and proof of publication will be forwarded as soon as it is received. Please contact me for payment of the application fee by credit card.

If you have any questions concerning this permit application, please contact me at (412) 395-3699 or by email at abosiljevac@eqt.com.

Sincerely,

A handwritten signature in blue ink, appearing to read 'ABOSILJEVAC'.

Alex Bosiljevac
EQT Corporation

Enclosures




EQT Production Company

G70-B General Permit Registration Application

OXF 159 Natural Gas Production Site (017-00152)

West Union, West Virginia

Prepared By:



ERM

**ENVIRONMENTAL RESOURCES MANAGEMENT, Inc.
Hurricane, West Virginia**

April 2016

INTRODUCTION

EQT Production Company (EQT) is submitting this G70-B General Permit Registration to the WVDEP's Department of Air Quality to receive the authority to operate new units at the OXF-159 facility, currently permitted under G70-A159. This site located in Doddridge County, West Virginia. This application addresses the operational activities associated with the production of natural gas and condensates at the OXF-159 pad.

FACILITY DESCRIPTION

The EQT OXF-159 natural gas production site operates in Doddridge County, WV and consists of seven (7) natural gas wells. Natural gas and liquids (including water and condensates) are extracted from underground deposits. The natural gas is transported from the wells to a gas line for compression and additional processing, as necessary. The produced liquids are stored in storage vessels.

The applicant is currently authorized to operate the following:

- Seven (7) natural gas wells;
- Seven (7) line heater each rated at 1.54 MMBtu/hr;
- One (1) 140 bbl sand trap blowdown tank for storage of condensate and water;
- Eight (8) 400 barrel (bbl) tanks for storage of condensate and water;
- Two (2) thermoelectric generator (TEG) each rated at 0.013 MMBtu/hr heat input;
- Two (2) enclosed combustion devices each with a capacity of 11.66 MMBtu/hr heat input; and
- One (1) Produced Fluids Loading Rack.

The applicant seeks to authorize the operation of:

- Addition of one (1) 110 HP stationary natural gas compressor engine; and
- Addition of one (1) line heater rated at 1.15 MMBtu/hr heat input.

A process flow diagram is included in this application in Attachment D.

STATEMENT OF AGGREGATION

The OXF-159 pad is located in Doddridge County, WV and operated by EQT Production Company. Stationary sources of air pollutants may require aggregation of total emission levels if these sources share the same industrial grouping, are operating under common control, and are classified as contiguous or adjacent properties. EQT will operate the OXF-159 with the same industrial

grouping as nearby facilities, and some of these facilities are under common control. EQT, however, is not subject to the aggregation of stationary emission sources because these sites do not meet the definition of contiguous or adjacent facilities.

The OXF-159 pad will operate under SIC code 1311 (Crude Petroleum and Natural Gas Extraction). There are surrounding wells and compressor stations operated by EQT that share the same two-digit major SIC code of 13 for Crude Petroleum and Natural Gas Extraction. Therefore, the OXF-159 pad does share the same SIC codes as the surrounding wells and compressor stations.

EQT Production Company is the sole operator of the OXF-159 pad. EQT is also the sole operator of other production sites and compressor stations in the area. Therefore, EQT does qualify as having nearby operations under common control.

There are no EQT owned or operated sites within a one (1) mile radius of the OXF-159 pad. EQT's OXF-138 Natural Gas Production site is 1.4 miles west of the OXF-159 pad. Nearby sites do not meet the definition of contiguous or adjacent properties since they are not in contact and do not share a common boundary. Operations conducted at the OXF-159 site do not rely on or interact with other sites. Furthermore, operations separated by this distance do not meet the common sense notion of a "plant."

On August 18, 2015 the EPA Administrator signed the *Source Determination for Certain Emission Units in the Oil and Natural Gas Sector*. This notice is to clarify how properties in the oil and natural gas sector are determined to be adjacent in order to assist permitting authorities and permit applicants in making consistent source determinations. The following proposed regulatory text defines "adjacent" for the oil and gas sector in terms of proximity.

Pollutant emitting activities shall be considered adjacent if they are located on the same surface site, or on surface sites that are located within ¼ mile of one another.

The OXF-159 and OXF-138 pads are located on surface sites located greater than EPA's ¼ mile proposed ruling. Although the applicant notes the proposed status of this adjacency determination, it is the only guidance available on a finite distance impacting the adjacency determination, and has been noted due to lack of finalized guidance. Based upon the proximity of nearby facilities, EQT does not believe aggregation based upon adjacency is required.

Based on the above reasoning, EQT is not subject to the aggregation of stationary emission sources since the stationary sources are not considered contiguous or adjacent facilities.

REGULATORY DISCUSSION

This section outlines the State air quality regulations that could be reasonably expected to apply to the OXF-159 pad and makes an applicability determination for each regulation based on activities conducted at the site and the emissions of regulated air pollutants. This review is presented to supplement and/or add clarification to the information provided in the WVDEP G70-B permit application forms.

The West Virginia State Regulations address federal regulations, including Prevention of Significant Deterioration permitting, Title V permitting, New Source Performance Standards, and National Emission Standards for Hazardous Air Pollutants. The regulatory requirements in reference to OXF-159 are described in detail in the below section.

WEST VIRGINIA STATE AIR REGULATIONS

45 CSR 02 – To Prevent and Control Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers

The line heaters are indirect heat exchangers that combust natural gas but are exempt since the heat input capacities are less than 10 MMBtu/hr.

45 CSR 04 – To Prevent and Control the Discharge of Air Pollutants into the Air Which Causes or Contributes to an Objectionable Odor

Operations conducted at the OXF-159 wellpad are subject to this requirement. Based on the nature of the process at the wellpad, the presence of objectionable odors is unlikely.

45 CSR 06 – Control of Air Pollution from the Combustion of Refuse

The enclosed combustion device located on the OXF-159 natural gas production site is subject to this regulation. Per 45 CSR 6-4.3, opacity of emissions from the enclosed combustion device shall not exceed 20 percent, except as provided by 4.4. Particulate matter emissions from this unit will not exceed the levels calculated in accordance with 6-4.1.

§45-6-4.1 Determination for Maximum Allowable Particulate Emissions

Emissions (lb/hr) = F x Incinerator Capacity (tons/hr)

Incinerator Capacity = 0.12 tons per hour or 245 lbs/hr

$\rho_{NG} = 0.042 \text{ lb/scf}$ – Density of NG from EPA AP42 – Sections 1.4 and 3.2 (NG combustion)

$$\frac{140,000 \text{ scf}}{\text{day}} * \frac{1 \text{ day}}{24 \text{ hours}} * \frac{0.042 \text{ lb}}{\text{scf}} = \frac{245 \text{ lb}}{\text{hr}} = \frac{1,073 \text{ tons}}{\text{year}}$$

If the Incinerator Capacity is less than 15,000 lbs/hr, then $F = 5.43$

$$F = 5.43 * (0.12 \text{ tons per hour})$$

$$F = 0.67 \text{ lbs / hour}$$

The enclosed combustion devices utilize AP-42 Section 1.4 PM emission factors to determine emissions from the combustion of refuse natural gas. Based upon the type of fuel combusted and the emission factors utilized, the PM emissions from the enclosed combustion devices will be well below the maximum allowable particulate emissions mandated by 45 CSR 06.

45 CSR 10 – To Prevent and Control Air Pollution from the Emission of Sulfur Oxides

The line heaters are indirect heat exchangers that combust natural gas but are exempt since the heat input capacities are less than 10 MMBtu/hr.

45 CSR 13 – Permits for Construction, Modification, Relocation, and Operation of Stationary Sources of Air Pollutants

This G70-B permit application is being submitted for the operational activities associated with EQT's production of natural gas.

45 CSR 14 – Permits for Construction and Major Modification of Major Stationary Sources of Air Pollution for the Prevention of Significant Deterioration

Federal construction permitting programs regulate new and modified sources of attainment pollutants under Prevention of Significant Deterioration (PSD). The G70B-applicability criterion excludes facilities that meet the definition of a major source as defined in 45 CSR 19 for being eligible for the general permit.

Operation of equipment at the OXF-159 pad will not exceed emission thresholds established by this permitting program. EQT will monitor future construction and modification activities at the site closely and will compare future increases in emissions with the PSD thresholds to ensure these activities will not trigger this program.

45 CSR 16 - Standards of Performance for New Stationary Sources (NSPS)

45CSR 16 applies to registrants that are subject to NSPS requirements described in more detail in the Federal Regulations section. Applicable requirements of NSPS, Subpart JJJJ and OOOO are included in the G70-B general permit.

This facility is expected to contain gas well affected facilities under Subpart OOOO. This facility will contain a spark ignition internal combustion engine subject to Subpart JJJJ. No additional NSPS are applicable for this facility. Additional discussion is provided in the Federal Regulation Discussion of this permit application.

45 CS R19 – Permits for Construction and Major Modification of Major Stationary Sources of Air Pollution which Cause or Contributed to Non-attainment

Federal construction permitting programs regulate new and modified sources of non-attainment pollutants under Non-Attainment New Source Review (NNSR). The G70-B applicability criterion excludes facilities that meet the definition of a major source as defined in 45 CSR 19 for being eligible for the general permit.

Operation of equipment at the OXF-159 pad will not exceed emission thresholds established by either of these permitting programs. EQT will monitor future construction and modification activities at the site closely and will compare future increases in emissions with the NSR thresholds to ensure these activities will not trigger this program.

45 CSR 25 – Control of Air Pollution from Hazardous Waste Treatment, Storage, and Disposal Facilities

No hazardous waste will be burnt at this well site; therefore, it is not subject to this hazardous waste rule.

45 CSR 30 – Requirements for Operating Permits

45 CSR 30 applies to the requirements of the federal Title V operating permit program (40 CFR 70). The major source thresholds with respect to the West Virginia Title V operating permit program regulations are 10 tons per year (tpy) of a single HAP, 25 tpy of any combination of HAP, and 100 tpy of other regulated pollutants.

The potential emissions of regulated pollutants are below the corresponding threshold(s) at this facility after the proposed project. Therefore, the wellpad is not a major source for Title V purposes.

45 CSR 34 – National Emission Standards for Hazardous Air Pollutants (NESHAP)

45 CSR 34 applies to registrants that are subject to NESHAP requirements. Excluded from G70-B general permit eligibility are sources that are subject to NESHAP Subpart HHH.

The following NESHAP included in the G70-B permit are not subject to the OXF-159 facility:

- 40CFR63 Subpart HH (National Emission Standards for Hazardous Air Pollutants from Oil and Natural Gas Production Facilities).

FEDERAL REGULATIONS

40 CFR 60 Subpart JJJJ (Standards of Performance for Stationary Spark Ignition Internal Combustion Engines).

Subpart JJJJ sets forth nitrogen oxides (NO_x), carbon monoxide (CO), and volatile organic compound (VOC) emission limits, fuel requirements, installation requirements, and monitoring requirements based on the year of installation of the subject internal combustion engine.

The Ford CSG-637 is a 110 HP EPA Certified 4 stroke rich burn (4SRB) spark ignition (SI) engine manufactured in 2015. Per 40CFR60.4230(a)(4)(iii), an engine manufactured on or after July 1, 2008 with a maximum engine power less than 500 HP must comply with the provisions of 40 CFR 60 Subpart JJJJ.

Emission standards contained in the EPA Certificate of Conformity issued to this engine conform to 40 CFR 60 Subpart JJJJ Table 1 - NO_x, CO, VOC Emissions Standards for Stationary Non-Emergency SI Engines greater than 100 HP. Therefore, per 40CFR60.4243(a)(1), EQT must operate and maintain the certified stationary SI internal combustion engine and control device according to the manufacturer's emission-related written instructions to ensure applicable emission standards outlined in Part 60 Subpart JJJJ Table 1 are maintained. Additionally, performance testing is not required.

40 CFR 60 Subpart OOOO (Standards of Performance for Crude oil and Natural Gas Production, Transmission and Distribution)

EPA published the NSPS for the oil and gas sector on August 16, 2012. EPA published final amendments to the subpart on September 23, 2013.

Subpart OOOO establishes emission standards and compliance schedules for the control of volatile organic compounds (VOC) and sulfur dioxide (SO₂) emissions from affected facilities that commence construction, modification or

reconstruction after August 23, 2011. The applicable provisions and requirements of Subpart OOOO are included under the G70-B permit.

The only affected facilities expected to be subject to Subpart OOOO located at the OXF-159 production pad are listed below:

- Each gas well affected facility, which is a single natural gas well.

There are several equipment types that will be installed at OXF-159 that do not meet the affected facility definitions as specified by EPA. These include pneumatic controllers and storage vessels.

Pneumatic Controllers: Pneumatic controllers installed at this facility will be intermittent bleed rate devices. Therefore, there will not be pneumatic controller affected facilities located at this site.

Storage vessels: Based on PTE calculations included within this permit, each storage vessel will be manifolded and routed to an enclosed combustion device such that emissions from each of these tanks are expected to be below 6 tons per year (tpy) of VOC. Therefore, these tanks will not be considered group 2 storage vessel affected facilities as specified in §60.5365(e).

No additional NSPS are expected to be applicable to this facility.

40CFR63 Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines)

Subpart ZZZZ establishes national emission limitations and operating limitations for hazardous air pollutants (HAPs) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This Subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations.

The Ford CSG-637 is a 110 HP EPA Certified 4 stroke rich burn (4SRB) spark ignition (SI) engine manufactured in 2015. The engine meets the requirements of 40 CFR 60 Subpart JJJJ. Per 40CFR63.6590(c)(1), no further requirements apply for a new stationary RICE located at an area source subject to regulation under 40 CFR 60 Subpart JJJJ.

No additional NESHAP are expected to be applicable to this facility.

General Permit G70-B will establish an emission cap on the following regulated and hazardous air pollutants:

Pollutant	Maximum Annual Emission Limit (tons/year)	OXF-159 Potential to Emit (PTE) (tons/year)
Nitrogen Oxides	50	15.41
Carbon Monoxide	80	15.24
Volatile Organic Compounds	80	3.30
Particulate Matter - 10/2.5	20	7.25
Sulfur Dioxide	20	0.08
Any Single Hazardous Air Pollutant	8	0.28 (Highest Single HAP)
Total Hazardous Air Pollutants	20	0.53

The fugitive emissions of a stationary source shall not be considered in determining whether it is a major stationary source for the purposes of 45CSR30-2.26.b or for eligibility of this General Permit.



west virginia department of environmental protection

Division of Air Quality
601 57th Street SE
Charleston, WV 25304
Phone (304) 926-0475
Fax (304) 926-0479
www.dep.wv.gov

G70-B GENERAL PERMIT REGISTRATION APPLICATION

PREVENTION AND CONTROL OF AIR POLLUTION IN REGARD TO THE CONSTRUCTION, MODIFICATION, RELOCATION, ADMINISTRATIVE UPDATE AND OPERATION OF NATURAL GAS PRODUCTION FACILITIES LOCATED AT THE WELL SITE

- CONSTRUCTION
- MODIFICATION
- RELOCATION
- CLASS I ADMINISTRATIVE UPDATE
- CLASS II ADMINISTRATIVE UPDATE

SECTION I. GENERAL INFORMATION

Name of Applicant (as registered with the WV Secretary of State's Office): **EQT Production Company**

Federal Employer ID No. (FEIN): **25-0724685**

Applicant's Mailing Address: **625 Liberty Avenue, Suite 1700**

City: **Pittsburgh**

State: **PA**

ZIP Code: **15222**

Facility Name: **OXF-159**

Operating Site Physical Address: **None**

If none available, list road, city or town and zip of facility. **Maxwell Ridge Road, West Union, WV 26456**

City: **West Union, WV**

Zip Code: **26456**

County: **Doddridge**

Latitude & Longitude Coordinates (NAD83, Decimal Degrees to 5 digits):

Latitude: **39.20784**

Longitude: **-80.76235**

SIC Code: **1311**

NAICS Code: **211111**

DAQ Facility ID No. (For existing facilities)

017-00152

CERTIFICATION OF INFORMATION

This G70-B General Permit Registration Application shall be signed below by a Responsible Official. A Responsible Official is a President, Vice President, Secretary, Treasurer, General Partner, General Manager, a member of the Board of Directors, or Owner, depending on business structure. A business may certify an Authorized Representative who shall have authority to bind the Corporation, Partnership, Limited Liability Company, Association, Joint Venture or Sole Proprietorship. Required records of daily throughput, hours of operation and maintenance, general correspondence, compliance certifications and all required notifications must be signed by a Responsible Official or an Authorized Representative. If a business wishes to certify an Authorized Representative, the official agreement below shall be checked off and the appropriate names and signatures entered. **Any administratively incomplete or improperly signed or unsigned G70-B Registration Application will be returned to the applicant. Furthermore, if the G70-B forms are not utilized, the application will be returned to the applicant. No substitution of forms is allowed.**

I hereby certify that _____ is an Authorized Representative and in that capacity shall represent the interest of the business (e.g., Corporation, Partnership, Limited Liability Company, Association Joint Venture or Sole Proprietorship) and may obligate and legally bind the business. If the business changes its Authorized Representative, a Responsible Official shall notify the Director of the Division of Air Quality immediately.

I hereby certify that all information contained in this G70-B General Permit Registration Application and any supporting documents appended hereto is, to the best of my knowledge, true, accurate and complete, and that all reasonable efforts have been made to provide the most comprehensive information possible.

Responsible Official Signature: _____

Name and Title: **Kenneth Kirk - Executive Vice President** Phone: **(412)553-5700** Fax: _____

Email: **kkirk@eqt.com**

Date: **4-26-2016**

If applicable:

Authorized Representative Signature: _____

Name and Title:

Phone:

Fax:

Email:

Date:

If applicable:

Environmental Contact: **Alex Bosiljevac**

Name and Title: **Environmental Coordinator** Phone: **(412) 395-3699** Fax: _____

Email: **abosiljevac@eqt.com**

Date:

OPERATING SITE INFORMATION

Briefly describe the proposed new operation and/or any change(s) to the facility: **EQT proposes the addition of one (1) 1.15 mmBtu/hr line heater and one (1) low pressure separator to regulate flashing emissions from produced fluids originating from the phase separators. The low pressure separator will be installed between the phase separators and produced fluid tanks. A natural gas compressor engine will be installed to compress the natural gas realized at the low pressure separator and directed to the sales pipeline.**

Directions to the facility: **Directions from West Union, WV: Travel south on WV-18S. After 4.8 miles, turn right onto Lick Run. After 2.6 miles, turn right onto county road 40/3. After 1.9 miles, turn left onto Maxwell Ridge. Turn right onto Oil Well Road after 300 feet. The facility is located 1.1 miles down Oil Well Road.**

ATTACHMENTS AND SUPPORTING DOCUMENTS

I have enclosed the following required documents:

Check payable to WVDEP – Division of Air Quality with the appropriate application fee (per 45CSR13 and 45CSR22).

- Check attached to front of application.
- I wish to pay by electronic transfer. Contact for payment (incl. name and email address):
- I wish to pay by credit card. Contact for payment (incl. name and email address): **Alex Bosiljevac - abosiljevac@egt.com**
- \$500 (Construction, Modification, and Relocation) \$300 (Class II Administrative Update)
- \$1,000 NSPS fee for 40 CFR60, Subpart IIII, JJJJ and/or OOOO ¹
- \$2,500 NESHAP fee for 40 CFR63, Subpart ZZZZ and/or HH ²

¹ Only one NSPS fee will apply.

² Only one NESHAP fee will apply. The Subpart ZZZZ NESHAP fee will be waived for new engines that satisfy requirements by complying with NSPS, Subparts IIII and/or JJJJ.

NSPS and NESHAP fees apply to new construction or if the source is being modified.

- Responsible Official or Authorized Representative Signature (if applicable)
- Single Source Determination Form (**must be completed in its entirety**) – Attachment A
- Siting Criteria Waiver (if applicable) – Attachment B Current Business Certificate – Attachment C
- Process Flow Diagram – Attachment D Process Description – Attachment E
- Plot Plan – Attachment F Area Map – Attachment G
- G70-B Section Applicability Form – Attachment H Emission Units/ERD Table – Attachment I
- Fugitive Emissions Summary Sheet – Attachment J
- Gas Well Affected Facility Data Sheet (if applicable) – Attachment K
- Storage Vessel(s) Data Sheet (include gas sample data, USEPA Tanks, simulation software (e.g. ProMax, E&P Tanks, HYSYS, etc.), etc. where applicable) – Attachment L
- Natural Gas Fired Fuel Burning Unit(s) Data Sheet (GPUs, Heater Treaters, In-Line Heaters if applicable) – Attachment M
- Internal Combustion Engine Data Sheet(s) (include manufacturer performance data sheet(s) if applicable) – Attachment N
- Tanker Truck Loading Data Sheet (if applicable) – Attachment O
- Glycol Dehydration Unit Data Sheet(s) (include wet gas analysis, GRI- GLYCalc™ input and output reports and information on reboiler if applicable) – Attachment P
- Pneumatic Controllers Data Sheet – Attachment Q
- Air Pollution Control Device/Emission Reduction Device(s) Sheet(s) (include manufacturer performance data sheet(s) if applicable) – Attachment R
- Emission Calculations (please be specific and include all calculation methodologies used) – Attachment S
- Facility-wide Emission Summary Sheet(s) – Attachment T
- Class I Legal Advertisement – Attachment U
- One (1) paper copy and two (2) copies of CD or DVD with pdf copy of application and attachments

All attachments must be identified by name, divided into sections, and submitted in order.

Table of Contents

ATTACHMENT A	SINGLE SOURCE DETERMINATION FORM
ATTACHMENT B	CITING CRITERIA WAIVER – (NOT APPLICABLE)
ATTACHMENT C	BUSINESS CERTIFICATE
ATTACHMENT D	PROCESS FLOW DIAGRAM
ATTACHMENT E	PROCESS DESCRIPTION
ATTACHMENT F	PLOT PLAN
ATTACHMENT G	AREA MAP
ATTACHMENT H	APPLICABILITY FORM
ATTACHMENT I	EMISSION UNITS / EMISSION REDUCTION DEVICES (ERD) TABLE
ATTACHMENT J	FUGITIVE EMISSIONS SUMMARY SHEET
ATTACHMENT K	GAS WELL AFFECTED FACILITY DATA SHEET
ATTACHMENT L	STORAGE VESSEL DATA SHEET
ATTACHMENT M	HEATER AND REBOILERS NOT SUBJECT TO 40CFR60 SUBPART Dc
ATTACHMENT N	INTERNAL COMBUSTION ENGINE DATA SHEET
ATTACHMENT O	TANKER TRUCK LOADING DATA SHEET
ATTACHMENT P	GLYCOL DEHYDRATION UNIT DATA SHEET – (NOT APPLICABLE)
ATTACHMENT Q	PNEUMATIC CONTROLLERS DATA SHEET
ATTACHMENT R	AIR POLLUTION CONTROL DEVICE / EMISSION REDUCTION DEVICE (ERD) SHEET
ATTACHMENT S	EMISSION CALCULATIONS
ATTACHMENT T	FACILITY-WIDE CONTROLLED EMISSIONS SUMMARY SHEET
ATTACHMENT U	CLASS I LEGAL ADVERTISEMENT

Attachment A

SINGLE SOURCE DETERMINATION FORM

ATTACHMENT A - SINGLE SOURCE DETERMINATION FORM

Classifying multiple facilities as one “stationary source” under 45CSR13, 45CSR14, and 45CSR19 is based on the definition of Building, structure, facility, or installation as given in §45-14-2.13 and §45-19-2.12. The definition states:

“Building, Structure, Facility, or Installation” means all of the pollutant-emitting activities which belong to the same industrial grouping, are located on one or more contiguous or adjacent properties, and are under the control of the same person (or persons under common control). Pollutant-emitting activities are a part of the same industrial grouping if they belong to the same “Major Group” (i.e., which have the same two (2)-digit code) as described in the Standard Industrial Classification Manual, 1987 (United States Government Printing Office stock number GPO 1987 0-185-718:QL 3).

Is there a facility owned by or associated with the natural gas industry located within one (1) mile of the proposed facility? Yes No

If Yes, please complete the questionnaire on the following page (Attachment A).

Please provide a source aggregation analysis for the proposed facility below:

See Introduction for additional source aggregation analysis.

Attachment B

CITING CRITERIA WAIVER – (NOT APPLICABLE)

Attachment C
BUSINESS CERTIFICATE

**WEST VIRGINIA
STATE TAX DEPARTMENT
BUSINESS REGISTRATION
CERTIFICATE**

ISSUED TO:
**EQT PRODUCTION COMPANY
625 LIBERTY AVE 1700
PITTSBURGH, PA 15222-3114**

BUSINESS REGISTRATION ACCOUNT NUMBER: 1022-8081

This certificate is issued on: 08/4/2010

*This certificate is issued by
the West Virginia State Tax Commissioner
in accordance with Chapter 11, Article 12, of the West Virginia Code*

*The person or organization identified on this certificate is registered
to conduct business in the State of West Virginia at the location above.*

This certificate is not transferrable and must be displayed at the location for which issued.
This certificate shall be permanent until cessation of the business for which the certificate of registration
was granted or until it is suspended, revoked or cancelled by the Tax Commissioner.

Change in name or change of location shall be considered a cessation of the business and a new
certificate shall be required.


TRAVELING/STREET VENDORS: Must carry a copy of this certificate in every vehicle operated by them.
CONTRACTORS, DRILLING OPERATORS, TIMBER/LOGGING OPERATIONS: Must have a copy of
this certificate displayed at every job site within West Virginia.

Attachment D
PROCESS FLOW DIAGRAM

Attachment D

OXF 159 Natural Gas Production

Process Flow Diagram



Attachment E

PROCESS DESCRIPTION

Attachment E

Process Description

This permit modification application is being filed for EQT Production Company and addresses operational activities associated with the OXF-159 natural gas production site. Incoming raw natural gas from the seven (7) wells enters the site through a pipeline. The raw gas is first routed through the sand traps to remove sediment. Fluids from these sand traps are manually blown down to the sand trap blowdown tank (S016), as needed. From the sand traps, raw gas is routed through line heaters (S001-S007) to assist with the phase separation process in the downstream high pressure phase separators. In the high pressure phase separators, produced fluids are removed from the raw gas before being dumped to a second stage of fluid separation. The produced fluids pass through a line heater (S023) to further assist in the separation process. At this low pressure separator, produced fluid pressure is reduced to 30 psig. Vapors realized at the low pressure separator are directed to a 110 bhp compressor engine (S022) and routed to the sales pipeline. Produced fluids from the low pressure separator are routed to the produced fluids storage tanks (S008-S015). Emissions from the produced fluids tanks and sand trap blowdown tank are directed to one of the two enclosed combustion devices (C018, C019) and combusted. Produced fluids are pumped into a tank truck (S017) on an as-needed basis and are disposed of off-site. Vapors during truck loading will be controlled by either of the two enclosed combustion devices.

Two thermoelectric generation units (S020, S021) are operated and provide power to the OXF-159 natural gas production site.





A process flow diagram is included as Attachment D.

Attachment F

PLOT PLAN

Coordinates
Latitude: 39.20784
Longitude: -80.76235
Elevation: 1250 ft
Drawn: 01/27/2016


Attachment F Plot Plan EQT OXF 159 Natural Gas Production Site Plant: 017-00152




TRUCK ENTRANCE

Attachment G


AREA MAP



West Virginia



LAT. 39.20784 LON. -80.76235
 DODDRIDGE COUNTY
 WEST VIRGINIA



Legend

- Site Location
- 300' Site Buffer
- 1 Mile Site Buffer

USGS 1:24K 7.5' Quadrangle:
 Pullman, WV

SITE LOCATION MAP



EQT PRODUCTION COMPANY

OXF-159 Well Pad
 Doddridge County, West Virginia

GIS Review: JS

CHK'D: JS

0250395

Drawn By:
 SRV-12/18/15

Environmental Resources Management

ATTACHMENT G

J:\GIS\Projects\EQT_MXD\OXF159_Site_Location_Map.mxd - 12/20/16/ISR/V

Copyright © 2013 National Geographic Society, i-cubed

Attachment H
APPLICABILITY FORM

ATTACHMENT H – G70-B SECTION APPLICABILITY FORM

**General Permit G70-B Registration
Section Applicability Form**

General Permit G70-B was developed to allow qualified applicants to seek registration for a variety of sources. These sources include gas well affected facilities, storage vessels, gas production units, in-line heaters, heater treaters, glycol dehydration units and associated reboilers, pneumatic controllers, centrifugal compressors, reciprocating compressors, reciprocating internal combustion engines (RICEs), tank truck loading, fugitive emissions, completion combustion devices, flares, enclosed combustion devices, and vapor recovery systems. All registered facilities will be subject to Sections 1.0, 2.0, 3.0, and 4.0.

General Permit G70-B allows the registrant to choose which sections of the permit they are seeking registration under. Therefore, please mark which additional sections that you are applying for registration under. If the applicant is seeking registration under multiple sections, please select all that apply. Please keep in mind, that if this registration is approved, the issued registration will state which sections will apply to your affected facility.

GENERAL PERMIT G70-B APPLICABLE SECTIONS	
<input checked="" type="checkbox"/> Section 5.0	Gas Well Affected Facility (NSPS, Subpart OOOO)
<input checked="" type="checkbox"/> Section 6.0	Storage Vessels Containing Condensate and/or Produced Water ¹
<input type="checkbox"/> Section 7.0	Storage Vessel Affected Facility (NSPS, Subpart OOOO)
<input checked="" type="checkbox"/> Section 8.0	Control Devices and Emission Reduction Devices not subject to NSPS Subpart OOOO and/or NESHAP Subpart HH
<input checked="" type="checkbox"/> Section 9.0	Small Heaters and Reboilers not subject to 40CFR60 Subpart Dc
<input type="checkbox"/> Section 10.0	Pneumatic Controllers Affected Facility (NSPS, Subpart OOOO)
<input type="checkbox"/> Section 11.0	Centrifugal Compressor Affected Facility (NSPS, Subpart OOOO) ²
<input type="checkbox"/> Section 12.0	Reciprocating Compressor Affected Facility (NSPS, Subpart OOOO) ²
<input checked="" type="checkbox"/> Section 13.0	Reciprocating Internal Combustion Engines, Generator Engines, Microturbines
<input checked="" type="checkbox"/> Section 14.0	Tanker Truck Loading ³
<input type="checkbox"/> Section 15.0	Glycol Dehydration Units ⁴

- 1 Applicants that are subject to Section 6 may also be subject to Section 7 if the applicant is subject to the NSPS, Subpart OOOO control requirements or the applicable control device requirements of Section 8.
- 2 Applicants that are subject to Section 11 and 12 may also be subject to the applicable RICE requirements of Section 13.
- 3 Applicants that are subject to Section 14 may also be subject to control device and emission reduction device requirements of Section 8.
- 4 Applicants that are subject to Section 15 may also be subject to the requirements of Section 9 (reboilers). Applicants that are subject to Section 15 may also be subject to control device and emission reduction device requirements of Section 8.

Attachment I

EMISSION UNITS / EMISSION REDUCTION DEVICES (ERD) TABLE

ATTACHMENT I – EMISSION UNITS / EMISSION REDUCTION DEVICES (ERD) TABLE

Include ALL emission units and air pollution control devices/ERDs that will be part of this permit application review. Do not include fugitive emission sources in this table. Deminimis storage tanks shall be listed in the Attachment L table. This information is required for all sources regardless of whether it is a construction, modification, or administrative update.

Emission Unit ID ¹	Emission Point ID ²	Emission Unit Description	Year Installed	Manufac. Date ³	Design Capacity	Type ⁴ and Date of Change	Control Device(s) ⁵	ERD(s) ⁶
S001	E001	Line Heater	2015	2015	1.54 mmBtu/hr	Existing	NA	NA
S002	E002	Line Heater	2015	2015	1.54 mmBtu/hr	Existing	NA	NA
S003	E003	Line Heater	2015	2015	1.54 mmBtu/hr	Existing	NA	NA
S004	E004	Line Heater	2015	2015	1.54 mmBtu/hr	Existing	NA	NA
S005	E005	Line Heater	2015	2015	1.54 mmBtu/hr	Existing	NA	NA
S006	E006	Line Heater	2015	2015	1.54 mmBtu/hr	Existing	NA	NA
S007	E007	Line Heater	2015	2015	1.54 mmBtu/hr	Existing	NA	NA
S008	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S009	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S010	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S011	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S012	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S013	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S014	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S015	E018 E019	Produced Fluid Tank	2015	2015	400 bbl	Modification	C018 C019	NA
S016	E018 E019	Sand Trap Blow Tank	2015	2015	140 bbl	Modification	C018 C019	NA
S017	E017 E018 E019	Tank Truck Loading Rack	2015	2015	28,980 gal/day	Modification	NA	NA
C018	E018	Enclosed Combustion Device	2015	2015	11.66 mmBtu/hr	Modification	NA	NA
C019	E019	Enclosed Combustion Device	2015	2015	11.66 mmBtu/hr	Modification	NA	NA

S020	E020	Thermal Electric Generator	2015	2015	0.013 mmBtu/hr	Existing	NA	NA
S021	E021	Thermal Electric Generator	2015	2015	0.013 mmBtu/hr	Existing	NA	NA
S022	E022	Compressor Engine	2016	2015	110 bhp	New	NA	Non-Selective Catalytic Reduction
S023	E023	Line Heater	2016	2015	1.15 mmBtu/hr	New	NA	NA

¹ For Emission Units (or Sources) use the following numbering system: 1S, 2S, 3S,... or other appropriate designation.

² For Emission Points use the following numbering system: 1E, 2E, 3E, ... or other appropriate designation.

³ When required by rule

⁴ New, modification, removal, existing

⁵ For Control Devices use the following numbering system: 1C, 2C, 3C,... or other appropriate designation.

⁶ For ERDs use the following numbering system: 1D, 2D, 3D,... or other appropriate designation.

Attachment J

FUGITIVE EMISSIONS SUMMARY SHEET

ATTACHMENT J – FUGITIVE EMISSIONS SUMMARY SHEET

Sources of fugitive emissions may include loading operations, equipment leaks, blowdown emissions, etc.
Use extra pages for each associated source or equipment if necessary.

Source/Equipment: **Facility Wide**

Leak Detection Method Used		<input type="checkbox"/> Audible, visual, and olfactory (AVO) inspections	<input type="checkbox"/> Infrared (FLIR) cameras	<input checked="" type="checkbox"/> Other (please describe) Permittee will follow section 4.1.4 in issued permit.	<input type="checkbox"/> None required		
Component Type	Closed Vent System	Count	Source of Leak Factors (EPA, other (specify))	Stream type (gas, liquid, etc.)	Estimated Emissions (tpy)		
					VOC	HAP	GHG (CO ₂ e)
Pumps	<input type="checkbox"/> Yes <input type="checkbox"/> No			<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both			
Valves	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	296	EPA, 40 CFR 98 Subpart W	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	0.30	0.05	28.38
Safety Relief Valves	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	8	EPA, 40 CFR 98 Subpart W	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	0.01	<0.01	1.14
Open Ended Lines	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	20	EPA, 40 CFR 98 Subpart W	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	0.04	<0.01	4.22
Sampling Connections	<input type="checkbox"/> Yes <input type="checkbox"/> No			<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both			
Connections (Not sampling)	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	1,296	EPA, 40 CFR 98 Subpart W	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both	0.14	0.02	13.81
Compressors	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	1	EPA, 40 CFR 98 Subpart W Table W-1B: Default average component counts are used for major equipment. Compressor components (12 valves and 57 connections) are included in valve and connection counts.	<input checked="" type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both			
Flanges	<input type="checkbox"/> Yes <input type="checkbox"/> No			<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both			
Other ¹	<input type="checkbox"/> Yes <input type="checkbox"/> No			<input type="checkbox"/> Gas <input type="checkbox"/> Liquid <input type="checkbox"/> Both			

¹ Other equipment types may include compressor seals, relief valves, diaphragms, drains, meters, etc.

Please provide an explanation of the sources of fugitive emissions (e.g. pigging operations, equipment blowdowns, pneumatic controllers, etc.):
Fugitive emissions occur from sealed surfaces associated with production equipment, including equipment leaks.

Please indicate if there are any closed vent bypasses (include component):

NA

Specify all equipment used in the closed vent system (e.g. VRU, ERD, thief hatches, tanker truck loading, etc.)

NA

Attachment K

GAS WELL AFFECTED FACILITY DATA SHEET

ATTACHMENT K – GAS WELL AFFECTED FACILITY DATA SHEET

Complete this data sheet if you are the owner or operator of a gas well affected facility for which construction, modification or reconstruction commenced after August 23, 2011. This form must be completed for natural gas well affected facilities regardless of when flowback operations occur (or have occurred).

API Number	Date of Flowback	Date of Well Completion	Green Completion and/or Combustion Device
047-017-06503			Green Completion
047-017-06502			Green Completion
047-017-06504			Green Completion
047-017-06505			Green Completion
047-017-06506			Green Completion
047-017-06507			Green Completion
TBD			

Note: If future wells are planned and no API number is available please list as PLANNED. If there are existing wells that commenced construction prior to August 23, 2011, please acknowledge as existing.

This is the same API (American Petroleum Institute) well number(s) provided in the well completion notification and as provided to the WVDEP, Office of Oil and Gas for the well permit. The API number may be provided on the application without the state code (047).

Every oil and gas well permitted in West Virginia since 1929 has been issued an API number. This API is used by agencies to identify and track oil and gas wells.

The API number has the following format: 047-001-00001

Where,

*047 = State code. The state code for WV is 047.
 001 = County Code. County codes are odd numbers, beginning with 001 (Barbour) and continuing to 109 (Wyoming).
 00001= Well number. Each well will have a unique well number.*

Attachment L
STORAGE VESSEL DATA SHEET

ATTACHMENT L – STORAGE VESSEL DATA SHEET

GENERAL INFORMATION (REQUIRED)

1. Bulk Storage Area Name OXF-122 Storage Tank Area	2. Tank Name Produced Fluid Tanks (S011-S016)
3. Emission Unit ID number S011 – S016	4. Emission Point ID number E019 or E020
5. Date Installed , Modified or Relocated (<i>for existing tanks</i>) Anticipated 6/2016 Was the tank manufactured after August 23, 2011? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	6. Type of change: <input type="checkbox"/> New construction <input type="checkbox"/> New stored material <input checked="" type="checkbox"/> Other <input type="checkbox"/> Relocation
7A. Description of Tank Modification (<i>if applicable</i>) Addition of upstream low pressure separator.	
7B. Will more than one material be stored in this tank? <i>If so, a separate form must be completed for each material.</i> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
7C. Was USEPA Tanks simulation software utilized? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>If Yes, please provide the appropriate documentation and items 8-42 below are not required.</i>	

TANK INFORMATION

8. Design Capacity (<i>specify barrels or gallons</i>). Use the internal cross-sectional area multiplied by internal height. 16,800 gallons	
9A. Tank Internal Diameter (ft.) 12	9B. Tank Internal Height (ft.) 20
10A. Maximum Liquid Height (ft.) 20	10B. Average Liquid Height (ft.) 10
11A. Maximum Vapor Space Height (ft.) 20	11B. Average Vapor Space Height (ft.) 10
12. Nominal Capacity (<i>specify barrels or gallons</i>). This is also known as “working volume”. 16,800 gallons	
13A. Maximum annual throughput (gal/yr) 28,769,597	13B. Maximum daily throughput (gal/day) 78,821
14. Number of tank turnovers per year 1,713	15. Maximum tank fill rate (gal/min) 54.74
16. Tank fill method <input type="checkbox"/> Submerged <input type="checkbox"/> Splash <input checked="" type="checkbox"/> Bottom Loading	
17. Is the tank system a variable vapor space system? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If yes, (A) What is the volume expansion capacity of the system (gal)? (B) What are the number of transfers into the system per year?	
18. Type of tank (check all that apply): <input checked="" type="checkbox"/> Fixed Roof <input checked="" type="checkbox"/> vertical <input type="checkbox"/> horizontal <input type="checkbox"/> flat roof <input checked="" type="checkbox"/> cone roof <input type="checkbox"/> dome roof <input type="checkbox"/> other (describe) <input type="checkbox"/> External Floating Roof <input type="checkbox"/> pontoon roof <input type="checkbox"/> double deck roof <input type="checkbox"/> Domed External (or Covered) Floating Roof <input type="checkbox"/> Internal Floating Roof <input type="checkbox"/> vertical column support <input type="checkbox"/> self-supporting <input type="checkbox"/> Variable Vapor Space <input type="checkbox"/> lifter roof <input type="checkbox"/> diaphragm <input type="checkbox"/> Pressurized <input type="checkbox"/> spherical <input type="checkbox"/> cylindrical <input type="checkbox"/> Other (describe)	

PRESSURE/VACUUM CONTROL DATA

19. Check as many as apply:	
<input type="checkbox"/> Does Not Apply	<input type="checkbox"/> Rupture Disc (psig)
<input type="checkbox"/> Inert Gas Blanket of _____	<input type="checkbox"/> Carbon Adsorption ¹
<input checked="" type="checkbox"/> Vent to Vapor Combustion Device ¹ (vapor combustors, flares, thermal oxidizers, enclosed combustors)	
<input type="checkbox"/> Conservation Vent (psig)	<input type="checkbox"/> Condenser ¹
Vacuum Setting	Pressure Setting
<input checked="" type="checkbox"/> Emergency Relief Valve (psig)	
-0.5 oz Vacuum Setting 14.4 oz Pressure Setting	
<input type="checkbox"/> Thief Hatch Weighted <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No - A lock down screw hatch will be installed instead of Thief Hatch.	
¹ Complete appropriate Air Pollution Control Device Sheet	

20. Expected Emission Rate (submit Test Data or Calculations here or elsewhere in the application).									
Material Name	Flashing Loss		Breathing Loss		Working Loss		Total Emissions Loss		Estimation Method ¹
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	
Produced Fluid (Pre-Control)	136.38	597.34	0.02	0.07	0.10	0.43	136.49	597.84	O - ProMax

¹ EPA = EPA Emission Factor, MB = Material Balance, SS = Similar Source, ST = Similar Source Test, Throughput Data, O = Other (specify)
Remember to attach emissions calculations, including TANKS Summary Sheets and other modeling summary sheets if applicable.

TANK CONSTRUCTION AND OPERATION INFORMATION			
21. Tank Shell Construction: <input type="checkbox"/> Riveted <input type="checkbox"/> Gunitite lined <input type="checkbox"/> Epoxy-coated rivets <input checked="" type="checkbox"/> Other (describe) WELDED			
21A. Shell Color: Green		21B. Roof Color: Green	
21C. Year Last Painted: NA			
22. Shell Condition (if metal and unlined): <input checked="" type="checkbox"/> No Rust <input type="checkbox"/> Light Rust <input type="checkbox"/> Dense Rust <input type="checkbox"/> Not applicable			
22A. Is the tank heated? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		22B. If yes, operating temperature:	
22C. If yes, how is heat provided to tank?			
23. Operating Pressure Range (psig): Must be listed for tanks using VRUs with closed vent system.			
24. Is the tank a Vertical Fixed Roof Tank ? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		24A. If yes, for dome roof provide radius (ft):	
		24B. If yes, for cone roof, provide slop (ft/ft): 0.06	
25. Complete item 25 for Floating Roof Tanks <input type="checkbox"/> Does not apply <input checked="" type="checkbox"/>			
25A. Year Internal Floaters Installed:			
25B. Primary Seal Type (check one): <input type="checkbox"/> Metallic (mechanical) shoe seal <input type="checkbox"/> Liquid mounted resilient seal <input type="checkbox"/> Vapor mounted resilient seal <input type="checkbox"/> Other (describe):			
25C. Is the Floating Roof equipped with a secondary seal? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25D. If yes, how is the secondary seal mounted? (check one) <input type="checkbox"/> Shoe <input type="checkbox"/> Rim <input type="checkbox"/> Other (describe):			
25E. Is the floating roof equipped with a weather shield? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25F. Describe deck fittings:			
26. Complete the following section for Internal Floating Roof Tanks <input checked="" type="checkbox"/> Does not apply			
26A. Deck Type: <input type="checkbox"/> Bolted <input type="checkbox"/> Welded		26B. For bolted decks, provide deck construction:	
26C. Deck seam. Continuous sheet construction: <input type="checkbox"/> 5 ft. wide <input type="checkbox"/> 6 ft. wide <input type="checkbox"/> 7 ft. wide <input type="checkbox"/> 5 x 7.5 ft. wide <input type="checkbox"/> 5 x 12 ft. wide <input type="checkbox"/> other (describe)			
26D. Deck seam length (ft.):		26E. Area of deck (ft ²):	
		26F. For column supported tanks, # of columns:	
		26G. For column supported tanks, diameter of column:	
27. Closed Vent System with VRU? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
28. Closed Vent System with Enclosed Combustor? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			
SITE INFORMATION			
29. Provide the city and state on which the data in this section are based: Charleston, WV			
30. Daily Avg. Ambient Temperature (°F): 70.0		31. Annual Avg. Maximum Temperature (°F): 65.5	
32. Annual Avg. Minimum Temperature (°F): 44.0		33. Avg. Wind Speed (mph): 18 mph	
34. Annual Avg. Solar Insulation Factor (BTU/ft ² -day): 1,123		35. Atmospheric Pressure (psia): 14.7 (Atmosphere)	
LIQUID INFORMATION			
36. Avg. daily temperature range of bulk liquid (°F): 82.9		36A. Minimum (°F): 82.9	
		36B. Maximum (°F): 82.9	
37. Avg. operating pressure range of tank (psig): 0 psig		37A. Minimum (psig): 0 psig	
		37B. Maximum (psig): 0 psig	

38A. Minimum liquid surface temperature (°F): 82.9	38B. Corresponding vapor pressure (psia): 0.43
39A. Avg. liquid surface temperature (°F): 82.9	39B. Corresponding vapor pressure (psia): 0.43
40A. Maximum liquid surface temperature (°F): 82.9	40B. Corresponding vapor pressure (psia): 0.43
41. Provide the following for each liquid or gas to be stored in the tank. Add additional pages if necessary.	
41A. Material name and composition:	Produced Fluid
41B. CAS number:	
41C. Liquid density (lb/gal):	7.9
41D. Liquid molecular weight (lb/lb-mole):	19.68
41E. Vapor molecular weight (lb/lb-mole):	
41F. Maximum true vapor pressure (psia):	
41G. Maximum Reid vapor pressure (psia):	
41H. Months Storage per year.	From: January To: December
42. Final maximum gauge pressure and temperature prior to transfer into tank used as inputs into flashing emission calculations.	30 psig 110 F

STORAGE TANK DATA TABLE

List all deminimis storage tanks (i.e. lube oil, glycol, diesel etc.)

Source ID # ¹	Status ²	Content ³	Volume ⁴
NA	NA	NA	NA

1. Enter the appropriate Source Identification Numbers (Source ID #) for each storage tank located at the compressor station. Tanks should be designated T01, T02, T03, etc.
2. Enter storage tank Status using the following:
 EXIST Existing Equipment
 NEW Installation of New Equipment
 REM Equipment Removed
3. Enter storage tank content such as condensate, pipeline liquids, glycol (DEG or TEG), lube oil, diesel, mercaptan etc.
4. Enter the maximum design storage tank volume in gallons.

ATTACHMENT L – STORAGE VESSEL DATA SHEET

GENERAL INFORMATION (REQUIRED)

1. Bulk Storage Area Name OXF-122 Storage Tank Area	2. Tank Name Sand Trap Blowdown Tank
3. Emission Unit ID number S017	4. Emission Point ID number E019 or E020
5. Date Installed , Modified or Relocated (<i>for existing tanks</i>) Anticipated 06/2016 Was the tank manufactured after August 23, 2011? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	6. Type of change: <input type="checkbox"/> New construction <input type="checkbox"/> New stored material <input checked="" type="checkbox"/> Other <input type="checkbox"/> Relocation
7A. Description of Tank Modification (<i>if applicable</i>) Addition of low pressure separator.	
7B. Will more than one material be stored in this tank? <i>If so, a separate form must be completed for each material.</i> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
7C. Was USEPA Tanks simulation software utilized? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>If Yes, please provide the appropriate documentation and items 8-42 below are not required.</i>	

TANK INFORMATION

8. Design Capacity (<i>specify barrels or gallons</i>). Use the internal cross-sectional area multiplied by internal height. 5,880 gallons	
9A. Tank Internal Diameter (ft.) 10	9B. Tank Internal Height (ft.) 10
10A. Maximum Liquid Height (ft.) 8	10B. Average Liquid Height (ft.) 5
11A. Maximum Vapor Space Height (ft.) 8	11B. Average Vapor Space Height (ft.) 5
12. Nominal Capacity (<i>specify barrels or gallons</i>). This is also known as “working volume”. 5,880 gallons	
13A. Maximum annual throughput (gal/yr) 306,600	13B. Maximum daily throughput (gal/day) 840
14. Number of tank turnovers per year 52	15. Maximum tank fill rate (gal/min) 4.1
16. Tank fill method <input type="checkbox"/> Submerged <input type="checkbox"/> Splash <input checked="" type="checkbox"/> Bottom Loading	
17. Is the tank system a variable vapor space system? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If yes, (A) What is the volume expansion capacity of the system (gal)? (B) What are the number of transfers into the system per year?	
18. Type of tank (check all that apply): <input checked="" type="checkbox"/> Fixed Roof <input type="checkbox"/> vertical <input checked="" type="checkbox"/> horizontal <input type="checkbox"/> flat roof <input type="checkbox"/> cone roof <input type="checkbox"/> dome roof <input type="checkbox"/> other (describe) <input type="checkbox"/> External Floating Roof <input type="checkbox"/> pontoon roof <input type="checkbox"/> double deck roof <input type="checkbox"/> Domed External (or Covered) Floating Roof <input type="checkbox"/> Internal Floating Roof <input type="checkbox"/> vertical column support <input type="checkbox"/> self-supporting <input type="checkbox"/> Variable Vapor Space <input type="checkbox"/> lifter roof <input type="checkbox"/> diaphragm <input type="checkbox"/> Pressurized <input type="checkbox"/> spherical <input type="checkbox"/> cylindrical <input type="checkbox"/> Other (describe)	

PRESSURE/VACUUM CONTROL DATA

19. Check as many as apply:	
<input type="checkbox"/> Does Not Apply	<input type="checkbox"/> Rupture Disc (psig)
<input type="checkbox"/> Inert Gas Blanket of _____	<input type="checkbox"/> Carbon Adsorption ¹
<input checked="" type="checkbox"/> Vent to Vapor Combustion Device ¹ (vapor combustors, flares, thermal oxidizers, enclosed combustors)	
<input type="checkbox"/> Conservation Vent (psig)	<input type="checkbox"/> Condenser ¹
Vacuum Setting Pressure Setting	
<input checked="" type="checkbox"/> Emergency Relief Valve (psig)	
-0.5 oz Vacuum Setting 14.4 oz Pressure Setting	
<input type="checkbox"/> Thief Hatch Weighted <input type="checkbox"/> Yes <input type="checkbox"/> No - Two (2) emergency hatches set at 16 oz	

¹ Complete appropriate Air Pollution Control Device Sheet

20. Expected Emission Rate (submit Test Data or Calculations here or elsewhere in the application).

Material Name	Flashing Loss		Breathing Loss		Working Loss		Total Emissions Loss		Estimation Method ¹
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	
Produced Fluid (Pre control)	5.49	1.00	<0.01	<0.01	<0.01	<0.01	5.50	1.00	EPA - ProMax

¹ EPA = EPA Emission Factor, MB = Material Balance, SS = Similar Source, ST = Similar Source Test, Throughput Data, O = Other (specify)
Remember to attach emissions calculations, including TANKS Summary Sheets and other modeling summary sheets if applicable.

TANK CONSTRUCTION AND OPERATION INFORMATION			
21. Tank Shell Construction: <input type="checkbox"/> Riveted <input type="checkbox"/> Gunitite lined <input type="checkbox"/> Epoxy-coated rivets <input checked="" type="checkbox"/> Other (describe) WELDED			
21A. Shell Color: Green	21B. Roof Color: Green	21C. Year Last Painted: NA	
22. Shell Condition (if metal and unlined): <input checked="" type="checkbox"/> No Rust <input type="checkbox"/> Light Rust <input type="checkbox"/> Dense Rust <input type="checkbox"/> Not applicable			
22A. Is the tank heated? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	22B. If yes, operating temperature:	22C. If yes, how is heat provided to tank?	
23. Operating Pressure Range (psig): Must be listed for tanks using VRUs with closed vent system.			
24. Is the tank a Vertical Fixed Roof Tank ? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	24A. If yes, for dome roof provide radius (ft): 5 ft.	24B. If yes, for cone roof, provide slop (ft/ft): NA	
25. Complete item 25 for Floating Roof Tanks <input type="checkbox"/> Does not apply <input checked="" type="checkbox"/>			
25A. Year Internal Floaters Installed:			
25B. Primary Seal Type (check one): <input type="checkbox"/> Metallic (mechanical) shoe seal <input type="checkbox"/> Liquid mounted resilient seal <input type="checkbox"/> Vapor mounted resilient seal <input type="checkbox"/> Other (describe):			
25C. Is the Floating Roof equipped with a secondary seal? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25D. If yes, how is the secondary seal mounted? (check one) <input type="checkbox"/> Shoe <input type="checkbox"/> Rim <input type="checkbox"/> Other (describe):			
25E. Is the floating roof equipped with a weather shield? <input type="checkbox"/> Yes <input type="checkbox"/> No			
25F. Describe deck fittings:			
26. Complete the following section for Internal Floating Roof Tanks <input checked="" type="checkbox"/> Does not apply			
26A. Deck Type: <input type="checkbox"/> Bolted <input type="checkbox"/> Welded		26B. For bolted decks, provide deck construction:	
26C. Deck seam. Continuous sheet construction: <input type="checkbox"/> 5 ft. wide <input type="checkbox"/> 6 ft. wide <input type="checkbox"/> 7 ft. wide <input type="checkbox"/> 5 x 7.5 ft. wide <input type="checkbox"/> 5 x 12 ft. wide <input type="checkbox"/> other (describe)			
26D. Deck seam length (ft.):	26E. Area of deck (ft ²):	26F. For column supported tanks, # of columns:	26G. For column supported tanks, diameter of column:
27. Closed Vent System with VRU? <input type="checkbox"/> Yes <input type="checkbox"/> No			
28. Closed Vent System with Enclosed Combustor? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			
SITE INFORMATION			
29. Provide the city and state on which the data in this section are based: Charleston, WV			

30. Daily Avg. Ambient Temperature (°F): 70 °F		31. Annual Avg. Maximum Temperature (°F): 65.5 °F	
32. Annual Avg. Minimum Temperature (°F): 44 °F		33. Avg. Wind Speed (mph): 18 mph	
34. Annual Avg. Solar Insulation Factor (BTU/ft ² -day): 1,123		35. Atmospheric Pressure (psia): 14.70	
LIQUID INFORMATION			
36. Avg. daily temperature range of bulk liquid (°F): 79.6		36A. Minimum (°F): 79.6	
		36B. Maximum (°F): 79.6	
37. Avg. operating pressure range of tank (psig): 0.0 (atmospheric)		37A. Minimum (psig): 0.0 (atmospheric)	
		37B. Maximum (psig): 0.0 (atmospheric)	
38A. Minimum liquid surface temperature (°F): 79.6		38B. Corresponding vapor pressure (psia): 0.59	
39A. Avg. liquid surface temperature (°F): 79.6		39B. Corresponding vapor pressure (psia): 0.59	
40A. Maximum liquid surface temperature (°F): 79.6		40B. Corresponding vapor pressure (psia): 0.59	
41. Provide the following for each liquid or gas to be stored in the tank. Add additional pages if necessary.			
41A. Material name and composition:		Produced Fluid	
41B. CAS number:			
41C. Liquid density (lb/gal):		6.83	
41D. Liquid molecular weight (lb/lb-mole):		21.72	
41E. Vapor molecular weight (lb/lb-mole):		37.33	
41F. Maximum true vapor pressure (psia):			
41G. Maximum Reid vapor pressure (psia):			
41H. Months Storage per year.		From: January To: December	
42. Final maximum gauge pressure and temperature prior to transfer into tank used as inputs into flashing emission calculations.		85.0 F 393 psig	

Gas Analytical Services

Tulsa, OK
918-827-5770

Customer : 01 - GAS ANALYTICAL SERVICES-MOUNDS	Date Sampled : 10/23/2015
Station Id : 513700	Date Analyzed : 11/05/2015
Cylinder Id : 32	Effective Date : 11/01/2015
Producer : EQT PRODUCTION	Line Pressure : 0.00000
Lease : MAXWELL OXF 159 PAD	Cyl Pressure : 750.00000
Area : MGM D	Temp : 0.00000
Sample By : R MOORE	Cylinder Type : Spot
Property Cd :	Formation :

COMPONENT		Mole Percent	WT. Percent	Liq Vol Percent
Methane	C1	12.0883	2.0724	4.7592
Ethane	C2	7.8631	2.5267	4.8832
Propane	C3	5.5315	2.6066	3.5391
Iso-Butane	IC4	1.3547	0.8414	1.0295
Normal-Butane	NC4	3.4686	2.1544	2.5395
Iso-Pentane	IC5	1.6931	1.3054	1.4377
Normal-Pentane	NC5	2.0423	1.5747	1.7190
Nitrogen	N2	0.0061	0.0018	0.0011
Carbon-Dioxide	CO2	0.2444	0.1149	0.0964
BENZENE	BENZENE	0.1502	0.1254	0.0970
TOLUENE	TOLUENE	0.7588	0.7471	0.5896
ETHYLBENZENE	E-BENZENE	0.0943	0.1069	0.0843
M-XYLENE/P-XYLENE	M-XYLENE/P-XYLENE	0.8104	0.9195	0.7279
C6's	C6's	11.2622	10.3718	10.7630
C7's	C7's	14.0473	19.0341	18.1088
C8's	C8's	7.5660	9.0859	8.7701
C9's	C9's	6.9027	9.1020	8.4661
C10's	C10's	3.4358	4.7876	4.2595
C11's	C11's	10.0244	14.4992	11.9130
C12's	C12's	9.0484	14.8557	13.3497
C13's	C13's	1.6071	3.1664	2.8662
TOTAL		99.9997	100.0000	100.0000

Totals

SPECIFIC GRAVITY @ 60 DEG. F. (WATER = 1)	0.6883
MOLECULAR WEIGHT	93.5782

Comments:

POUNDS/GALLON (ABSOLUTE DENSITY)	5.7385
CALC. VAPOR PRESSURE @ 14.65 PSIA, 100 Deg. F.	670.8797
CUFT. VAPOR / GALLON @ 14.65 PSIA, 60 Deg. G.	23.4174
BTU / CUFT. DRY GAS @ 14.65 PSIA, 60 Deg. F.	4,864.3860
BTU / GALLON LIQUID	117,559.7344
BTU / POUND	20,382.0537

Comments:

Gas Analytical

Report Date: Sep 14, 2015 9:23a

Client:	Equitable Production	Date Sampled:	Sep 8, 2015 11:00a
Site:	514394	Analysis Date:	Sep 11, 2015 2:17p
Field No:	9998	Collected By:	J. Brown
Meter:	514394	Date Effective:	Sep 8, 2015 12:00a
Source Laboratory	Clarksburg (Bridgeport), WV	Sample Pressure (PSI):	70.0
Lab File No:	X_CH1-6024.CHR	Sample Temp (°F):	
Sample Type:	Spot	Field H2O:	No Test
Reviewed By:		Field H2S:	No Test

Component	Mol %	Gal/MSCF
Methane	78.1311	
Ethane	14.2559	3.79
Propane	4.0036	1.10
I-Butane	0.5947	0.19
N-Butane	1.1890	0.37
I-Pentane	0.3163	0.12
N-Pentane	0.3248	0.12
Nitrogen	0.4544	
Oxygen	<MDL	
Carbon Dioxide	0.1535	
Hexanes+	0.5767	0.24
TOTAL	100.0000	5.93

Analytical Results at Base Conditions (Real)	
BTU/SCF (Dry):	1,262.4954 BTU/ft ³
BTU/SCF (Saturated):	1,241.4002 BTU/ft ³
PSIA:	14.730 PSI
Temperature (°F):	60.00 °F
Z Factor (Dry):	0.99644
Z Factor (Saturated):	0.99604

Analytical Results at Contract Conditions (Real)	
BTU/SCF (Dry):	1,262.4954 BTU/ft ³
BTU/SCF (Saturated):	1,241.4002 BTU/ft ³
PSIA:	14.730 PSI
Temperature (°F):	60.00 °F
Z Factor (Dry):	0.99644
Z Factor (Saturated):	0.99604

Calculated Specific Gravities		
Ideal Gravity:	0.7188	Real Gravity: 0.7211
Molecular Wt:	20.8177 lb/lbmol	

Gross Heating Values are Based on:
 GPA 2145-09, 2186
 Compressibility is Calculated using AGA-8.

Source	Date	Notes
Gas Analytical	Sep 11, 2015	results to Bob Gum

Attachment M

**HEATER AND REBOILERS NOT SUBJECT TO
40CFR60 SUBPART Dc**

**ATTACHMENT M – SMALL HEATERS AND REBOILERS NOT SUBJECT TO
40CFR60 SUBPART DC
DATA SHEET**

Complete this data sheet for each small heater and reboiler not subject to 40CFR60 Subpart Dc at the facility. *The Maximum Design Heat Input (MDHI) must be less than 10 MMBTU/hr.*

Emission Unit ID# ¹	Emission Point ID# ²	Emission Unit Description (manufacturer, model #)	Year Installed/Modified	Type ³ and Date of Change	Maximum Design Heat Input (MMBTU/hr) ⁴	Fuel Heating Value (BTU/scf) ⁵
S001	E001	Line Heater	2015	Existing	1.54	1,262
S002	E002	Line Heater	2015	Existing	1.54	1,262
S003	E003	Line Heater	2015	Existing	1.54	1,262
S004	E004	Line Heater	2015	Existing	1.54	1,262
S005	E005	Line Heater	2015	Existing	1.54	1,262
S006	E006	Line Heater	2015	Existing	1.54	1,262
S007	E007	Line Heater	2015	Existing	1.54	1,262
S020	E020	Thermal Electric Generator	2015	Existing	0.013	1,262
S021	E021	Thermal Electric Generator	2015	Existing	0.013	1,262
S023	E023	Line Heater	2016	New	1.15	1,262

¹ Enter the appropriate Emission Unit (or Source) identification number for each fuel burning unit located at the production pad. Gas Producing Unit Burners should be designated GPU-1, GPU-2, etc. Heater Treaters should be designated HT-1, HT-2, etc. Heaters or Line Heaters should be designated LH-1, LH-2, etc. For sources, use 1S, 2S, 3S...or other appropriate designation. Enter glycol dehydration unit Reboiler Vent data on the Glycol Dehydration Unit Data Sheet.

² Enter the appropriate Emission Point identification numbers for each fuel burning unit located at the production pad. Gas Producing Unit Burners should be designated GPU-1, GPU-2, etc. Heater Treaters should be designated HT-1, HT-2, etc. Heaters or Line Heaters should be designated LH-1, LH-2, etc. For emission points, use 1E, 2E, 3E...or other appropriate designation.

³ New, modification, removal

⁴ Enter design heat input capacity in MMBtu/hr.

⁵ Enter the fuel heating value in BTU/standard cubic foot.

Attachment N

INTERNAL COMBUSTION ENGINE DATA SHEET

ATTACHMENT N – INTERNAL COMBUSTION ENGINE DATA SHEET

Complete this data sheet for each internal combustion engine at the facility. Include manufacturer performance data sheet(s) or any other supporting document if applicable. Use extra pages if necessary. *Generator(s) and microturbine generator(s) shall also use this form.*

Emission Unit ID# ¹		S022					
Engine Manufacturer/Model		Ford / CSG-637					
Manufacturers Rated bhp/rpm		110 / 3200					
Source Status ²		NS					
Date Installed/ Modified/Removed/Relocated ³		06/01/2016					
Engine Manufactured /Reconstruction Date ⁴		2015					
Check all applicable Federal Rules for the engine (include EPA Certificate of Conformity if applicable) ⁵		<input checked="" type="checkbox"/> 40CFR60 Subpart JJJ <input checked="" type="checkbox"/> JJJ Certified? <input type="checkbox"/> 40CFR60 Subpart IIII <input type="checkbox"/> IIII Certified? <input type="checkbox"/> 40CFR63 Subpart ZZZZ <input type="checkbox"/> NESHAP ZZZZ/ NSPS JJJJ Window <input type="checkbox"/> NESHAP ZZZZ Remote Sources		<input type="checkbox"/> 40CFR60 Subpart JJJ <input type="checkbox"/> JJJ Certified? <input type="checkbox"/> 40CFR60 Subpart IIII <input type="checkbox"/> IIII Certified? <input type="checkbox"/> 40CFR63 Subpart ZZZZ <input type="checkbox"/> NESHAP ZZZZ/ NSPS JJJJ Window <input type="checkbox"/> NESHAP ZZZZ Remote Sources		<input type="checkbox"/> 40CFR60 Subpart JJJ <input type="checkbox"/> JJJ Certified? <input type="checkbox"/> 40CFR60 Subpart IIII <input type="checkbox"/> IIII Certified? <input type="checkbox"/> 40CFR63 Subpart ZZZZ <input type="checkbox"/> NESHAP ZZZZ/ NSPS JJJJ Window <input type="checkbox"/> NESHAP ZZZZ Remote Sources	
Engine Type ⁶		4SRB					
APCD Type ⁷		NSCR					
Fuel Type ⁸		PQ					
H ₂ S (gr/100 scf)		0.25					
Operating bhp/rpm		110 / 3,200					
BSFC (BTU/bhp-hr)		6,552.9					
Hourly Fuel Throughput		686.5	ft ³ /hr gal/hr		ft ³ /hr gal/hr		ft ³ /hr gal/hr
Annual Fuel Throughput (Must use 8,760 hrs/yr unless emergency generator)		6.01	MMft ³ /yr gal/yr		MMft ³ /yr gal/yr		MMft ³ /yr gal/yr
Fuel Usage or Hours of Operation Metered		Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>		Yes <input type="checkbox"/> No <input type="checkbox"/>		Yes <input type="checkbox"/> No <input type="checkbox"/>	
Calculation Methodology ⁹	Pollutant ¹⁰	Hourly PTE (lb/hr) ¹¹	Annual PTE (tons/year) ¹¹	Hourly PTE (lb/hr) ¹¹	Annual PTE (tons/year) ¹¹	Hourly PTE (lb/hr) ¹¹	Annual PTE (tons/year) ¹¹
MD	NO _x	0.42	1.85				
MD	CO	0.88	3.85				
MD	VOC	0.29	1.29				
AP	SO ₂	<0.01	<0.01				
AP	PM (Filterable)	<0.01	0.03				
AP	PM (Condensable)	<0.01	0.03				
AP	Formaldehyde	0.01	0.06				
AP	Total HAPs	0.02	0.07				
AP	GHG (CO ₂ e)	82.58	361.69				

1 Enter the appropriate Source Identification Number for each natural gas-fueled reciprocating internal combustion compressor/generator engine located at the compressor station. Multiple compressor engines should be designated CE-1, CE-2, CE-3 etc. Generator engines should be designated GE-1, GE-2, GE-3 etc. Microturbine generator engines should be designated MT-1, MT-2, MT-3 etc. If more than three (3) engines exist, please use additional sheets.

2 Enter the Source Status using the following codes:

NS Construction of New Source (installation) ES Existing Source

**Engine Air Pollution Control Device
(Emission Unit ID# E022, use extra pages as necessary)**

Air Pollution Control Device Manufacturer's Data Sheet included?
Yes No

NSCR SCR Oxidation Catalyst

Provide details of process control used for proper mixing/control of reducing agent with gas stream:

Manufacturer: Ford	Model #: CSG-637
---------------------------	-------------------------

Design Operating Temperature: 1,600 °F °F	Design gas volume: scfm
--------------------------------------------------	------------------------------------

Service life of catalyst: 5000 hrs	Provide manufacturer data? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
-------------------------------------------	------------------------------------------------------------------------------------------------

Volume of gas handled: 444.9 cfm at 1,600 °F	Operating temperature range for NSCR/Ox Cat: From °F to °F
------------------------------------------------------------	-------------------------------------------------------------------------------------

Reducing agent used, if any:	Ammonia slip (ppm):
------------------------------	---------------------

Pressure drop against catalyst bed (delta P): **6"** inches of H₂O

Provide description of warning/alarm system that protects unit when operation is not meeting design conditions:

Is temperature and pressure drop of catalyst required to be monitored per 40CFR63 Subpart ZZZZ?
 Yes No

How often is catalyst recommended or required to be replaced (hours of operation)?
5000 hrs

How often is performance test required?

- Initial
- Annual
- Every 8,760 hours of operation
- Field Testing Required
- No performance test required. If so, why (please list any maintenance required and the applicable sections in NSPS/GACT, **40CFR60.4243(a)(1) – EQT must operate and maintain the certified stationary SI internal combustion engine and control device according to the manufacturer's emission-related written instructions, keep records of conducted maintenance to demonstrate compliance, but no performance testing is required.**

EDI Ford Industrial LSI Fuel and Power Figures



CSG637

RPM	Gasoline				LPG				NG				
	Power Cont. [HP]	Power Int. [HP]	BSFC [lb/hp-hr]	Fuel Consumption [gal/hr]	Power Cont. [HP]	Power Int. [HP]	BSFC [lb/hp-hr]	Fuel Consumption [gal/hr]	Power Cont. [HP]	Power Int. [HP]	BSFC [ft ³ /hp-hr]	Fuel Consumption [ft ³ /hr]	Fuel Consumption [btu/hr]
1500	42.3	47.0	0.48	3.7	52.1	57.9	0.34	4.1	47.8	53.1	6.81	361.8	379,914
1600	47.7	53.0	0.45	3.9	56.8	63.2	0.33	4.3	52.4	58.2	6.54	380.9	399,966
1700	52.2	58.0	0.43	4.1	60.0	66.7	0.33	4.6	54.7	60.8	6.58	400.0	420,019
1800	55.0	61.1	0.43	4.2	63.1	70.2	0.33	4.8	57.0	63.3	6.62	419.1	440,071
1900	58.5	65.0	0.42	4.4	66.3	73.7	0.33	5.0	60.1	66.7	6.57	438.2	460,124
2000	61.2	68.0	0.41	4.6	69.5	77.2	0.33	5.2	63.1	70.2	6.52	457.3	480,176
2100	65.7	73.0	0.40	4.7	73.1	81.2	0.33	5.5	66.0	73.4	6.49	476.4	500,229
2200	70.2	78.0	0.39	4.9	76.7	85.2	0.33	5.7	68.9	76.6	6.47	495.5	520,281
2300	74.7	83.0	0.37	5.0	81.1	90.1	0.32	5.9	73.0	81.1	6.34	514.6	540,334
2400	79.2	88.0	0.36	5.2	85.4	94.9	0.32	6.2	77.1	85.6	6.23	533.7	560,386
2500	82.8	92.0	0.35	5.3	89.4	99.3	0.31	6.4	80.7	89.6	6.17	552.8	580,439
2600	85.5	95.0	0.35	5.4	93.3	103.7	0.31	6.6	84.3	93.6	6.11	571.9	600,491
2700	87.3	97.0	0.35	5.5	95.9	106.6	0.31	6.9	87.0	96.6	6.12	591.0	620,544
2800	88.2	98.0	0.35	5.7	98.6	109.5	0.31	7.1	89.7	99.6	6.12	610.1	640,596
2900	89.1	99.0	0.36	5.8	101.0	112.3	0.32	7.3	92.6	102.9	6.11	629.2	660,649
3000	90.9	101.0	0.36	5.9	103.5	115.0	0.32	7.5	95.5	106.1	6.11	648.3	680,701
3100	93.6	104.0	0.35	6.0	104.8	116.5	0.32	7.8	97.3	108.1	6.17	667.4	700,754
3200	96.3	107.0	0.35	6.1	106.1	117.9	0.33	8.0	99.0	110.0	6.24	686.5	720,806

*Fuel Consumption and BSFC listed is 100% Intermittent Load

*Figures are Gross; Fan losses not accounted for.

Attachment O

TANKER TRUCK LOADING DATA SHEET

ATTACHMENT O – TANKER TRUCK LOADING DATA SHEET

Emission Unit ID#: S017	Emission Point ID#: E017, E018, E019	Year Installed/Modified: 2015/2016
--------------------------------	---------------------------------------------	-------------------------------------------

Emission Unit Description: **Tank Truck Loading Rack**

Loading Area Data

Number of Pumps: 1	Number of Liquids Loaded: 1	Max number of trucks loading at one (1) time: 1
---------------------------	------------------------------------	--------------------------------------------------------

Are tanker trucks pressure tested for leaks at this or any other location? Yes No Not Required
 If Yes, Please describe:

Provide description of closed vent system and any bypasses. **Emissions collected and controlled by enclosed combustion device. Bypass is not available.**

Are any of the following truck loadout systems utilized?
 Closed System to tanker truck passing a MACT level annual leak test?
 Closed System to tanker truck passing a NSPS level annual leak test?
 Closed System to tanker truck not passing an annual leak test and has vapor return?

Projected Maximum Operating Schedule (for rack or transfer point as a whole)

Time	Jan – Mar	Apr - Jun	Jul – Sept	Oct - Dec
Hours/day	As needed	As needed	As needed	As needed
Days/week	As needed	As needed	As needed	As needed

Bulk Liquid Data (use extra pages as necessary)

Liquid Name	Produced Fluids		
Max. Daily Throughput (1000 gal/day)	28.98		
Max. Annual Throughput (1000 gal/yr)	10,578		
Loading Method ¹	BF		
Max. Fill Rate (gal/min)	42		
Average Fill Time (min/loading)	100 min		
Max. Bulk Liquid Temperature (°F)	70 °F		
True Vapor Pressure ²	NA		
Cargo Vessel Condition ³	U		
Control Equipment or Method ⁴	Enclosed Combustion Device (C018 or C019)		
Max. Collection Efficiency (%)	70 %		
Max. Control Efficiency (%)	98 %		
Max. VOC Emission Rate	Loading (lb/hr)	0.01	
	Annual (ton/yr)	0.06	
Max. HAP Emission Rate	Loading (lb/hr)	<0.01	
	Annual (ton/yr)	<0.01	
Estimation Method ⁵	EPA AP-42, ProMax		

- | | | | | | | |
|---|-----|---------------------------------------------------------------------------------------------|----|-------------|-----|-----------------------------------------|
| 1 | BF | Bottom Fill | SP | Splash Fill | SUB | Submerged Fill |
| 2 | | At maximum bulk liquid temperature | | | | |
| 3 | B | Ballasted Vessel | C | Cleaned | U | Uncleaned (dedicated service) |
| | O | Other (describe) | | | | |
| 4 | | List as many as apply (complete and submit appropriate Air Pollution Control Device Sheets) | | | | |
| | CA | Carbon Adsorption | | VB | | Dedicated Vapor Balance (closed system) |
| | ECD | Enclosed Combustion Device | | F | | Flare |
| | TO | Thermal Oxidization or Incineration | | | | |
| 5 | EPA | EPA Emission Factor in AP-42 | | | MB | Material Balance |

Attachment Q

PNEUMATIC CONTROLLERS DATA SHEET

**ATTACHMENT Q – PNEUMATIC CONTROLLERS
DATA SHEET**

Are there any continuous bleed natural gas driven pneumatic controllers at this facility that commenced construction, modification or reconstruction after August 23, 2011?

Yes No

Please list approximate number.

Are there any continuous bleed natural gas driven pneumatic controllers at this facility with a bleed rate greater than 6 standard cubic feet per hour that are required based on functional needs, including but not limited to response time, safety and positive actuation that commenced construction, modification or reconstruction after August 23, 2011?

Yes No

Please list approximate number.

Attachment R

**AIR POLLUTION CONTROL DEVICE / EMISSION
REDUCTION DEVICE (ERD) SHEET**

**ATTACHMENT R – AIR POLLUTION CONTROL DEVICE /
EMISSION REDUCTION DEVICE SHEETS**

**VAPOR COMBUSTION
(Including Enclosed Combustors)**

General Information

Control Device ID#: C018	Installation Date: 2015 <input type="checkbox"/> New <input checked="" type="checkbox"/> Modified <input type="checkbox"/> Relocated	
Maximum Rated Total Flow Capacity ~7,800 scfh 188,000 scfd	Maximum Design Heat Input (from mfg. spec sheet) 11.66 MMBTU/hr	Design Heat Content 1,262 BTU/scf

Control Device Information

Type of Vapor Combustion Control?		
<input checked="" type="checkbox"/> Enclosed Combustion Device <input type="checkbox"/> Thermal Oxidizer	<input type="checkbox"/> Elevated Flare	<input type="checkbox"/> Ground Flare
Manufacturer: LEED Fabrication Model: Enclosed Combustor 48"	Hours of operation per year? 8,760	

List the emission units whose emissions are controlled by this vapor control device (Emission Point ID# **S008-S017**)

Emission Unit ID#	Emission Source Description	Emission Unit ID#	Emission Source Description
S008-S015	Produced Fluid Tanks		
S016	Sand Trap Blowdown Tank		
S017	Tank Truck Loading Rack		

If this vapor combustor controls emissions from more than six (6) emission units, please attach additional pages.

Assist Type (Flares only)	Flare Height	Tip Diameter	Was the design per §60.18?
<input type="checkbox"/> Steam <input type="checkbox"/> Air <input type="checkbox"/> Pressure <input checked="" type="checkbox"/> Non	~25 feet	4 feet	<input type="checkbox"/> Yes <input type="checkbox"/> No Provide determination.

Waste Gas Information

Maximum Waste Gas Flow Rate 102.93 (lb/hr)	Heat Value of Waste Gas Stream Variable BTU/ft³	Exit Velocity of the Emissions Stream (ft/s)
------------------------------------------------------	----------------------------------------------------------------------	-------------------------------------------------

Provide an attachment with the characteristics of the waste gas stream to be burned.

Pilot Gas Information

Number of Pilot Lights 1	Fuel Flow Rate to Pilot Flame per Pilot ~30 scfh	Heat Input per Pilot 0.03 BTU/hr	Will automatic re-ignition be used? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
------------------------------------	------------------------------------------------------------	--------------------------------------------	------------------------------------------------------------------------------------------------------------

If automatic re-ignition is used, please describe the method.

Is pilot flame equipped with a monitor to detect the presence of the flame? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If Yes, what type? <input checked="" type="checkbox"/> Thermocouple <input type="checkbox"/> Infrared <input type="checkbox"/> Ultraviolet <input type="checkbox"/> Camera <input type="checkbox"/> Other:
-------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Describe all operating ranges and maintenance procedures required by the manufacturer to maintain the warranty. *(If unavailable, please indicate).* **See attached manufacture specification sheet.**

Additional information attached? Yes No
Please attach copies of manufacturer's data sheets, drawings, flame demonstration per §60.18 or §63.11(b) and performance testing.

VAPOR COMBUSTION (Including Enclosed Combustors)

General Information

Control Device ID#: C019	Installation Date: 2015 <input type="checkbox"/> New <input checked="" type="checkbox"/> Modified <input type="checkbox"/> Relocated	
Maximum Rated Total Flow Capacity ~ 7,800 scfh 188,000 scfd	Maximum Design Heat Input (from mfg. spec sheet) 11.66 MMBTU/hr	Design Heat Content 1,262 BTU/scf

Control Device Information

Type of Vapor Combustion Control?		
<input checked="" type="checkbox"/> Enclosed Combustion Device <input type="checkbox"/> Thermal Oxidizer	<input type="checkbox"/> Elevated Flare	<input type="checkbox"/> Ground Flare
Manufacturer: LEED Fabrication Model: Enclosed Combustor 48"	Hours of operation per year? 8,760	

List the emission units whose emissions are controlled by this vapor control device (Emission Point ID# **S008-S017**)

Emission Unit ID#	Emission Source Description	Emission Unit ID#	Emission Source Description
S008-S015	Produced Fluid Tanks		
S016	Sand Trap Blowdown Tank		
S017	Tank Truck Loading Rack		

If this vapor combustor controls emissions from more than six (6) emission units, please attach additional pages.

Assist Type (Flares only)	Flare Height	Tip Diameter	Was the design per §60.18?
<input type="checkbox"/> Steam <input type="checkbox"/> Air <input type="checkbox"/> Pressure <input checked="" type="checkbox"/> Non	~ 25 feet	4 feet	<input type="checkbox"/> Yes <input type="checkbox"/> No Provide determination.

Waste Gas Information

Maximum Waste Gas Flow Rate 102.93 (lb/hr)	Heat Value of Waste Gas Stream Variable BTU/ft ³	Exit Velocity of the Emissions Stream (ft/s)
------------------------------------------------------	-----------------------------------------------------------------------	-------------------------------------------------

Provide an attachment with the characteristics of the waste gas stream to be burned.

Pilot Gas Information

Number of Pilot Lights 1	Fuel Flow Rate to Pilot Flame per Pilot ~ 30 scfh	Heat Input per Pilot 0.03 BTU/hr	Will automatic re-ignition be used? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
------------------------------------	-------------------------------------------------------------	--------------------------------------------	------------------------------------------------------------------------------------------------------------

If automatic re-ignition is used, please describe the method.

Is pilot flame equipped with a monitor to detect the presence of the flame? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	If Yes, what type? <input checked="" type="checkbox"/> Thermocouple <input type="checkbox"/> Infrared <input type="checkbox"/> Ultraviolet <input type="checkbox"/> Camera <input type="checkbox"/> Other:
-------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Describe all operating ranges and maintenance procedures required by the manufacturer to maintain the warranty. *(If unavailable, please indicate).* **See attached manufacture specification sheet.**

Additional information attached? Yes No

Please attach copies of manufacturer's data sheets, drawings, flame demonstration per §60.18 or §63.11(b) and performance testing.



**Environmental Control Equipment
Data Sheet**

Item/Tag No.:		Page	1	of	2
Project No.:		Revision:	B		
Project:		Date:	27 February 2014		
P.O. No.:	-	By:	JS		
RFQ No.:	-	Checked:	SG		
Ref. P&ID:	-	Approved:	MS		
Client:		Supplier:	LEED FABRICATION		
Site:		Model No.:	L30-0011-00		
Unit/Lease:		Remarks:			

GENERAL

1 Design Code:		NDE:	LEED Fabrication Standards		
2 Service:		Customer Specs:	<input type="checkbox"/> Yes		
3 Description:	Standard Dual Stage 48 High Efficiency Combustor		<input checked="" type="checkbox"/> No		

PROCESS DATA

Gas Composition:	mol %	Process Conditions:		
		Variable	Value	Units
4 Methane		Flow Rate	Up to 140	Mscfd
5 Ethane		Pressure	Up to 12	oz/in2
6 Propane		Temperature		°F
7 I-Butane		Molecular Weight		
8 n-Butane		Process/Waste Stream	<input checked="" type="checkbox"/> Gas	<input type="checkbox"/> Liquid
9 I-Pentane		Detailed Process Description / Process Notes:		
10 n-Pentane		1. Turndown 10:1. Based on an expected normal operating rate indicated above.		
11 n-Hexane		2. DRE: 98 % operating at design conditions		
12 CO2		3. Burner Pressure Drop: Min. 0.10 oz/in2		
13 N2				
14 Helium				
15 H2O				
16 C7				
17 C8				
18 C9				
19 C10				
20 C11+				
21 TOTAL				
Other Components:	PPMV	Available Utilities:		
22 H2S		Fuel / Pilot Gas	Min. 30psig Natural Gas /Propane 40-50 SCFH	
23 Benzene		Instrument Air	NA	
24 Toluene		Power	120 V / 60 Hz or Solar Power	
25 E-Benzene		Steam	NA	
26 Xylene		Purge Gas		

DESIGN DATA

27 Ambient Temperatures:		Noise Performance Requirements:	Under 85 dBA	
28 Low, °F	-20	Structural Design Code:		
29 High, °F	120	Wind Design Code:	ASCE	
30 Design Conditions:	Pressure/Temperature			
31 Max. Relative Humidity, %	90	Pressure/Speed	100 mph	
32 Elevation (ASL), ft		Category		
33 Area Classification:	Class I Div 2	Seismic Design Code:		
34 Electrical Design Code:	NEC	Location		

EQUIPMENT SPECIFICATION

35 Type:	<input type="checkbox"/> Elevated <input checked="" type="checkbox"/> Enclosed	Equipment Design:		
36	<input type="checkbox"/> Above Ground	Component	Material / Size / Rating / Other	
37	<input checked="" type="checkbox"/> Stack <input type="checkbox"/> Multiple Stack	Burner		
38	<input type="checkbox"/> Portable / Trailer	Burner Tip / Assist Gas Burner	304 SS	
39		Burner Body	Carbon Steel	
40 Smokeless By:	<input type="checkbox"/> Steam <input type="checkbox"/> Assist Air	Pilot		
41	<input type="checkbox"/> Gas Assist <input checked="" type="checkbox"/> Staging	Pilot Tip	304 SS	
42		Pilot Line(s)	Carbon Steel	
43 Stack:	<input checked="" type="checkbox"/> Self Supporting	Firebox / Stack		
44 Flare Burner:	<input type="checkbox"/> Non-Smokeless <input checked="" type="checkbox"/> Smokeless <input type="checkbox"/> Gas Assist	Shell	Carbon Steel	
45 Pilot:	<input checked="" type="checkbox"/> Intermittent <input type="checkbox"/> Continuous	Piping	Carbon Steel	
46 Pilot Air Inspirator:	<input checked="" type="checkbox"/> Local <input type="checkbox"/> Remote	Nozzles	Carbon Steel	
47 Pilot Flame Control:	<input type="checkbox"/> No <input checked="" type="checkbox"/> Yes (Thermocouple)	Flanges	Carbon Steel	
48		Insulation	Blanket	
49 Pilot Ignition:	<input type="checkbox"/> Flamefront Generator <input checked="" type="checkbox"/> Inspiring Ignitor	Insulation Pins	304 SS	
50	<input type="checkbox"/> Electronic <input checked="" type="checkbox"/> Automatic <input type="checkbox"/> Manual	Refractory	NA	
51	<input type="checkbox"/> With Pilot Flame Control	Refractory Anchors	NA	
52	<input type="checkbox"/> With Auto Pilot Re-Ignition	Ladders and Platforms	NA	
53		Stack Sample Connections	Per EPA requirements	
54 Pilot Ignition Backup:	<input type="checkbox"/> Manual Specify: i.e Piezo-Electric	Sight Glass	2	
55	<input type="checkbox"/> Battery Pack	Other		



**Environmental Control Equipment
Data Sheet**

Item/Tag No.:		Page	2	of	3
Project No.:		Revision:	B		
Project:		Date:	27 February 2014		
P.O. No.:	-	By:	JS		
RFQ No.:	-	Checked:	SG		
Ref. P&ID:	-	Approved:	MS		
Remarks:	-	Supplier:	LEED FABRICATION		
		Model No.:	L30-0011-00		

Client:	
Site:	
Unit/Lease:	

EQUIPMENT SPECIFICATION

56	Flame Detection:	<input type="checkbox"/> Thermocouple	<input checked="" type="checkbox"/> Ionization Rod	Auxiliary Equipment	
57		<input type="checkbox"/> UV Scanner		Valves	NA
58	General Configuration:			Blowers	NA
59				Dampers	NA
60				Inlet KO / Liquid Seal	NA
61				Flame / Detonation Arrestor	Yes
62				Instrumentation & Controls	
63				Solenoids / Shut-Off Valves	Check with Sales for available config.
64				Flow Meters	NA
65				Calorimeter	NA
66				Pressure Switches/Transmitters	NA
67				Thermocouples	Check with Sales for available config.
68				Temperature Switches/Transmitters	NA
69				BMS	Check with Sales for available config.
70		CEMS	NA		
71		Other	NA		
72					
73					
74					
75					

FABRICATION AND INSPECTION

76	Special requirements	<input type="checkbox"/> Skid Mounted	<input checked="" type="checkbox"/> Concrete Pad	Equipment Info	
77		<input type="checkbox"/> Other		Component	Weight / Dimensions
78				Burner	
79	Inspection	<input checked="" type="checkbox"/> Vendor Standard		Burner Assembly	
80		<input type="checkbox"/> Other. Specify:		Stack	
81	Material Certification	<input checked="" type="checkbox"/> Vendor Standard		Stack Assembly	48" OD x 25' H
82		<input type="checkbox"/> MTR		Pilot Tip	
83		<input type="checkbox"/> Certificate of Compliance		Pilot Line(s)	
84		<input type="checkbox"/> Other (Specify):		Stack Assembly	
85	NDE	<input checked="" type="checkbox"/> Vendor Standard		Auxiliary Equipment	
86		<input type="checkbox"/> Radiography. Specify:		Blowers	
87		<input type="checkbox"/> Ultrasonic. Specify:		Inlet KO / Liquid Seal	
88		<input type="checkbox"/> Liquid Penetrant.		Flame / Detonation Arrestor	
89		<input type="checkbox"/> Magnetic Particles.		Skid	
90		<input type="checkbox"/> PMI. Specify:		Instrumentation & Controls	
91		<input type="checkbox"/> Other. Specify:		BMS	
92	Surface Preparation	<input checked="" type="checkbox"/> Vendor Standard		Control Panel	
93		<input type="checkbox"/> Other. Specify:			
94	Paint System	<input checked="" type="checkbox"/> Vendor Standard			
95		<input type="checkbox"/> Other. Specify:			
96	Finished Color	<input checked="" type="checkbox"/> Vendor Standard			
97		<input type="checkbox"/> Other. Specify:			
98					
99					


Additional Notes:



Environmental Control Equipment
Data Sheet

Item/Tag No.:		Page	3	of	3
Project No.:		Revision:	B		
Project:		Date:	27 February 2014		
P.O. No.:	-	By:	JS		
RFQ No.:	-	Checked:	SG		
Ref. P&ID:	-	Approved:	MS		
Client:		Supplier:	LEED FABRICATION		
Site:		Model No.:	L30-0011-00		
Unit/Lease:		Remarks:	-		

GENERAL ARRANGEMENT



§ MMBTU/hr values are calculated based on 1500 BTU/scf gas

Flare Size	# of Orifices (N)	Pressure (OZ/in ²)	m ³ /s	mSCFD	MMBTU/hr
18	2	1	0.0021	6.34	0.39
18	2	2	0.0029	8.97	0.56
18	2	3	0.0036	10.99	0.68
18	2	4	0.0042	12.69	0.78
18	2	5	0.0046	14.18	0.88
18	2	6	0.0051	15.54	0.96
18	2	7	0.0055	16.78	1.04
18	2	8	0.0059	17.94	1.11
18	2	9	0.0062	19.03	1.18
18	2	10	0.0066	20.06	1.24
18	2	11	0.0069	21.04	1.30
18	2	12	0.0072	21.97	1.36
18	2	13	0.0075	22.87	1.42
18	2	14	0.0078	23.73	1.47
18	2	15	0.0081	24.57	1.52
18	2	16	0.0083	25.37	1.57
18	2	17	0.0086	26.15	1.62
18	2	18	0.0088	26.91	1.67
24	4	1	0.0042	12.69	0.78
24	4	2	0.0059	17.94	1.11
24	4	3	0.0072	21.97	1.36
24	4	4	0.0083	25.37	1.57
24	4	5	0.0093	28.37	1.76
24	4	6	0.0102	31.08	1.92
24	4	7	0.0110	33.56	2.08
24	4	8	0.0118	35.88	2.22
24	4	9	0.0125	38.06	2.35
24	4	10	0.0131	40.12	2.48
24	4	11	0.0138	42.08	2.60
24	4	12	0.0144	43.95	2.72
24	4	13	0.0150	45.74	2.83
24	4	14	0.0156	47.47	2.94
24	4	15	0.0161	49.13	3.04
24	4	16	0.0166	50.75	3.14
24	4	17	0.0171	52.31	3.24
24	4	18	0.0176	53.82	3.33
36	10	1	0.0104	31.72	1.96
36	10	2	0.0147	44.85	2.78
36	10	3	0.0180	54.93	3.40

36	10	4	0.0208	63.43	3.92
36	10	5	0.0232	70.92	4.39
36	10	6	0.0255	77.69	4.81
36	10	7	0.0275	83.91	5.19
36	10	8	0.0294	89.71	5.55
36	10	9	0.0312	95.15	5.89
36	10	10	0.0329	100.29	6.21
36	10	11	0.0345	105.19	6.51
36	10	12	0.0360	109.87	6.80
36	10	13	0.0375	114.35	7.08
36	10	14	0.0389	118.67	7.34
36	10	15	0.0403	122.83	7.60
36	10	16	0.0416	126.86	7.85
36	10	17	0.0429	130.77	8.09
36	10	18	0.0441	134.56	8.33
48	14	1	0.0146	44.40	2.75
48	14	2	0.0206	62.79	3.89
48	14	3	0.0252	76.91	4.76
48	14	4	0.0291	88.80	5.49
48	14	5	0.0325	99.29	6.14
48	14	6	0.0356	108.76	6.73
48	14	7	0.0385	117.48	7.27
48	14	8	0.0412	125.59	7.77
48	14	9	0.0437	133.21	8.24
48	14	10	0.0460	140.41	8.69
48	14	11	0.0483	147.27	9.11
48	14	12	0.0504	153.81	9.52
48	14	13	0.0525	160.09	9.91
48	14	14	0.0545	166.14	10.28
48	14	15	0.0564	171.97	10.64
48	14	16	0.0582	177.61	10.99
48	14	17	0.0600	183.07	11.33
48	14	18	0.0617	188.38	11.66

Attachment S

EMISSION CALCULATIONS

Line Heaters S001 - S007

Pollutant	Emission Factor	Emission Factor Units	Emission Factor Basis / Source	Boiler Rating (MMBtu/hr)	Heat Value of Natural Gas (Btu/scf)	Annual Operating Hours	Max. Hourly Emissions. (lb/hr)	Max. Annual Emissions. (tpy)
VOC's	5.5	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	0.03
Hexane	1.8	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	<0.01
Formaldehyde	0.075	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	<0.01
Benzene	0.0021	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	<0.01
Toluene	0.0034	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	<0.01
Pb	0.0005	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	<0.01
CO	84	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	0.10	0.45
NO _x	100	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	0.12	0.53
PM _{Filterable}	1.9	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	0.01
PM _{Condensable}	5.7	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	0.03
PM _{Total}	7.6	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	0.04
SO ₂	0.6	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.54	1,262	8,760	<0.01	<0.01
CO ₂	53.06	kg CO ₂ / MMBtu	40CFR98 Subpart C	1.54	1,262	8,760	180.14	789.03
CH ₄	0.001	kg CH ₄ / MMBtu	40CFR98 Subpart C	1.54	1,262	8,760	<0.01	0.015
N ₂ O	0.0001	kg N ₂ O / MMBtu	40CFR98 Subpart C	1.54	1,262	8,760	<0.01	<0.01
Total HAPs							<0.01	0.01
Total CO ₂ e							180.33	789.85

- Notes:**
- Emission rates displayed above represent the max. hourly and max. annual emissions for one line heater. Cumulative emission rates for all line heaters are displayed in the Total Site Emissions Table.
 - Greenhouse Gas Emissions are calculated using 40 CFR 98 Subpart C Table C-1 and C-2 emission factors.
 - AP-42, Chapter 1.4 references are from the July 1998 revision.
 - Max. Annual Emissions based upon Max. Hourly Emissions @ 8760 hr/yr.
 - CO₂ equivalency solved for using Global Warming Potentials found in 40CFR98 Table A-1 (Updated January 2014). GWP CO₂=1, GWP CH₄=25, GWP N₂O=298

Example Equations:
 Max. Hourly Emission Rate (lb/hr) = Emission Factor (lb/10⁶ scf) ÷ Heating Value of Natural Gas (Btu/scf) x Boiler Rating (MMBtu/hr)

Line Heaters S023

Pollutant	Emission Factor	Emission Factor Units	Emission Factor Basis / Source	Boiler Rating (MMBtu/hr)	Heat Value of Natural Gas (Btu/scf)	Annual Operating Hours	Max. Hourly Emissions. (lb/hr)	Max. Annual Emissions. (tpy)
VOC's	5.5	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	0.02
Hexane	1.8	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	<0.01
Formaldehyde	0.075	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	<0.01
Benzene	0.0021	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	<0.01
Toluene	0.0034	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	<0.01
Pb	0.0005	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	<0.01
CO	84	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	0.08	0.34
NO _x	100	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	0.09	0.40
PM _{Filterable}	1.9	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	<0.01
PM _{Condensable}	5.7	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	0.02
PM _{Total}	7.6	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	0.03
SO ₂	0.6	lb/10 ⁶ scf	AP-42 Chapter 1.4	1.15	1,262	8,760	<0.01	<0.01
CO ₂	53.06	kg CO ₂ / MMBtu	40CFR98 Subpart C	1.15	1,262	8,760	134.52	589.21
CH ₄	0.001	kg CH ₄ / MMBtu	40CFR98 Subpart C	1.15	1,262	8,760	<0.01	0.011
N ₂ O	0.0001	kg N ₂ O / MMBtu	40CFR98 Subpart C	1.15	1,262	8,760	<0.01	<0.01
Total HAPs							<0.01	<0.01
Total CO ₂ e							134.66	589.82

- Notes:**
- Emission rates displayed above represent the max. hourly and max. annual emissions for one line heater. Cumulative emission rates for all line heaters are displayed in the Total Site Emissions Table.
 - Greenhouse Gas Emissions are calculated using 40 CFR 98 Subpart C Table C-1 and C-2 emission factors.
 - AP-42, Chapter 1.4 references are from the July 1998 revision.
 - Max. Annual Emissions based upon Max. Hourly Emissions @ 8760 hr/yr.
 - CO₂ equivalency solved for using Global Warming Potentials found in 40CFR98 Table A-1 (Updated January 2014). GWP CO₂=1, GWP CH₄=25, GWP N₂O=298

Example Equations:
 Max. Hourly Emission Rate (lb/hr) = Emission Factor (lb/10⁶ scf) ÷ Heating Value of Natural Gas (Btu/scf) x Boiler Rating (MMBtu/hr)

Thermoelectric Generators S020 & S021

Pollutant	Emission Factor	Emission Factor Units	Emission Factor Basis / Source	Boiler Rating (MMBtu/hr)	Heat Value of Natural Gas (Btu/scf)	Annual Operating Hours	Max. Hourly Emissions. (lb/hr)	Max. Annual Emissions. (tpy)
VOC's	5.5	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
Hexane	1.8	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
Formaldehyde	0.075	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
Benzene	0.0021	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
Toluene	0.0034	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
Pb	0.0005	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
CO	84	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
NO _x	100	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
PM _{Filterable}	1.9	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
PM _{Condensable}	5.7	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
PM _{Total}	7.6	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
SO ₂	0.6	lb/10 ⁶ scf	AP-42 Chapter 1.4	0.013	1,262	8,760	<0.01	<0.01
CO ₂	53.06	kg CO ₂ / MMBtu	40CFR98 Subpart C	0.013	1,262	8,760	1.52	6.66
CH ₄	0.001	kg CH ₄ / MMBtu	40CFR98 Subpart C	0.013	1,262	8,760	<0.01	<0.01
N ₂ O	0.0001	kg N ₂ O / MMBtu	40CFR98 Subpart C	0.013	1,262	8,760	<0.01	<0.01
Total HAPs							<0.01	<0.01
Total CO ₂ e							1.52	6.67

Notes:

- Emission rates displayed above represent the max. hourly and max. annual emissions for one TEG. Cumulative emission rates for both TEGs are displayed in the Total Site Emissions Table.
- Greenhouse Gas Emissions are calculated using 40 CFR 98 Subpart C Table C-1 and C-2 emission factors.
- AP-42, Chapter 1.4 references are from the July 1998 revision.
- Max. Annual Emissions based upon Max. Hourly Emissions @ 8760 hr/yr.
- CO₂ equivalency solved for using Global Warming Potentials found in 40CFR98 Table A-1 (Updated January 2014). GWP CO₂=1, GWP CH₄=25, GWP N₂O=298

Example Equations:

Max. Hourly Emission Rate (lb/hr) = Emission Factor (lb/10⁶ scf) ÷ Heating Value of Natural Gas (Btu/scf) x Boiler Rating (MMBtu/hr)

Natural Gas Compressor Engine S027

Pollutant	Emission Factor	Emission Factor Units	Emission Factor Basis / Source	Engine Rating (bhp)	Fuel Consumption (Btu/bhp-hr)	Heat Value of Natural Gas (Btu/scf)	Annual Operating Hours	Hourly Emissions (lb/hr)	Annual Emissions (tpy)
VOC's	1.21	g/bhp-hr	Vendor Guarantee	110.0	6,553	1,262	8,760	0.29	1.29
Formaldehyde	2.05E-02	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	0.01	0.06
Benzene	1.58E-03	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	<0.01	<0.01
Toluene	5.58E-04	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	<0.01	<0.01
Ethylbenzene	2.48E-05	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	<0.01	<0.01
Xylene	1.95E-04	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	<0.01	<0.01
CO	3.62	g/bhp-hr	Vendor Guarantee	110.0	6,553	1,262	8,760	0.88	3.85
NO _x	1.74	g/bhp-hr	Vendor Guarantee	110.0	6,553	1,262	8,760	0.42	1.85
PM _{Filterable}	9.50E-03	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	<0.01	0.03
PM _{Condensable}	9.10E-03	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	<0.01	0.03
SO ₂	5.88E-04	lb/MMBtu	AP-42 Chapter 3.2	110.0	6,553	1,262	8,760	<0.01	<0.01
CO ₂	53.06	kg CO ₂ / MMBtu	40 CFR Subpart C	110.0	6,553	1,262	8,760	82.49	361.32
CH ₄	0.001	kg CH ₄ / MMBtu	40 CFR Subpart C	110.0	6,553	1,262	8,760	<0.01	<0.01
N ₂ O	0.0001	kg N ₂ O / MMBtu	40 CFR Subpart C	110.0	6,553	1,262	8,760	<0.01	<0.01
Total HAPs								0.02	0.07
Total CO ₂ e								82.58	361.69

Notes:

- Emission rates displayed above represent the max. hourly and max. annual emissions for one NG compressor.
- Greenhouse Gas Emissions are calculated using 40 CFR 98 Subpart C Table C-1 and C-2 emission factors.
- AP-42, Chapter 3.2, Table 3.2-2 - Uncontrolled Emission Factors for 4-Stroke Rich Burn Engines
- Max. Annual Emissions based upon Max. Hourly Emissions @ 8760 hr/yr.
- CO₂ equivalency solved for using Global Warming Potentials found in 40 CFR 98 Table A-1 (Updated January 2014). GWP CO₂=1, GWP CH₄=25, GWP N₂O=298
- Vendor Guarantee Emissions are converted from g/kW-hr to g/bhp-hr. 1 kW = 1.34 bhp

Example Equations:

Max. Hourly Emission Rate (lb/hr) = Emission Factor (lb/10⁶ scf) ÷ Heating Value of Natural Gas (Btu/scf) x Boiler Rating (MMBtu/hr)

Produced Fluids Tanks S008 - S015

Pollutant	Max. Hourly Emissions using ProMax (lb/hr)	Max. Yearly Emissions using ProMax (tons/yr)
VOCs	13.97	61.18
HAPs	2.35	10.27
Hexane	2.25	9.83
Benzene	0.03	0.11
Toluene	0.05	0.23
Ethylbenzene	<0.01	0.01
Xylene	0.02	0.09
CO ₂	0.16	0.72
CH ₄	0.87	3.82
Total CO ₂ e	21.96	96.20

Notes:

- Emission rates for Produced Fluid Tanks S008 - S015 were calculated using ProMax software. ProMax output sheets for the OXF 159 Pad are attached.
- The emission rates displayed above are pre-control device emissions.
- CO₂ equivalency solved for using Global Warming Potentials found in 40CFR98 Table A-1 (Updated January 2014). GWP CO₂=1, GWP CH₄=25, GWP N₂O=298
- For emission calculation purposes, the total throughput for tanks S011 - S020 is modeled as being received through a single tank. The throughput value represents the total throughput for all ten (10) 400-barrel tanks. Therefore, emission rates represent a total from all produced fluids tanks located on the well pad. Actual throughput for each tank will vary based on operations.

Sand Trap Blow Tank S016

Pollutant	Max. Hourly Emissions using ProMax (lb/hr)	Max. Yearly Emissions using ProMax (tons/yr)
VOCs	1.76	0.32
HAPs	0.29	0.05
Hexane	0.28	0.05
Benzene	<0.01	<0.01
Toluene	<0.01	<0.01
Ethylbenzene	<0.01	<0.01
Xylene	<0.01	<0.01
CO ₂	0.03	<0.01
CH ₄	0.57	0.10
Total CO ₂ e	14.19	2.59

Notes:

- Blowdown operations are conducted on the OXF 159 pad daily to allow for the removal of fluids from the sand traps. Based on available operational information, blowdowns are assumed to occur for one hour per day.
- Emissions from the Sand Trap Blowdown Tank are routed to an enclosed combustion device. The values displayed above are pre-control emission rates.
- Emission rates for the Sand Trap Blowdown Tank were calculated using ProMax software. ProMax output sheets for the OXF 159 Pad are attached.
- CO₂ equivalency solved for using Global Warming Potentials found in 40CFR98 Table A-1. GWP CO₂=1, GWP CH₄=25, GWP N₂O=298

Tank Unloading Operations S017

Total Emissions from Tank Unloading Operations

Pollutant	Max. Hourly Emissions (lb/hr)	Max. Yearly Emissions (tons/yr)	Loading Rack Collection Efficiency	Enclosed Combustion Device Combusion Efficiency	Post-Control Max. Yearly Emissions (lb/hr)	Post-Control Max. Yearly Emissions (tons/yr)	Max. Hourly Emissions Not Collected by Loading Rack (lb/hr)	Max. Hourly Emissions Not Collected by Loading Rack (tons/yr)
VOCs	0.04	0.20	70%	98%	<0.01	<0.01	0.01	0.06
HAPs	<0.01	<0.01	70%	98%	<0.01	<0.01	<0.01	<0.01
CO ₂	0.02	0.09	70%	98%	0.27	1.16	<0.01	0.03
CH ₄	0.02	0.10	70%	98%	<0.01	<0.01	<0.01	0.03
Total CO ₂ e	0.59	2.60	--	--	0.27	1.20	0.18	0.78

Notes:

- Emission rates for liquid unloading operations were calculated using ProMax software. ProMax summary sheets are attached.
- Vapors from tank unloading operations are vapor-balanced to the produced fluid tanks and realized at one of the two enclosed combustion devices. AP-42 calculation methods were used to estimate the collection efficiency from tank unloading operations. Emissions that are not collected during the unloading events are realized at the Loading Rack Emission Point, E020.

Enclosed Ground Flares C018 - C019

Emissions from Tanks							Gas Composition of Vent Gas		
Input to Enclosed Combustion Device	Pollutant	Amount of Gas Sent to Enclosed Combustion Device (lbs/hr)	Amount of Gas Sent to Enclosed Combustion Device (tons/year)	Enclosed Combustion Device Combustion Efficiency	Max. Hourly Emissions (lb/hr)	Max. Yearly Emissions (tons/yr)	Gas Stream	Mole Fraction	
Produced Fluids Tanks S008 - S015	VOCs	6.98	30.59	98%	0.14	0.61	Methane	0.12	
	HAPs	1.17	5.14	98%	0.02	0.10	Ethane	0.25	
	Hexane	1.12	4.92	98%	0.02	0.10	Propane	0.25	
	Benzene	0.01	0.06	98%	<0.01	<0.01	Butane	0.16	
	Toluene	0.03	0.11	98%	<0.01	<0.01	Pentanes	0.06	
	Ethylbenzene	<0.01	<0.01	98%	<0.01	<0.01	Carbon Dioxide	0.007	
	Xylene	0.01	0.04	98%	<0.01	<0.01			
	CO ₂	0.08	0.36	98%	262.98	1,151.87	Vent Gas Properties		
	CH ₄	0.44	1.91	98%	<0.01	0.04			
Sand Trap Blowdown Tank - S016	VOCs	0.88	0.16	98%	0.02	<0.01	Vent Gas Properties	Mass Flow Rate (lb/hr)	Density (lb/ft³)
	HAPs	0.14	0.03	98%	<0.01	<0.01	Produced Fluids Tank	101.30	0.10
	Hexane	0.14	0.03	98%	<0.01	<0.01	Blowdown Tank	1.63	0.08
	Benzene	<0.01	<0.01	98%	<0.01	<0.01			
	Toluene	<0.01	<0.01	98%	<0.01	<0.01			
	Ethylbenzene	<0.01	<0.01	98%	<0.01	<0.01			
	Xylene	<0.01	<0.01	98%	<0.01	<0.01			
	CO ₂	0.01	<0.01	98%	5.21	22.83			
	CH ₄	0.28	0.05	98%	<0.01	<0.01			
Truck Loading - S017	VOCs	0.02	0.10	98%	<0.01	<0.01			
	HAPs	<0.01	<0.01	98%	<0.01	<0.01			
	CO ₂	0.01	0.05	98%	0.13	0.58			
	CH ₄	0.01	0.05	98%	<0.01	<0.01			
Totals	VOCs	7.89	30.85	--	0.16	0.62			
	HAPs	1.32	5.16	--	0.03	0.10			
	Hexane	1.26	4.94	--	0.03	0.10			
	Benzene	0.01	0.06	--	<0.01	<0.01			
	Toluene	0.03	0.11	--	<0.01	<0.01			
	Ethylbenzene	<0.01	<0.01	--	<0.01	<0.01			
	Xylene	0.01	0.04	--	<0.01	<0.01			
	CO ₂	0.11	0.41	--	268.33	1,175.28			
	CH ₄	0.73	2.01	--	0.01	0.04			
	CO ₂ e	18.37	50.70	--	268.69	1,176.28			

Emissions from Pilot Operations

Pollutant	Emission Factor (lb/10 ⁶ scf)	Emission Factors (kg XX/MMBtu)	Heat Value of Natural Gas (Btu/scf)	Enclosed Ground Flare Pilot Rating (Btu/hr)	Enclosed Ground Flare Burner Rating (Btu/hr)	Pilot Max. Hourly Emissions (lb/yr)	Pilot Max. Hourly Emissions (tons/yr)	Burner Max.Hourly Emissions (lb/hr)	Burner Max.Hourly Emissions (tons/hr)	Max. Hourly Emissions (lb/hr)	Max. Yearly Emissions (tons/yr)
VOCs	5.50	--	1,262	30,000	11,660,000	<0.01	<0.01	--	--	<0.01	<0.01
Hexane	1.80	--	1,262	30,000	11,660,000	<0.01	<0.01	--	--	<0.01	<0.01
Formaldehyde	0.075	--	1,262	30,000	11,660,000	<0.01	<0.01	--	--	<0.01	<0.01
CO	84	--	1,262	30,000	11,660,000	<0.01	0.01	0.90	3.94	0.90	3.95
NO _x	100	--	1,262	30,000	11,660,000	<0.01	0.01	1.07	4.69	1.07	4.71
PM _{Condensable}	5.70	--	1,262	30,000	11,660,000	<0.01	<0.01	0.06	0.27	0.06	0.27
PM _{Filterable}	1.90	--	1,262	30,000	11,660,000	<0.01	<0.01	0.02	0.09	0.02	0.09
PM _{Total}	7.60	--	1,262	30,000	11,660,000	<0.01	<0.01	0.08	0.36	0.08	0.36
SO ₂	0.60	--	1,262	30,000	11,660,000	<0.01	<0.01	<0.01	0.03	<0.01	0.03
CO ₂	120,000	53.06	1,262	30,000	11,660,000	3.51	15.37	1,363.95	5,974.12	1,367.46	5,989.49
CH ₄	2.3	0.001	1,262	30,000	11,660,000	<0.01	<0.01	0.03	0.11	0.03	0.11
N ₂ O	2.2	<0.001	1,262	30,000	11,660,000	<0.01	<0.01	<0.01	0.01	<0.01	0.01
Total HAPs										<0.01	<0.01
CO ₂ e										1,368.88	5,995.67

Total Enclosed Combustion Device Emissions

Pollutant	Max. Hourly Emissions (lb/hr)	Max. Yearly Emissions (tons/yr)
VOCs	0.16	0.62
HAPs	0.03	0.10
CO	0.90	3.95
NO _x	1.07	4.71
PM _{Condensable}	0.06	0.27
PM _{Filterable}	0.02	0.09
PM _{Total}	0.08	0.36
SO ₂	<0.01	0.03
CO ₂	1,635.79	7,164.77
CH ₄	0.04	0.15
N ₂ O	<0.01	0.01
CO ₂ e	1,637.57	7,171.95

Notes:

- Emissions from Enclosed Combustion Device Operations from AP-42, Chapter 1.4 references are from the July 1998 revision.
- Greenhouse Gas Emissions from the Enclosed Combustion Device Pilot and Burner calculated using 40 CFR 98 Subpart C Table C-1 and C-2 emission factors.
- Max. Annual Emissions based upon Max. Hourly Emissions @ 8760 hr/yr.
- CO₂ equivalency solved for using Global Warming Potentials found in 40CFR98 Table A-1 (Updated January 2014). GWP CO₂=1, GWP CH₄=25, GWP N₂O=298

Example Calculations:

- Emissions from Tanks VOCs (lb/hr) = Amount of Gas sent to Enclosed Combustion Device (lb/hr) x 0.02 = Max. Hourly Emissions (lb/hr)
- Emissions from Enclosed Combustion Device Operations (lb/hr) = Emission factor (lb/106 Btu) x Heat Value of Natural Gas (Btu/scf) ÷ 1,000,000 x Enclosed Combustion Device Pilot Gas Usage (mcf/d) x 1,000 ÷ 24
- Emissions from Enclosed Combustion Device Vapor Destruction CO₂ Methodologies shown below sample equation
- Emissions from Enclosed Combustion Device Operations CO₂ (tons/yr) = ((Enclosed Combustion Device Pilot Gas Usage (mcf/d) x 1,000 x 365 x Fraction of Gas Combusted by Enclosed Combustion Device x Mole Fraction of Methane x Number of Carbon Atoms in Methane) + ... + (Enclosed Combustion Device Pilot Gas Usage (mcf/d) x 1,000 x 365 x Fraction of Gas Combusted by Enclosed Combustion Device x Mole Fraction of Pentanes-plus x Number of Carbon Atoms in Pentanes-plus)) x .0526 (kg/ft³) CO₂ x .001 x 1.102 tons/tonnes

$$E_{a,CH_4}(un-combusted) = V_a * (1 - \eta) * X_{CH_4} \quad (\text{Eq. W-19})$$

$$E_{a,CO_2}(un-combusted) = V_a * X_{CO_2} \quad (\text{Eq. W-20})$$

$$E_{a,CO_2}(combusted) = \sum_{j=1}^5 (\eta * V_a * Y_j * R_j) \quad (\text{Eq. W-21})$$

Where:

- Ea,CH₄(un-combusted) = Contribution of annual un-combusted CH₄ emissions from Enclosed Combustion Device stack in cubic feet, under actual conditions.
- Ea,CO₂(un-combusted) = Contribution of annual un-combusted CO₂ emissions from Enclosed Combustion Device stack in cubic feet, under actual conditions.
- Ea,CO₂(combusted) = Contribution of annual combusted CO₂ emissions from Enclosed Combustion Device stack in cubic feet, under actual conditions.
- V_a = Volume of gas sent to Enclosed Combustion Device in cubic feet, during the year.
- η = Fraction of gas combusted by a burning Enclosed Combustion Device (default is 0.98). For gas sent to an unlit Enclosed Combustion Device, η is zero.
- X_{CH₄} = Mole fraction of CH₄ in gas to the Enclosed Combustion Device.
- X_{CO₂} = Mole fraction of CO₂ in gas to the Enclosed Combustion Device.
- Y_j = Mole fraction of gas hydrocarbon constituents j (such as methane, ethane, propane, butane, and pentanes-plus).
- R_j = Number of carbon atoms in the gas hydrocarbon constituent j: 1 for methane, 2 for ethane, 3 for propane, 4 for butane, and 5 for pentanes plus).

Fugitive Emissions from Unpaved Haul Roads

Constant	Industrial Roads		
	PM	PM-10	PM-2.5
k (lb/VMT)	4.9	1.5	0.15
a	0.7	0.9	0.9
b	0.45	0.45	0.45

where

k		Particle size multiplier ¹
s	4.8	Silt content of road surface material (%) ²
p	150	Number of days per year with precipitation >0.01 in. ³

Item Number	Description	Number of Wheels	W	Mean Vehicle Speed (mph)	Miles per Trip	Maximum Trips per Hour	Maximum Trips per Year	Control Device ID Number	Control Efficiency (%)	PM Emissions (lbs/hr)	PM Emissions (tons/yr)	PM-10 Emissions (lbs/hr)	PM-10 Emissions (tons/yr)	PM-2.5 Emissions (lbs/hr)	PM-2.5 Emissions (tons/yr)
			Mean Vehicle Weight (tons)												
1	Liquids Hauling	14	30	10	1.72	1	1,826	NA	NA	7.37	6.73	1.88	1.71	0.19	0.171
2	Employee Vehicles	4	3	10	1.72	1	200	NA	NA	2.61	0.26	0.67	0.07	0.07	<0.01
Totals:										9.98	6.99	2.54	1.78	0.25	0.178

Notes:

¹ - Particle Size Multiplier used from AP-42 13.2.2 - Final Version 11/2006

² - Silt Content of Road Surface uses Sand and Gravel Processing Plant Road from AP-42 13.2.2 - Final Version 11/2006

³ - Number of days per year with precipitation >0.01 in³ found using AP-42 13.2.2 Figure 13.2.2-1 - Final Version 11/2006

Example Calculations:

Emissions (lb/Vehicle Mile Traveled) - $E = k \times (s/12)^a \times (W/3)^b$

Equation 1a from AP-42 13.2.2 - Final Version 11/2006

Size Specific Emissions (lb/VMT) - $E_{ext} = E[(365-p)/365]$

Equation 2 from AP-42 13.2.2 - Final Version 11/2006

Fugitive Leaks

Default Average Component Counts for Major Onshore Natural Gas Production Equipment ¹				
Facility Equipment Type	Valves	Connectors	Open-ended Lines	Pressure Relief Valves
Wellheads	8	38	0.5	0
Separators	1	6	0	0
Meters/Piping	12	45	0	0
Compressors	12	57	0	0
In-line Heaters	14	65	2	1
Dehydrators	24	90	2	2

¹ Table W-1B to 40CFR98 Subpart W

Well Specific Equipment Counts	
Facility Equipment Type	Count on Site
Wellheads	7
Separators	8
Meters/Piping	9
Compressors	1
In-line Heaters	8
Dehydrators	0

Gas Composition						
Emissions from Flaring Operations	Propane	Butane	Pentanes	Hexanes +	CO ₂	CH ₄
Mole %	4.00	1.78	0.64	0.58	0.15	78.13
MW	44	58	72	86.00	44.00	16.00

Fugitive Emissions															
Facility Equipment Type	Total Count	Emission Rate (scf/hr/component) ²	Hours of Operation	VOCs (lbs/hr)	VOCs (tons/yr)	Hexane (lbs/hr)	Hexane (tons/yr)	HAPs (lbs/hr)	HAPs (tons/yr)	CO ₂ (lbs/hr)	CO ₂ (tons/yr)	CH ₄ (lbs/hr)	CH ₄ (tons/yr)	Total CO _{2e} (lbs/hr)	Total CO _{2e} (tons/yr)
Valves	296	0.027	8760	0.07	0.30	0.01	0.05	0.01	0.05	<0.01	<0.01	0.26	1.14	6.48	28.38
Connectors	1296	0.003	8760	0.03	0.14	<0.01	0.02	<0.01	0.02	<0.01	<0.01	0.13	0.55	3.15	13.81
Open-ended Lines	20	0.061	8760	0.01	0.04	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.04	0.17	0.96	4.22
Pressure Relief Valves	8	0.040	8760	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01	0.05	0.26	1.14
Total Emissions:				0.11	0.50	0.02	0.08	0.02	0.08	<0.01	0.01	0.43	1.90	10.86	47.55

² Table W-1A to 40CFR98 Subpart W

Notes:

-A gas sample from the OXF-159 Site is included with this submittal

Example Equations:

Fugitive Emissions (lb/hr) = Count x Emission Rate x Hours of Operation ÷ 385.5 scf/lbmol x mol VOC's

Total OXF 159 Site Emission Levels

Emission Sources	VOCs		HAPs		CO		NO _x		PM _{Total}		PM _{Filterable}		PM _{Condensable}		SO ₂		CO ₂		CH ₄		N ₂ O		CO ₂ e	
	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr
Line Heater (E001)	<0.01	0.03	<0.01	0.01	0.10	0.45	0.12	0.53	<0.01	0.04	<0.01	0.01	<0.01	0.03	<0.01	<0.01	180.14	789.03	<0.01	0.01	<0.01	<0.01	180.33	789.85
Line Heater (E002)	<0.01	0.03	<0.01	0.01	0.10	0.45	0.12	0.53	<0.01	0.04	<0.01	0.01	<0.01	0.03	<0.01	<0.01	180.14	789.03	<0.01	0.01	<0.01	<0.01	180.33	789.85
Line Heater (E003)	<0.01	0.03	<0.01	0.01	0.10	0.45	0.12	0.53	<0.01	0.04	<0.01	0.01	<0.01	0.03	<0.01	<0.01	180.14	789.03	<0.01	0.01	<0.01	<0.01	180.33	789.85
Line Heater (E004)	<0.01	0.03	<0.01	0.01	0.10	0.45	0.12	0.53	<0.01	0.04	<0.01	0.01	<0.01	0.03	<0.01	<0.01	180.14	789.03	<0.01	0.01	<0.01	<0.01	180.33	789.85
Line Heater (E005)	<0.01	0.03	<0.01	0.01	0.10	0.45	0.12	0.53	<0.01	0.04	<0.01	0.01	<0.01	0.03	<0.01	<0.01	180.14	789.03	<0.01	0.01	<0.01	<0.01	180.33	789.85
Line Heater (E006)	<0.01	0.03	<0.01	0.01	0.10	0.45	0.12	0.53	<0.01	0.04	<0.01	0.01	<0.01	0.03	<0.01	<0.01	180.14	789.03	<0.01	0.01	<0.01	<0.01	180.33	789.85
Line Heater (E007)	<0.01	0.03	<0.01	0.01	0.10	0.45	0.12	0.53	<0.01	0.04	<0.01	0.01	<0.01	0.03	<0.01	<0.01	180.14	789.03	<0.01	0.01	<0.01	<0.01	180.33	789.85
*Tank Truck Loading Operations (E017)	0.01	0.06	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	--	--	--	--	--	--	<0.01	<0.01	<0.01	0.03	<0.01	0.03	<0.01	<0.01	0.18	0.78
Enclosed Combustion Unit (E018)	0.16	0.62	0.03	0.10	0.90	3.95	1.07	4.71	0.08	0.36	0.02	0.09	0.06	0.27	<0.01	0.03	1,635.79	7,164.77	0.04	0.15	<0.01	0.01	1,637.57	7,171.95
Enclosed Combustion Unit (E019)	0.16	0.62	0.03	0.10	0.90	3.95	1.07	4.71	0.08	0.36	0.02	0.09	0.06	0.27	<0.01	0.03	1,635.79	7,164.77	0.04	0.15	<0.01	0.01	1,637.57	7,171.95
TEG (E020)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	1.52	6.66	<0.01	<0.01	<0.01	<0.01	1.52	6.67
TEG (E021)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	1.52	6.66	<0.01	<0.01	<0.01	<0.01	1.52	6.67
Compressor Engine (E022)	0.29	1.29	0.02	0.07	0.88	3.85	0.42	1.85	0.00	0.06	<0.01	0.03	<0.01	0.03	<0.01	<0.01	82.49	361.32	<0.01	<0.01	<0.01	<0.01	82.58	361.69
Line Heater (S023)	<0.01	0.02	<0.01	<0.01	0.08	0.34	0.09	0.40	<0.01	0.03	<0.01	<0.01	<0.01	0.02	<0.01	<0.01	134.52	589.21	<0.01	0.011	<0.01	<0.01	134.66	589.82
Haul Roads	--	--	--	--	--	--	--	--	9.98	6.99	9.98	6.99	<0.01	<0.01	--	--	--	--	--	--	--	--	--	--
Fugitives Leaks	0.11	0.50	0.02	0.08	--	--	--	--	--	--	--	--	--	--	--	--	<0.01	0.01	0.43	1.90	--	--	10.86	47.55
Totals	0.79	3.30	0.10	0.43	3.48	15.24	3.52	15.41	10.23	8.08	10.05	7.28	0.18	0.80	0.02	0.08	4,752.66	20,816.66	0.55	2.36	0.01	0.03	4,768.77	20,886.03

-Two enclosed combustion devices are being included in this application. Emissions from the produced fluids tanks, sand trap blowdown tanks, and truck loading are routed to either C018 or C019. For the permitting of these sources, it is assumed that vapors are being evenly distributed between the two enclosed combustion devices. For this reason, the emissions from the combustion of vent gases between C018 and C019 are additive.

*Emissions from Tank Truck Loading Operations are routed to the enclosed combustion devices. The collection efficiency of the vapors has been calculated using AP-42 methodologies. Emissions that are not collected and routed the enclosed combustion devices are realized at the Tank Truck Loading Operations Emission Point.

Total OXF 159 Site Emission Levels - HAP Speciation

Emission Sources	Total HAPs		Formaldehyde		Hexane		Benzene		Toluene		Ethylbenzene		Xylene	
	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr	lb/hr	tons/yr
Line Heater (E001)	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Line Heater (E002)	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Line Heater (E003)	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Line Heater (E004)	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Line Heater (E005)	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Line Heater (E006)	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Line Heater (E007)	<0.01	0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Tank Truck Loading Activities (E017)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Enclosed Combustion Unit (E018)	0.03	0.10	<0.01	<0.01	0.03	0.10	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Enclosed Combustion Unit (E019)	0.03	0.10	<0.01	<0.01	0.03	0.10	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
TEG (E020)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
TEG (E021)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Compressor Engine (E022)	0.02	0.07	0.01	0.06	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Line Heater (E023)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Haul Roads	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Fugitives Leaks	0.02	0.08	<0.01	<0.01	0.02	0.08	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Totals	0.10	0.43	0.02	0.07	0.08	0.28	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01

-Two enclosed combustion devices are being included in this application. Emissions from the produced fluids tanks, sand trap blowdown tanks, and truck loading are routed to either C018 or C019. For the permitting of these sources, it is assumed that vapors are being evenly distributed between the two enclosed combustion devices. For this reason, the emissions from the combustion of vent gases between C018 and C019 are additive.

Gas Analytical

Report Date: Sep 14, 2015 9:23a

Client:	Equitable Production	Date Sampled:	Sep 8, 2015 11:00a
Site:	514394	Analysis Date:	Sep 11, 2015 2:17p
Field No:	9998	Collected By:	J. Brown
Meter:	514394	Date Effective:	Sep 8, 2015 12:00a
Source Laboratory	Clarksburg (Bridgeport), WV	Sample Pressure (PSI):	70.0
Lab File No:	X_CH1-6024.CHR	Sample Temp (°F):	
Sample Type:	Spot	Field H2O:	No Test
Reviewed By:		Field H2S:	No Test

Component	Mol %	Gal/MSCF
Methane	78.1311	
Ethane	14.2559	3.79
Propane	4.0036	1.10
I-Butane	0.5947	0.19
N-Butane	1.1890	0.37
I-Pentane	0.3163	0.12
N-Pentane	0.3248	0.12
Nitrogen	0.4544	
Oxygen	<MDL	
Carbon Dioxide	0.1535	
Hexanes+	0.5767	0.24
TOTAL	100.0000	5.93

Analytical Results at Base Conditions (Real)	
BTU/SCF (Dry):	1,262.4954 BTU/ft ³
BTU/SCF (Saturated):	1,241.4002 BTU/ft ³
PSIA:	14.730 PSI
Temperature (°F):	60.00 °F
Z Factor (Dry):	0.99644
Z Factor (Saturated):	0.99604

Analytical Results at Contract Conditions (Real)	
BTU/SCF (Dry):	1,262.4954 BTU/ft ³
BTU/SCF (Saturated):	1,241.4002 BTU/ft ³
PSIA:	14.730 PSI
Temperature (°F):	60.00 °F
Z Factor (Dry):	0.99644
Z Factor (Saturated):	0.99604

Calculated Specific Gravities		
Ideal Gravity:	0.7188	Real Gravity: 0.7211
Molecular Wt:	20.8177 lb/lbmol	

Gross Heating Values are Based on:
 GPA 2145-09, 2186
 Compressibility is Calculated using AGA-8.

Source	Date	Notes
Gas Analytical	Sep 11, 2015	results to Bob Gum

Gas Analytical Services

Tulsa, OK
918-827-5770

Customer : 01 - GAS ANALYTICAL SERVICES-MOUNDS	Date Sampled : 10/23/2015
Station Id : 513700	Date Analyzed : 11/05/2015
Cylinder Id : 32	Effective Date : 11/01/2015
Producer : EQT PRODUCTION	Line Pressure : 0.00000
Lease : MAXWELL OXF 159 PAD	Cyl Pressure : 750.00000
Area : MGM D	Temp : 0.00000
Sample By : R MOORE	Cylinder Type : Spot
Property Cd :	Formation :

COMPONENT		Mole Percent	WT. Percent	Liq Vol Percent
Methane	C1	12.0883	2.0724	4.7592
Ethane	C2	7.8631	2.5267	4.8832
Propane	C3	5.5315	2.6066	3.5391
Iso-Butane	IC4	1.3547	0.8414	1.0295
Normal-Butane	NC4	3.4686	2.1544	2.5395
Iso-Pentane	IC5	1.6931	1.3054	1.4377
Normal-Pentane	NC5	2.0423	1.5747	1.7190
Nitrogen	N2	0.0061	0.0018	0.0011
Carbon-Dioxide	CO2	0.2444	0.1149	0.0964
BENZENE	BENZENE	0.1502	0.1254	0.0970
TOLUENE	TOLUENE	0.7588	0.7471	0.5896
ETHYLBENZENE	E-BENZENE	0.0943	0.1069	0.0843
M-XYLENE/P-XYLENE	M-XYLENE/P-XYLENE	0.8104	0.9195	0.7279
C6's	C6's	11.2622	10.3718	10.7630
C7's	C7's	14.0473	19.0341	18.1088
C8's	C8's	7.5660	9.0859	8.7701
C9's	C9's	6.9027	9.1020	8.4661
C10's	C10's	3.4358	4.7876	4.2595
C11's	C11's	10.0244	14.4992	11.9130
C12's	C12's	9.0484	14.8557	13.3497
C13's	C13's	1.6071	3.1664	2.8662
TOTAL		99.9997	100.0000	100.0000

Totals

SPECIFIC GRAVITY @ 60 DEG. F. (WATER = 1)	0.6883
MOLECULAR WEIGHT	93.5782


Comments:

POUNDS/GALLON (ABSOLUTE DENSITY)	5.7385
CALC. VAPOR PRESSURE @ 14.65 PSIA, 100 Deg. F.	670.8797
CUFT. VAPOR / GALLON @ 14.65 PSIA, 60 Deg. G.	23.4174
BTU / CUFT. DRY GAS @ 14.65 PSIA, 60 Deg. F.	4,864.3860
BTU / GALLON LIQUID	117,559.7344
BTU / POUND	20,382.0537


Comments:

Installation Drawings


Front End View



Left Side View



Power Curves (corrected per SAE J1349)



Powertrain Assemblies
& Components
Provided By Ford
Component Sales

For additional information Contact:


**ENGINE
DISTRIBUTORS
INC.**



400 University Ct • Blackwood NJ 08012
856/228-7298 • Fax:856/228-5531
www.edi-dist.com

CSG-637 EFI

3.7 Liter 6-Cylinder



Options

Engine Cooling Fans

- 14" (355mm) diameter suction
- 14" (355mm) diameter pusher

Flywheels

- 11.5" (292mm) SAE over-center clutch
- flat face flywheel

Flywheel Housings

- SAE #3

Exhaust Manifold

- rear dump down

Power Steering Pump

Air Conditioning

Wiring Harnesses

Discrete Speed Switch

Variable Speed Hand Throttle

Variable Speed Foot Pedal

Engine Mounts

- Automotive with insulators
- Open power unit

Electronic Instrument Panel, Gauges

Three Way Catalyst / Muffler Standard

Transmissions

6R80 electronic shift

Emissions Information

California Air Resources Board (CARB)
Environmental Protection Agency (EPA)
Emission Certified Packages

Warranty

Contact Engine Distributors, Inc
for warranty details.



Powertrain Assemblies
& Components
Provided By Ford
Component Sales

Specifications

Engine Type	V-6
Bore and Stroke	3.7" x 3.4" (94mm x 86mm)
Displacement	3.7L Liter (225.7 CID)
Compression Ratio	10.5:1
Oil Capacity	6 qts. including filter
Net Weight	355 Lbs. with accessories (161 Kgs.)
Dimensions	L 25.4" x W 29.5" x H 29.4" (646 mm x 751 mm x 748 mm)

Gasoline (corrected per SAE J1349)

Unleaded 87 or 89 octane		
Intermittent Power	107 [HP] @ 3200rpm	(80 [kW] @ 3200rpm)
Continuous Power	96 [HP] @ 3200rpm	(72 [kW] @ 3200rpm)
Intermittent Torque	193 [ft-lbs] @ 2600rpm	(261 [N-m] @ 2600rpm)
Continuous Torque	173 [ft-lbs] @ 2600rpm	(235 [N-m] @ 3200rpm)

Natural Gas (corrected per SAE J1349)

Fuel Specification	1050 BTU/FT3	
Intermittent Power	110 [HP] @ 3200rpm	(82 [kW] @ 3200rpm)
Continuous Power	99 [HP] @ 3200rpm	(74 [kW] @ 3200rpm)
Intermittent Torque	191 [ft-lbs] @ 1600rpm	(259 [N-m] @ 1600rpm)
Continuous Torque	172 [ft-lbs] @ 1600rpm	(233 [N-m] @ 1600rpm)

Liquefied Petroleum Gas (corrected per SAE J1349)

Fuel Specification	HD-5	
Intermittent Power	118 [HP] @ 3200rpm	(88 [kW] @ 3200rpm)
Continuous Power	106 [HP] @ 3200rpm	(79 [kW] @ 3200rpm)
Intermittent Torque	209 [ft-lbs] @ 2600rpm	(284 [N-m] @ 2600rpm)
Continuous Torque	188 [ft-lbs] @ 2600rpm	(255 [N-m] @ 2600rpm)

Standard Features / Benefits

Set-for-life valvetrain

Deep skirted, ribbed cylinder block casting for rigidity

150 AMP Alternator

Aluminum cylinder block and heads.

Chain driven dual camshafts with automatic tensioning system

Structural front cover and deep sump oil pan

Alternate fuel ready valvetrain components

Individual coil on plug electronic ignition

Four main bolts with side bolts through block for strength
and durability

Gasoline Sequential Port Fuel Injection

Closed loop fuel control for all fuels

Electronic engine management system with built-in engine
protection against detonation, high coolant temperature, low oil
pressure, over speed shutdown and starter lockout

Next generation governing – discrete speeds, variable speeds,
drive by wire – using the highest quality components.

Variable CAM Timing for intake camshafts - advances or retards
timing to maximize engine power and fuel efficiency

Forged steel crankshaft




**UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
2015 MODEL YEAR
CERTIFICATE OF CONFORMITY
WITH THE CLEAN AIR ACT**

**OFFICE OF TRANSPORTATION
AND AIR QUALITY
ANN ARBOR, MICHIGAN 48105**

Certificate Issued To: Engine Distributors, Inc.
(U.S. Manufacturer or Importer)
Certificate Number: FEDIB03.7CSG-006

Effective Date:
06/08/2015

Expiration Date:
12/31/2015


Byron J. Bunker, Division Director
Compliance Division

Issue Date:
06/08/2015
Revision Date:
N/A

Manufacturer: Engine Distributors, Inc.
Engine Family: FEDIB03.7CSG
Mobile/Stationary Certification Type: Mobile and Stationary
Fuel : LPG/Propane
Gasoline (up to and including 10% Ethanol)
Natural Gas (CNG/LNG)
Emission Standards :
Mobile Part 1048
HC + NOx (g/kW-hr) : 0.8
NMHC + NOx (g/kW-hr) : 0.8
CO (g/kW-hr) : 20.6
Part 60 Subpart JJJJ Table 1
NOx (g/kW-hr) : 1.3
HC + NOx (g/kW-hr) : 0.8
CO (g/kW-hr) : 2.7
CO (g/kW-hr) : 20.6
VOC (g/kW-hr) : 0.9
Emergency Use Only : N

Pursuant to Section 213 of the Clean Air Act (42 U.S.C. section 7547) and 40 CFR Part 60, 40 CFR Part 1048, 1065, 1068, and 60 (stationary only and combined stationary and mobile) and subject to the terms and conditions prescribed in those provisions, this certificate of conformity is hereby issued with respect to the test engines which have been found to conform to applicable requirements and which represent the following nonroad engines, by engine family, more fully described in the documentation required by 40 CFR Part 60, 40 CFR Part 1048 and produced in the stated model year.

This certificate of conformity covers only those new nonroad spark-ignition engines which conform in all material respects to the design specifications that applied to those engines described in the documentation required by 40 CFR Part 60, 40 CFR Part 1048 and which are produced during the model year stated on this certificate of the said manufacturer, as defined in 40 CFR Part 60, 40 CFR Part 1048. This certificate of conformity does not cover nonroad engines imported prior to the effective date of the certificate.

It is a term of this certificate that the manufacturer shall consent to all inspections described in 40 CFR 1068.20 and authorized in a warrant or court order. Failure to comply with the requirements of such a warrant or court order may lead to revocation or suspension of this certificate for reasons specified in 40 CFR Part 60, 40 CFR Part 1048. It is also a term of this certificate that this certificate may be revoked or suspended or rendered void *ab initio* for other reasons specified in 40 CFR Part 60, 40 CFR Part 1048.

This certificate does not cover large nonroad engines sold, offered for sale, or introduced, or delivered for introduction, into commerce in the U.S. prior to the effective date of the certificate.

Flowsheet1 Plant Schematic

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	
Flowsheet:	Flowsheet1	

EQT OXF 159 Well Pad
Blowdown Tank

Temperature	85°	°F
Pressure	750°	psig
Std Liquid Volumetric Flow	2.86#	bb/d

Stream 4 C3+ Mass Flow = 1.759 lb/h

Temperature	85°	°F
Pressure	750°	psig
Std Liquid Volumetric Flow	17.61#	bb/d

Temperature	85.3	°F
Pressure	0	psig
Std Liquid Volumetric Flow	20	bb/d
Water(Volumetric Fraction)	87.971	%

Tank loss calculations for "5":
Total working and breathing losses from the Horizontal Cylinder are 0.004841 lb/h.
Loading losses are 0.004271 lb/h of loaded liquid.

Note
Working, Breathing and Loading losses include non-VOC components

Process Streams Report
All Streams
 Tabulated by Total Phase

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	
Flowsheet:	Flowsheet1	

Connections

	OXF 159 Pad Condensate	Produced Water	3	4	5
From Block	--	--	MIX-100	VSSL-100	VSSL-100
To Block	MIX-100	MIX-100	VSSL-100	--	--

Stream Composition

	OXF 159 Pad Condensate %	Produced Water %	3 %	4 %	5 %
Methane	12.0883 *	0 *	0.245954	38.7579	0.0035423
Ethane	7.86312 *	0 *	0.159986	23.8626	0.0107912
Propane	5.53152 *	0 *	0.112546	14.506	0.0219477
Isobutane	1.3547 *	0 *	0.0275634	2.7534	0.0104057
n-Butane	3.46861 *	0 *	0.0705738	6.11698	0.0325149
Isopentane	1.69311 *	0 *	0.0344486	1.76038	0.0235848
n-Pentane	2.04231 *	0 *	0.0415536	1.73689	0.0308824
Nitrogen	0.00610002 *	0 *	0.000124113	0.0197355	6.70552E-07
Carbon Dioxide	0.244401 *	0 *	0.00497268	0.718091	0.000483987
Benzene	0.1502 *	0 *	0.00305604	0.0448011	0.00279328
Toluene	0.758802 *	0 *	0.0154389	0.0722949	0.015081
Ethylbenzene	0.0943003 *	0 *	0.00191867	0.00312243	0.0019111
m-Xylene	0.810402 *	0 *	0.0164888	0.0226763	0.0164498
C6	11.2622 *	0 *	0.229146	3.54448	0.208278
C7	14.0473 *	0 *	0.285813	1.57398	0.277705
C8	7.56602 *	0 *	0.153941	0.283136	0.153128
C9	6.90272 *	0 *	0.140446	0.0866503	0.140784
C10	3.43581 *	0 *	0.0699064	0.0144391	0.0702555
C11	10.0244 *	0 *	0.203961	0.0129074	0.205164
C12	9.04843 *	0 *	0.184103	0.00461187	0.185233
C13	1.6071 *	0 *	0.0326988	0.000243033	0.0329031
Water	0 *	100 *	97.9654	4.10468	98.5562

	OXF 159 Pad Condensate %	Produced Water %	3 %	4 %	5 %
Methane	2.05568 *	0 *	0.201639	18.41	0.00291739
Ethane	2.50629 *	0 *	0.24584	21.2452	0.0166582
Propane	2.58557 *	0 *	0.253617	18.9393	0.0496849
Isobutane	0.834649 *	0 *	0.0818699	4.73843	0.0310493
n-Butane	2.13705 *	0 *	0.209621	10.5269	0.0970206
Isopentane	1.29488 *	0 *	0.127014	3.76061	0.0873575
n-Pentane	1.56195 *	0 *	0.15321	3.71042	0.114388
Nitrogen	0.0018114 *	0 *	0.000177678	0.0163695	9.64356E-07
Carbon Dioxide	0.114016 *	0 *	0.0111837	0.935725	0.0010935
Benzene	0.124367 *	0 *	0.012199	0.103616	0.0112013
Toluene	0.741117 *	0 *	0.0726955	0.197229	0.0713363
Ethylbenzene	0.106124 *	0 *	0.0104096	0.00981514	0.010416
m-Xylene	0.912009 *	0 *	0.0894582	0.0712814	0.0896565
C6	10.2879 *	0 *	1.00913	9.04396	0.921436
C7	14.9206 *	0 *	1.46355	4.66978	1.42856
C8	9.16135 *	0 *	0.898628	0.95762	0.897984
C9	9.38452 *	0 *	0.920519	0.329054	0.926974
C10	5.18198 *	0 *	0.508295	0.0608292	0.513179
C11	16.6096 *	0 *	1.62922	0.059737	1.64635
C12	16.3378 *	0 *	1.60256	0.0232597	1.6198
C13	3.14074 *	0 *	0.308072	0.00132665	0.31142
Water	0 *	100 *	90.1911	2.18949	91.1515

Process Streams Report All Streams Tabulated by Total Phase

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	
Flowsheet:	Flowsheet1	

Mass Flow	OXF 159 Pad Condensate lb/h	Produced Water lb/h	3 lb/h	4 lb/h	5 lb/h
Methane	0.57441 *	0 *	0.57441	0.566189	0.00822105
Ethane	0.700324 *	0 *	0.700324	0.653382	0.0469419
Propane	0.722477 *	0 *	0.722477	0.582468	0.140009
Isobutane	0.233223 *	0 *	0.233223	0.145727	0.0874953
n-Butane	0.597148 *	0 *	0.597148	0.323749	0.273399
Isopentane	0.361824 *	0 *	0.361824	0.115655	0.246169
n-Pentane	0.43645 *	0 *	0.43645	0.114112	0.322338
Nitrogen	0.000506152 *	0 *	0.000506152	0.000503435	2.7175E-06
Carbon Dioxide	0.0318591 *	0 *	0.0318591	0.0287777	0.00308142
Benzene	0.0347514 *	0 *	0.0347514	0.00318666	0.0315648
Toluene	0.207087 *	0 *	0.207087	0.00606566	0.201022
Ethylbenzene	0.0296537 *	0 *	0.0296537	0.000301859	0.0293518
m-Xylene	0.254839 *	0 *	0.254839	0.00219222	0.252647
C6	2.8747 *	0 *	2.8747	0.278141	2.59656
C7	4.16922 *	0 *	4.16922	0.143616	4.0256
C8	2.55992 *	0 *	2.55992	0.029451	2.53047
C9	2.62228 *	0 *	2.62228	0.0101199	2.61216
C10	1.44798 *	0 *	1.44798	0.00187077	1.44611
C11	4.64115 *	0 *	4.64115	0.00183718	4.63932
C12	4.56521 *	0 *	4.56521	0.000715336	4.5645
C13	0.877604 *	0 *	0.877604	4.08004E-05	0.877563
Water	0 *	256.927 *	256.927	0.0673363	256.86

Stream Properties

Property	Units	OXF 159 Pad Condensate	Produced Water	3	4	5
Temperature	°F	85 *	85 *	85.0322	85.3144	85.3144
Pressure	psia	764.696 *	764.696 *	764.696	14.6959 *	14.6959
Mole Fraction Vapor	%	0	0	0	100	0
Mole Fraction Light Liquid	%	100	100	1.9773	0	1.44191
Mole Fraction Heavy Liquid	%	0	0	98.0227	0	98.5581
Molecular Weight	lb/lbmol	94.3372	18.0153	19.5682	33.7736	19.4787
Mass Density	lb/ft^3	42.5484	62.1657	59.4945	0.0856498	59.9534
Molar Flow	lbmol/h	0.2962	14.2616	14.5578	0.0910604	14.4668
Mass Flow	lb/h	27.9426	256.927	284.87	3.07544	281.794
Vapor Volumetric Flow	ft^3/h	0.656726	4.13294	4.78817	35.9071	4.70023
Liquid Volumetric Flow	gpm	0.0818775	0.515276	0.596966	4.47673	0.586002
Std Vapor Volumetric Flow	MMSCFD	0.00269768	0.12989	0.132587	0.000829344	0.131758
Std Liquid Volumetric Flow	sgpm	0.0834177 *	0.513616 *	0.597034	0.0137043	0.58333
Compressibility		0.290062	0.0379124	0.0430267	0.990834	0.000816388
Specific Gravity		0.682204	0.99674	0.953912	1.16611	0.961269
API Gravity		72.1028	9.92101	16.0588		14.9647
Enthalpy	Btu/h	-26630	-1.75009E+06	-1.77672E+06	-4032.05	-1.77269E+06
Mass Enthalpy	Btu/lb	-953.025	-6811.63	-6236.96	-1311.05	-6290.72
Mass Cp	Btu/(lb*°F)	0.515421	0.980868	0.93572	0.432006	0.939886
Ideal Gas CpCv Ratio		1.0558	1.32512	1.29605	1.15853	1.29765
Dynamic Viscosity	cP	0.369408	0.83769	0.772736	0.00947241	0.792497
Kinematic Viscosity	cSt	0.542004	0.841224	0.800382	6.9042	0.823367
Thermal Conductivity	Btu/(h*ft*°F)	0.0705431	0.353848	0.314667	0.0136664	0.320189
Surface Tension	lbf/ft	0.000907691 ?	0.00492858	0.00437905 ?		0.00450497 ?
Net Ideal Gas Heating Value	Btu/ft^3	4793.76	0	97.5359	1737.76	87.2116
Net Liquid Heating Value	Btu/lb	19129.2	-1059.76	920.558	19378.4	719.113
Gross Ideal Gas Heating Value	Btu/ft^3	5171.4	50.31	154.506	1897.81	143.533
Gross Liquid Heating Value	Btu/lb	20648.3	0	2025.37	21176.7	1816.36

Remarks

* User Specified Values
? Extrapolated or Approximate Values

	Blocks MIX-100 Mixer/Splitter Report	
--	----------------------------------------------------------	--

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	Modified: 2:14 PM, 7/24/2014
Flowsheet:	Flowsheet1	Status: Solved 9:51 AM, 2/4/2016

Connections					
Stream	Connection Type	Other Block	Stream	Connection Type	Other Block
Produced Water	Inlet		OXF 159 Pad Condensate	Inlet	
3	Outlet	VSSL-100			

Block Parameters			
Pressure Drop	0 psi	Fraction to PStream 3	100 %

Remarks

Blocks
VSSL-100
Separator Report

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	Modified: 1:11 PM, 7/17/2014
Flowsheet:	Flowsheet1	Status: Solved 9:51 AM, 2/4/2016

Connections

Stream	Connection Type	Other Block	Stream	Connection Type	Other Block
3	Inlet	MIX-100	4	Vapor Outlet	
5	Light Liquid Outlet				

Block Parameters

Pressure Drop	750 psi	Main Liquid Phase	Light Liquid
Mole Fraction Vapor	0.625508 %	Heat Duty	0 Btu/h
Mole Fraction Light Liquid	1.43289 %	Heat Release Curve Type	Plug Flow
Mole Fraction Heavy Liquid	97.9416 %	Heat Release Curve Increments	5

Remarks

Flowsheet Environment Environment1					
Client Name:	EQT			Job:	
Location:	OXF 159 Blowdown Tank				
Flowsheet:	Flowsheet1				
Environment Settings					
Number of Poynting Intervals	0	Freeze Out Temperature Threshold Difference	10 °F		
Gibbs Excess Model Evaluation Temperature	77 °F	Phase Tolerance	1 %		
Components					
Component Name	Henry's Law Component	Phase Initiator	Component Name	Henry's Law Component	Phase Initiator
Methane	False	False	Ethylbenzene	False	False
Ethane	False	False	m-Xylene	False	False
Propane	False	False	C6	False	False
Isobutane	False	False	C7	False	False
n-Butane	False	False	C8	False	False
Isopentane	False	False	C9	False	False
n-Pentane	False	False	C10	False	False
Nitrogen	False	False	C11	False	False
Carbon Dioxide	False	False	C12	False	False
Benzene	False	False	C13	False	False
Toluene	False	False	Water	False	True
Physical Property Method Sets					
Liquid Molar Volume	COSTALD	Overall Package	Peng-Robinson		
Stability Calculation	Peng-Robinson	Vapor Package	Peng-Robinson		
Light Liquid Package	Peng-Robinson	Heavy Liquid Package	Peng-Robinson		
Remarks					

Calculator Report

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	

Simple Solver 1

Source Code

Residual Error (for CV1) = TP / 20 - 1

Calculated Variable [CV1]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!OXF 159 Pad Condensate!Phases!Total!Properties!Std Liquid Volumetric Flow
Value	2.86004
Unit	bb/d

Measured Variable [TP]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!5!Phases!Total!Properties!Std Liquid Volumetric Flow
Value	19.9999
Unit	bb/d

Solver Properties

Status: Solved

Error	-6.47642E-06	Iterations	6
Calculated Value	0.0834177	Max Iterations	20
Lower Bound	sgpm	Weighting	1
Upper Bound	sgpm	Priority	0
Step Size	sgpm	Solver Active	Active
Is Minimizer	False	Group	
Algorithm	Default	Skip Dependency Check	False

Remarks

Simple Solver 2

Source Code

Residual Error (for CV1) = LF / 88 - 1

Calculated Variable [CV1]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!Produced Water!Phases!Total!Properties!Std Liquid Volumetric Flow
Value	17.6097
Unit	bb/d

Measured Variable [LF]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!5!Phases!Total!Composition!Std. Liquid Volumetric Fraction!Water
Value	88.026
Unit	%

Solver Properties

Status: Solved

Error	0.000295209	Iterations	6
Calculated Value	0.513616	Max Iterations	20
Lower Bound	sgpm	Weighting	1
Upper Bound	sgpm	Priority	0
Step Size	sgpm	Solver Active	Active
Is Minimizer	False	Group	
Algorithm	Default	Skip Dependency Check	False

Remarks

User Value Sets Report

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	

Cn+ Flow/Frac.

User Value [CnPlusSum]

* Parameter	1.75925 lb/h	Upper Bound	
Lower Bound	lb/h	* Enforce Bounds	False

Remarks

This User Value Set was programmatically generated. GUID={E867C485-3D3C-49CB-BC24-EA16096DB2B1}

Tank Losses

User Value [ShellLength]

* Parameter	10 ft	Upper Bound	
* Lower Bound	0 ft	* Enforce Bounds	False

User Value [ShellDiam]

* Parameter	10 ft	Upper Bound	
* Lower Bound	0 ft	* Enforce Bounds	False

User Value [BreatherVP]

* Parameter	0.03 psig	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [BreatherVacP]

* Parameter	-0.03 psig	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [DomeRadius]

Parameter	ft	Upper Bound	ft
Lower Bound	ft	* Enforce Bounds	False

User Value [OpPress]

* Parameter	0 psig	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [AvgPercentLiq]

* Parameter	50 %	Upper Bound	
Lower Bound	%	* Enforce Bounds	False

User Value [MaxPercentLiq]

* Parameter	90 %	Upper Bound	
Lower Bound	%	* Enforce Bounds	False

User Value [AnnNetTP]

* Parameter	19.8551 bbl/day	Upper Bound	
* Lower Bound	0 bbl/day	* Enforce Bounds	False

User Value [OREff]

* Parameter	0 %	Upper Bound	
Lower Bound	%	* Enforce Bounds	False

User Value [AtmPressure]

* Parameter	14.1085 psia	Upper Bound	
Lower Bound		* Enforce Bounds	False

* User Specified Values
 ? Extrapolated or Approximate Values

User Value Sets Report

Client Name:	EQT	Job:
Location:	OXF 159 Blowdown Tank	

User Value [TVP]

* Parameter	0.353397 psia	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [AvgLiqSurfaceT]

* Parameter	57.7675 °F	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [MaxLiqSurfaceT]

* Parameter	66.3119 °F	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [TotalLosses]

* Parameter	0.00484103 lb/h	Upper Bound	
Lower Bound	lb/h	* Enforce Bounds	False

User Value [WorkingLosses]

* Parameter	0.0212037 ton/yr	Upper Bound	
Lower Bound	ton/yr	* Enforce Bounds	False

User Value [StandingLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound	ton/yr	* Enforce Bounds	False

User Value [RimSealLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [WithdrawalLoss]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [LoadingLosses]

* Parameter	0.00427056 lb/h	Upper Bound	
Lower Bound	lb/h	* Enforce Bounds	False

User Value [DeckFittingLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [DeckSeamLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [FlashingLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [GasMoleWeight]

* Parameter	0.0240714 kg/mol	Upper Bound	
Lower Bound		* Enforce Bounds	False


Remarks

This User Value Set was programmatically generated. GUID={B57AFC7E-AAE8-4873-921B-7B4031991004}

Flowsheet1 Plant Schematic

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	
Flowsheet:	Flowsheet1	

EQT OXF 159 Well Pad
Adjusted Contingency
With Low Pressure Tower



Note
Working, Breathing and Loading losses include non-VOC components

* User Specified Values
? Extrapolated or Approximate Values

Process Streams Report
All Streams
 Tabulated by Total Phase

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	
Flowsheet:	Flowsheet1	

Connections

	Flash Gas	OXF 159 Pad Condensate	Produced Water	Stable Liquid	To Sales Pipeline
From Block	VSSL-100	--	--	VSSL-100	Low Pressure Tower
To Block	--	MIX-100	MIX-100	--	--

Stream Composition

	Flash Gas	OXF 159 Pad Condensate	Produced Water	Stable Liquid	To Sales Pipeline
Mole Fraction	%	%	%	%	%
Methane	12.6524	12.0883 *	0 *	0.0010686	46.042
Ethane	23.9335	7.86312 *	0 *	0.00902996	25.5431
Propane	22.7886	5.53152 *	0 *	0.0263771	12.9561
Isobutane	4.74153	1.3547 *	0 *	0.0129059	2.04264
n-Butane	10.5439	3.46861 *	0 *	0.0393977	4.25071
Isopentane	2.96072	1.69311 *	0 *	0.0262184	1.07324
n-Pentane	2.91865	2.04231 *	0 *	0.0334961	1.0384
Nitrogen	0.00269923	0.00610002 *	0 *	8.80962E-08	0.0239695
Carbon Dioxide	0.860391	0.244401 *	0 *	0.000472161	0.735543
Benzene	0.0758285	0.1502 *	0 *	0.00284095	0.0258909
Toluene	0.130279	0.758802 *	0 *	0.0150127	0.0442438
Ethylbenzene	0.00605048	0.0943003 *	0 *	0.00189198	0.00206768
m-Xylene	0.0446529	0.810402 *	0 *	0.0162785	0.0152788
C6	6.07648	11.2622 *	0 *	0.211984	2.07783
C7	2.85496	14.0473 *	0 *	0.276751	0.973499
C8	0.552772	7.56602 *	0 *	0.151621	0.189629
C9	0.182377	6.90272 *	0 *	0.139168	0.062958
C10	0.0328659	3.43581 *	0 *	0.0694219	0.0115144
C11	0.0319445	10.0244 *	0 *	0.202717	0.0113155
C12	0.0121375	9.04843 *	0 *	0.183024	0.00434053
C13	0.000703234	1.6071 *	0 *	0.0325111	0.000255115
Water	8.59662	0 *	100 *	98.5478	2.87544

	Flash Gas	OXF 159 Pad Condensate	Produced Water	Stable Liquid	To Sales Pipeline
Mass Fraction	%	%	%	%	%
Methane	4.65074	2.05568 *	0 *	0.000880201	24.6255
Ethane	16.4894	2.50629 *	0 *	0.0139412	25.6066
Propane	23.0246	2.58557 *	0 *	0.0597198	19.0471
Isobutane	6.31451	0.834649 *	0 *	0.0385145	3.95815
n-Butane	14.0418	2.13705 *	0 *	0.117573	8.23687
Isopentane	4.89448	1.29488 *	0 *	0.0971251	2.58158
n-Pentane	4.82492	1.56195 *	0 *	0.124085	2.49777
Nitrogen	0.00173255	0.0018114 *	0 *	1.26712E-07	0.0223864
Carbon Dioxide	0.867605	0.114016 *	0 *	0.00106692	1.07923
Benzene	0.135715	0.124367 *	0 *	0.011394	0.0674253
Toluene	0.275039	0.741117 *	0 *	0.0710222	0.13591
Ethylbenzene	0.0147181	0.106124 *	0 *	0.0103132	0.00731852
m-Xylene	0.10862	0.912009 *	0 *	0.0887341	0.0540791
C6	11.9982	10.2879 *	0 *	0.937955	5.9697
C7	6.55474	14.9206 *	0 *	1.42384	3.25215
C8	1.44677	9.16135 *	0 *	0.889259	0.722167
C9	0.53595	9.38452 *	0 *	0.916454	0.269206
C10	0.107146	5.18198 *	0 *	0.507155	0.0546197
C11	0.114408	16.6096 *	0 *	1.62692	0.0589676
C12	0.047371	16.3378 *	0 *	1.60069	0.0246493
C13	0.00297064	3.14074 *	0 *	0.307749	0.00156807
Water	3.54853	0 *	100 *	91.1556	1.72705

Process Streams Report
All Streams
 Tabulated by Total Phase

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	
Flowsheet:	Flowsheet1	

Mass Flow	Flash Gas lb/h	OXF 159 Pad Condensate lb/h	Produced Water lb/h	Stable Liquid lb/h	To Sales Pipeline lb/h
Methane	0.870182	19.0098 *	0 *	0.0830642	18.0565
Ethane	3.08527	23.1768 *	0 *	1.31563	18.776
Propane	4.30805	23.91 *	0 *	5.63573	13.9662
Isobutane	1.18148	7.71838 *	0 *	3.6346	2.9023
n-Butane	2.62731	19.7623 *	0 *	11.0953	6.03965
Isopentane	0.915787	11.9744 *	0 *	9.16565	1.89293
n-Pentane	0.902772	14.4441 *	0 *	11.7098	1.83148
Nitrogen	0.000324171	0.0167508 *	0 *	1.19578E-05	0.0164147
Carbon Dioxide	0.162334	1.05436 *	0 *	0.100685	0.79134
Benzene	0.0253932	1.15008 *	0 *	1.07525	0.0494393
Toluene	0.0514616	6.85345 *	0 *	6.70233	0.0996558
Ethylbenzene	0.00275384	0.981373 *	0 *	0.973253	0.00536627
m-Xylene	0.0203235	8.43377 *	0 *	8.37379	0.0396533
C6	2.24493	95.1365 *	0 *	88.5143	4.37726
C7	1.22643	137.978 *	0 *	134.367	2.38463
C8	0.2707	84.7192 *	0 *	83.919	0.529526
C9	0.10028	86.783 *	0 *	86.4853	0.197394
C10	0.0200476	47.9201 *	0 *	47.86	0.0400497
C11	0.0214065	153.597 *	0 *	153.532	0.0432378
C12	0.0088634	151.083 *	0 *	151.056	0.018074
C13	0.000555824	29.0438 *	0 *	29.0421	0.00114978
Water	0.663952	0 *	8604.24 *	8602.31	1.26635

Stream Properties

Property	Units	Flash Gas	OXF 159 Pad Condensate	Produced Water	Stable Liquid	To Sales Pipeline
Temperature	°F	109.707	85 *	85 *	109.707	110 *
Pressure	psia	14.6959 *	764.696 *	764.696 *	14.6959	44.6959 *
Mole Fraction Vapor	%	100	0	0	0	100
Mole Fraction Light Liquid	%	0	100	100	1.45147	0
Mole Fraction Heavy Liquid	%	0	0	0	98.5485	0
Molecular Weight	lb/lbmol	43.6436	94.3372	18.0153	19.4762	29.9944
Mass Density	lb/ft^3	0.106402	42.5484	62.1657	59.5714	0.22365
Molar Flow	lbmol/h	0.428714	9.80256	477.608	484.537	2.44461
Mass Flow	lb/h	18.7106	924.746	8604.24	9436.95	73.3246
Vapor Volumetric Flow	ft^3/h	175.848	21.734	138.408	158.414	327.854
Liquid Volumetric Flow	gpm	21.9239	2.70969	17.2561	19.7503	40.8753
Std Vapor Volumetric Flow	MMSCFD	0.00390457	0.0892781	4.34988	4.41299	0.0222646
Std Liquid Volumetric Flow	sgpm	0.0725239	2.76067 *	17.2005 *	19.5377	0.350985
Compressibility		0.986515	0.290062	0.0379124	0.000786322	0.980511
Specific Gravity		1.50689	0.682204	0.99674	0.955144	1.03563
API Gravity			72.1028	9.92101	15.0343	
Enthalpy	Btu/h	-22466.2	-881306	-5.86089E+07	-5.91519E+07	-100341
Mass Enthalpy	Btu/lb	-1200.72	-953.025	-6811.63	-6268.12	-1368.45
Mass Cp	Btu/(lb*°F)	0.427446	0.515421	0.980868	0.941084	0.456873
Ideal Gas CpCv Ratio		1.11993	1.0558	1.32512	1.29564	1.17211
Dynamic Viscosity	cP	0.00908206	0.369408	0.83769	0.611393	0.0102541
Kinematic Viscosity	cSt	5.3286	0.542004	0.841224	0.641482	2.86225
Thermal Conductivity	Btu/(h*ft*°F)	0.0120441	0.0705431	0.353848	0.328206	0.0156232
Surface Tension	lbf/ft		0.000907691 ?	0.00492858	0.00432805 ?	
Net Ideal Gas Heating Value	Btu/ft^3	2181.42	4793.76	0	87.1724	1561.68
Net Liquid Heating Value	Btu/lb	18785.4	19129.2	-1059.76	718.529	19625.4
Gross Ideal Gas Heating Value	Btu/ft^3	2373.81	5171.4	50.31	143.49	1708.93
Gross Liquid Heating Value	Btu/lb	20458.3	20648.3	0	1815.84	21488.4

Remarks

* User Specified Values
 ? Extrapolated or Approximate Values

Process Streams Report
All Streams
 Tabulated by Total Phase

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	
Flowsheet:	Flowsheet1	

Connections

	1	3			
From Block	Low Pressure Tower	MIX-100			
To Block	VSSL-100	Low Pressure Tower			

Stream Composition

Mole Fraction	1 %	3 %			
Methane	0.0122525	0.243115			
Ethane	0.0301794	0.158139			
Propane	0.0464991	0.111247			
Isobutane	0.017086	0.0272451			
n-Butane	0.0486838	0.069759			
Isopentane	0.0288126	0.0340509			
n-Pentane	0.0360466	0.0410739			
Nitrogen	2.47416E-06	0.000122681			
Carbon Dioxide	0.00123234	0.00491527			
Benzene	0.00290547	0.00302076			
Toluene	0.0151146	0.0152607			
Ethylbenzene	0.00189566	0.00189652			
m-Xylene	0.0163036	0.0162984			
C6	0.217168	0.226501			
C7	0.27903	0.282513			
C8	0.151975	0.152164			
C9	0.139207	0.138824			
C10	0.0693896	0.0690993			
C11	0.202566	0.201606			
C12	0.182873	0.181978			
C13	0.0324829	0.0323213			
Water	98.4683	97.9888			

Mass Fraction	1 %	3 %			
Methane	0.0100812	0.199494			
Ethane	0.0465424	0.243225			
Propane	0.105162	0.250918			
Isobutane	0.0509333	0.0809989			
n-Butane	0.145126	0.207391			
Isopentane	0.106618	0.125663			
n-Pentane	0.133387	0.15158			
Nitrogen	3.55478E-06	0.000175788			
Carbon Dioxide	0.0027816	0.0110648			
Benzene	0.01164	0.0120693			
Toluene	0.0714259	0.0719221			
Ethylbenzene	0.0103219	0.0102988			
m-Xylene	0.0887734	0.0885065			
C6	0.95984	0.998391			
C7	1.43399	1.44798			
C8	0.890362	0.889068			
C9	0.915701	0.910726			
C10	0.506364	0.502888			
C11	1.62393	1.61189			
C12	1.59762	1.58551			
C13	0.307146	0.304795			
Water	90.9823	90.2954			

Mass Flow	1 lb/h	3 lb/h			
Methane	0.953247	19.0098			

Process Streams Report
All Streams
 Tabulated by Total Phase

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	
Flowsheet:	Flowsheet1	

Mass Flow	1 lb/h	3 lb/h			
Ethane	4.4009	23.1768			
Propane	9.94378	23.91			
Isobutane	4.81608	7.71838			
n-Butane	13.7226	19.7623			
Isopentane	10.0814	11.9744			
n-Pentane	12.6126	14.4441			
Nitrogen	0.000336128	0.0167508			
Carbon Dioxide	0.263019	1.05436			
Benzene	1.10064	1.15008			
Toluene	6.75379	6.85345			
Ethylbenzene	0.976007	0.981373			
m-Xylene	8.39412	8.43377			
C6	90.7593	95.1365			
C7	135.593	137.978			
C8	84.1897	84.7192			
C9	86.5856	86.783			
C10	47.8801	47.9201			
C11	153.553	153.597			
C12	151.065	151.083			
C13	29.0427	29.0438			
Water	8602.98	8604.24			

Stream Properties

Property	Units	1	3		
Temperature	°F	110	85.0322		
Pressure	psia	44.6959	764.696		
Mole Fraction Vapor	%	0	0		
Mole Fraction Light Liquid	%	1.52666	1.95389		
Mole Fraction Heavy Liquid	%	98.4733	98.0461		
Molecular Weight	lb/lbmol	19.4976	19.5502		
Mass Density	lb/ft ³	59.4869	59.5219		
Molar Flow	lbmol/h	484.966	487.411		
Mass Flow	lb/h	9455.66	9528.99		
Vapor Volumetric Flow	ft ³ /h	158.954	160.092		
Liquid Volumetric Flow	gpm	19.8176	19.9595		
Std Vapor Volumetric Flow	MMSCFD	4.41689	4.43915		
Std Liquid Volumetric Flow	sgpm	19.6102	19.9612		
Compressibility		0.00239629	0.0429675		
Specific Gravity		0.95379	0.954351		
API Gravity		15.2159	15.9932		
Enthalpy	Btu/h	-5.91744E+07	-5.94902E+07		
Mass Enthalpy	Btu/lb	-6258.09	-6243.07		
Mass Cp	Btu/(lb*°F)	0.940445	0.936205		
Ideal Gas CpCv Ratio		1.29524	1.29635		
Dynamic Viscosity	cP	0.606105	0.77339		
Kinematic Viscosity	cSt	0.635768	0.800801		
Thermal Conductivity	Btu/(h*ft*°F)	0.327352	0.315063		
Surface Tension	lbf/ft	0.00431214	0.00438466	?	
Net Ideal Gas Heating Value	Btu/ft ³	89.0238	96.4099		
Net Liquid Heating Value	Btu/lb	754.279	899.49		
Gross Ideal Gas Heating Value	Btu/ft ³	145.461	153.303		
Gross Liquid Heating Value	Btu/lb	1852.73	2003.83		

Remarks

Energy Stream Report

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	
Flowsheet:	Flowsheet1	

Energy Streams

Energy Stream	Energy Rate	Power	From Block	To Block
Q-1	215463 Btu/h	84.6801 hp	--	Low Pressure Tower

Remarks

Blocks
Low Pressure Tower
Separator Report

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	Modified: 10:57 AM, 1/21/2016
Flowsheet:	Flowsheet1	Status: Solved 9:45 AM, 2/4/2016

Connections

Stream	Connection Type	Other Block	Stream	Connection Type	Other Block
3	Inlet	MIX-100	To Sales Pipeline	Vapor Outlet	
1	Light Liquid Outlet	VSSL-100	Q-1	Energy	

Block Parameters

Pressure Drop	720 psi	Main Liquid Phase	Light Liquid
Mole Fraction Vapor	0.50155 %	Heat Duty	215463 Btu/h
Mole Fraction Light Liquid	1.51901 %	Heat Release Curve Type	Plug Flow
Mole Fraction Heavy Liquid	97.9794 %	Heat Release Curve Increments	5

Remarks

	Blocks MIX-100 Mixer/Splitter Report	
--	----------------------------------------------------------	--

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	Modified: 2:14 PM, 7/24/2014
Flowsheet:	Flowsheet1	Status: Solved 9:45 AM, 2/4/2016

Connections					
-------------	--	--	--	--	--

Stream	Connection Type	Other Block	Stream	Connection Type	Other Block
Produced Water	Inlet		OXF 159 Pad Condensate	Inlet	
3	Outlet	Low Pressure Tower			

Block Parameters			
------------------	--	--	--

Pressure Drop	0 psi	Fraction to PStream 3	100 %
---------------	-------	-----------------------	-------

Remarks

Blocks
VSSL-100
Separator Report

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	Modified: 4:05 PM, 1/19/2016
Flowsheet:	Flowsheet1	Status: Solved 9:45 AM, 2/4/2016

Connections

Stream	Connection Type	Other Block	Stream	Connection Type	Other Block
1	Inlet	Low Pressure Tower	Flash Gas	Vapor Outlet	
Stable Liquid	Light Liquid Outlet				

Block Parameters

Pressure Drop	30	psi	Main Liquid Phase	Light Liquid
Mole Fraction Vapor	0.0884008	%	Heat Duty	0 Btu/h
Mole Fraction Light Liquid	1.45019	%	Heat Release Curve Type	Plug Flow
Mole Fraction Heavy Liquid	98.4614	%	Heat Release Curve Increments	5

Remarks

Flowsheet Environment Environment1					
Client Name:	EQT			Job: with Low Pressure Tower	
Location:	OXF 159 Adjusted Contingency				
Flowsheet:	Flowsheet1				
Environment Settings					
Number of Poynting Intervals	0		Freeze Out Temperature Threshold Difference	10 °F	
Gibbs Excess Model Evaluation Temperature	77 °F		Phase Tolerance	1 %	
Components					
Component Name	Henry's Law Component	Phase Initiator	Component Name	Henry's Law Component	Phase Initiator
Methane	False	False	Ethylbenzene	False	False
Ethane	False	False	m-Xylene	False	False
Propane	False	False	C6	False	False
Isobutane	False	False	C7	False	False
n-Butane	False	False	C8	False	False
Isopentane	False	False	C9	False	False
n-Pentane	False	False	C10	False	False
Nitrogen	False	False	C11	False	False
Carbon Dioxide	False	False	C12	False	False
Benzene	False	False	C13	False	False
Toluene	False	False	Water	False	True
Physical Property Method Sets					
Liquid Molar Volume	COSTALD		Overall Package	Peng-Robinson	
Stability Calculation	Peng-Robinson		Vapor Package	Peng-Robinson	
Light Liquid Package	Peng-Robinson		Heavy Liquid Package	Peng-Robinson	
Remarks					

Calculator Report

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	

Simple Solver 1

Source Code

Residual Error (for CV1) = TP / 244500 - 1

Calculated Variable [CV1]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!OXF 159 Pad Condensate!Phases!Total!Properties!Std Liquid Volumetric Flow		
Value	94.6514		
Unit	bbl/d		

Measured Variable [TP]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!Stable Liquid!Phases!Total!Properties!Std Liquid Volumetric Flow		
Value	244500		
Unit	bbl/yr		

Solver Properties Status: Solved

Error	-5.14125E-07	Iterations	6
Calculated Value	2.76067 sgpm	Max Iterations	20
Lower Bound	sgpm	Weighting	1
Upper Bound	sgpm	Priority	0
Step Size	sgpm	Solver Active	Active
Is Minimizer	False	Group	
Algorithm	Default	Skip Dependency Check	False

Remarks

Simple Solver 2

Source Code

Residual Error (for CV1) = LF / 88 - 1

Calculated Variable [CV1]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!Produced Water!Phases!Total!Properties!Std Liquid Volumetric Flow		
Value	589.732		
Unit	bbl/d		

Measured Variable [LF]

SourceMoniker	ProMax:ProMax!Project!Flowsheets!Flowsheet1!PStreams!Stable Liquid!Phases!Total!Composition!Std. Liquid Volumetric Fraction!Water		
Value	88.0179		
Unit	%		

Solver Properties Status: Solved

Error	0.000203786	Iterations	6
Calculated Value	17.2005 sgpm	Max Iterations	20
Lower Bound	sgpm	Weighting	1
Upper Bound	sgpm	Priority	0
Step Size	sgpm	Solver Active	Active
Is Minimizer	False	Group	
Algorithm	Default	Skip Dependency Check	False

Remarks

* User Specified Values
 ? Extrapolated or Approximate Values

User Value Sets Report

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	

Cn+ Flow/Frac.

User Value [CnPlusSum]

* Parameter	13.9285 lb/h	Upper Bound	
Lower Bound	lb/h	* Enforce Bounds	False

Remarks
 This User Value Set was programmatically generated. GUID={E867C485-3D3C-49CB-BC24-EA16096DB2B1}

Tank Losses

User Value [ShellLength]

* Parameter	20 ft	Upper Bound	
* Lower Bound	0 ft	* Enforce Bounds	False

User Value [ShellDiam]

* Parameter	12 ft	Upper Bound	
* Lower Bound	0 ft	* Enforce Bounds	False

User Value [BreatherVP]

* Parameter	0.03 psig	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [BreatherVacP]

* Parameter	-0.03 psig	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [DomeRadius]

Parameter	ft	Upper Bound	ft
Lower Bound	ft	* Enforce Bounds	False

User Value [OpPress]

* Parameter	0 psig	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [AvgPercentLiq]

* Parameter	50 %	Upper Bound	
Lower Bound	%	* Enforce Bounds	False

User Value [MaxPercentLiq]

* Parameter	90 %	Upper Bound	
Lower Bound	%	* Enforce Bounds	False

User Value [AnnNetTP]

* Parameter	669.032 bbl/day	Upper Bound	
* Lower Bound	0 bbl/day	* Enforce Bounds	False

User Value [OREff]

* Parameter	0 %	Upper Bound	
Lower Bound	%	* Enforce Bounds	False

User Value [AtmPressure]

* Parameter	14.1085 psia	Upper Bound	
Lower Bound		* Enforce Bounds	False

* User Specified Values
 ? Extrapolated or Approximate Values

User Value Sets Report

Client Name:	EQT	Job: with Low Pressure Tower
Location:	OXF 159 Adjusted Contingency	

User Value [TVP]

* Parameter	0.335982 psia	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [AvgLiqSurfaceT]

* Parameter	57.7675 °F	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [MaxLiqSurfaceT]

* Parameter	66.3119 °F	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [TotalLosses]

* Parameter	0.128007 lb/h	Upper Bound	
Lower Bound	lb/h	* Enforce Bounds	False

User Value [WorkingLosses]

* Parameter	0.0739061 ton/yr	Upper Bound	
Lower Bound	ton/yr	* Enforce Bounds	False

User Value [StandingLosses]

* Parameter	0.0195388 ton/yr	Upper Bound	
Lower Bound	ton/yr	* Enforce Bounds	False

User Value [RimSealLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [WithdrawalLoss]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [LoadingLosses]

* Parameter	0.14157 lb/h	Upper Bound	
Lower Bound	lb/h	* Enforce Bounds	False

User Value [DeckFittingLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [DeckSeamLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [FlashingLosses]

* Parameter	0 ton/yr	Upper Bound	
Lower Bound		* Enforce Bounds	False

User Value [GasMoleWeight]

* Parameter	0.0249091 kg/mol	Upper Bound	
Lower Bound		* Enforce Bounds	False

Remarks

This User Value Set was programmatically generated. GUID={B57AFC7E-AAE8-4873-921B-7B4031991004}

Attachment T

FACILITY-WIDE CONTROLLED EMISSIONS SUMMARY SHEET

ATTACHMENT T – FACILITY-WIDE CONTROLLED EMISSIONS SUMMARY SHEET

List all sources of emissions in this table. Use extra pages if necessary.

Emission Point ID#	NO _x		CO		VOC		SO ₂		PM ₁₀		PM _{2.5}		GHG (CO ₂ e)	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
Line Heater (S001)	0.12	0.53	0.10	0.45	<0.01	0.03	<0.01	<0.01	<0.01	0.01	<0.01	0.01	180.33	789.85
Line Heater (S002)	0.12	0.53	0.10	0.45	<0.01	0.03	<0.01	<0.01	<0.01	0.01	<0.01	0.01	180.33	789.85
Line Heater (S003)	0.12	0.53	0.10	0.45	<0.01	0.03	<0.01	<0.01	<0.01	0.01	<0.01	0.01	180.33	789.85
Line Heater (S004)	0.12	0.53	0.10	0.45	<0.01	0.03	<0.01	<0.01	<0.01	0.01	<0.01	0.01	180.33	789.85
Line Heater (S005)	0.12	0.53	0.10	0.45	<0.01	0.03	<0.01	<0.01	<0.01	0.01	<0.01	0.01	180.33	789.85
Line Heater (S006)	0.12	0.53	0.10	0.45	<0.01	0.03	<0.01	<0.01	<0.01	0.01	<0.01	0.01	180.33	789.85
Line Heater (S007)	0.12	0.53	0.10	0.45	<0.01	0.03	<0.01	<0.01	<0.01	0.01	<0.01	0.01	180.33	789.85
Tank Truck Loading Activities (S017)	--	--	--	--	0.01	0.06	--	--	--	--	--	--	0.18	0.78
Enclosed Combustion Unit (C018)	1.07	4.71	0.90	3.95	0.16	0.62	<0.01	0.03	0.02	0.09	0.02	0.09	1,637.57	7,171.95
Enclosed Combustion Unit (C019)	1.07	4.71	0.90	3.95	0.16	0.62	<0.01	0.03	0.02	0.09	0.02	0.09	1,637.57	7,171.95
TEG (S020)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	1.52	6.67
TEG (S021)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	1.52	6.67
Compressor Engine (S022)	0.42	1.85	0.88	3.85	0.29	1.29	<0.01	<0.01	<0.01	0.03	<0.01	0.03	82.58	361.69
Line Heater (S023)	0.09	0.40	0.08	0.34	<0.01	0.02	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	134.66	589.82
TOTAL	3.52	15.41	3.48	15.24	0.62	2.81	0.02	0.08	0.04	0.28	0.04	0.28	4,757.91	20,838.48

Annual emissions shall be based on 8,760 hours per year of operation for all emission units except emergency generators.

According to 45CSR14 Section 2.43.e, fugitive emissions are not included in the major source determination because it is not listed as one of the source categories in Table 1. Therefore, fugitive emissions shall not be included in the PTE above.

ATTACHMENT T – FACILITY-WIDE HAP CONTROLLED EMISSIONS SUMMARY SHEET

List all sources of emissions in this table. Use extra pages if necessary.

Emission Point ID#	Formaldehyde		Benzene		Toluene		Ethylbenzene		Xylenes		Hexane		Total HAPs	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
Line Heater (S001)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01
Line Heater (S002)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01
Line Heater (S003)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01
Line Heater (S004)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01
Line Heater (S005)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01
Line Heater (S006)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01
Line Heater (S007)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.01
Tank Truck Loading Activities (S017)	--	--	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Enclosed Combustion Unit (C018)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.03	0.10	0.10
Enclosed Combustion Unit (C019)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.03	0.10	0.10
TEG (S020)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
TEG (S021)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Compressor Engine (S022)	0.01	0.06	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.07
Line Heater (S023)	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
TOTAL	0.04	0.17	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	0.06	0.20	0.44

Annual emissions shall be based on 8,760 hours per year of operation for all emission units except emergency generators.

According to 45CSR14 Section 2.43.e, fugitive emissions are not included in the major source determination because it is not listed as one of the source categories in Table 1. Therefore, fugitive emissions shall not be included in the PTE above

Attachment U

CLASS I LEGAL ADVERTISEMENT

AIR QUALITY PERMIT NOTICE

Notice of Application

Notice is given that EQT Production Company has applied to the West Virginia Department of Environmental Protection, Division of Air Quality, for a G70-B General Permit for the OXF-159 natural gas production facility located in West Union, Doddridge County, West Virginia. The latitude and longitude coordinates are: 39.20784 and -80.76235.

The applicant estimates the potential to discharge the following regulated air pollutants on a facility-wide basis will be:

Carbon Monoxide (CO) = 15.24 tpy
Nitrogen Oxides (NO_x) = 15.41 tpy
Particulate Matter (Total) = 8.08 tpy
Sulfur Dioxide (SO₂) = 0.08 tpy
Volatile Organic Compounds (VOC) = 3.30 tpy
Formaldehyde = 0.07 tpy
Hexane = 0.28 tpy
Hazardous Air Pollutants (HAPs) = 0.43 tpy
Carbon Dioxide Equivalents (CO₂e) = 20,886.03 tpy

Written comments will be received by the West Virginia Department of Environmental Protection, Division of Air Quality, 601 57th Street, SE, Charleston, WV 25304, for at least 30 calendar days from the date of publication of this notice.

Any questions regarding this permit application should be directed to the DAQ at (304) 926-0499, extension 1250, during normal business hours.

Dated this the XXth day of March, 2016.

By: EQT Production Company
Kenneth Kirk
Executive Vice President
625 Liberty Avenue, Suite 1700
Pittsburgh, PA 15222