MODIFICATION APPLICATION TO GENERAL PERMIT REGISTRATION G40-C003E MILLVILLE QUARRY

Prepared for:

Bardon, Inc.

6401 Golden Triangle Drive, Suite 400 Greenbelt, Maryland 20770

Prepared by:

Potesta & Associates, Inc.

7012 MacCorkle Avenue, S.E. Charleston, West Virginia 25304

Phone: (304) 342-1400 Fax: (304) 343-9031

Email: potesta@potesta.com

Project No. 0101-16-0231

June 2016



TABLE OF CONTENTS

Application for General Permit Registration
Business Certificate
Process Description
Description of Fugitive Emissions
Process Flow Diagram
Plot Plan
Area MapATTACHMENT F
Then map
Equipment Data Sheets and Registration Section Applicability Form
Equipment Data Sheets and Registration Section Applicability Form
Equipment Data Sheets and Registration Section Applicability Form

Attachments not required for this application: H, M, N, and Other.

SECTION I APPLICATION FOR GENERAL PERMIT REGISTRATION



WEST VIRGINIA DEPARTMENT OF ENVIRONMENTAL PROTECTION DIVISION OF AIR QUALITY

601 57th Street, SE Charleston, WV 25304

Phone: (304) 926-0475 • www.den.wv.gov/dag

APPLICATION FOR GENERAL PERMIT REGISTRATION

CONSTRUCT, MODIFY, RELOCATE OR ADMINISTRATIVELY UPDATE A STATIONARY SOURCE OF AIR POLLUTANTS

	Phone:	(304) 926-0475 * WWW.	.aep.wv.gov/aaq	$\perp \perp^A$	SIAII	ONARYS	SOURCE OF A	IR POLLUTANTS
□ CONSTRU	ICTION	■ MODIFICATION	□ RELC	CATION		□ CLASS	I ADMINISTRAT	IVE UPDATE
					_	□ CLASS	II ADMINISTRAT	TIVE UPDATE
	CHECK	WHICH TYPE OF GEN	ERAL PERMIT	REGIST	RATIO	N YOU AR	E APPLYING FO	DR:
☐ G10-D – Coal I	Preparation a	and Handling			■ G40	-C – Nonme	etallic Minerals Pro	cessing
☐ G20-B – Hot M	lix Asphalt				□ G50	-B - Concre	ete Batch	
☐ G30-D Natur	al Gas Comp	pressor Stations			□ G60	-C - Class I	II Emergency Gene	erator
☐ G33-A - Spark	Ignition Inte	rnal Combustion Engines			□ G65	-C - Class I	Emergency Gener	ator
☐ G35-A – Natur	al Gas Comp	pressor Stations (Flare/Gly	col Dehydration L	Jnit)	☐ G70	I-A - Class I	II Oil and Natural G	as Production Facility
		SEC	ΓΙΟΝ Ι. GENER	RAL INFO	RMATI	ON		
1. Name of applica Bardon, Inc.	ınt (as regist	ered with the WV Secretar	y of State's Office	:):		2. Federal 54-15445	l Employer ID No. (348	FEIN):
3. Applicant's maili Bardon, Inc. 6401 Golden Tria Greenbelt, MD 2		4. Applicant's physical address: 57 Blair Road Harpers Ferry, WV 25425						
5. If applicant is a s	subsidiary co	rporation, please provide t	he name of parer	nt corporat	ion: NA			
6. WV BUSINESS	IF YES, pro change ar IF NO, prov	FION. Is the applicant a resolution of the Certification of the Certification of the Busine ide a copy of the Certification of the or other Business Certifications or other Business Certifications.	ate of Incorporation (te of Authority /	on/ Orgar Certificate Authority	nization / as Attac	Limited Pa		
		SECI	ION II. FACIL	TY INFO	RMATIC			
7. Type of plant or modified, relocated preparation plant, p Crusher Replacer	ucted, 8a. Clas	8a. Standard Industrial AND 8b. North American Industry Classification Classification (SIC) code: 1422 System (NAICS) code: 212312				,		
9. DAQ Plant ID No	10. with	List all current 45CSR13 and other General Permit numbers associated with this process (for existing facilities only):				it numbers associated		
037-00015			G40)-C003E				

A: PRIMARY OPERATING SITE INFORMATION

	A. TRIMART OF ERATING SITE IN ORMA	TION							
11A. Facility name of primary operating site:	12A. Address of primary operating site:								
Millville Quarry	Mailing: See Box 3 Physical See Box	4							
13A. Does the applicant own, lease, have an option of the second of the		pposed site? ■ YES □ NO							
☐ IF NO , YOU ARE NOT ELIGIBLE FOR A P	ERMIT FOR THIS SOURCE.								
14A. □ For Modifications or Administrative Unearest state road;	pdates at an existing facility, please provide	directions to the present location of the facility from the							
For Construction or Relocation permits, MAP as Attachment F.	For Construction or Relocation permits, please provide directions to the proposed new site location from the nearest state road. Include a								
From Charles town take US 340 heading tow road, if you get to the railroad tracks you have	vards Harpers Ferry and make a right on we gone too far. Turn right into Millville	nto Blair Road. Go about 2 miles on winding e Quarry just before the railroad tracks.							
15A. Nearest city or town:	16A. County:	17A. UTM Coordinates:							
Millville	Jefferson	Northing (KM): 4,352.354							
		Easting (KM): 259.027							
		Zone: 18							
18A. Briefly describe the proposed new operation		19A. Latitude & Longitude Coordinates (NAD83, Decimal Degrees to 5 digits):							
Replacement of an existing Hazemag Crushe	r.	Latitude: 39.287							
		Longitude: -77.794							
B. 4 ST ALTERNATE OPERATING SITE INC.	ODMATION (anis available for COO CAO R	OSA CANADA MANAGA PRINCIPA DI CANADA							
11B. Name of 1 st alternate operating site:	12B. Address of 1 st alternate operating site:	G50 General Permits) NOT APPLICABLE							
	-								
	Mailing:	Physical:							
)——————————————————————————————————————								
13B. Does the applicant own, lease, have an option IF YES, please explain:	n to buy, or otherwise have control of the pro	posed site?							
□ IF NO, YOU ARE NOT ELIGIBLE FOR A PE	ERMIT FOR THIS SOURCE.								
14B. ♥ For Modifications or Administrative Up nearest state road;	odates at an existing facility, please provide of	directions to the present location of the facility from the							
For Construction or Relocation permits, p MAP as Attachment F.	please provide directions to the proposed new	v site location from the nearest state road. Include a							
	· · · · · · · · · · · · · · · · · · ·								

15B. Nearest city or town:			
	16B. County:		17B. UTM Coordinates:
		Northi	ing (VM):
			ing (KM):
		Eastin	ng (KM):
		Zone:	
19B Briefly describe the prepared new appeal		19B.	Latitude & Longitude Coordinates
18B. Briefly describe the proposed new operation	or change (s) to the fa		83, Decimal Degrees to 5 digits):
		·	
		Latitud	
		Longit	ude:
•			
C: 2 ND ALTERNATE OPERATING SITE INF	ORMATION (only avai	lable for G20, G40, & G50 Genera	al Permits): NOT APPLICABLE
11C. Name of 2 nd alternate operating site:	12C. Address of 2 ¹¹⁰ a	Iternate operating site:	
	1		
	Mailing:	Physica	al:
13C. Does the applicant own, lease, have an option	on to buy, or otherwise	have control of the proposed site?	☐ YES ☐ NO
□ IF YES, please explain: □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □			
☐ IF NO , YOU ARE NOT ELIGIBLE FOR A P	ERMIT FOR THIS SOL	RCE.	
14C C For Modifications or Administrative U	ndatas at an aviatina f	cility places provide directions to	the managed leading of the field for the
14C. ➡ For Modifications or Administrative U nearest state road;	poates at an existing n	icility, please provide directions to t	the present location of the facility from the
,			
For Construction or Relocation permits,	please provide directio	is to the proposed new site location	n from the nearest state road. Include a
MAP as Attachment F.			
		-	
15C. Nearest city or town:	16C. County:		470 LITM 0
Too. Hoursel only of tomit.	100. County.		
	ļ	Northin	17C. UTM Coordinates:
		11010111	
			ng (KM):
		Easting	
		Easting Zone:	ng (KM): g (KM):
18C. Briefly describe the proposed new operation	or change (s) to the fac	Easting Zone:	g (KM):
18C. Briefly describe the proposed new operation	or change (s) to the fac	Easting Zone:	ng (KM): g (KM):
18C. Briefly describe the proposed new operation	or change (s) to the fac	Zone: 19C. L (NAD8	ag (KM):
18C. Briefly describe the proposed new operation	or change (s) to the fac	Zone: ### 19C. L (NAD8 Latitud	ang (KM): g (KM): Latitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le:
18C. Briefly describe the proposed new operation		Easting Zone: illity: 19C. L (NAD8 Latitud Longitu	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
		Easting Zone: illity: 19C. L (NAD8 Latitud Longitu	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
18C. Briefly describe the proposed new operation 20. Provide the date of anticipated installation or ch		Zone: ### 19C. L (NAD8 Latitud	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
		Easting Zone: illity: 19C. L (NAD8 Latitud Longitu	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
20. Provide the date of anticipated installation or ch	nange:	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
	nange:	Easting Zone: illity: 19C. L (NAD8 Latitud Longitu	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
20. Provide the date of anticipated installation or ch	nange:	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
20. Provide the date of anticipated installation or characteristic of this is an After-The-Fact permit application, provided in the control of the control o	nange:	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
20. Provide the date of anticipated installation or ch	nange:	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
20. Provide the date of anticipated installation or characteristic of this is an After-The-Fact permit application, provided in the control of the control o	nange:	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
20. Provide the date of anticipated installation or characteristic of this is an After-The-Fact permit application, provided in the control of the control o	nange:	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions	atitude & Longitude Coordinates 3, Decimal Degrees to 5 digits): le: ude:
20. Provide the date of anticipated installation or characteristic of this is an After-The-Fact permit application, providing the proposed change did happen:	nange: 21	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions 08 / 01 / 2016	atitude & Longitude Coordinates (3, Decimal Degrees to 5 digits): le: ude: istration is granted:
20. Provide the date of anticipated installation or characteristic of this is an After-The-Fact permit application, provided the proposed change did happen: 22. Provide maximum projected Operating Scheduler	nange: ide the date upon	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions 08 / 01 / 2016	atitude & Longitude Coordinates (3, Decimal Degrees to 5 digits): le: ude: istration is granted:
20. Provide the date of anticipated installation or characteristic of this is an After-The-Fact permit application, providing the proposed change did happen:	nange: ide the date upon	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions 08 / 01 / 2016	atitude & Longitude Coordinates (3, Decimal Degrees to 5 digits): le: ude: istration is granted:
20. Provide the date of anticipated installation or change of this is an After-The-Fact permit application, provided the proposed change did happen: 22. Provide maximum projected Operating Schedother than 24/7/52 may result in a restriction to the	nange: ide the date upon lule of activity/activities facility's operation).	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions 08 / 01 / 2016 outlined in this application if other to	ang (KM): g (KM): Latitude & Longitude Coordinates 13, Decimal Degrees to 5 digits): le: ude: istration is granted: than 8760 hours/year. (Note: anything
20. Provide the date of anticipated installation or change of this is an After-The-Fact permit application, provided the proposed change did happen: 22. Provide maximum projected Operating Schedother than 24/7/52 may result in a restriction to the	nange: ide the date upon lule of activity/activities facility's operation).	Easting Zone: 19C. L (NAD8 Latitud Longitu Date of anticipated Start-up if regions 08 / 01 / 2016	ang (KM): g (KM): Latitude & Longitude Coordinates 13, Decimal Degrees to 5 digits): le: ude: istration is granted: than 8760 hours/year. (Note: anything

SECTION III. ATTACHMENTS AND SUPPORTING DOCUMENTS

- 23. Include a check payable to WVDEP Division of Air Quality with the appropriate application fee (per 45CSR22 and 45CSR13).
- 24. Include a Table of Contents as the first page of your application package.

All of the required forms and additional information can be found under the Permitting Section (General Permits) of DAQ's website, or requested by phone.

- 25. Please check all attachments included with this permit application. Please refer to the appropriate reference document for an explanation of the attachments listed below.
 - ATTACHMENT A: CURRENT BUSINESS CERTIFICATE
 - ATTACHMENT B: PROCESS DESCRIPTION
 - ATTACHMENT C: DESCRIPTION OF FUGITIVE EMISSIONS
 - ATTACHMENT D: PROCESS FLOW DIAGRAM
 - ATTACHMENT E: PLOT PLAN
 - ATTACHMENT F: AREA MAP
 - ATTACHMENT G: EQUIPMENT DATA SHEETS AND REGISTRATION SECTION APPLICABILITY FORM
 - ☐ ATTACHMENT H: AIR POLLUTION CONTROL DEVICE SHEETS
 - ATTACHMENT I: EMISSIONS CALCULATIONS
 - ATTACHMENT J: CLASS I LEGAL ADVERTISEMENT
 - ATTACHMENT K: ELECTRONIC SUBMITTAL
 - ATTACHMENT L: GENERAL PERMIT REGISTRATION APPLICATION FEE
 - ☐ ATTACHMENT M: SITING CRITERIA WAIVER
 - ☐ ATTACHMENT N: MATERIAL SAFETY DATA SHEETS (MSDS)
 - ATTACHMENT O: EMISSIONS SUMMARY SHEETS
 - □ OTHER SUPPORTING DOCUMENTATION NOT DESCRIBED ABOVE (Equipment Drawings, Aggregation Discussion, etc.)

Please mail an original and two copies of the complete General Permit Registration Application with the signature(s) to the DAQ Permitting Section, at the address shown on the front page of this application. Please DO NOT fax permit applications. For questions regarding applications or West Virginia Air Pollution Rules and Regulations, please refer to the website shown on the front page of the application or call the phone number also provided on the front page of the application.

SECTION IV. CERTIFICATION OF INFORMATION

This General Permit Registration Application shall be signed below by a Responsible Official. A Responsible Official is a President, Vice President, Secretary, Treasurer, General Partner, General Manager, a member of a Board of Directors, or Owner, depending on business structure. A business may certify an Authorized Representative who shall have authority to bind the Corporation, Partnership, Limited Liability Company, Association, Joint Venture or Sole Proprietorship. Required records of daily throughput, hours of operation and maintenance, general correspondence, Emission Inventory, Certified Emission Statement, compliance certifications and all required notifications must be signed by a Responsible Official or an Authorized Representative. If a business wishes to certify an Authorized Representative, the official agreement below shall be checked off and the appropriate names and signatures entered. Any administratively incomplete or improperly signed or unsigned Registration Application will be returned to the applicant.

FOF	R A CORPORATION (domestic or foreign)		
•	I certify that I am a President, Vice Presi corporation	dent, Secretary, Treasurer or in charge of a prin	cipal business function of the
FOF	A PARTNERSHIP		
	I certify that I am a General Partner		
FOF	A LIMITED LIABILITY COMPANY		
	I certify that I am a General Partner or G	eneral Manager	
FOF	AN ASSOCIATION		
	I certify that I am the President or a mem	ber of the Board of Directors	
<u> FOF</u>	<u>A JOINT VENTURE</u>		
	I certify that I am the President, General	Partner or General Manager	
FOR	A SOLE PROPRIETORSHIP		
	I certify that I am the Owner and Propriet	or	
□ Thereby ce	rtify that (please print or type)		
is an Authori. Liability Com	red Representative and in that capacity shall repairly. Association Joint Venture or Sole Proprie	epresent the interest of the business (e.g., Corpo etorship) and may obligate and legally bind the t ial shall notify the Director of the Office of Air Qu	ousiness. If the business
hereto is, to t	fy that all information contained in this General he best of my knowledge, true, accurate and c ve information possible	Permit Registration Application and any suppor omplete, and that all reasonable efforts have be	ting documents appended en made to provide the most
Signature	ho M		0/15/2016
(please use blue ink)	Responsible Official		Date
Name & Title Josep M	Maset. Vice President		
a:			
Signature NOT APP (please use blue ink)	Authorized Representative (if applicable)		Date
Applicant's Name Ba	ordon Inc		
_			
Phone & Fax	301-982-1400 X60520 Phone	855-293-6428 Fax	
	Thone	rax	

Email Lisa Hunt, Area Environmental Manager at lisa.hunt@aggregate-us.com

ATTACHMENT A BUSINESS CERTIFICATE



I, Natalie E. Tennant, Secretary of State of the State of West Virginia, hereby certify that

BARDON, INC.

Control Number: 99R50

a corporation formed under the laws of Maryland has filed its "Application for Certificate of Authority" to transact business in West Virginia as required by the provisions of the West Virginia Code. I hereby declare the organization to be registered as a foreign corporation from its effective date of September 23, 2011.

Therefore, I issue this

CERTIFICATE OF AUTHORITY

to the corporation authorizing it to transact business in West Virginia



Given under my hand and the Great Seal of the State of West Virginia on this day of September 23, 2011

Natelil Egenment

ATTACHMENT B PROCESS DESCRIPTION

ATTACHMENT B

PROCESS DESCRIPTION

Introduction to Project

Bardon, Inc. is applying for a revised registration under General Permit G40-C to include replacement of the existing Hazemag 1322K tertiary crusher with a new Metso Model HP6 crusher which is identified as 331-CZ03. The hourly rate and the yearly rate of the new crusher will be the same as the existing crusher. Total facility production remains the same with a feed rate of 1,200 tons per hour and 6.0 million tons per year. In Attachment G, the proposed crusher is shown in red text.

Permitting History Since Entering the General Permit Program

Bardon, Inc. was initially registered under the General Permit G40 by G40-003 in December 2000; an amendment to the registration was approved in September 2001 under G40-003A, then an initial flooding registration G40-003B was approved on July 26, 2002. Afterwards, the registration was modified to allow the installation of log washers on February 29, 2003 (G40-003C). G40-003D for facility streamlining was issued on February 22, 2005. The current existing registration was issued as G40-C003E on November 24, 2015.

Facility and Process Description

The stone production facilities involve the operations of trucking from the quarry pits, stone sizing and crushing, and final product loadout. The facility is comprised of primary crushing and screening, main plant operations for sized aggregate production, and Wash 1 and Wash 2 operations. Final sized products are loaded to truck and rail via endloaders. For the potential to emit, the hourly emissions estimate is based on the entire facility concurrently operating except for the duplicate screens - full hourly rates are only shown through one screen in the screen pair. The yearly emissions are based on the total yearly throughput and worst-case transfers to avoid double counting of throughput. Operating rates are listed in the affected source sheets for the processing and conveying equipment.

Primary Crushing Operation

Quarried rock is loaded in the pits and trucked and dumped into the Dump Box (3600.311-HP01) at a maximum rate of 1,200tph/6,000,000tpy. The Dump Box is followed with a grizzly screen (3600.311-RZ01) which scalps off the large rock and sends it directly to the Jaw Crusher (3600.311-JC01). The crushed rock and the pass-through rock from the grizzly transfer to conveyor P1 (3600.311-BC01) then to P2 (3600.311-BC02) then to screen PS1 (3600.311-VS01). Screen pass through goes to reversing conveyor P3 (3600.311-BC03) then to either P4 (3600.311-BC04) or to P6 (3600.321-BC01). Material from P3 transfers to P4

(3600.311-BC04) to stacker P5 (3600.311-ST01) to stockpile SP1. Oversize from PS1 is diverted to the gabion stockpile SP2 or to the 7 Crusher (3600.321-CZ01. Material from 7 Crusher transfers to P6. From P6, the material can drop to the surge pile SP3 or transfer to P7 (3600.321-BC02) then to SP3 or P8 (3600.321-BC03) then to SP3 or P9 (3600.321-BC04) then to SP3.

Main Plant

Material from SP3 is reclaimed by conveyor M1 (3600.331-BC01), transferred to stacker M2 (3600.331-ST01) and then to the Main Surge Pile SP4. SP4 is reclaimed by M3 (3600.331-BC02) transferred to M4 (3600.331-BC03) and goes to screens MS1 (3600.331-VS01) and MS2 (3600.331-VS02). Oversize from MS1 and MS2 scalps off to M5 (3600.331-BC04) to M6 (3600.331-BC05) to Hopper Feed Bin 5 (3600.331-HP05). Pass through material from MS1 and MS2 transfer to M14 (3600.331-BC09), M7 (3600.331-BC10), and S1 (3600.352-BC03). M14 transfers to screens MS3 (3600.331-VS03) and MS4 (3600.33-VS04). M7 transfers to M8 (3600.331-BC11) to stacker M9 (3600.331-ST02) to stockpile SP7. S1 transfers to S2 (3600.352-BC04) to the Sand Screen (3600.352-VS01). The Sand Screen is proposed to be replaced with like equipment in 2015. Material from Hopper Feed Bin 5 transfers to the Hazemag Crusher (3600.331-HI1) to conveyor M10 (3600.331-BC06) to screens MS5 (3600.331-VS05) and MS6 (3600.331-VS06). A Metso Crusher (331-CZ03) will replace the Hazemag Crusher.

MS3 and MS4 send oversize to conveyor M11 (3600.331-BC07) to M13 (3600.331-BC08) to Hopper Feed Bin 9 (3600.331-HP09). Pass-through materials transfer to M22 (3600.331-BC13), M15 (3600.351-BC01), and M19 (3600.351-BC04). M22 sends material to M24 (3600.331-BC15) to stacker M25 (3600.331-ST03) to stockpile SP14. M15 transfers to M16 (3600.351-BC02) to wash screen MS7 (3600.351-VS01). M19 transfers to M20 (3600.351-BC05) to wash screen MS8 (3600.351-VS02). Hopper Feed Bin 9 transfers to crushers HP500 (3600.331-CZ01) and HP300 (3600.331-CZ02). Material from HP500 and HP300 transfers to M14 and back to screens MS3 and MS4.

MS5 and MS6 send oversize to conveyor M12 (3600.331-BC12) to M13 to Hopper Feed Bin 9 to HP500 and HP300 to M14. Pass-through materials go to reversing conveyor M23 (3600.331-BC14), M15 (see above), and M19 (see above). M23 can send material to either M24 (see above) or to M27 (3600.352-BC01) to M28 (3600.352-BC02) to S2 (see above).

Wash 1

Wash screen MS7 sends material to M17 (3600.351-BC03) and the 67s Screw (3600.351-SY01). M17 transfers to stacker M18 (3600.351-ST01) to stockpile SP13. The 67s Screw transfers to M26 (3600.351-BC07) to M24 (see above). Wash screen MS8 transfers to stacker M21 (3600.351-ST02) to stockpile SP9.

Wash 2

The Sand Screen (a wash screen) transfers oversize to S3 (3600.341-BC01) to the Barmac Crusher (3600.341-VI01) to S4 (3600.341-BC02) to S2 and back to the Sand Screen. Screen pass through transfers to S5 (3600.352-BC05), S6 (3600.352-BC06), or the Sand Screw (3600.352-SY01). S5 transfers to stockpile SP5A, S6 to stockpile SP5B, and the Sand Screw to S7 (3600.352-BC07) to SP5.

Product stockpiles are reclaimed by endloader to truck for transport to remote stockpiling (SP6, 8, 10, 11, 12, 15, 16, 17, and 18) or off site, or reclaimed by endloader to railcar.


ATTACHMENT C DESCRIPTION OF FUGITIVE EMISSIONS

ATTACHMENT C

DESCRIPTION OF FUGITIVE EMISSIONS

Fugitive emissions from the facility include particulate emissions from haulroads, stockpiles, and work areas. Water is applied to the haulroads as needed via a water truck. Water is also applied to the work areas around the stockpiles and plant by the water truck to control particulate emissions.

ATTACHMENT D PROCESS FLOW DIAGRAM




AGGREGATE INDUSTRIES, INC. Millville Quarry SAP Chad Abramson customers or equipment manufacturers. Use this information for estimating purposes only. Date: June/19/2015

All calculations performed by AggFlow. http://www.AggFlow.com

implied warranty, but shows results of calculations based on information provided by

ATTACHMENT E PLOT PLAN






7012 MacCorkle Avenue, S.E Charleston, West Virginia 25304 Phone: (304) 342-1400 Fax: (304) 343-9031

Fax:

Millville Quarry Bardon, Inc. Jefferson County, West Virginia

ATTACHMENT F AREA MAP



ATTACHMENT G

EQUIPMENT DATA SHEETS AND REGISTRATION SECTION APPLICABILITY FORM

General Permit G40-C Registration Section Applicability Form

General Permit G40-C allows qualified registrants to seek registration for a variety of sources. These sources include nonmetallic mineral processing plants which include crushers, screens, transfer points (loading, unloading, etc.), open stockpiles, bins, haulroads, reciprocating internal combustion engine driven compressors, emergency standby generators, and tanks. All registered facilities will be subject to Sections 1.0, 1.1, 2.0, 3.0 and 4.0.

General Permit G40-C allows the registrant to choose which sections of the permit that they wish to seek registration under. Therefore, please mark which sections that you are applying for registration under. Please keep in mind, that if this registration is approved, the issued registration will state which sections will apply to your affected facility.

Section 5 ¹	Nonmetallic Mineral Processing Operations	\boxtimes
Section 6	Standards of Performance for Nonmetallic Mineral Processing Plants	$\overline{\boxtimes}$
	that Commenced Construction, Reconstruction or Modification after	
	August 31, 1983 but before April 22, 2008 (40CFR60 Subpart OOO)	
Section 7	Standards of Performance for Nonmetallic Mineral Processing Plants	\boxtimes
	that Commenced Construction, Reconstruction or Modification on	
	or after April 22, 2008. (40CFR60 Subpart OOO)	
Section 8 ²	Reciprocating Internal Combustion Engines (R.I.C.E.)	
Section 9	Tanks	
Section 10	Standards of Performance for Stationary Compression Ignition Internal	
	Combustion Engines (40CFR60 Subpart IIII)	_
Section 11	Standards of Performance for Stationary Spark Ignition Internal	
	Combustion Engines (40CFR60 Subpart JJJJ)	_

Affected facilities that are subject to Section 5 may also be subject to Sections 6 and 7. Therefore, if the applicant is seeking registration under multiple sections, they will need to select all applicable sections.

Affected facilities that are subject to Section 8 may also be subject to Sections 10 or 11. Therefore, if the applicant is seeking registration under multiple sections, they will need to select all applicable sections.

CRUSHING AND SCREENING AFFECTED SOURCE SHEET

Source Identification N	umber ¹	3600.311- JC01 (Jaw Crusher)	3600.321- CZ01 (7 Crusher)	3600.331- HI01 (Hazemag Crusher)	331-CZ03 Metso Crusher	3600.331- CZ01 (HP 500)	3600.331- CZ02 (HP 300)	3600.341- VI01 (Barmac Crusher)
Type of Crusher or So	creen ²	JC	CC	IMP	CC	CC	CC	IMP
Make, Model No., Seri	al No. ³	NA	NA	NA	HP6	NA	NA	NA
Date of Construction, Reco		2001	2001	To Be Removed	2016	2006	1999	2007
Maximum Throughput ⁵	tons/hour	600	700	800	800	1,000	1,000	400
Waximum Tinougnput	tons/year	3,000,000	4,000,000	2,500,000	2,500,000	2,000	0,000	750,000
Material sized from	/to: ⁶	0"-6"	4"-8"	0.5"-4"	0.5"-4"	0.5"-2.5"	0.5"-2.5"	0.5"-2.5"
Average Moisture Conte	ent (%) ⁷	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Control Device ID Nu	mber ⁸	FE	FE	FE	FE	FE	FE	FE
	height (ft)							
	diameter (ft)							
Baghouse Stack Parameters ⁹	volume (ACFM							
	exit temp (F)							
	UTM Coordin ates							
	hours/da y	24	24	24	24	24	24	24
Maximum Operating Schedule ¹⁰	days/yea r	365	365	365	365	365	365	365
	hours/ye ar	8,760	8,760	8,760	8,760	8,760	8,760	8,760

Enter the appropriate Source Identification Number for each crusher and screen. For example, in the case of an operation which incorporates multiple crushers, the crushers should be designated CR-1, CR-2, CR-3 etc. beginning with the breaker or primary crusher. Multiple screens should be designated S-1, S-2, S-3 etc.

2. Describe types of crushers and screens using the following codes:

HM	Hammermill	SS	Stationary	Screen	DR	Dou	ole Roll Crusher
SD	Single Deck Screen		BM	Ball Mill		DD	Double-Deck Screen
RB	Rotary Breaker		TD	Triple Deck Screen		JC	Jaw Crusher
GC	Gyratory Crusher		OT	Other	CC (Cone Crushe	r IMP Impact Crusher

3. Enter the make, model number, and serial number of the crusher/screen.

- Enter the date that each crusher and screen was constructed, reconstructed, or modified.
- Enter the maximum throughput for each crusher and screen in tons per hour and tons per year.

Describe the nominal material size reduction (e.g. +2"/-3%").

- 7. Enter the average percent moisture content of the material processed.
- 8. Enter the appropriate Control Device Identification Number for each crusher and screen. Refer to Table A Control Device Listing and Control Device Identification Number Instructions in the Reference Document for Control Device ID prefixes and numbering.

Enter the appropriate stack parameters if a baghouse control device is used.

10. Enter the maximum operating schedule for each crusher and screen in hours per day, days per year and hours per year.

CRUSHING AND SCREENING AFFECTED SOURCE SHEET CON'T

Source Ider	Source Identification Number ¹		3600.311- VS01 (PS1)	3600.331- VS01 (MS1)	3600.331- VS02 (MS2)	3600.331- VS03 (MS3)	3600.331- VS04 (MS4)
Type of C	rusher or Screen ²	Grizzly	DD	TD	TD	TD	TD
Make, Mod	lel No., Serial No. ³	NA	NA	NA	NA	NA	NA
	Date of Construction, Reconstruction, or Modification (Month/Year) ⁴		2009	2004	2004	2004	2011
Maximum	tons/hour	1,200	1,200	1,000	1,000	1,000	1,000
Throughput⁵	tons/year	6,000,000	6,000,000	6,000	0,000	4,500,000	
Material	Material sized from/to: ⁶		0"-8"	0"-4"	0"-4"	0"-2"	0"-2"
Average Mo	Average Moisture Content (%) ⁷		1.5	1.5	1.5	1.5	1.5
Control De	Control Device ID Number ⁸		PE-MC	PE-MC	PE-MC	PE-MC	PE-MC
	height (ft)						
Baghouse	diameter (ft)						
Stack	volume (ACFM)						
Parameters ⁹	exit temp (F)						
	UTM Coordinates						
Maximum	hours/day	25	24	24	24	24	24
Operating	days/year	365	365	365	365	365	365
Schedule 10	hours/year	8,760	8,760	8,760	8,760	8,760	8,760

1. Enter the appropriate Source Identification Number for each crusher and screen. For example, in the case of an operation which incorporates multiple crushers, the crushers should be designated CR-1, CR-2, CR-3 etc. beginning with the breaker or primary crusher. Multiple screens should be designated S-1, S-2, S-3 etc.

2. Describe types of crushers and screens using the following codes:

HM	Hammermill	SS	Stationary Screen	DR	Double Roll Crusher
SD	Single Deck Screen	BM	Ball Mill	DD	Double-Deck Screen
RB	Rotary Breaker	TD	Triple Deck Screen	JC	Jaw Crusher
GC	Gyratory Crusher	OT	Other		

- 3. Enter the make, model number, and serial number of the crusher/screen.
- 4. Enter the date that each crusher and screen was constructed, reconstructed, or modified.
- 5. Enter the maximum throughput for each crusher and screen in tons per hour and tons per year.
- 6. Describe the nominal material size reduction (e.g. +2"/ -3%").
- 7. Enter the average percent moisture content of the material processed.
- 8. Enter the appropriate Control Device Identification Number for each crusher and screen. Refer to Table A Control Device Listing and Control Device Identification Number Instructions in the Reference Document for Control Device ID prefixes and numbering.
- 9. Enter the appropriate stack parameters if a baghouse control device is used.
- 10. Enter the maximum operating schedule for each crusher and screen in hours per day, days per year and hours per year.

CRUSHING AND SCREENING AFFECTED SOURCE SHEET CON'T

Source Ider	ntification Number ¹	3600.331- VS05 (MS5)	3600.331- VS06 (MS6)	3600.351- VS01 (MS7)	3600.351- VS02 (MS8)	3600.352- VS01 (Sand Screen)
Type of C	rusher or Screen ²	TD	TD	TD	TD	TD
Make, Mod	lel No., Serial No.3	NA	NA	NA	NA	NA
	uction, Reconstruction, tion (Month/Year) ⁴	2005	2005	2013	2011	2015
Maximum	tons/hour	800	800	400	600	500
Throughput ⁵	tons/year	2,500	0,000	1,500,000	3,500,000	750,000
Material	Material sized from/to:6		0"-1.5"	0"-3"	0"-3"	0"-1.5"
Average Mo	Average Moisture Content (%) ⁷		1.5	Wet	Wet	Wet
Control De	Control Device ID Number ⁸		PE-MC	Wet	Wet	Wet
	height (ft)					
Baghouse	diameter (ft)					
Stack	volume (ACFM)					
Parameters ⁹	exit temp (F)	<u> </u>				
	UTM Coordinates					
Maximum	hours/day	24	24	24	24	24
Operating	days/year	365	365	365	365	365
Schedule 10	hours/year	8,760	8,760	8,760	8,760	8,760

1. Enter the appropriate Source Identification Number for each crusher and screen. For example, in the case of an operation which incorporates multiple crushers, the crushers should be designated CR-1, CR-2, CR-3 etc. beginning with the breaker or primary crusher. Multiple screens should be designated S-1, S-2, S-3 etc.

2. Describe types of crushers and screens using the following codes:

HM	Hammermill	SS	Stationary Screen	DR	Double Roll Crusher	
SD	Single Deck Screen	BM	Ball Mill	DD	Double-Deck Screen	
RB	Rotary Breaker	TD	Triple Deck Screen	JC	Jaw Crusher	
GC	Gyratory Crusher	OT	Other	CC	Cone Crusher IMP	Impact
		Crusher				

- 3. Enter the make, model number, and serial number of the crusher/screen.
- 4. Enter the date that each crusher and screen was constructed, reconstructed, or modified.
- 5. Enter the maximum throughput for each crusher and screen in tons per hour and tons per year.
- 6. Describe the nominal material size reduction (e.g. +2"/-3/8").
- 7. Enter the average percent moisture content of the material processed.
- 8. Enter the appropriate Control Device Identification Number for each crusher and screen. Refer to Table A Control Device Listing and Control Device Identification Number Instructions in the Reference Document for Control Device ID prefixes and numbering.
- 9. Enter the appropriate stack parameters if a baghouse control device is used.
- 10. Enter the maximum operating schedule for each crusher and screen in hours per day, days per year and hours per year.

CONVEYING AFFECTED SOURCE SHEET

Source Cor Reco	Date of Construction, Reconstruction	Type of Material	Size of Material	Maximum Material Transfer Rate⁵		Average Moisture Content	Control Device ⁷
	Modification (Month/Year) ²	Handled ³	Handled ⁴	tons/hour	tons/year	(%) ⁶	Device
3600.311-BC01 (P1)	2001	Aggregate	0"-8"	1,200	6,000,000	1.5	N
3600.311-BC02 (P2)	2001	Aggregate	0"-8"	1,200	6,000,000	1.5	WS
3600.311-BC03 (P3)	2001	Aggregate	0"-4"	500	2,000,000	1.5	N
3600.311-BC04 (P4)	2001	Aggregate	0"-4"	300	2,000,000	1.5	N
3600.311-ST01 (P5)	2001	Aggregate	0"-4"	300	2,000,000	1.5	N
3600.321-BC01 (P6)	2001	Aggregate	0"-4"	1,200	6,000,000	1.5	WS
3600.321-BC02 (P7)	2001	Aggregate	0"-4"	1,200	6,000,000	1.5	N
3600.321-BC03 (P8)	2001	Aggregate	0"-4"	1,200	6,000,000	1.5	N
3600.321-BC04 (P9)	2001	Aggregate	0"-4"	1,200	6,000,000	1.5	N
3600.331-BC01 (M1)	2001	Aggregate	0"-4"	1,200	6,000,000	1.5	PE
3600.331-ST01 (M2)	2001	Aggregate	0"-4"	1,200	6,000,000	1.5	N
3600.331-BC02 (M3)	1984	Aggregate	0"-4"	1,000	6,000,000	1.5	PE
3600.331-BC03 (M4)	1984	Aggregate	0"-4"	1,000	6,000,000	1.5	N
3600.331-BC04 (M5)	1984	Aggregate	0"-4"	800	2,500,000	1.5	N
3600.331-BC05 (M6)	2005	Aggregate	0"-4"	800	2,500,000	1.5	N
3600.331-BC06 (M10)	2005	Aggregate	0"-1.5"	800	2,500,000	1.5	WS
3600.331-BC12 (M12)	2005	Aggregate	0"-1.5"	300	2,000,000	1.5	N

Enter the appropriate Source Identification Number for each conveyor using the following codes. For example, multiple belt conveyors should be designated BC-1, BC-2, BC-3 etc. Transfer points are considered emission points, not sources, and should not be included in the Conveying Affected Source Sheet. Transfer Point Identification Numbers shall be assigned in the Emission Calculation Sheet.

BC Belt Conveyor BE Bucket Elevator DL Drag-link Conveyor PS Pneumatic System SC Screw Conveyor VC Vibrating Conveyor OT Other

OT Other

- 2. Enter the date that each crusher and screen was constructed, reconstructed, or modified.
- 3. Enter the type of material being handled Raw Material (RM) Sized Material (SM) Refuse (R) Other (O)
- 4. Enter the nominal size of the material being conveyed (e.g. sized material- ¾ x 0). If more than one material is handled by the listed conveyor, list each material and enter the appropriate data for each material.
- 5. Enter the maximum material transfer rate for each conveyor in tons per hour and tons per year.
- 6. Enter the average percent moisture content of the conveyed material.
- 7. Enter the control device for the conveyor. PE Partial Enclosure (example 3/4 hoop), FE Full Enclosure, N None

CONVEYING AFFECTED SOURCE SHEET CON'T

Source Identification Number ¹	Date of Construction, Reconstruction , or Modification	Type of Material Handled ³	Size of Material Handled ⁴	Maximum Material Transfer Rate⁵		Average Moisture Content	Control Device ⁷	
	(Month/Year) ²	Trancied	Halluleu	tons/hour	tons/year	(%) ⁶		
3600.331-BC08 (M13)	1984	Aggregate	0"-1.5"	600	2,000,000	1.5	N	
3600.331-BC09 (M14)	1984	Aggregate	0"-1.5"	1,000	4,500,000	1.5	ws	
3600.331-BC10 (M7)	1984	Aggregate	4"	400	250,000	1.5	N	
3600.331-BC11 (M8)	1984	Aggregate	4"	400	250,000	1.5	N	
3600.331-ST02 (M9)	1984	Aggregate	4"	400	250,000	1.5	WS	
3600.331-BC07 (M11)	1984	Aggregate	0"-1.5"	300	2,000,000	1.5	N	
3600.331-BC13 (M22)	1984	Aggregate	0"-1.5"	200	1,752,0000	1.5	N	
3600.331-BC14 (M23)	1984	Aggregate	0"-1.5"	200	1,752,0000	1.5	N	
3600.331-BC15 (M24)	2006	Aggregate	0"-1.5"	400	3,500,000	1.5	N	
3600.331-ST03 (M25)	2005	Aggregate	0"-1.5"	400	3,500,000	1.5	N	
3600.351-BC01 (M15)	2005	Aggregate	0"-1.5"	600	3,500,000	1.5	N	
3600.351-BC02 (M16)	2005	Aggregate	0"-1.5"	600	3,500,000	1.5	N	
3600.351-BC03 (M17)	2005	Aggregate	0"-1.5"	600	3,500,000	1.5	N	
3600.351-ST01 (M18)	2014	Aggregate	0"-1.5"	600	3,500,000	1.5	N	
3600.351-SY01 (67's Screw)	2013	Aggregate	0"-1.5"	50	438,000	1.5	Wet	
3600.351-BC07 (M26)	2013	Aggregate	0"-1.5"	50	438,000	1.5	N	
3600.351-BC04 (M19)	2005	Aggregate	0"-1.5"	400	1,500,000	1.5	N	
3600.351-BC05 (M20)	2005	Aggregate	0"-1.5"	400	1,500,000	1.5	N	

1. Enter the appropriate Source Identification Number for each conveyor using the following codes. For example, multiple belt conveyors should be designated BC-1, BC-2, BC-3 etc. Transfer points are considered emission points, not sources, and should not be included in the *Conveying Affected Source Sheet*. Transfer Point Identification Numbers shall be assigned in the *Emission Calculation Sheet*.

BC Belt Conveyor BE Bucket Elevator DL Drag-link Conveyor PS Pneumatic System SC Screw Conveyor VC Vibrating Conveyor OT Other

2. Enter the date that each crusher and screen was constructed, reconstructed, or modified.

3. Enter the type of material being handled - Raw Material (RM) Sized Material (SM) Refuse (R) Other (O)

- 4. Enter the nominal size of the material being conveyed (e.g. sized material- 3/4" x 0). If more than one material is handled by the listed conveyor, list each material and enter the appropriate data for each material.
- 5. Enter the maximum material transfer rate for each conveyor in tons per hour and tons per year.
- 6. Enter the average percent moisture content of the conveyed material.
- 7. Enter the control device for the conveyor. PE Partial Enclosure (example 3/4 hoop), FE Full Enclosure, N None

CONVEYING AFFECTED SOURCE SHEET CON'T

Source Identification Number ¹	Date of Construction, Reconstruction, or Modification	Type of Material	Size of Material	Maximum Material Transfer Rate⁵		Average Moisture	Control
Identification Number	(Month/Year) ²	Handled ³	Handled ⁴	tons/hour	tons/year	Content (%) ⁶	Device ⁷
3600.351-ST02 (M21)	2005	Aggregate	0"-1.5"	400	1,500,000	1.5	N
3600.352-BC01 (M27)	1998	Aggregate	0"-1.5"	200	750,000	1.5	N
3600.352-BC02 (M28)	1998	Aggregate	0"-1.5"	200	750,000	1.5	N
3600.352-BC03 (S1)	1998	Aggregate	0"-1.5"	300	750,000	1.5	N
3600.352-BC04 (S2)	1998	Aggregate	0"-1.5"	500	750,000	1.5	N
3600.352-BC05 (S5)	1998	Aggregate	0"-1.5"	400	750,000	1.5	N
3600.352-BC06 (S6)	1998	Aggregate	0"-1.5"	200	750,000	1.5	N
3600.352-SY01 (Sand Screw)	1998	Sand	Sand	400	750,000	Wet	Wet
3600.352-BC07 (S7)	1998	Sand	Sand	400	750,000	1.5	N
3600.341-BC01 (S3)	1998	Aggregate	0"-1.5"/sand	400	750,000	1.5	N
3600.341-BC02 (S4)	1998	Aggregate	0"-1.5"/sand	400	750,000	1.5	N
			_				

1. Enter the appropriate Source Identification Number for each conveyor using the following codes. For example, multiple belt conveyors should be designated BC-1, BC-2, BC-3 etc. Transfer points are considered emission points, not sources, and should not be included in the *Conveying Affected Source Sheet*. Transfer Point Identification Numbers shall be assigned in the *Emission Calculation Sheet*.

BC Belt Conveyor BE Bucket Elevator DL Drag-link Conveyor PS Pneumatic System SC Screw Conveyor VC Vibrating Conveyor OT Other

2. Enter the date that each crusher and screen was constructed, reconstructed, or modified.

3. Enter the type of material being handled - Raw Material (RM) Sized Material (SM) Refuse (R) Other (O)

4. Enter the nominal size of the material being conveyed (e.g. sized material- 3/4" x 0). If more than one material is handled by the listed conveyor, list each material and enter the appropriate data for each material.

5. Enter the maximum material transfer rate for each conveyor in tons per hour and tons per year.

. Enter the average percent moisture content of the conveyed material.

7. Enter the control device for the conveyor. PE - Partial Enclosure (example 3/4 hoop), FE - Full Enclosure, N - None

STORAGE ACTIVITY AFFECTED SOURCE SHEET

Source Identification Number ¹	311-HP01 (Dump Box)	331-HP05 (Hopper Feed Bin 5)	331-HP09 (Hopper Feed Bin 9)	SP1	SP2	SP3
Type of Material Stored ²	Raw Aggregate	Aggregate	Aggregate	CR6	Gabion Stone	Surge Pile
Average Moisture Content (%) ³	1.5	1.5	1.5	1.5	1.5	1.5
Maximum Yearly Storage Throughput (tons) ⁴	6,000,000	2,500,000	1,750,000	2,000,000		6,000,000
Maximum Storage Capacity (tons) ⁵	200	30	30	100,000		37,500
Maximum Base Area (ft²) ⁶	NA	NA	NA	90,000	10,000	74,000
Maximum Pile Height (ft) ⁷	NA	NA	NA	50	40	40
Method of Material Load-in ⁸	TD	SS	SS	RS	FC	SS
Load-in Control Device Identification Number ⁹	PE-WS	PE-MC	PE-MC	MC	МС	МС
Storage Control Device Identification Number ⁹	PE	PE	PE	N	N	N
Method of Material Load-out ⁸	FC	FC	FC	FE	FE	UC
Load-out Control Device Identification Number ⁹	FE	FE-MC	РЕ-МС	MD	MD	FE-MC

- Enter the appropriate Source Identification Number for each storage activity using the following codes. For example, if the facility utilizes three storage bins, four open stockpiles and one storage building (full enclosure), the Source Identification Numbers should be BS-1, BS-2, and BS-3; OS-1, OS-2, OS-3, and OS-4; and SB-1, respectively.
 - BS Bin or Storage Silo (full enclosure)
- E3 Enclosure (three sided enclosure)
- OS Open Stockpile SF Stockpiles with wind fences
- SBStorage Building (full enclosure)
- OT Other
- Describe the type of material stored or stockpiled. (e.g. sized material, raw material, refuse, etc).
- Enter the average percent moisture content of the stored material.
- Enter the maximum yearly storage throughput for each storage activity.
- Enter the maximum storage capacity for each storage activity in tons (e.g. silo capacity, maximum stockpile size, etc.)
- For stockpiles, enter the maximum stockpile base area.
- For stockpiles, enter the maximum stockpile height.
- Enter the method of load-in or load-out to/from stockpiles or bins using the following codes:
 - CS Clamshell

- SS Stationary Conveyor/Stacker Stacking Tube
- FC Fixed Height Chute from Bins FE Front Endloader
- TC Telescoping Chute from Bins
- MC Mobile Conveyor/Stacker
- TD Truck Dump
- UC Under-pile or Under-Bin Reclaim Conveyor
- Pneumatic Conveyor/Stacker
- RC Rake or Bucket Reclaim Conveyor
- OT Other RS Radial Stacker

STORAGE ACTIVITY AFFECTED SOURCE SHEET CON'T

					Γ	
Source Identification Number ¹	SP4	SP5	SP5A	SP6	SP7	SP8
Type of Material Stored ²	Main Surge Pile	Washed #8/#9/Sand	Washed #8	Various	Dry Ballast	Various
Average Moisture Content (%) ³	1.5	1.5	1.5	1.5	1.5	1.5
Maximum Yearly Storage Throughput (tons) ⁴	6,000,000	750	,000	5,000,000	250,000	20,000
Maximum Storage Capacity (tons) ⁵	20,000	130,000	700	23,000	120,000	2,000
Maximum Base Area (ft²) ⁶	70,000	350,000	9,000	33,000	237,000	18,000
Maximum Pile Height (ft) ⁷	40	40	40	40	40	40
Method of Material Load-in ⁸	RS	SS	SS	FE	RS	FE
Load-in Control Device Identification Number ⁹	MC	MC	МС	MC	МС	МС
Storage Control Device Identification Number ⁹	N	N	N	N	N	N
Method of Material Load-out ⁸	UC	FE	FE	FE	FE	FE
Load-out Control Device Identification Number ⁹	FE-MC	MD	MD	MD	MD	MD

- 1. Enter the appropriate Source Identification Number for each storage activity using the following codes. For example, if the facility utilizes three storage bins, four open stockpiles and one storage building (full enclosure), the Source Identification Numbers should be BS-1, BS-2, and BS-3; OS-1, OS-2, OS-3, and OS-4; and SB-1, respectively.
 - BS Bin or Storage Silo (full enclosure)
- E3 Enclosure (three sided enclosure)
- OS Open Stockpile
- SB Storage Building (full enclosure)
- SF Stockpiles with wind fences
- OT Other RS Radial Stacker
- 2. Describe the type of material stored or stockpiled. (e.g. sized material, raw material, refuse, etc).
- 3. Enter the average percent moisture content of the stored material.
- 4. Enter the maximum yearly storage throughput for each storage activity.
- 5. Enter the maximum storage capacity for each storage activity in tons (e.g. silo capacity, maximum stockpile size, etc.)
- 6. For stockpiles, enter the maximum stockpile base area.
- For stockpiles, enter the maximum stockpile height.
- Enter the method of load-in or load-out to/from stockpiles or bins using the following codes:
 - CS Clamshell

- SS Stationary Conveyor/Stacker
- FC Fixed Height Chute from Bins
- ST Stacking Tube
- FE Front Endloader
 MC Mobile Conveyor/Stacker
- TC Telescoping Chute from Bins TD Truck Dump
- UC Under-pile or Under-Bin Reclaim Conveyor
- PC Pneumatic Conveyor/Stacker
- RC Rake or Bucket Reclaim Conveyor
- OT Other
- 9. Enter the appropriate Control Device Identification Number for each storage activity. Refer to Table A Control Device Listing and Control Device Identification Number Instructions in the Reference Document for Control Device ID prefixes and numbering.

STORAGE ACTIVITY AFFECTED SOURCE SHEET CON'T

	Т					
Source Identification Number ¹	SP9	SP10	SP11	SP12	SP13	SP14
Type of Material Stored ²	Washed #8/#7	Various	Various	Various	67/57	Dry #10
Average Moisture Content (%) ³	1.5	1.5	1.5	1.5	1.5	1.5
Maximum Yearly Storage Throughput (tons) ⁴	1,500,000	300,000	20,000	200,000	3,50	00,000
Maximum Storage Capacity (tons) ⁵	80,000	100,000	3,000	10,000	250,000	250,000
Maximum Base Area (ft²) ⁶	97,000	219,000	50,000	83,000	277,000	222,000
Maximum Pile Height (ft) ⁷	40	40	40	40	40	40
Method of Material Load-in ⁸	RS	TD/FE	TD/FE	TD/FE	RS	RS
Load-in Control Device Identification Number ⁹	MC	MD	MD	MD	МС	МС
Storage Control Device Identification Number ⁹	N	N	N	N	N	N
Method of Material Load-out ⁸	FE	FE	FE	FE	FE	FE
Load-out Control Device Identification Number ⁹	MD	MD	MD	MD	MD	MD

- Enter the appropriate Source Identification Number for each storage activity using the following codes. For example, if the facility utilizes three storage bins, four open stockpiles and one storage building (full enclosure), the Source Identification Numbers should be BS-1, BS-2, and BS-3; OS-1, OS-2, OS-3, and OS-4; and SB-1, respectively.
 - BS Bin or Storage Silo (full enclosure)
- E3 Enclosure (three sided enclosure)
- Open Stockpile OS SF Stockpiles with wind fences
- SB Storage Building (full enclosure)
- OT
- Describe the type of material stored or stockpiled. (e.g. sized material, raw material, refuse, etc).
- Enter the average percent moisture content of the stored material.
- Enter the maximum yearly storage throughput for each storage activity.
- Enter the maximum storage capacity for each storage activity in tons (e.g. silo capacity, maximum stockpile size, etc.)
- For stockpiles, enter the maximum stockpile base area.
- For stockpiles, enter the maximum stockpile height.
- Enter the method of load-in or load-out to/from stockpiles or bins using the following codes:
 - CS Clamshell

- Stationary Conveyor/Stacker
- FC Fixed Height Chute from Bins FE Front Endloader
- STStacking Tube
- MC Mobile Conveyor/Stacker
- Telescoping Chute from Bins
- Under-pile or Under-Bin Reclaim Conveyor UC
- TD Truck Dump PC Pneumatic Conveyor/Stacker
- RC Rake or Bucket Reclaim Conveyor
- OT Other
- Enter the appropriate Control Device Identification Number for each storage activity. Refer to Table A Control Device Listing and Control Device Identification Number Instructions in the Reference Document for Control Device ID prefixes and numbering.

STORAGE ACTIVITY AFFECTED SOURCE SHEET CON'T

	1				
Source Identification Number ¹	SP15	SP16	SP17	SP18	
Type of Material Stored ²	Various	Various	Various	Various	
Average Moisture Content (%) ³	1.5	1.5	1.5	1.5	
Maximum Yearly Storage Throughput (tons) ⁴	60,000	30,000	30,000	30,000	
Maximum Storage Capacity (tons) ⁵	20,000	10,000	30,000	10,000	
Maximum Base Area (ft²) ⁶	128,000	85,000	129,000	61,000	
Maximum Pile Height (ft) ⁷	40	40	40	40	
Method of Material Load-in ⁸	TD/FE	TD/FE	TD/FE	TD/FE	
Load-in Control Device Identification Number ⁹	MD	MD	MD	MD	
Storage Control Device Identification Number ⁹	N	N	N	N	
Method of Material Load-out ⁸	FE	FE	FE	FE	
Load-out Control Device Identification Number ⁹	MD	MD	МС	MC	

- Enter the appropriate Source Identification Number for each storage activity using the following codes. For example, if the facility utilizes
 three storage bins, four open stockpiles and one storage building (full enclosure), the Source Identification Numbers should be BS-1, BS-2,
 and BS-3; OS-1, OS-2, OS-3, and OS-4; and SB-1, respectively.
 - BS Bin or Storage Silo (full enclosure)
- E3 Enclosure (three sided enclosure)
 SB Storage Building (full enclosure)
- SF Stockpiles with wind fences

Open Stockpile

- OT Other
- 2. Describe the type of material stored or stockpiled. (e.g. sized material, raw material, refuse, etc).
- 3. Enter the average percent moisture content of the stored material.
- 4. Enter the maximum yearly storage throughput for each storage activity.
- 5. Enter the maximum storage capacity for each storage activity in tons (e.g. silo capacity, maximum stockpile size, etc.)
- 6. For stockpiles, enter the maximum stockpile base area.
- 7. For stockpiles, enter the maximum stockpile height.
- 8. Enter the method of load-in or load-out to/from stockpiles or bins using the following codes:
 - CS Clamshell

FC

OS

SS Stationary Conveyor/Stacker ST Stacking Tube

FE Front Endloader

TC Telescoping Chute from Bins

- MC Mobile Conveyor/Stacker
- TD Truck Dump
- UC Under-pile or Under-Bin Reclaim Conveyor
- PC Pneumatic Conveyor/Stacker
- RC Rake or Bucket Reclaim Conveyor

Fixed Height Chute from Bins

- OT Other
- 9. Enter the appropriate Control Device Identification Number for each storage activity. Refer to Table A Control Device Listing and Control Device Identification Number Instructions in the Reference Document for Control Device ID prefixes and numbering.

HAULROAD EMISSIONS

Include G40-C Emission Calculation Spreadsheet indicating haulroad emissions, or submit calculations indicating assumptions made to substantiate emission values.

Emission Source	Uncontrolle	d Emissions	Controlled Emissions		
	(PM/PM1	10/PM2.5)	(PM/PM10/PM2.5)		
	Hourly (lb/hr)	Annual (tpy)	Hourly (lb/hr)	Annual (tpy)	
Raw Trucks	214.70/63.46/6.27	521.54/154.15/15.23	53.68/15.87/1.57	130.39/38.54/3.81	
Product Trucks	352.98/104.41/10.60	350.53/103.69/10.53	88.25/26.10/2.65	87.63/25.92/2.63	
Endloaders	11.24/3.32/0.33	33.72/9.96/0.99	2.81/0.83/0.08	8.43/2.49/0.25	

BAGHOUSE AIR POLLUTION CONTROL DEVICE SHEET NOT APPLICABLE

Complete a Baghouse Air Pollution Control Device Sheet for each baghouse control device. Baghouse Control Device Identification Number: 2. Manufacturer's name and model identification: 3. Number of compartments in baghouse: Number of compartments online during normal operation and conditions: 4. Gas flow rate into baghouse: _____ ACFM @ _____ °F 5. and _____ PSIA Total cloth area: ____ ft² 6. 7. Operating air to cloth ratio: _____ ft/min 8. Filter media type: 9. Stabilized static pressure drop across baghouse: _____ inches H₂O 10. Baghouse operation is: □ Continuous □ Automatic □ Intermittent 11. Method used to clean bags: □ Shaker□ Pulse jet □ Reverse jet □ Other 12. Emission rate of particulate matter entering and exiting baghouse at maximum design operating conditions: Entering baghouse: _____ lb/hr and grains/ACF Exiting baghouse: _____ lb/hr and _____ grains/ACF 13. Guaranteed minimum baghouse collection efficiency: ______ % 14. Provide a written description of the capture system (e.g. hooding and ductwork arrangement), size of ductwork and hoods and air volume, capacity and operating horsepower of fan:

15. Describe the method of disposal for the collected material:

Air Pollution Control Device Sheet NOT APPLICABLE

(WET COLLECTING SYSTEM-SCRUBBER)

Control Device ID No. (must match Emission Units Table):

Equipment	t Infori	mation
-----------	----------	--------

	Equipmo	nt Information							
1.	Manufacturer:	2. Method: Packed Bed Venturi							
	W 1137	Spray Tower Cyclone							
	Model No.	☐ Mechanical ☐ Orifice ☐ Other, specify							
3.	Provide diagram(s) of unit describing capture system	with duct arrangement and size of duct, air volume, capa	city						
1	horsepower of movers. If applicable, state hood face	relocity and hood collection efficiency.	city,						
4.	Provide a scale diagram of the scrubber showing internal construction. Please include packing type and size, spray								
	configurations, baffle plates, and mist eliminators.	one construction of the state o	praj						
5.	What type of liquid entrainment eliminators or system	will be used? Submit a schematic diagram showing thickr	iess,						
	mesh, and material of construction.								
6.	Describe the scrubber's construction material:								
7.	What will be the power requirements of the collector?								
	Fan HP	Inlet scrubbing liquid pump:							
8.	What type of fan(s) will be used?								
	Type of fan blade: Number	of blades: Diameter of blade:							
	in.								
<u> </u>	Also supply a fan curve for each fan to be used.								
9.	Estimated gas pressure drop at maximum flow rate:	inches H ₂ O							
	Scrubbing Lic	uor Characteristics							
10.	Scrubbing Liquor	11. Scrubbing liquor losses (evaporation, etc.):							
	Composition Weight 9	gal/1000 ACF g	as						
	1	12. Liquor pressure to scrubber:	SIA						
		4							
	2								
	3	13. Pressure drop through scrubber: in. I	H_2O						
		-							
	4								
14.	Source of liquor (explain):	15. Liquor flow rates to scrubber:							
		Design maximum: gal/	min						
		Average expected: gal/	min						
16.	Describe system to be used to supply liquor to collecte	r:							

17.	Give the expected solids con	tent of the liqu	or:				
18.	If the liquor is to be recircula	ited, describe a	nv_treatment	performe	q.		
			ily a cultivione	periorine	u .		
19.	Data for Venturi Scrubber:			20. Da	ta for Packed Towe	ers:	
	Throat Dimensions: (Specify Units)				Type of Pack	_	vals Dod.
	Throat Velocity:	ft/s	ec		Superficial O	ias Velocity thro	ign Bed:
		0	Gas Stream C	haracte	ristics		
21.	Gas flow into the collector:			22. Ga	s stream temperatur	re:	
	ACF @	°F and	PSIA		Inle	t:	°F
23.	Gas flow rate:			24. Par	ticulate Grain Load	ling in grains/scf	
	Design Maximum:	AC	FM		Inle	t:	
	Average Expected:	AC			Outl	let:	
	Emission rate of each polluta	nt (specify) int	o and out of c	collector:	O	UT	Guaranteed Minimum
		lb/hr	grain	s/acf	lb/hr	grains/acf	Collection Efficiency
	A						
	В						
	C						
	D						
	Е						
26.	Type of pollutant(s) controlle	d: 🔲 :	SO _x		Odor		
	Particulate (type):				Other:		
27.	By what method were the unc	controlled emis Other:	sions calculat	ed?	Material E	Balance	Stack Test
28.	Dimensions of stack:	Height		ft.	Dion	neter	ft
	Difficusions of stack.	Height		It.	Diai	neter	11
	Supply an equilibrium curve a		y data (at var				11

30.	Supply a curve showing propose	d collection efficiency	versus gas vo	olume from 2	25 to 10	00 percent of	design rating of
	collector.						

Par	ticulate Distribution				
31.	Describe any air pollution	control device inl	let and outlet	as conditioning pr	oce

31.	Describe any air poligas humidification):	lution control device inlet and outlet g	gas conditioning processes (e.g., gas cooling, gas reheating,
32.	Describe the collection	on material disposal system:	
33.	Have you included	Wet Collecting (Scrubber) Control	Device in the Emissions Points Data Summary Sheet?
	Please propose mon	ng, Recordkeeping, Reporting, and itoring, recordkeeping, and reporting. Please propose testing in order to de	Festing in order to demonstrate compliance with the proposed emonstrate compliance with the proposed emissions limits. RECORDKEEPING:
REP	ORTING:		TESTING:
MOI	NITORING:	Please list and describe the process in order to demonstrate compliance device.	parameters and ranges that are proposed to be monitored with the operation of this process equipment or air control
	ORDKEEPING: ORTING:	Please describe the proposed records	seeping that will accompany the monitoring. sions testing for this process equipment on air pollution
TES	TING:		sions testing for this process equipment on air pollution

0.5	
	Manufacturer's Guaranteed Capture Efficiency for each air pollutant.
30.	Manufacturer's Guaranteed Control Efficiency for each air pollutant.
27	
37.	Describe all operating ranges and maintenance procedures required by Manufacturer to maintain warranty.

ENGINE DATA SHEET NOT APPLICABLE

	EII (OII (I		OTTES T	OI THE L	TOTABLE		
Source Ider	ntification Number ¹				_		
Engine Man	ufacturer and Model						
Manufactur	er's Rated bhp/rpm						
Sou	irce Status ²						
Date Installed	n/Modified/Removed						
Engine Manufactu	red/Reconstruction Date ⁴						
Is this a Certified Ignition Engine account IIII? (Yes or No) ⁵	Stationary Compression ording to 40CFR60 Subpart						
Is this a Certified Engine according t (Yes or No) ⁶	Stationary Spark Ignition o 40CFR60 Subpart JJJJ?						
	Engine Type ⁷						
	APCD Type ⁸						
.	Fuel Type ⁹						
Engine, Fuel and	H ₂ S (gr/100 scf)						
Combustion Data	Operating bhp/rpm						
Data	BSFC (Btu/bhp-hr)						
	Fuel throughput (ft ³ /hr)						
	Fuel throughput (MMft ³ /yr)						
	Operation (hrs/yr)						
Reference ¹⁰	Potential Emissions ¹¹	lbs/hr	tons/yr	lbs/hr	tons/yr	lbs/hr	tons/yr
	NO _X						
	CO						
	VOC						
	SO ₂						
	PM ₁₀						
	Formaldehyde						

1. Enter the appropriate Source Identification Number for each reciprocating internal combustion compressor/generator engine located at the facility. Multiple compressor engines should be designated CE-1, CE-2, CE-3 etc. Emergency Generator engines should be designated EG-1, EG-2, EG-3 etc. If more than three (3) engines exist, please use additional sheets.

2. Enter the Source Status using the following codes:

Construction of New Source (installation) MS

Modification of Existing Source

ES **Existing Source**

RS Removal of Source

- 3. Enter the date (or anticipated date) of the engine's installation (construction of source), modification or removal.
- Enter the date that the engine was manufactured, modified or reconstructed.
- 5. Is the engine a certified stationary compression ignition internal combustion engine according to 40CFR60 Subpart IIII. If so, the engine and control device must be operated and maintained in accordance with the manufacturer's emission-related written instructions. You must keep records of conducted maintenance to demonstrate compliance, but no performance testing is required. If the certified engine is not operated and maintained in accordance with the manufacturer's emissionrelated written instructions, the engine will be considered a non-certified engine and you must demonstrate compliance according to 40CFR§60.4210 as appropriate.

Provide a manufacturer's data sheet for all engines being registered.

6. Is the engine a certified stationary spark ignition internal combustion engine according to 40CFR60 Subpart JJJJ. If so, the engine and control device must be operated and maintained in accordance with the manufacturer's emission-related written instructions. You must keep records of conducted maintenance to demonstrate compliance, but no performance testing is required. If the certified engine is not operated and maintained in accordance with the manufacturer's emission-related written instructions, the engine will be considered a non-certified engine and you must demonstrate compliance according to 40CFR§60.4243a(2)(i) through (iii), as appropriate.

Provide a manufacturer's data sheet for all engines being registered.

7. Enter the Engine Type designation(s) using the following codes:

LB2S Lean Burn Two Stroke

RB4S Rich Burn Four Stroke

LB4S Lean Burn Four Stroke

8. Enter the Air Pollution Control Device (APCD) type designation(s) using the following codes:

A/F Air/Fuel Ratio Ignition Retard

HEIS High Energy Ignition System

SIPC Screw-in Precombustion Chambers

PSC Prestratified Charge

LEC Low Emission Combustion

NSCR Rich Burn & Non-Selective Catalytic Reduction

Lean Burn & Selective Catalytic Reduction SCR

9. Enter the Fuel Type using the following codes:

PO Pipeline Quality Natural Gas

RG Raw Natural Gas

2FO #2 Fuel Oil LPG Liquid Propane Gas

10. Enter the Potential Emissions Data Reference designation using the following codes. Attach all referenced data to this Compressor/Generator Data Sheet(s).

MD Manufacturer's Data GR

AP AP-42

GRI-HAPCalcTM

OT Other ___

(please list)

11. Enter each engine's Potential to Emit (PTE) for the listed regulated pollutants in pounds per hour and tons per year. PTE shall be calculated at manufacturer's rated brake horsepower and may reflect reduction efficiencies of listed Air Pollution Control Devices. Emergency generator engines may use 500 hours of operation when calculating PTE. PTE data from this data sheet shall be incorporated in the Emissions Summary Sheet.

STORAGE TANK DATA SHEET NOT APPLICABLE

Source ID #1	Status ²	Content ³	Volume ⁴	Dia ⁵	Throughput ⁶	Orientation ⁷	Liquid Height ⁸
		-					
					<u> </u>		
					<u> </u>		
						_	

- 1. Enter the appropriate Source Identification Numbers (Source ID #) for each storage tank located at the facility. Tanks should be designated T01, T02, T03, etc.
- 2. Enter storage tank Status using the following:

EXIST Existing Equipment

REM Equipment Removed

NEW Installation of New Equipment

- 3. Enter storage tank content such as condensate, pipeline liquids, glycol (DEG or TEG), lube oil, etc.
- 4. Enter storage tank volume in gallons.
- 5. Enter storage tank diameter in feet.
- 6. Enter storage tank throughput in gallons per year.
- 7. Enter storage tank orientation using the following:

VERT Vertical Tank

HORZ Horizontal Tank

8. Enter storage tank average liquid height in feet.

ATTACHMENT I EMISSIONS CALCULATIONS

Potesta & Associates, Inc. Project No. 0101-16-0231

 By: ADM
 Checked By: PEW

 Date: 06/14/2016
 Date: 06/14/2016

This project is for replacement of a crusher. There is no change to the potential to emit. The replaced crusher is shown in red on page I6 of I8.

Proposed Facility Emissions

Total Facility	Uncor	ıtrolled	Controlled		
	lb/hr tpy		lb/hr	tpy	
PM	1,087.45	1,725.40	263.53	410.19	
PM10	413.35	658.08	99.36	154.44	
PM2.5	53.52	85.29	12.78	19.81	

Point Sources

Transfer Points	Uncon	itrolled	Controlled		
	lb/hr tpy		lb/hr	tpy	
PM	351.19	476.83	92.44	119.10	
PM10	167.23	227.06	44.02	56.71	
PM2.5	25.09	34.06	6.60	8.51	

Crushing	Uncon	trolled	Controlled		
	lb/hr tpy		lb/hr	tpy	
PM	16.86	20.33	3.37	4.07	
PM10	8.03	9.68	1.60	1.94	
PM2.5	1.20	1.45	0.24	0.29	

Screening	Uncor	ntrolled	Controlled		
	lb/hr	tpy	lb/hr	l tpy	
PM	137.50	309.38	20.00	47.50	
PM10	65.48	147.32	9.52	22.62	
PM2.5	9.82	22.10	1.43	3.39	

Total	Uncor	ntrolled	Controlled		
Point Source	lb/hr	tpy_	lb/hr	tpy	
PM	505.55	806.54	115.81	170.67	
PM10	240.74	240.74 384.06		81.27	
PM2.5	36.11	57.61	8.27	12.19	

Potesta & Associates, Inc. Project No. 0101-16-0231

 By: ADM
 Checked By: PEW

 Date: 06/14/2016
 Date: 06/14/2016

Proposed Facility Emissions

Fugitive Sources

Stockpiles	Uncor	trolled	Cont	rolled
	lb/hr	tpy	lb/hr	tpy
PM	2.98	13.07	2.98	13.07
PM10	1.42	6.22	1.42	6.22
PM2.5	0.21	0.93	0.21	0.93

Haulroads	Uncor	trolled	Controlled		
	lb/hr	tpy	lb/hr	tpy	
PM	578.92	905.79	144.74	226.45	
PM10	171.19	267.80	42.80	66.95	
PM2.5	17.20	26.75	4.30	6.69	

Total	Uncor	itrolled	Controlled			
Fugitive Source	lb/hr	tpy	lb/hr	tpy		
PM	581.90	918.86	147.72	239.52		
PM10	172.61	274.02	44.22	73.17		
PM2.5	17.41	27.68	4.51	7.62		

 By: ADM
 Checked By: PEW

 Date: 06/14/2016
 Date: 06/14/2016

Transfer Points

 $E(lbs/ton) = k*(0.0032)*[(U/5)^1.3]/[(M/2)^1.4]$

Transfer Point	Material	Material	Control	Control	P	M		PM
ID Number	Throughput	Throughput	Device	Efficiency	Uncor	trolled	Controlled	
	(tph)	(tpy)		(%)	(lb/hr)	(tpy)	(lb/hr)	(tpy)
TP1	1,200	6,000,000	PE-WS	80	6.60	16.50	1.32	3.30
TP2	1,200	6,000,000	FE-MC	90	6.60	16.50	0.66	1.65
TP3	1,200	3,000,000	FE-MC	90	6.60	8.25	0.66	0.83
TP4	600	3,000,000	FE-MC	90	3.30	8.25	0.33	0.83
TP5	600	3,000,000	FE	80	3.30	8.25	0.66	1.65
TP6	1,200	6,000,000	PE	50	6.60	16.50	3.30	8.25
TP7	1,200	6,000,000	PE-MC	80	6.60	16.50	1.32	3.3
TP8	500	6,000,000	FE-MC	90	2.75	16.50	0.28	1.65
TP9A	500	2,000,000	PE-MC	80	2.75	5.50	0.55	1.10
TP9B	300	0	PE-MC	80	1.65	0	0.33	0
TP10	300	0	PE-MC	80	1.65	0	0.33	0
TP11	300	0	MC	50	1.65	0	0.83	0
TP12	700	4,000,000	MC	50	3.85	11.00	1.93	5.5
TP13	700	4,000,000	PE	50	3.85	11.00	1.93	5.5
TP14	1,200	6,000,000	PE-MC	80	6.60	16.50	1.32	3.3
TP15	1,200	0	MC	50	6.60	0	3.3	0
TP16	1,200	6,000,000	PE-MC	80	6.60	16.50	1.32	3.3
TP17	1,200	0	MC	50	6.60	0	3.3	0
TP18	1,200	6,000,000	PE-MC	80	6.60	16.50	1.32	3.3
TP19	1,200	0	MC	50	6.60	0	3.3	0
TP20	1,200	6,000,000	MC	50	6.60	16.50	3.3	8.25
TP21	1,200	6,000,000	FE-MC	90	6.60	16.50	0.66	1.65
TP22	1,200	6,000,000	PE-MC	80	6.60	16.50	1.32	3.3
TP23	1,200	6,000,000	MC	50	6.60	16.50	3.30	8.25
TP24	1,000	6,000,000	FE-MC	90	5.50	16.50	0.55	1.65
TP25	1,000	6,000,000	FE-MC	90	5.50	16.50	0.55	1.65
TP26	1,000	6,000,000	PE-MC	80	5.50	16.50	1.10	3.30
TP27	800	2,500,000	PE-MC	80	4.40	6.88	0.88	1.38
TP28	1,000	0	PE-MC	80	5.50	0	1.10	0
TP29	1,000	3,500,000	PE-MC	80	5.50	9.63	1.10	1.93
TP30	1,000	0	FE-MC	90	5.50	0	0.55	0
TP31	800	0	PE-MC	80	4.40	0	0.88	0
TP32	1,000	0	PE-MC	80	5.50	0	1.10	0
TP33	1,000	0	PE-MC	80	5.50	0	1.10	0

 By: ADM
 Checked By: PEW

 Date: 06/14/2016
 Date: 06/14/2016

Transfer Points

 $E(lbs/ton) = k*(0.0032)*[(U/5)^1.3]/[(M/2)^1.4]$

Transfer Point	Material	Material	Control	Control	Р	M		PM
ID Number	Throughput	Throughput	Device	Efficiency		itrolled	1	ntrolled
	(tph)	(tpy)		(%)	(lb/hr)		(lb/hr) tpy	
TP34	1,000	0	FE-MC	90	5.50	0	0.55	0
TP35	800	2,500,000	PE-MC	80	4.40	6.88	0.88	1.38
TP36	800	2,500,000	PE-MC	80	4.40	6.88	0.88	1.38
TP37	800	2,500,000	FE-MC	90	4.40	6.88	0.44	0.69
TP38	800	2,500,000	PE	50	4.40	6.88	2.20	3.44
TP39	800	2,500,000	PE-MC	80	4.40	6.88	0.88	1.38
TP40	300	2,000,000	PE-MC	80	1.65	5.50	0.33	1.10
TP41	600	0	PE-MC	80	3.30	0	0.66	0
TP42	600	500,000	PE-MC	80	3.30	1.38	0.66	0.28
TP43	200	0	FE-MC	90	1.10	0	0.11	0
TP44	300	0	PE-MC	80	1.65	0	0.33	0
TP45	600	0	PE-MC	80	3.30	0	0.66	0
TP46	600	0	PE-MC	80	3.30	0	0.66	0
TP47	200	0	FE-MC	90	1.10	0	0.11	0
TP48	300	2,000,000	PE-MC	80	1.65	5.50	0.33	1.10
TP49	600	2,000,000	PE-MC	80	3.30	5.50	0.66	1.10
TP50	1,000	2,000,000	PE-MC	80	5.50	5.50	1.10	1.10
TP51	1,000	2,000,000	FE	80	5.50	5.50	1.10	1.10
TP52	1,000	0	FE	80	5.50	0	1.10	0
TP53	1,000	4,500,000	PE-MC	80	5.50	12.38	1.10	2.48
TP54	300	4,500,000	PE-MC	80	1.65	12.38	0.33	2.48
TP55	600	0	PE-MC	80	3.30	0	0.66	0
TP56	600	0	PE-MC	80	3.30	0	0.66	0
TP57	200	0	FE-MC	90	1.10	0	0.11	0
TP58	300	0	PE-MC	80	1.65	0	0.33	0
TP59	600	0	PE-MC	80	3.30	0	0.66	0
TP60	600	0	PE-MC	80	3.30	0	0.66	0
TP61	200	0	FE-MC	90	1.10	0	0.11	0
TP62	300	0	PE-MC	80	1.65	0	0.33	0
TP63	200	0	PE-MC	80	1.10	0	0.22	0
TP64	400	438,000	PE-MC	80	2.20	1.20	0.44	0.24
TP65	400	438,000	MC	50	2.20	1.20	1.10	0.6
TP66	400	250,000	PE-MC	80	2.20	0.69	0.44	0.14
TP67	400	250,000	PE-MC	80	2.20	0.69	0.44	0.14
TP68	400	250,000	MC	50	2.20	0.69	1.10	0.35
TP69A	200	0	PE-MC	80	1.10	0.00	0.22	0

By: ADM Checked By: PEW Date: 06/14/2016 Date: 06/14/2016

Transfer Points

 $E(lbs/ton) = k*(0.0032)*[(U/5)^1.3]/[(M/2)^1.4]$

Transfer Point	Material	Material	Control	P	M	PM		
ID Number	Throughput	Throughput	Device	Efficiency	Uncor	trolled	Controlled	
	(tph)	(tpy)		(%)	(lb/hr)	(tpy)	(lb/hr)	(tpy)
TP69B	200	750,000	PE-MC	80	1.10	2.06	0.22	0.41
TP70	600	3,500,000	PE-MC	80	3.30	9.63	0.66	1.93
TP71	600	3,500,000	PE-MC	80	3.30	9.63	0.66	1.93
TP72	600	0	PE-MC	80	3.30	0	0.66	0
TP73	600	0	PE-MC	80	3.30	0	0.66	0
TP74	600	0	PE-MC	80	3.30	0	0.66	0
TP75	50	438,000	PE-MC	80	0.28	1.20	0.06	0.24
TP76	50	438,000	PE-MC	80	0.28	1.20	0.06	0.24
TP77	50	438,000	PE-MC	80	0.28	1.20	0.06	0.24
TP78	400	1,500,000	PE-MC	80	2.20	4.13	0.44	0.83
TP79	400	1,500,000	PE-MC	80	2.20	4.13	0.44	0.83
TP80	400	1,500,000	PE-MC	80	2.20	4.13	0.44	0.83
TP81	400	1,500,000	MC	50	2.20	4.13	1.10	2.07
TP82	200	750,000	PE-MC	80	1.10	2.06	0.22	0.41
TP83	200	750,000	MC	50	1.10	2.06	0.55	1.03
TP84	300	0	PE-MC	80	1.65	0.00	0.33	0
TP85	500	750,000	PE	50	2.75	2.06	1.38	1.03
TP86	400	750,000	PE-MC	80	2.20	2.06	0.44	0.41
TP87	400	0	PE-MC	80	2.20	0	0.44	0
TP88	200	0	PE-MC	80	1.10	0	0.22	0
TP89	400	750,000	PE-MC	80	2.20	2.06	0.44	0.41
TP90	400	750,000	FE	80	2.20	2.06	0.44	0.41
TP91	400	750,000	PE	50	2.20	2.06	1.10	1.03
TP92	400	0	MC	50	2.20	0	1.10	0
TP93	200	0	MC	50	1.10	0	0.55	0
TP94	400	0	PE-MC	80	2.20	0	0.44	0
TP95	400	750,000	PE-MC	80	2.20	2.06	0.44	0.41
TP96	400	750,000	MC	50	2.20	2.06	1.10	1.03
TP97	1,000	2,938,000	MD	0	5.50	8.08	5.50	8.08
TP98	600	0	MC	50	3.30	0	1.65	0
TP99	600	0	MC	50	3.30	0	1.65	0
				Total PM		476.83	92.44	119.10
MS3, 4 Recycle	100%		,	Total PM10			44.02	56.71

1. PM conversion to PM10 and PM2.5:

Particle size multipliers (k) AP42 Section 13.2.4-4 (11/06):

muni	ipiicis (k) / ii -	rz beetion 15.2	.T-T (11/0
	PM	PM10	PM2.5
	0.74	0.35	0.053
Con	version Factor	2.1	14

2. Rates/throughputs set to zero are not in the worst case material flow.

Total PM2.5 25.09 34.06

By: ADM Date: 06/14/2016 Checked By: PEW Date: 06/14/2016

Crushing and Screening

Emission Factors	PM	Source
Primary Crushing	0.002	DAQ G40-C Emissions Worksheet
Secondary & Tertiary Crushing	0.0054	AP-42 Section 11.19.2-8 (Table 11.19.2-2)
Screening	0.025	AP-42 Section 11.19.2-8 (Table 11.19.2-2)

	Totals for Crus	otals for Crushing and Screening									
	Uncor	trolled	Cont	rolled							
	(lb/hr)	(tons/уг)	(lb/hr)	(tons/yr)							
PM	154.36	329.71	23.37	52							
PM10	73.51	157.00	11.12	25							
PM2.5	11.02	23.55	1.67	4							

Crusher Emissions

Tusher Emissions									
Crusher Identification	ID	Th	roughput	Control	Control	Uncor	ntrolled	Con	trolled
		(ton/hr)	(tons/yr)	Туре	Efficiency (%)	(lb/hr)	(tons/yr)	(lb/hr)	(tons/yr)
Jaw Crusher	3600.311-JC01	600	3,000,000	FE	80	1.2	3	0.24	0.60
7 Crusher	3600.321-CZ01	700	4,000,000	FE	80	3.78	10.8	0.76	2.16
Hazemag Crusher replaced by HP6	3600,331-HI01 3600,331-CZ03	800	2,500,000	FE	80	4.32	2.5	0.86	0.50
HP500	3600.331-CZ01	1,000	2,000,000	FE	80	5.4	2	1.08	0.40
HP300	3600.331-CZ02	0	0	FE	80	0	0	0	0
Barmac Crusher	3600.341-VI01	400	750,000	FE	80	2.16	2.03	0.43	0.41
					PM	16.86	20,33	3.37	4.07
					PM10	8.03	9.68	1.6	1.94
					PM2.5	1.2	1.45	0.24	0.29

Screen Emissions (3)

Screen Identification	ID	Th	roughput	Control	Control	Uncor	trolled	Cont	trolled
		(ton/hr)	(tons/yr)	Туре	Efficiency (%)	(lb/hr)	(tons/yr)	(lb/hr)	(tons/yr)
PS1	3600.311-VS01	1,200	6,000,000	PE-MC	80	30.00	75	6.00	15.00
MS1	3600.331-VS01	1,000	6,000,000	PE-MC	80	25.00	75	5.00	15.00
MS2	3600.331-VS02	0	0	PE-MC	80	0	0	0	0
MS3	3600.331-VS03	1,000	4,500,000	PE-MC	80	25.00	56.25	5.00	11.25
MS4	3600.331-VS04	0	0	PE-MC	80	0	0	0	0
MS5	3600,331-VS05	800	2,500,000	PE-MC	80	20.00	31.25	4.00	6.25
MS6	3600.331-VS06	0	0	PE-MC	80	0	0	0	0
MS7	3600.351-VS01	400	1,500,000	Wet	100	10.00	18.75	0	0
MS8	3600.351-VS02	600	3,500,000	Wet	100	15.00	43.75	0	0
Sand Screen	3600.352-VS01	500	750,000	Wet	100	12.50	9.38	0	0
					PM	137.50	309.38	20.00	47.50
					PM10	65.48	147.32	9.52	22.62
					PM2.5	9.82	22.10	1.43	3.39

1. PM conversion to PM10 and PM2.5:

Particle size multipliers (k) AP42 Section 13.2.4-4 (11/06):

~	3000001 13.2.4-4 (1	1700).		
	PM	PM10	PM2.5	Ξ
	0.74	0.35	0.053	
	Conversion Factor	2.1	14	_

2. Rates/throughputs set to zero are not in the worst case material flow.

3. Grizzly screen 311-RZ01 emissions are based on transfers of materials onto end of the screen and are included in transfer points.

Potesta & Associates, Inc. Project No. 0101-16-0231

By: ADM Date: 06/14/2016 Checked By: PEW Date: 06/14/2016

Facility Stockpiles

Reference: AP-42 Section 11.2.3, Fugitive Emissions (May, 1983), Equation #2

E = 1.7 (s/1.5) ((365-p)/235) (f/15)

$\mathbf{E} =$?	Emissions factor, pound per day per acre, (lb/day/acre)
s =	2	Silt content of material (%)
p =	148	number of days with at least 0.254 mm (0.01 in.) of precipitation per year
f =	10	Time wind speed exceeds 12 mph (%)

E = 1.395 lb/day/acre

	R	Counding to	
--	---	-------------	--

2

Stockpile	Stockpile	Base Area	Control	Control Eff.	Uncontrolle	d Emissions	Controlle	d Emissions
ID	Material	(acres)	Device	(%)	lb/hr	tpy	lb/hr	tpy
SP1	CR6	2.1	N	0	0.12	0.53	0.12	0.53
SP2	Gabion	0.2	N	0	0.01	0.05	0.01	0.05
SP3	Surge Pile	1.7	N	0	0.1	0.43	0.1	0.43
SP4	Main Surge Pile	1.6	N	0	0.09	0.41	0.09	0.41
SP5	Washed #8/#9/Sand	8.0	N	0	0.47	2.04	0.47	2.04
SP5A	Washed #8	0.2	N	0	0.01	0.05	0.01	0.05
SP6	Various	0.8	N	0	0.05	0.2	0.05	0.2
SP7	Dry Ballast	5.4	N	0	0.31	1.37	0.31	1.37
SP8	Various	0.4	N	0	0.02	0.1	0.02	0.1
SP9	Washed #8/#7	2.2	N	0	0,13	0.56	0.13	0.56
SP10	Various	5.0	N	0	0.29	1.27	0.29	1.27
SP11	Various	1.1	N	0	0.06	0.28	0.06	0.28
SP12	Various	1.9	N	0	0.11	0.48	0.11	0.48
SP13	67/57	6.4	N	0	0.37	1.63	0.37	1.63
SP14	Dry #10	5.1	N	0	0.3	1.3	0.3	1.3
SP15	Various	2.9	N	0	0.17	0.74	0.17	0.74
SP16	Various	2.0	N	0	0.12	0.51	0.12	0.51
SP17	Various	3.0	N	0	0.17	0.76	0.17	0.76
SP18	Various	1.4	N	0	0.08	0.36	0.08	0.36
				PM:	2.98	13.07	2.98	13.07
				PM10:	1.42	6.22	1.42	6.22
				PM2.5	0.21	0.93	0.21	0.93

1. PM conversion to PM10 and PM2.5:

Particle size multipliers (k) AP42 Section 13.2.4-4 (11/06):

٦			
	PM	PM10	PM2.5
	0.74	0.35	0.053
	Conversion Factor	2.1	14

By: ADM Date: 06/14/2016

Checked By: PEW Date: 06/14/2016

Vehicular Traffic (VT)

Unpaved Haulroads PM

Source	Vehicle Trips	Vehicle Trips	Miles	Emission	Uncontrolled	Uncontrolled	Control	Control	Controlled	Controlled
	per Hour	рет Үеаг	per Trip	Factor (1)			Device	Efficiency		
				(lb/VMT)	(lb/hr)	(tpy)		(%)	(lb/hr)	(tpy)
Raw Trucks	19	92,308	1.0	11.30	214.70	521.54	RWMW	75	53.68	130.39
Product Trucks	53	105,264	1.0	6.66	352.98	350.53	RWMW	75	88.25	87.63
Endloaders	50	300,000	0.02	11.24	11.24	33.72	RWMW	75	2.81	8.43
			"	Total	578.92	905.79		Total	144.74	226.45

PM10

Source	Vehicle Trips	Vehicle Trips	Miles	Emission	Uncontrolled	Uncontrolled	Control	Control	Controlled	Controlled
	per Hour	per Year	рег Тгір	Factor (1)			Device	Efficiency		
				(lb/VMT)	(lb/hr)	(tpy)		(%)	(lb/hr)	(tpy)
Raw Trucks	19	92,308	1.0	3.34	63.46	154.15	RWMW	75	15.87	38.54
Product Trucks	53	105,264	1.0	1.97	104.41	103.69	RWMW	75	26.1	25.92
Endloaders	50	300,000	0.02	3.32	3.32	9.96	RWMW	75	0.83	2.49
			_	Total	171.19	267.80		Total	42.80	66.95

PM2.5

Source	Vehicle Trips	Vehicle Trips	Miles	Emission	Uncontrolled	Uncontrolled	Control	Control	Controlled	Controlled
	per Hour	per Year	per Trip	Factor (1)			Device	Efficiency		
				(lb/VMT)	(lb/hr)	(tpy)		(%)	(lb/hr)	(tpy)
Raw Trucks	19	92,308	1.0	0.33	6.27	15.23	RWMW	75	1.57	3.81
Product Trucks	53	105,264	1.0	0.20	10.60	10.53	RWMW	75	2.65	2.63
Endloaders	50	300,000	0.02	0.33	0.33	0.99	RWMW	75	0.08	0,25
				Total	17.20	26.75		Total	4.30	6.69

		nission Factors	1)	
	PM	PM10	PM2.5	
k =	4.9	1.5	0.15	dimensionless, particle size multiplier
s =	10	10	10	%, surface material silt content
$W_{raw} =$	81	81	81	tons, mean vehicle weight
$W_{product} =$	25	25	25	
$W_{cndloader} =$	80	80	80	
a =	0.7	0.9	0.9	constants
b =	0.45	0.45	0.45	constants
p =	148	148	148	no. days/year with 0.1 in of rain
e =	11,30	3.34	0.33	lb/VMT Raw Trucks
e =	6.66	1.97	0.20	lb/VMT Product Trucks
e =	11.24	3.32	0.20	lb/VMT Endloaders
c –	11.24	3.32	0.55	ID/ VIVI I Endioaders
	Raw	Product	Endloaders	
Total Hauled (tpy) =	6,000,000	2,000,000	6,000,000	
Load Weight (tons) =	65	19	20	
Vehicles Per Year =	92,308	105,264	300,000	(1) Emission Equation AP-42 Section 13.2.2, Unpaved Roads (12/03), where:
Total Hauled (tph) =	1,200	1,000	1,000	$e = k [(s/12)^a (W/3)^b] [(365-p)/365]$
Load Weight (tons) =	65	19	20	e = Emission factor, pounds per vehicle-mile-traveled, (lb/VMT)
Vehicles Per Hour =	19	53	50	k, a & b = Constants for equation given in AP-42 Table 13.2.2-2 (dimensionless)
Empty Vehicle Weight (tons) =	48	15	70	s = Silt content of road surface material (%)
Loaded Vehicle Weight (tons) =	113	34	90	W = Mean vehicle weight, ton
Average Vehicle Weight (tons) =	81	25	80	p = Number of days with at least 0.01 in. of precipitation per year
				1 or prosipilation per year

ATTACHMENT J CLASS I LEGAL ADVERTISEMENT

AIR QUALITY PERMIT NOTICE

Notice of Application

Notice is given that Bardon, Inc. has applied to the West Virginia Department of Environmental Protection, Division of Air Quality for a modification to General Permit Registration G40-C003E for Millville Quarry to replace a tertiary crusher. The facility is located off of County Route 23 (Blair Road) near Millville in Jefferson County, West Virginia. The latitude and longitude coordinates are: 39.287, -77.794.

The applicant estimates the potential to discharge will not change as a result of replacing the crusher.

The facility is operational. The replacement tertiary crusher will be installed in July 2016. Written comments will be received by the West Virginia Department of Environmental Protection, Division of Air Quality, 601 57th Street, SE, Charleston, WV 25304 for at least 30 calendar days from the date of publication of this notice.

Any questions regarding this permit application should be directed to the DAQ at (304) 926-0499, extension 1250, during normal business hours.

Dated this the (Insert Date) day of June, 2016.

By: Bardon, Inc. Josep Maset Bardon, Inc.

6401 Golden Triangle Drive Greenbelt, Maryland 20770

ATTACHMENT L GENERAL PERMIT REGISTRATION APPLICATION FEE

General Permit Levels Construction, Modification, Relocation, Administrative Update

Class II General Permits - G10-D (Coal Preparation and Handling), G20-B (Hot Mix Asphalt), G30-D (Natural Gas Compressor Stations), G35-A (Natural Gas Compressor Stations with Flares/Glycol Dehydration Units), G40-C (Nonmetallic Minerals Processing), G50-B (Concrete Batch Plant), G60-C (Emergency Generators)

Class I General Permit - G33-A (Spark Ignition Internal Combustion Engines 25 HP-500 HP), G65-C (Emergency Generators)

General Permit	Public Notice	Review Period	Application Fee	Criteria	Application Type
		as per 45CSR13			
Class II General Permit	30 days	45 days	\$500 + applicable	6 lb/hr and 10 tpy of any regulated air pollutant	Registration Application
	(applicalit)		NSPS rees	OR 144 lb/day of any regulated air pollutant, OR 2 lb/hr of any hazardous air pollutant OR 5 tpy of	
				aggregated HAP OR 45CSR27 TAP (10%	
				increase if above BAT triggers or increase to	
				BAT triggers) or subject to applicable standard or	
				rule, but subject to specific eligibility	
				requirements	
Class II General Permit	30 days	45 days	\$500 + applicable	Same as Class II General Permit (Construction)	Registration Application
(Modification)	(applicant)		NSPS fees	but subject to specific eligibility requirements	
Administrative Update	None	60 days	None	Jo l	Registration Application
(Class I)				equipment OR more stringent requirements or	or Written Request
		S		change in MRR that is equivalent or superior	•
Administrative Update	30 days	60 days	\$300 + applicable	than	Registration Application
(Class II)	(applicant)		NSPS fees		
Relocation	30 days	45 days	\$500 + applicable	change in facility	Registration Application
0	(applicant)		NSPS fees	design or equipment	
Class I General Permit	None	45 days	\$250	Same as Class II General Permit (Construction) Registration Application	Registration Application
				but subject to specific eligibility requirements	

ATTACHMENT O EMISSIONS SUMMARY SHEETS

	EM	NOISSI	SUMMA	RY SHE	ET FOR C	RITERI	EMISSION SUMMARY SHEET FOR CRITERIA POLLUTANTS	TANTS		
							Registratio	Registration Number (Agency Use) G40-C	cy Use) G40-C	
		Potentia	Potential Emissions (lbs/hr)	(lbs/hr)			Potenti	Potential Emissions (tons/yr)	tons/yr)	
Source ID No.	NOx	со	VOC	SO_2	PM ₁₀	NOx	00	VOC	SO_2	\mathbf{PM}_{10}
Transfer Points					44.02					56.71
Crushing					1.60					1.94
Screening] = 1				9.52					22.62
Stockpiles					1.42					6.22
Haul Roads					42.80					66.95
		-								
Total					99.36					154.44

02 of 02

			- de	T			T	T	1	Ţ	T	J	Τ
FOR HAZARDOUS/TOXIC POLLUTANTS NOT APPLICABLE	Registration Number (Agency Use) G40-C	Potential Emissions (tons/yr)	Formalde- hyde										
			n- Hexane										
			Xylenes										
			Toluene										
			Ethyl- benzene										
			Benzene										
EMISSION SUMMARY SHEET FOR HAZARDOUS/T		Potential Emissions (lbs/hr)	Formalde- hyde										
			n- Hexane										
			Xylenes										
			Toluene										
			Ethyl- benzene										
			Benzene										
EMIS			Source ID No.										