ATTACHMENT G - Air Pollution Control Device Form

Control device ID number:	**List all emission units associated with this control device.**	
226C	226X, 226Y	
Manufacturer:	**Model number:**	**Installation date:**
Cyanamid	In-house design	1987

Type of Air Pollution Control Device:

___ Baghouse/Fabric Filter ___ Venturi Scrubber ___ Multiclone

___ Carbon Bed Adsorber _X_ Packed Tower Scrubber ___ Single Cyclone

___ Carbon Drum(s) ___ Other Wet Scrubber ___ Cyclone Bank

___ Catalytic Incinerator ___ Condenser ___ Settling Chamber

___ Thermal Incinerator ___ Flare ___ Other (describe) _____

___ Wet Plate Electrostatic Precipitator ___ Dry Plate Electrostatic Precipitator

List the pollutants for which this device is intended to control and the capture and control efficiencies.

Pollutant	Capture Efficiency	Control Efficiency
HCL	100%	98%

Explain the characteristic design parameters of this control device (flow rates, pressure drops, number of bags, size, temperatures, etc.).

Water Flow Rate >= 3 GPM

Is this device subject to the CAM requirements of 40 C.F.R. 64? ___ Yes _X_ No

If Yes, **Complete ATTACHMENT H**

If No**, Provide justification.** Control Device 226C is not a subject Pollutant-Specific Emissions Unit as defined at 40 C.F.R. §64.1, because this control device has potential pre-control device annual emissions of applicable regulated air pollutants that are less than major source levels, and thus is exempt per 40 C.F.R. §64.2(a)(3).

Describe the parameters monitored and/or methods used to indicate performance of this control device.

Presence or absence of flow is monitored with a flow switch.
Flow meter monitors flow rate.