

West Virginia Department of Environmental Protection
Division of Air Quality



Title V Operating Permit Revision

Jim Justice
Governor

Austin Caperton
Cabinet Secretary

For Minor Modification Permitting Action Under 45CSR30 and Title V of the Clean Air Act

Permit Action Number: MM01 **SIC:** 3275
Name of Permittee: CertainTeed Gypsum WV, Inc.
Facility Name/Location: Moundsville
County: Marshall
Facility Address: 9622 Energy Road, Proctor, WV 26055

Description of Permit Revision: The changes for this minor modification consist of the removal of EU07 (a small dust collector on the top of screw conveyor #3) as permitted in R13-2656F.

Title V Permit Information:

Permit Number: R30-05100113-2015
Issued Date: May 27, 2015
Effective Date: June 10, 2015
Expiration Date: May 27, 2020

Directions To Facility: The plant is located approximately 5 miles south of Moundsville on State Highway 2.

THIS PERMIT REVISION IS ISSUED IN ACCORDANCE WITH THE WEST VIRGINIA AIR POLLUTION CONTROL ACT (W.VA. CODE §§ 22-5-1 ET SEQ.) AND 45CSR30 - "REQUIREMENTS FOR OPERATING PERMITS." THE PERMITTEE IDENTIFIED AT THE FACILITY ABOVE IS AUTHORIZED TO OPERATE THE STATIONARY SOURCES OF AIR POLLUTANTS IDENTIFIED HEREIN IN ACCORDANCE WITH ALL TERMS AND CONDITIONS OF THIS PERMIT.

A handwritten signature in blue ink, appearing to read "William F. Durham".

William F. Durham
Director

A handwritten date "12-12-2017" in blue ink.

Date Issued

Permit Number: **R30-05100113-2015**
Permittee: **CertainTeed Gypsum WV, Inc.**
Facility Name: **Moundsville**
Permittee Mailing Address: **9622 Energy Road, Proctor, WV 26055**

This permit is issued in accordance with the West Virginia Air Pollution Control Act (West Virginia Code §§ 22-5-1 et seq.) and 45CSR30 — Requirements for Operating Permits. The permittee identified at the above-referenced facility is authorized to operate the stationary sources of air pollutants identified herein in accordance with all terms and conditions of this permit.

Facility Location:	Moundsville, Marshall County, West Virginia
Facility Mailing Address:	9622 Energy Road, Moundsville, WV 26055
Telephone Number:	(304) 843 - 3000
Type of Business Entity:	Corporation
Facility Description:	Gypsum wallboard forming facility
SIC Codes:	3275
UTM Coordinates:	516 km Easting • 4,408 km Northing • Zone 17

Permit Writer: Denton B. McDerment

Any person whose interest may be affected, including, but not necessarily limited to, the applicant and any person who participated in the public comment process, by a permit issued, modified or denied by the Secretary may appeal such action of the Secretary to the Air Quality Board pursuant to article one [§§ 22B-1-1 et seq.], Chapter 22B of the Code of West Virginia. West Virginia Code §22-5-14.

Issuance of this Title V Operating Permit does not supersede or invalidate any existing permits under 45CSR13, 14 or 19, although all applicable requirements from such permits governing the facility's operation and compliance have been incorporated into the Title V Operating Permit.

Table of Contents

1.0 Emission Units and Active R13, R14, and R19 Permits..... 4

2.0 General Conditions 6

3.0 Facility-Wide Requirements..... 15

4.0 Source-Specific Requirements [Facility-wide Emission Units] 22

1.0 Emission Units and Active R13, R14, and R19 Permits

1.1 Emission Units

Emission Unit ID	Emission Point ID	Emission Unit Description	Year Installed	Design Capacity	Control Device
EU02	EP02	End Saw System	2008	2 tph	Fabric Filter
EU03	EP03	Dunnage Machine	2008	2 tph	Fabric Filter
EU05	EP05	Cage Mill DSG Dryer	2007	50 mmbtu/hr	Fabric Filter
EU06	EP06	Cage Mill Feed Silo	2007	200 tons	Fabric Filter
EU07	EP07	DSG Conveying Equipment	2008	120 tph	Fabric Filter Full Enclosure
EU08	EP08	#1 Intermediate DSG Silo	2007	186 tons	Fabric Filter
EU12	EP12	K10 Kettle	2008	31.7 mmbtu/hr	Fabric Filter
EU13	EP13	K20 Kettle	2008	31.7 mmbtu/hr	Fabric Filter
EU14	EP14	Stucco Cooler	2008	88 tph	Fabric Filter
EU16	EP16	HRA DSG Silo	2007	2.61 tons/hr	Fabric Filter
EU17	EP17	HRA Dextrose Silo	2007	0.14 tons/hr	Fabric Filter
EU18	EP18	HRA Ball Mill System	2007	1.65 tph	Fabric Filter
EU20	EP20	Stucco Silo	2007	600 tons/hr	Fabric Filter
EU21	EP21	Mixer and Additives Storage	2007	96 tph	Fabric Filter
EU22	EP22	Stucco Metering Equipment	2008	96 tph	Fabric Filter
EU23	EP23	Intermediate Stucco Silo	2007	100 tons	Fabric Filter
EU24	EP24	Stucco Ball Mill	2008	67.2 tph	Fabric Filter
EU25	EP25	Starch Silo	2008	24.8 tph	Fabric Filter
EU27	EP27	Semi-Bulk Transfer Station Bin	2008	24.8 tons/hr	Fabric Filter
EU29	EP29	Boric Acid Feeder Bin	2007	3 tons/hr	Fabric Filter
EU30	EP30	Potash Feeder Bin	2007	6 tons/hr	Fabric Filter
EU31	EP31	Dextrose Feeder Bin	2007	2.5 tons/hr	Fabric Filter
EU33	EP33	Starch Feeder Bin	2007	2 tph	Fabric Filter
EU34	EP34	HRA Feeder Bin	2007	4 tph	Fabric Filter
EU36	EP36	Board Dryer	2007	147 mmbtu/hr	None

Emission Unit ID	Emission Point ID	Emission Unit Description	Year Installed	Design Capacity	Control Device
EU37	EP37	Two Paper Heaters	2007	1.9 mmbtu/hr (total)	None
EU39	Fugitive	Storage Piles	2007	6.83 acres (total)	None
EU40	Fugitive	Material Handling	2007	330-1100 tph	None
EU41	Fugitive	Haul Roads	2007	67,085 MPY	None
EU42	EP42	Foaming Agent Tank 01	2007	9500 Gallons	None
EU43	EP43	Foaming Agent Tank 02	2007	100 Gallons	None
EU44	EP44	K10 Kettle Supply Screw	2007	120 tph	Fabric Filter
EU45	EP45	K20 Kettle Bad Batch Return Screw	2007	22 tph	Fabric Filter
EU46	EP46	Stucco Cooler Bypass Screw #2	2007	88 tph	Fabric Filter
EU47	EP47	Cage Mill Cyclone Transfer Screw	2007	120 tph	Fabric Filter
EU48	EP48	K20 Kettle Transfer Screw	2007	120 tph	Fabric Filter
EU49	Fugitive	Inking Operations	2007	3.3 lb/hr	None
EU50	EP50	Ethylated Starch Silo	2013	5,000 ft ³	Fabric Filter
EU51	EP51	Ethylated Starch Feeder Bin	2013	1 ton/hr	Fabric Filter
EU52	EP52	Vermiculite Silo	2013	3,000 ft ³	Fabric Filter
EU53	EP53	Vermiculite Feeder Bin	2013	1 ton/hr	Fabric Filter

MPY – Miles per year

1.2. Active R13, R14, and R19 Permits

The underlying authority for any conditions from R13, R14, and/or R19 permits contained in this operating permit is cited using the original permit number (e.g. R13-1234). The current applicable version of such permit(s) is listed below.

Permit Number	Date of Issuance
R13-2656E	August 22, 2013
R13-2656F	August 14, 2017

2.0 General Conditions

2.1. Definitions

- 2.1.1. All references to the "West Virginia Air Pollution Control Act" or the "Air Pollution Control Act" mean those provisions contained in W.Va. Code §§ 22-5-1 to 22-5-18.
- 2.1.2. The "Clean Air Act" means those provisions contained in 42 U.S.C. §§ 7401 to 7671q, and regulations promulgated thereunder.
- 2.1.3. "Secretary" means the Secretary of the Department of Environmental Protection or such other person to whom the Secretary has delegated authority or duties pursuant to W.Va. Code §§ 22-1-6 or 22-1-8 (45CSR§30-2.12.). The Director of the Division of Air Quality is the Secretary's designated representative for the purposes of this permit.
- 2.1.4. Unless otherwise specified in a permit condition or underlying rule or regulation, all references to a "rolling yearly total" shall mean the sum of the monthly data, values or parameters being measured, monitored, or recorded, at any given time for the previous twelve (12) consecutive calendar months.

2.2. Acronyms

CAAA	Clean Air Act Amendments	NO_x	Nitrogen Oxides
CBI	Confidential Business Information	NSPS	New Source Performance Standards
CEM	Continuous Emission Monitor	PM	Particulate Matter
CES	Certified Emission Statement	PM₁₀	Particulate Matter less than 10µm in diameter
C.F.R. or CFR	Code of Federal Regulations	pph	Pounds per Hour
CO	Carbon Monoxide	ppm	Parts per Million
C.S.R. or CSR	Codes of State Rules	PSD	Prevention of Significant Deterioration
DAQ	Division of Air Quality	psi	Pounds per Square Inch
DEP	Department of Environmental Protection	SIC	Standard Industrial Classification
FOIA	Freedom of Information Act	SIP	State Implementation Plan
HAP	Hazardous Air Pollutant	SO₂	Sulfur Dioxide
HON	Hazardous Organic NESHAP	TAP	Toxic Air Pollutant
HP	Horsepower	TPY	Tons per Year
lbs/hr or lb/hr	Pounds per Hour	TRS	Total Reduced Sulfur
LDAR	Leak Detection and Repair	TSP	Total Suspended Particulate
m	Thousand	USEPA	United States Environmental Protection Agency
MACT	Maximum Achievable Control Technology	UTM	Universal Transverse Mercator
mm	Million	VEE	Visual Emissions Evaluation
mmBtu/hr	Million British Thermal Units per Hour	VOC	Volatile Organic Compounds
mmft³/hr or mmcf/hr	Million Cubic Feet Burned per Hour		
NA or N/A	Not Applicable		
NAAQS	National Ambient Air Quality Standards		
NESHAPS	National Emissions Standards for Hazardous Air Pollutants		

2.3. Permit Expiration and Renewal

- 2.3.1. Permit duration. This permit is issued for a fixed term of five (5) years and shall expire on the date specified on the cover of this permit, except as provided in 45CSR§30-6.3.b. and 45CSR§30-6.3.c.
[45CSR§30-5.1.b.]
- 2.3.2. A permit renewal application is timely if it is submitted at least six (6) months prior to the date of permit expiration.
[45CSR§30-4.1.a.3.]
- 2.3.3. Permit expiration terminates the source's right to operate unless a timely and complete renewal application has been submitted consistent with 45CSR§30-6.2. and 45CSR§30-4.1.a.3.
[45CSR§30-6.3.b.]
- 2.3.4. If the Secretary fails to take final action to deny or approve a timely and complete permit application before the end of the term of the previous permit, the permit shall not expire until the renewal permit has been issued or denied, and any permit shield granted for the permit shall continue in effect during that time.
[45CSR§30-6.3.c.]

2.4. Permit Actions

- 2.4.1. This permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay any permit condition.
[45CSR§30-5.1.f.3.]

2.5. Reopening for Cause

- 2.5.1. This permit shall be reopened and revised under any of the following circumstances:
 - a. Additional applicable requirements under the Clean Air Act or the Secretary's legislative rules become applicable to a major source with a remaining permit term of three (3) or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which the permit is due to expire, unless the original permit or any of its terms and conditions has been extended pursuant to 45CSR§§30-6.6.a.1.A. or B.
 - b. Additional requirements (including excess emissions requirements) become applicable to an affected source under Title IV of the Clean Air Act (Acid Deposition Control) or other legislative rules of the Secretary. Upon approval by U.S. EPA, excess emissions offset plans shall be incorporated into the permit.
 - c. The Secretary or U.S. EPA determines that the permit contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of the permit.
 - d. The Secretary or U.S. EPA determines that the permit must be revised or revoked and reissued to assure compliance with the applicable requirements.

[45CSR§30-6.6.a.]

2.6. Administrative Permit Amendments

- 2.6.1. The permittee may request an administrative permit amendment as defined in and according to the procedures specified in 45CSR§30-6.4.
[45CSR§30-6.4.]

2.7. Minor Permit Modifications

- 2.7.1. The permittee may request a minor permit modification as defined in and according to the procedures specified in 45CSR§30-6.5.a.
[45CSR§30-6.5.a.]

2.8. Significant Permit Modification

- 2.8.1. The permittee may request a significant permit modification, in accordance with 45CSR§30-6.5.b., for permit modifications that do not qualify for minor permit modifications or as administrative amendments.
[45CSR§30-6.5.b.]

2.9. Emissions Trading

- 2.9.1. No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading, and other similar programs or processes for changes that are provided for in the permit and that are in accordance with all applicable requirements.
[45CSR§30-5.1.h.]

2.10. Off-Permit Changes

- 2.10.1. Except as provided below, a facility may make any change in its operations or emissions that is not addressed nor prohibited in its permit and which is not considered to be construction nor modification under any rule promulgated by the Secretary without obtaining an amendment or modification of its permit. Such changes shall be subject to the following requirements and restrictions:
- a. The change must meet all applicable requirements and may not violate any existing permit term or condition.
 - b. The permittee must provide a written notice of the change to the Secretary and to U.S. EPA within two (2) business days following the date of the change. Such written notice shall describe each such change, including the date, any change in emissions, pollutants emitted, and any applicable requirement that would apply as a result of the change.
 - c. The change shall not qualify for the permit shield.
 - d. The permittee shall keep records describing all changes made at the source that result in emissions of regulated air pollutants, but not otherwise regulated under the permit, and the emissions resulting from those changes.
 - e. No permittee may make any change subject to any requirement under Title IV of the Clean Air Act (Acid Deposition Control) pursuant to the provisions of 45CSR§30-5.9.

- f. No permittee may make any changes which would require preconstruction review under any provision of Title I of the Clean Air Act (including 45CSR14 and 45CSR19) pursuant to the provisions of 45CSR§30-5.9.

[45CSR§30-5.9.]

2.11. Operational Flexibility

- 2.11.1. The permittee may make changes within the facility as provided by § 502(b)(10) of the Clean Air Act. Such operational flexibility shall be provided in the permit in conformance with the permit application and applicable requirements. No such changes shall be a modification under any rule or any provision of Title I of the Clean Air Act (including 45CSR14 and 45CSR19) promulgated by the Secretary in accordance with Title I of the Clean Air Act and the change shall not result in a level of emissions exceeding the emissions allowable under the permit.

[45CSR§30-5.8]

- 2.11.2. Before making a change under 45CSR§30-5.8., the permittee shall provide advance written notice to the Secretary and to U.S. EPA, describing the change to be made, the date on which the change will occur, any changes in emissions, and any permit terms and conditions that are affected. The permittee shall thereafter maintain a copy of the notice with the permit, and the Secretary shall place a copy with the permit in the public file. The written notice shall be provided to the Secretary and U.S. EPA at least seven (7) days prior to the date that the change is to be made, except that this period may be shortened or eliminated as necessary for a change that must be implemented more quickly to address unanticipated conditions posing a significant health, safety, or environmental hazard. If less than seven (7) days notice is provided because of a need to respond more quickly to such unanticipated conditions, the permittee shall provide notice to the Secretary and U.S. EPA as soon as possible after learning of the need to make the change.

[45CSR§30-5.8.a.]

- 2.11.3. The permit shield shall not apply to changes made under 45CSR§30-5.8., except those provided for in 45CSR§30-5.8.d. However, the protection of the permit shield will continue to apply to operations and emissions that are not affected by the change, provided that the permittee complies with the terms and conditions of the permit applicable to such operations and emissions. The permit shield may be reinstated for emissions and operations affected by the change:

- a. If subsequent changes cause the facility's operations and emissions to revert to those authorized in the permit and the permittee resumes compliance with the terms and conditions of the permit, or
- b. If the permittee obtains final approval of a significant modification to the permit to incorporate the change in the permit.

[45CSR§30-5.8.c.]

- 2.11.4. "Section 502(b)(10) changes" are changes that contravene an express permit term. Such changes do not include changes that would violate applicable requirements or contravene enforceable permit terms and conditions that are monitoring (including test methods), recordkeeping, reporting, or compliance certification requirements.

[45CSR§30-2.39]

2.12. Reasonably Anticipated Operating Scenarios

- 2.12.1. The following are terms and conditions for reasonably anticipated operating scenarios identified in this permit.
- a. Contemporaneously with making a change from one operating scenario to another, the permittee shall record in a log at the permitted facility a record of the scenario under which it is operating and to document the change in reports submitted pursuant to the terms of this permit and 45CSR30.
 - b. The permit shield shall extend to all terms and conditions under each such operating scenario; and
 - c. The terms and conditions of each such alternative scenario shall meet all applicable requirements and the requirements of 45CSR30.

[45CSR§30-5.1.i.]

2.13. Duty to Comply

- 2.13.1. The permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the West Virginia Code and the Clean Air Act and is grounds for enforcement action by the Secretary or USEPA; for permit termination, revocation and reissuance, or modification; or for denial of a permit renewal application.

[45CSR§30-5.1.f.1.]

2.14. Inspection and Entry

- 2.14.1. The permittee shall allow any authorized representative of the Secretary, upon the presentation of credentials and other documents as may be required by law, to perform the following:
- a. At all reasonable times (including all times in which the facility is in operation) enter upon the permittee's premises where a source is located or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
 - b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
 - c. Inspect at reasonable times (including all times in which the facility is in operation) any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under the permit;
 - d. Sample or monitor at reasonable times substances or parameters to determine compliance with the permit or applicable requirements or ascertain the amounts and types of air pollutants discharged.

[45CSR§30-5.3.b.]

2.15. Schedule of Compliance

- 2.15.1. For sources subject to a compliance schedule, certified progress reports shall be submitted consistent with the applicable schedule of compliance set forth in this permit and 45CSR§30-4.3.h., but at least every six (6) months, and no greater than once a month, and shall include the following:
- a. Dates for achieving the activities, milestones, or compliance required in the schedule of compliance, and dates when such activities, milestones or compliance were achieved; and
 - b. An explanation of why any dates in the schedule of compliance were not or will not be met, and any preventative or corrective measure adopted.

[45CSR§30-5.3.d.]

2.16. Need to Halt or Reduce Activity not a Defense

- 2.16.1. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit. However, nothing in this paragraph shall be construed as precluding consideration of a need to halt or reduce activity as a mitigating factor in determining penalties for noncompliance if the health, safety, or environmental impacts of halting or reducing operations would be more serious than the impacts of continued operations.

[45CSR§30-5.1.f.2.]

2.17. Emergency

- 2.17.1. An "emergency" means any situation arising from sudden and reasonably unforeseeable events beyond the control of the source, including acts of God, which situation requires immediate corrective action to restore normal operation, and that causes the source to exceed a technology-based emission limitation under the permit, due to unavoidable increases in emissions attributable to the emergency. An emergency shall not include noncompliance to the extent caused by improperly designed equipment, lack of preventative maintenance, careless or improper operation, or operator error.

[45CSR§30-5.7.a.]

- 2.17.2. Effect of any emergency. An emergency constitutes an affirmative defense to an action brought for noncompliance with such technology-based emission limitations if the conditions of 45CSR§30-5.7.c. are met.

[45CSR§30-5.7.b.]

- 2.17.3. The affirmative defense of emergency shall be demonstrated through properly signed, contemporaneous operating logs, or other relevant evidence that:

- a. An emergency occurred and that the permittee can identify the cause(s) of the emergency;
- b. The permitted facility was at the time being properly operated;
- c. During the period of the emergency the permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards, or other requirements in the permit; and

- d. Subject to the requirements of 45CSR§30-5.1.c.3.C.1, the permittee submitted notice of the emergency to the Secretary within one (1) working day of the time when emission limitations were exceeded due to the emergency and made a request for variance, and as applicable rules provide. This notice, report, and variance request fulfills the requirement of 45CSR§30-5.1.c.3.B. This notice must contain a detailed description of the emergency, any steps taken to mitigate emissions, and corrective actions taken.

[45CSR§30-5.7.c.]

- 2.17.4. In any enforcement proceeding, the permittee seeking to establish the occurrence of an emergency has the burden of proof.

[45CSR§30-5.7.d.]

- 2.17.5. This provision is in addition to any emergency or upset provision contained in any applicable requirement.

[45CSR§30-5.7.e.]

2.18. Federally-Enforceable Requirements

- 2.18.1. All terms and conditions in this permit, including any provisions designed to limit a source's potential to emit and excepting those provisions that are specifically designated in the permit as "State-enforceable only", are enforceable by the Secretary, USEPA, and citizens under the Clean Air Act.

[45CSR§30-5.2.a.]

- 2.18.2. Those provisions specifically designated in the permit as "State-enforceable only" shall become "Federally-enforceable" requirements upon SIP approval by the USEPA.

2.19. Duty to Provide Information

- 2.19.1. The permittee shall furnish to the Secretary within a reasonable time any information the Secretary may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Secretary copies of records required to be kept by the permittee. For information claimed to be confidential, the permittee shall furnish such records to the Secretary along with a claim of confidentiality in accordance with 45CSR31. If confidential information is to be sent to USEPA, the permittee shall directly provide such information to USEPA along with a claim of confidentiality in accordance with 40 C.F.R. Part 2.

[45CSR§30-5.1.f.5.]

2.20. Duty to Supplement and Correct Information

- 2.20.1. Upon becoming aware of a failure to submit any relevant facts or a submittal of incorrect information in any permit application, the permittee shall promptly submit to the Secretary such supplemental facts or corrected information.

[45CSR§30-4.2.]

2.21. Permit Shield

2.21.1. Compliance with the conditions of this permit shall be deemed compliance with any applicable requirements as of the date of permit issuance provided that such applicable requirements are included and are specifically identified in this permit or the Secretary has determined that other requirements specifically identified are not applicable to the source and this permit includes such a determination or a concise summary thereof.

[45CSR§30-5.6.a.]

2.21.2. Nothing in this permit shall alter or affect the following:

- a. The liability of an owner or operator of a source for any violation of applicable requirements prior to or at the time of permit issuance; or
- b. The applicable requirements of the Code of West Virginia and Title IV of the Clean Air Act (Acid Deposition Control), consistent with § 408 (a) of the Clean Air Act.
- c. The authority of the Administrator of U.S. EPA to require information under § 114 of the Clean Air Act or to issue emergency orders under § 303 of the Clean Air Act.

[45CSR§30-5.6.c.]

2.22. Credible Evidence

2.22.1. Nothing in this permit shall alter or affect the ability of any person to establish compliance with, or a violation of, any applicable requirement through the use of credible evidence to the extent authorized by law. Nothing in this permit shall be construed to waive any defenses otherwise available to the permittee including but not limited to any challenge to the credible evidence rule in the context of any future proceeding.

[45CSR§30-5.3.e.3.B. and 45CSR38]

2.23. Severability

2.23.1. The provisions of this permit are severable. If any provision of this permit, or the application of any provision of this permit to any circumstance is held invalid by a court of competent jurisdiction, the remaining permit terms and conditions or their application to other circumstances shall remain in full force and effect.

[45CSR§30-5.1.e.]

2.24. Property Rights

2.24.1. This permit does not convey any property rights of any sort or any exclusive privilege.

[45CSR§30-5.1.f.4]

2.25. Acid Deposition Control

- 2.25.1. Emissions shall not exceed any allowances that the source lawfully holds under Title IV of the Clean Air Act (Acid Deposition Control) or rules of the Secretary promulgated thereunder.
- a. No permit revision shall be required for increases in emissions that are authorized by allowances acquired pursuant to the acid deposition control program, provided that such increases do not require a permit revision under any other applicable requirement.
 - b. No limit shall be placed on the number of allowances held by the source. The source may not, however, use allowances as a defense to noncompliance with any other applicable requirement.
 - c. Any such allowance shall be accounted for according to the procedures established in rules promulgated under Title IV of the Clean Air Act.

[45CSR§30-5.1.d.]

- 2.25.2. Where applicable requirements of the Clean Air Act are more stringent than any applicable requirement of regulations promulgated under Title IV of the Clean Air Act (Acid Deposition Control), both provisions shall be incorporated into the permit and shall be enforceable by the Secretary and U. S. EPA.

[45CSR§30-5.1.a.2.]

3.0. Facility-Wide Requirements

3.1. Limitations and Standards

- 3.1.1. **Open burning.** The open burning of refuse by any person is prohibited except as noted in 45CSR§6-3.1. [45CSR§6-3.1.]
- 3.1.2. **Open burning exemptions.** The exemptions listed in 45CSR§6-3.1 are subject to the following stipulation: Upon notification by the Secretary, no person shall cause or allow any form of open burning during existing or predicted periods of atmospheric stagnation. Notification shall be made by such means as the Secretary may deem necessary and feasible. [45CSR§6-3.2.]
- 3.1.3. **Asbestos.** The permittee is responsible for thoroughly inspecting the facility, or part of the facility, prior to commencement of demolition or renovation for the presence of asbestos and complying with 40 C.F.R. § 61.145, 40 C.F.R. § 61.148, and 40 C.F.R. § 61.150. The permittee, owner, or operator must notify the Secretary at least ten (10) working days prior to the commencement of any asbestos removal on the forms prescribed by the Secretary if the permittee is subject to the notification requirements of 40 C.F.R. § 61.145(b)(3)(i). The USEPA, the Division of Waste Management and the Bureau for Public Health - Environmental Health require a copy of this notice to be sent to them. [40 C.F.R. §61.145(b) and 45CSR34]
- 3.1.4. **Odor.** No person shall cause, suffer, allow or permit the discharge of air pollutants which cause or contribute to an objectionable odor at any location occupied by the public. [45CSR§4-3.1 State-Enforceable only.]
- 3.1.5. **Standby plan for reducing emissions.** When requested by the Secretary, the permittee shall prepare standby plans for reducing the emissions of air pollutants in accordance with the objectives set forth in Tables I, II, and III of 45CSR11. [45CSR§11-5.2]
- 3.1.6. **Emission inventory.** The permittee is responsible for submitting, on an annual basis, an emission inventory in accordance with the submittal requirements of the Division of Air Quality. [W.Va. Code § 22-5-4(a)(14)]
- 3.1.7. **Ozone-depleting substances.** For those facilities performing maintenance, service, repair or disposal of appliances, the permittee shall comply with the standards for recycling and emissions reduction pursuant to 40 C.F.R. Part 82, Subpart F, except as provided for Motor Vehicle Air Conditioners (MVACs) in Subpart B:
- a. Persons opening appliances for maintenance, service, repair, or disposal must comply with the prohibitions and required practices pursuant to 40 C.F.R. §§ 82.154 and 82.156.
 - b. Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 C.F.R. § 82.158.
 - c. Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 C.F.R. § 82.161.

[40 C.F.R. 82, Subpart F]

- 3.1.8. **Risk Management Plan.** Should this stationary source, as defined in 40 C.F.R. § 68.3, become subject to Part 68, then the owner or operator shall submit a risk management plan (RMP) by the date specified in 40 C.F.R. § 68.10 and shall certify compliance with the requirements of Part 68 as part of the annual compliance certification as required by 40 C.F.R. Part 70 or 71.
[40 C.F.R. 68]

3.2. Monitoring Requirements

- 3.2.1. Reserved.

3.3. Testing Requirements

- 3.3.1. **Stack testing.** As per provisions set forth in this permit or as otherwise required by the Secretary, in accordance with the West Virginia Code, underlying regulations, permits and orders, the permittee shall conduct test(s) to determine compliance with the emission limitations set forth in this permit and/or established or set forth in underlying documents. The Secretary, or his duly authorized representative, may at his option witness or conduct such test(s). Should the Secretary exercise his option to conduct such test(s), the operator shall provide all necessary sampling connections and sampling ports to be located in such manner as the Secretary may require, power for test equipment and the required safety equipment, such as scaffolding, railings and ladders, to comply with generally accepted good safety practices. Such tests shall be conducted in accordance with the methods and procedures set forth in this permit or as otherwise approved or specified by the Secretary in accordance with the following:
- a. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with 40 C.F.R. Parts 60, 61, and 63, if applicable, in accordance with the Secretary's delegated authority and any established equivalency determination methods which are applicable.
 - b. The Secretary may on a source-specific basis approve or specify additional testing or alternative testing to the test methods specified in the permit for demonstrating compliance with applicable requirements which do not involve federal delegation. In specifying or approving such alternative testing to the test methods, the Secretary, to the extent possible, shall utilize the same equivalency criteria as would be used in approving such changes under Section 3.3.1.a. of this permit.
 - c. All periodic tests to determine mass emission limits from or air pollutant concentrations in discharge stacks and such other tests as specified in this permit shall be conducted in accordance with an approved test protocol. Unless previously approved, such protocols shall be submitted to the Secretary in writing at least thirty (30) days prior to any testing and shall contain the information set forth by the Secretary. In addition, the permittee shall notify the Secretary at least fifteen (15) days prior to any testing so the Secretary may have the opportunity to observe such tests. This notification shall include the actual date and time during which the test will be conducted and, if appropriate, verification that the tests will fully conform to a referenced protocol previously approved by the Secretary.

- d. The permittee shall submit a report of the results of the stack test within 60 days of completion of the test. The test report shall provide the information necessary to document the objectives of the test and to determine whether proper procedures were used to accomplish these objectives. The report shall include the following: the certification described in paragraph 3.5.1; a statement of compliance status, also signed by a responsible official; and, a summary of conditions which form the basis for the compliance status evaluation. The summary of conditions shall include the following:
 1. The permit or rule evaluated, with the citation number and language.
 2. The result of the test for each permit or rule condition.
 3. A statement of compliance or non-compliance with each permit or rule condition.

[WV Code § 22-5-4(a)(14-15) and 45CSR13; 45CSR§7-8.1.; 45CSR13, R13-2656, 3.3.1.]

3.4. Recordkeeping Requirements

- 3.4.1. **Monitoring information.** The permittee shall keep records of monitoring information that include the following:
 - a. The date, place as defined in this permit and time of sampling or measurements;
 - b. The date(s) analyses were performed;
 - c. The company or entity that performed the analyses;
 - d. The analytical techniques or methods used;
 - e. The results of the analyses; and
 - f. The operating conditions existing at the time of sampling or measurement.

[45CSR§30-5.1.c.2.A.] [45CSR13, R13-2656, 4.2.6.]

- 3.4.2. **Retention of records.** The permittee shall retain records of all required monitoring data and support information for a period of at least five (5) years from the date of monitoring sample, measurement, report, application, or record creation date. Support information includes all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by the permit. Where appropriate, records may be maintained in computerized form in lieu of the above records.

[45CSR§30-5.1.c.2.B.] [45CSR13, R13-2656, 3.4.1.]

- 3.4.3. **Odors.** For the purposes of 45CSR4, the permittee shall maintain a record of all odor complaints received, any investigation performed in response to such a complaint, and any responsive action(s) taken.

[45CSR§30-5.1.c. State-Enforceable only.] [45CSR13, R13-2656, 3.4.2.]

3.4.4. **Record of Maintenance of Air Pollution Control Equipment.** For all pollution control equipment listed in Section 1.0, the permittee shall maintain accurate records of all required pollution control equipment inspection and/or preventative maintenance procedures.
[45CSR13, R13-2656, 4.2.7.]

3.4.5. **Record of Malfunctions of Air Pollution Control Equipment.** For all air pollution control equipment listed in Section 1.0, the permittee shall maintain records of the occurrence and duration of any malfunction or operational shutdown of the air pollution control equipment during which excess emissions occur. For each such case, the following information shall be recorded:

- a. The equipment involved.
- b. Steps taken to minimize emissions during the event.
- c. The duration of the event.
- d. The estimated increase in emissions during the event.

For each such case associated with an equipment malfunction, the additional information shall also be recorded:

- e. The cause of the malfunction.
- f. Steps taken to correct the malfunction.
- g. Any changes or modifications to equipment or procedures that would help prevent future recurrences of the malfunction.

[45CSR13, R13-2656, 4.2.8.]

3.5. Reporting Requirements

3.5.1. **Responsible official.** Any application form, report, or compliance certification required by this permit to be submitted to the DAQ and/or USEPA shall contain a certification by the responsible official that states that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate and complete.
[45CSR§§30-4.4. and 5.1.c.3.D.]

3.5.2. A permittee may request confidential treatment for the submission of reporting required under 45CSR§30-5.1.c.3. pursuant to the limitations and procedures of W.Va. Code § 22-5-10 and 45CSR31.
[45CSR§30-5.1.c.3.E.]

3.5.3. Except for the electronic submittal of the annual [compliance](#) certification [and semi-annual monitoring reports](#) to the [DAQ and USEPA](#) as required in 3.5.5 [and 3.5.6](#) below, all notices, requests, demands, submissions and other communications required or permitted to be made to the Secretary of DEP and/or USEPA shall be made in writing and shall be deemed to have been duly given when delivered by hand, [or](#) mailed first class or by private carrier with postage prepaid to the address(es), [or submitted in electronic format by e-mail as](#) set forth below or to such other person or address as the Secretary of the Department of Environmental Protection may designate:

If to the DAQ:

Director
WVDEP
Division of Air Quality
601 57th Street SE
Charleston, WV 25304
~~Phone: 304/926-0475~~
FAX: 304/926-0478

If to the US EPA:

Associate Director
Office of Air Enforcement and Compliance
Assistance (3AP20)
U. S. Environmental Protection Agency
Region III
1650 Arch Street
Philadelphia, PA 19103-2029

DAQ Compliance and Enforcement¹:

DEPAirQualityReports@wv.gov

¹[For all self-monitoring reports \(MACT, GACT, NSPS, etc.\), stack tests and protocols, Notice of Compliance Status reports, Initial Notifications, etc.](#)

- 3.5.4. **Certified emissions statement.** The permittee shall submit a certified emissions statement and pay fees on an annual basis in accordance with the submittal requirements of the Division of Air Quality. **[45CSR§30-8.]**

- 3.5.5. **Compliance certification.** The permittee shall certify compliance with the conditions of this permit on the forms provided by the DAQ. In addition to the annual compliance certification, the permittee may be required to submit certifications more frequently under an applicable requirement of this permit. The annual certification shall be submitted to the DAQ and USEPA on or before March 15 of each year, and shall certify compliance for the period ending December 31. ~~The annual certification to the USEPA shall be submitted in electronic format only. It shall be submitted by e-mail to the following address: R3_APD_Permits@epa.gov.~~ The permittee shall maintain a copy of the certification on site for five (5) years from submittal of the certification. [The annual certification shall be submitted in electronic format by e-mail to the following addresses:](#)

DAQ:

DEPAirQualityReports@wv.gov

US EPA:

R3_APD_Permits@epa.gov

[45CSR§30-5.3.e.]

- 3.5.6. **Semi-annual monitoring reports.** The permittee shall submit reports of any required monitoring on or before September 15 for the reporting period January 1 to June 30 and on or before March 15 for the reporting period July 1 to December 31. All instances of deviation from permit requirements must be clearly identified in such reports. All required reports must be certified by a responsible official consistent with 45CSR§30-4.4. [The semi-annual monitoring reports shall be submitted in electronic format by e-mail to the following address:](#)

DAQ:

DEPAirQualityReports@wv.gov

[45CSR§30-5.1.c.3.A.]

3.5.7. **Emergencies.** For reporting emergency situations, refer to Section 2.17 of this permit.

3.5.8. **Deviations.**

- a. In addition to monitoring reports required by this permit, the permittee shall promptly submit supplemental reports and notices in accordance with the following:
 1. Any deviation resulting from an emergency or upset condition, as defined in 45CSR§30-5.7., shall be reported by telephone or telefax within one (1) working day of the date on which the permittee becomes aware of the deviation, if the permittee desires to assert the affirmative defense in accordance with 45CSR§30-5.7. A written report of such deviation, which shall include the probable cause of such deviations, and any corrective actions or preventative measures taken, shall be submitted and certified by a responsible official within ten (10) days of the deviation.
 2. Any deviation that poses an imminent and substantial danger to public health, safety, or the environment shall be reported to the Secretary immediately by telephone or telefax. A written report of such deviation, which shall include the probable cause of such deviation, and any corrective actions or preventative measures taken, shall be submitted by the responsible official within ten (10) days of the deviation.
 3. Deviations for which more frequent reporting is required under this permit shall be reported on the more frequent basis.
 4. All reports of deviations shall identify the probable cause of the deviation and any corrective actions or preventative measures taken.

[45CSR§30-5.1.c.3.C.]

- b. The permittee shall, in the reporting of deviations from permit requirements, including those attributable to upset conditions as defined in this permit, report the probable cause of such deviations and any corrective actions or preventive measures taken in accordance with any rules of the Secretary.

[45CSR§30-5.1.c.3.B.]

3.5.9. **New applicable requirements.** If any applicable requirement is promulgated during the term of this permit, the permittee will meet such requirements on a timely basis, or in accordance with a more detailed schedule if required by the applicable requirement.

[45CSR§30-4.3.h.1.B.]

3.6. Compliance Plan

3.6.1. Reserved.

3.7. Permit Shield

- 3.7.1. The permittee is hereby granted a permit shield in accordance with 45CSR§30-5.6. The permit shield applies provided the permittee operates in accordance with the information contained within this permit.
- 3.7.2. The following requirements specifically identified are not applicable to the source based on the determinations set forth below. The permit shield shall apply to the following requirements provided the conditions of the determinations are met.
- a. **45CSR2 – To Prevent and Control Particulate Air Pollution from Combustion of Fuel in Indirect Heat Exchangers.** This rule applies to fuel burning units that operate as indirect heat exchangers. Since the DSG cage mill system, kettles, paper heaters, and board dryer are all direct heat transfer units, these units are not subject to 45CSR2 as they are not classified as fuel burning units. In addition, the Stucco Cooler (EU14) does not meet the definition of a fuel burning unit since there is no combustion associated with it. This determination applies to the following sources: Cage Mill DSG Dryer (EU05), K10 Kettle (EU12), K20 Kettle (EU13), Board Dryer (EU36), Two Paper Heaters (EU37), and Stucco Cooler (EU14).
 - b. **40 C.F.R. Part 64 Compliance Assurance Monitoring (CAM).** The facility utilizes a number of baghouses; however, these baghouses are an integral part of the material transfer and separation process and are not considered air pollution control devices for purposes of meeting an emission limitation. All of the material collected by the baghouses is reintroduced into the process. In addition, the bin vent filters used at the facility are integrated into the bins they serve and operate passively to capture material in displacement air and return it to the storage bin. Therefore, because the baghouses and bin vent filters are for product recovery and are thereby inherent process equipment as defined in 40 C.F.R §64.1, they are not considered control devices with respect to CAM and this regulation does not apply.

4.0. Source-Specific Requirements [Facility-wide Emission Units; EU02, EU03, EU05-EU08, EU05, EU06, EU08, EU12-EU14, EU16-EU18, EU20-EU25, EU27, EU29-EU31, EU33, EU34, EU36, EU37, EU40, EU42-EU53]

4.1. Limitations and Standards

4.1.1. Point Source emissions from the facility shall not exceed the following:

Source	PM _{2.5}		PM ₁₀ ³		NO _x		CO		SO ₂		VOC		HAPs ⁴	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
EU02	0.99	4.32	1.97	8.63	--	--	--	--	--	--	--	--	--	--
EU03	0.3	1.31	0.60	2.63	--	--	--	--	--	--	--	--	--	--
EU05	6.0	26.3	6.0	26.3	2.29	10.1	2.65	11.6	0.03	0.13	0.27	1.18	0.09	0.40
EU06	0.12	0.51	0.23	1.01	--	--	--	--	--	--	--	--	--	--
EU07	0.39	1.72	0.79	3.44	--	--	--	--	--	--	--	--	--	--
EU08	0.07	0.28	0.13	0.57	--	--	--	--	--	--	--	--	--	--
EU12	3.23	14.1	3.23	14.1	6.80	29.8	25.62	112.22	0.02	0.08	0.17	0.75	0.06	0.26
EU13	3.23	14.1	3.23	14.1	6.80	29.8	25.62	112.22	0.02	0.08	0.17	0.75	0.06	0.26
EU14	0.09	0.38	0.17	0.75	--	--	--	--	--	--	--	--	--	--
EU16	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU17	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU18	0.26	1.15	0.52	2.30	--	--	--	--	--	--	--	--	--	--
EU20	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU21	0.05	0.22	0.10	0.44	--	--	--	--	--	--	--	--	--	--
EU22	0.11	0.5	0.23	0.99	--	--	--	--	--	--	--	--	--	--
EU23	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU24	0.15	0.66	0.30	1.33	--	--	--	--	--	--	--	--	--	--
EU25	0.06	0.27	0.12	0.53	--	--	--	--	--	--	--	--	--	--
EU27	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU29	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU30	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU31	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU33	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--

EU34	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
Source	PM _{2.5}		PM ₁₀ ³		NO _x		CO		SO ₂		VOC		HAPs ⁴	
	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy	lb/hr	tpy
EU36 ¹	2.15	9.4	2.15	9.4	4.65	20.4	13.9	60.8	0.07	0.3	14.3	62.5	0.22	1.0
EU36 ²	32.03	19.32	32.03	19.32	3.01	13.2	10.4	45.4	0.02	0.1	0.18	0.8	0.05	0.2
	2.4		2.4											
EU37	0.02	0.07	0.02	0.07	0.18	0.76	0.08	0.33	0.01	0.01	0.01	0.05	0.01	0.02
EU40	0.55	2.4	3.41	14.9	--	--	--	--	--	--	--	--	--	--
EU42	--	--	--	--	--	--	--	--	--	--	0.01	0.01	--	--
EU43	--	--	--	--	--	--	--	--	--	--	0.01	0.01	--	--
EU44	0.01	0.04	0.02	0.08	--	--	--	--	--	--	--	--	--	--
EU45	0.01	0.04	0.02	0.08	--	--	--	--	--	--	--	--	--	--
EU46	0.01	0.04	0.02	0.08	--	--	--	--	--	--	--	--	--	--
EU47	0.01	0.04	0.02	0.08	--	--	--	--	--	--	--	--	--	--
EU48	0.01	0.04	0.02	0.08	--	--	--	--	--	--	--	--	--	--
EU49	--	--	--	--	--	--	--	--	--	--	3.0	13.0	--	--
EU50	0.06	0.27	0.12	0.53	--	--	--	--	--	--	--	--	--	--
EU51	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
EU52	0.06	0.27	0.12	0.53	--	--	--	--	--	--	--	--	--	--
EU53	0.03	0.11	0.05	0.22	--	--	--	--	--	--	--	--	--	--
Total	52.7	99.1	58.6	124.9	23.7	104.1	78.3	342.6	0.2	0.7	18.1	79.1	0.5	2.1

¹Zones 1 and 2

²Zone 3. High hourly PM_{2.5} and PM₁₀ apply when processing Moisture Resistant Board. Low hourly PM_{2.5} and PM₁₀ apply when processing Regular Board.

³All PM₁₀ emission limits are also total PM limits except for emissions from EU40.

⁴From combustion of natural gas only (excludes HAP emissions from additives, inks and foaming agents which are accounted for in condition 4.1.14).

[45CSR13, R13-2656, 4.1.1, 4.1.6; 45CSR§7-4.1.]

Note: Compliance with PM limits in section 4.1.1 shall show compliance with 45CSR§7-4.1.

4.1.2 Fugitive PM emissions from EU40 shall not exceed 7.06 pounds per hour nor 30.9 tons per year.
[45CSR13, R13-2656, 4.1.2.]

4.1.3 The facility shall burn only pipeline quality natural gas for fuel.
[45CSR13, R13-2656, 4.1.3.]

4.1.4 Natural gas usage by the entire facility shall not exceed 251.84 mscf per hour nor 2,206.12 mmscf per year.

[45CSR13, R13-2656, 4.1.4.]

- 4.1.5 No person shall cause, suffer, allow, or permit emissions of smoke and/or particulate matter into the open air from any process source operation greater than twenty (20) percent opacity, except as noted in subsections 3.2, 3.3, 3.4, 3.5, 3.6, and 3.7 of 45CSR7.

[45CSR13, R13-2656, 4.1.5; 45CSR§7-3.1]

- 4.1.6 a. No person shall circumvent the provisions of 45CSR7 by adding additional gas to any exhaust or group of exhausts for the purpose of reducing the stack gas concentration.

[45CSR§7-4.3]

- b. Any stack serving any process source operation or air pollution control equipment on any process source operation shall contain flow straightening devices or a vertical run of sufficient length to establish flow patterns consistent with acceptable stack sampling procedures.

[45CSR§7-4.12]

- 4.1.7 No person shall cause, suffer, allow or permit any manufacturing process or storage structure generating fugitive particulate matter to operate that is not equipped with a system, which may include, but not be limited to, process equipment design, control equipment design or operation and maintenance procedures, to minimize the emissions of fugitive particulate matter. To minimize means such system shall be installed, maintained and operated to ensure the lowest fugitive particulate matter emissions reasonably achievable.

[45CSR13, R13-2656, 4.1.7; 45CSR§7-5.1]

- 4.1.8 The owner or operator of a plant shall maintain particulate matter control of the plant premises, and plant owned, leased or controlled access roads, by paving, application of asphalt, chemical dust suppressants or other suitable dust control measures. Good operating practices shall be implemented and when necessary particulate matter suppressants shall be applied in relation to stockpiling and general material handling to minimize particulate matter generation and atmospheric entrainment.

[45CSR13, R13-2656, 4.1.8; 45CSR§7-5.2]

- 4.1.9. No person shall cause, suffer, allow or permit visible emissions from any storage structure(s) associated with any manufacturing process(es) that pursuant to condition 4.1.7 is required to have a full enclosure and be equipped with a particulate matter control device.

[45CSR§7-3.7] [EU06, EU08, EU16, EU17, EU20, EU21, EU23, EU25, EU27, EU30, EU31, EU34, E050, E051, EU52, EU53]

Note: This visible emissions standard applies only when the storage structure(s) is (are) holding materials and not when material is added or removed from the storage structure(s). Condition 4.1.5 applies when material is added into or removed from the storage structure(s).

- 4.1.10. (a) Affected facilities must meet the stack emission limits and compliance requirements in Table 2 of 40 C.F.R. 60 Subpart OOO within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under 40 C.F.R. §60.8. The requirements in Table 2 of 40 C.F.R. 60 Subpart OOO apply for affected facilities with capture systems used to capture and transport particulate matter to a control device.

[45CSR13, R13-2656, 4.1.9., 4.1.10, 4.1.11; 40 C.F.R. §60.672(a); 45CSR16] [EU05, EU06, ~~EU07~~, EU08, EU16, EU18, EU52, EU53]

Note: ~~EU05-EU08~~, [EU05](#), [EU06](#), [EU08](#), EU16 and EU18 have been tested.

- (b) Affected facilities must meet the fugitive emission limits and compliance requirements in Table 3 of 40 C.F.R. 60 Subpart OOO within **60** days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup as required under 40 C.F.R. §60.11. The requirements in Table 3 of 40 C.F.R. 60 Subpart OOO apply for fugitive emissions from affected facilities without capture systems and for fugitive emissions escaping capture systems.

[45CSR13, R13-2656, 4.1.9., 4.1.12; 40 C.F.R. §60.672(b); 45CSR16] [EU05, EU06, ~~EU07~~, EU08, EU16, EU18, EU52, EU53]

Note: ~~EU05-EU08~~, [EU05, EU06, EU08](#), EU16 and EU18 have been tested.

- (e) If any transfer point on a conveyor belt or any other affected facility is enclosed in a building, then each enclosed affected facility must comply with the emission limits in paragraphs (a) and (b) of this section, or the building enclosing the affected facility or facilities must comply with the following emission limits:
- (1) Fugitive emissions from the building openings (except for vents as defined in 40 C.F.R. §60.671) must not exceed 7 percent opacity; and
 - (2) Vents (as defined in 40 C.F.R. §60.671) in the building must meet the applicable stack emission limits and compliance requirements in Table 2 of 40 C.F.R. 60 Subpart OOO.

[45CSR13, R13-2656, 4.1.9., 4.1.13; 40 C.F.R. §60.672(e); 45CSR16] [EU05, EU06, ~~EU07~~, [DSG Conveying Equipment](#), EU08, EU16, EU18, EU52, EU53]

Note: Buildings enclosing ~~EU05-EU08~~, [EU05, EU06, EU08](#), EU16 and EU18 have been tested.

- (f) Any baghouse that controls emissions from only an individual, enclosed storage bin is exempt from the applicable stack PM concentration limit (and associated performance testing) in Table 2 of 40 C.F.R. 60 Subpart OOO but must meet the applicable stack opacity limit and compliance requirements in Table 2 of 40 C.F.R. 60 Subpart OOO. This exemption from the stack PM concentration limit does not apply for multiple storage bins with combined stack emissions.

[40 C.F.R. §60.672(f); 45CSR16] [EU52, EU53]

Table 2 to 40 C.F.R. 60 Subpart OOO—Stack Emission Limits for Affected Facilities With Capture Systems

For * * *	The owner or operator must meet a PM limit of * * *	And the owner or operator must meet an opacity limit of * * *	The owner or operator must demonstrate compliance with these limits by conducting * * *
Affected facilities (as defined in §§60.670 and 60.671) that commenced construction, modification, or reconstruction after August 31, 1983 but before April 22, 2008	0.05 g/dscm (0.022 gr/dscf) ^a	7 percent for dry control devices	N/A
Affected facilities (as defined in §§ 60.670 and 60.671) that commence construction, modification, or reconstruction on or after April 22, 2008	N/A ^a	7 percent for dry control devices on individual enclosed storage bins	Monitoring of baghouses according to § 60.674(c), (d), or (e) and § 60.676(b).

^aExceptions to the PM limit apply for individual enclosed storage bins and other equipment. See §60.672(d) through (f).

Table 3 to 40 C.F.R. 60 Subpart OOO—Fugitive Emission Limits

For * * *	The owner or operator must meet the following fugitive emissions limit for grinding mills, screening operations, bucket elevators, transfer points on belt conveyors, bagging operations, storage bins, enclosed truck or railcar loading stations or from any other affected facility (as defined in §§60.670 and 60.671) * * *	The owner or operator must meet the following fugitive emissions limit for crushers at which a capture system is not used * * *	The owner or operator must demonstrate compliance with these limits by conducting * * *
Affected facilities (as defined in §§60.670 and 60.671) that commenced construction, modification, or reconstruction after August 31, 1983 but before April 22, 2008	10 percent opacity	15 percent opacity	N/A
Affected facilities (as defined in §§ 60.670 and 60.671) that commence construction, modification, or reconstruction on or after April 22, 2008	7 percent opacity	N/A	An initial performance test according to § 60.11 of this part and § 60.675 of this subpart; and A repeat performance test according to § 60.11 of this part and § 60.675 of this subpart within 5 years from the previous performance test for fugitive emissions from affected facilities without water sprays.

- 4.1.11. Each owner or operator of any affected facility that is subject to the requirements of 40 C.F.R. 60 Subpart UUU shall comply with the emission limitations set forth in 40 C.F.R. §60.732 on and after the date on which the initial performance test required by 40 C.F.R. §60.8 is completed, but not later than 180 days after the initial startup, whichever date comes first. No emissions shall be discharged into the atmosphere from any affected facility that:
- (a) Contains particulate matter in excess of 0.092 gram per dry standard cubic meter (g/dscm) [0.040 grain per dry standard cubic foot (gr/dscf)] for calciners and for calciners and dryers installed in series and in excess of 0.057 g/dscm (0.025 gr/dscf) for dryers; and
 - (b) Exhibits greater than 10 percent opacity, unless the emissions are discharged from an affected facility using a wet scrubbing control device.
- [45CSR13, R13-2656, 4.1.14., 4.1.15, 4.1.16, 4.1.17, 4.1.18; 40 C.F.R. §60.732; 45CSR16] [EU12, EU13]**

4.1.12.1. The total number of Gypsum Supply and Finished Wallboard vehicle miles traveled* (combined) shall not exceed 35,098 miles per year based on a rolling 12 month total.

[45CSR13, R13-2656, 4.1.19.]

*as defined in facility's 45CSR13 permit application.

4.1.12.2. The total number of Paper vehicle miles traveled* shall not exceed 979 miles per year based on a rolling 12 month total.

[45CSR13, R13-2656, 4.1.20.]

*as defined in facility's 45CSR13 permit application.

4.1.12.3. The total number of miscellaneous raw material truck vehicle miles traveled* shall not exceed 489 miles per year based on a rolling 12 month total.

[45CSR13, R13-2656, 4.1.21.]

*as defined in facility's 45CSR13 permit application.

4.1.12.4. The total number of reject to reclaim truck vehicle miles traveled* shall not exceed 734 miles per year based on a rolling 12 month total.

[45CSR13, R13-2656, 4.1.22.]

*as defined in facility's 45CSR13 permit application.

4.1.12.5. The total number of reclaim to main process area truck vehicle miles traveled* shall not exceed 5,400 miles per year based on a rolling 12 month total.

[45CSR13, R13-2656, 4.1.23.]

*as defined in facility's 45CSR13 permit application.

4.1.13. The total annual VOC content of all inks, wet additives and foaming agents shall not exceed 75.5 tons per year based on a 12 month rolling total.

[45CSR13, R13-2656, 4.1.24.]

4.1.14. The total annual HAP content of all inks, wet additives and foaming agents shall not exceed 22.6 tons per year of all total HAPs nor 7.5 tons per year of any individual HAP based on a 12 month rolling total.

[45CSR13, R13-2656, 4.1.25.]

4.1.15. **Operation and Maintenance of Air Pollution Control Equipment.** The permittee shall, to the extent practicable, install, maintain, and operate all pollution control equipment listed in Section 1.0 and associated monitoring equipment in a manner consistent with safety and good air pollution control practices for minimizing emissions, or comply with any more stringent limits set forth in this permit or as set forth by any State rule, Federal regulation, or alternative control plan approved by the Secretary.

[45CSR13, R13-2656, 4.1.28] [45CSR§13-5.11]

4.1.16. No person shall cause, suffer, allow or permit the emission into the open air from any source operation an in-stack sulfur dioxide concentration exceeding 2,000 parts per million by volume from existing source operations.

[45CSR§10-4.1] [EU36]

Compliance with the allowable sulfur dioxide concentration limitations from manufacturing process source operation(s) set forth in 45CSR10 shall be based on a block three (3) hour averaging time.

[45CSR§10-4.2] [EU36]

- 4.1.17. The pressure drop across the baghouses shall be maintained between 0.5 and 6 in. H₂O.
[45CSR§30-12.7] [EU02, EU03, ~~EU05-08~~, EU05, EU06, EU08, EU12-14, EU16-18, EU20-25, EU27, EU29-31, EU33, EU34, EU44-48 and EU50-53]
- 4.1.18. The amount of recycled material introduced into Kettles K10 and K20 (EU12 & EU13) shall not exceed 7.7% of the total amount of material introduced.
[45CSR13, R13-2656, 4.1.26]
- 4.1.19. The Wallboard Dryer (EU36) shall not process “moisture resistant” board more than 594 hours per year based on a rolling 12 month total.
[45CSR13, R13-2656, 4.1.27]

4.2. Monitoring Requirements

- 4.2.1. The permittee shall monitor and record the pressure drop across all fabric filters on a weekly basis.
[45CSR13, R13-2656, 4.2.1.]
- 4.2.2. During any period of malfunction of any fabric filter (if any of the emission units associated with each station are in operation) a daily log of the following information shall be monitored and recorded:
- 4.2.2.1. Whether there were any visible emissions. If visible emissions are observed, the permittee shall record the following information:
- 4.2.2.1.1. Whether the visible emissions are normal for the process.
- 4.2.2.1.2. The cause of any abnormal emissions.
- 4.2.2.1.3. Any corrective action taken.
- 4.2.2.1.4. Document all routine and non-routine maintenance activities performed on the fabric filters.
[45CSR13, R13-2656, 4.2.2.]
- 4.2.3. The permittee shall monitor and record the quantity of all inks, wet additives and foaming agents used along with their VOC and HAP content.
[45CSR13, R13-2656, 4.2.3.]
- 4.2.4. The permittee shall monitor and record the number of gypsum supply, finished wallboard, paper, miscellaneous raw material, reject to reclaim and reclaim to main process area truck vehicle miles traveled* on a monthly basis.
[45CSR13, R13-2656, 4.2.4.]
*as defined in facility’s 45CSR13 permit application
- 4.2.5. For the purpose of determining compliance with the opacity limits of 4.1.5, 4.1.10, and 4.1.11, the permittee shall conduct visible emission checks and/or opacity monitoring and recordkeeping for all emission sources subject to an opacity limit.

The visible emission check shall determine the presence or absence of visible emissions. At a minimum, the observer must be trained and knowledgeable regarding the effects of background contrast, ambient lighting, observer position relative to lighting, wind, and the presence of uncombined water (condensing water vapor) on

the visibility of emissions. This training may be obtained from written materials found in the References 1 and 2 from 40CFR Part 60, Appendix A, Method 22 or from the lecture portion of the 40CFR Part 60, Appendix A, Method 9 certification course.

Visible emission checks shall be conducted at least once per calendar month with a maximum of forty-five (45) days between consecutive readings. These checks shall be performed at each source (stacks, conveyors, crushers, silos, bins, and screens) for a sufficient time interval, but no less than one (1) minute, to determine if any visible emissions are present. Visible emission checks shall be performed during periods of normal facility operation and appropriate weather conditions.

If visible emissions are present at a source(s) for six (6) consecutive monthly checks, the permittee shall conduct an opacity reading at that source(s) using the procedures and requirements of Method 9 as soon as practicable, but within seventy-two (72) hours of the final visual emission check. Method 9 checks shall be performed on the source for at least six (6) minutes. A Method 9 observation at a source(s) restarts the count of the number of consecutive readings with the presence of visible emissions.

[45CSR13, R13-2656, 4.2.5.] [45CSR§30-5.1.c.]

- 4.2.6. To show compliance with the VOC, individual HAP and total HAPs limits in Sections 4.1.13 and 4.1.14, monthly VOC, individual HAP and total HAPs emissions from foaming agents, inks and additives shall be calculated by the 15th day of the subsequent month.

A twelve month rolling total of emissions shall be maintained to verify compliance with the long term ton per year (TPY) emission limitations. Each month a new twelve month total shall be calculated using the previous twelve months data. Records indicating the twelve month rolling total emissions shall be maintained on site or at a reasonably available location. **[45CSR§30-5.1.c.]**

Compliance with above shall show compliance with Section 4.1.1 VOC limits for EU42, EU43 and EU49.

- 4.2.7. To show compliance with the PM₁₀ and PM_{2.5} limits for EU40 in Section 4.1.1, monthly PM₁₀ and PM_{2.5} emissions from EU40 shall be calculated using AP-42 factors by the 15th day of the subsequent month.

A twelve month rolling total of emissions shall be maintained to verify compliance with the long term ton per year (TPY) emission limitations. Each month a new twelve month total shall be calculated using the previous twelve months data. Records indicating the twelve month rolling total emissions shall be maintained on site or at a reasonably available location.

[45CSR§30-5.1.c.] [EU40]

- 4.2.8. To show compliance with the yearly natural gas usage limits in Section 4.1.4, monthly records of entire facility natural gas usage shall be maintained.

A twelve month rolling total of entire facility natural gas usage shall be maintained to verify compliance with the long term natural gas usage limitation. Each month a new twelve month total shall be calculated using the previous twelve months data. Records indicating the twelve month rolling total natural gas usage shall be maintained on site or at a reasonably available location.

[45CSR§30-5.1.c.]

- 4.2.9. In order to determine compliance with 4.1.18 of this permit, the permittee shall monitor and record the amount of recycle material, total material and resultant percentage of recycled material introduced into each kettle (EU12 & EU13) on a monthly basis.

[45CSR13, R13-2656, 4.2.9]

- 4.2.10. In order to determine compliance with 4.1.19 of this permit, the permittee shall monitor and record the number of hours each month that the Wall Board Dryer (EU36) processes moisture resistant board.

[45CSR13, R13-2656, 4.2.10]

4.2.11. (c) Except as specified in paragraph (d) or (e) of 40 C.F.R. §60.674, the owner or operator of any affected facility for which construction, modification, or reconstruction commenced on or after April 22, 2008, that uses a baghouse to control emissions must conduct quarterly 30-minute visible emissions inspections using EPA Method 22 (40 CFR part 60, Appendix A-7). The Method 22 (40 CFR part 60, Appendix A-7) test shall be conducted while the baghouse is operating. The test is successful if no visible emissions are observed. If any visible emissions are observed, the owner or operator of the affected facility must initiate corrective action within 24 hours to return the baghouse to normal operation. The owner or operator must record each Method 22 (40 CFR part 60, Appendix A-7) test, including the date and any corrective actions taken, in the logbook required under § 60.676(b). The owner or operator of the affected facility may establish a different baghouse-specific success level for the visible emissions test (other than no visible emissions) by conducting a PM performance test according to § 60.675(b) simultaneously with a Method 22 (40 CFR part 60, Appendix A-7) to determine what constitutes normal visible emissions from that affected facility's baghouse when it is in compliance with the applicable PM concentration limit in Table 2 of 40 C.F.R. 60 Subpart OOO. The revised visible emissions success level must be incorporated into the permit for the affected facility.

(d) As an alternative to the periodic Method 22 (40 CFR part 60, Appendix A-7) visible emissions inspections specified in paragraph (c) of §60.674, the owner or operator of any affected facility for which construction, modification, or reconstruction commenced on or after April 22, 2008, that uses a baghouse to control emissions may use a bag leak detection system. The owner or operator must install, operate, and maintain the bag leak detection system according to paragraphs (d)(1) through (3) of §60.674.

(1) Each bag leak detection system must meet the specifications and requirements in paragraphs (d)(1)(i) through (viii) of §60.674.

(i) The bag leak detection system must be certified by the manufacturer to be capable of detecting PM emissions at concentrations of 1 milligram per dry standard cubic meter (0.00044 grains per actual cubic foot) or less.

(ii) The bag leak detection system sensor must provide output of relative PM loadings. The owner or operator shall continuously record the output from the bag leak detection system using electronic or other means (*e.g.* , using a strip chart recorder or a data logger).

(iii) The bag leak detection system must be equipped with an alarm system that will sound when the system detects an increase in relative particulate loading over the alarm set point established according to paragraph (d)(1)(iv) of §60.674, and the alarm must be located such that it can be heard by the appropriate plant personnel.

(iv) In the initial adjustment of the bag leak detection system, the owner or operator must establish, at a minimum, the baseline output by adjusting the sensitivity (range) and the averaging period of the device, the alarm set points, and the alarm delay time.

(v) Following initial adjustment, the owner or operator shall not adjust the averaging period, alarm set point, or alarm delay time without approval from the Administrator or delegated authority except as provided in paragraph (d)(1)(vi) of §60.674.

(vi) Once per quarter, the owner or operator may adjust the sensitivity of the bag leak detection system to account for seasonal effects, including temperature and humidity, according to the procedures identified in the site-specific monitoring plan required by paragraph (d)(2) of §60.674.

(vii) The owner or operator must install the bag leak detection sensor downstream of the fabric filter.

(viii) Where multiple detectors are required, the system's instrumentation and alarm may be shared among detectors.

(2) The owner or operator of the affected facility must develop and submit to the Administrator or delegated authority for approval of a site-specific monitoring plan for each bag leak detection system. The owner or operator must operate and maintain the bag leak detection system according to the site-specific monitoring plan at all times. Each monitoring plan must describe the items in paragraphs (d)(2)(i) through (vi) of §60.674.

- (i) Installation of the bag leak detection system;
- (ii) Initial and periodic adjustment of the bag leak detection system, including how the alarm set-point will be established;
- (iii) Operation of the bag leak detection system, including quality assurance procedures;
- (iv) How the bag leak detection system will be maintained, including a routine maintenance schedule and spare parts inventory list;
- (v) How the bag leak detection system output will be recorded and stored; and
- (vi) Corrective action procedures as specified in paragraph (d)(3) of §60.674. In approving the site-specific monitoring plan, the Administrator or delegated authority may allow owners and operators more than 3 hours to alleviate a specific condition that causes an alarm if the owner or operator identifies in the monitoring plan this specific condition as one that could lead to an alarm, adequately explains why it is not feasible to alleviate this condition within 3 hours of the time the alarm occurs, and demonstrates that the requested time will ensure alleviation of this condition as expeditiously as practicable.

(3) For each bag leak detection system, the owner or operator must initiate procedures to determine the cause of every alarm within 1 hour of the alarm. Except as provided in paragraph (d)(2)(vi) of §60.674, the owner or operator must alleviate the cause of the alarm within 3 hours of the alarm by taking whatever corrective action(s) are necessary. Corrective actions may include, but are not limited to the following:

- (i) Inspecting the fabric filter for air leaks, torn or broken bags or filter media, or any other condition that may cause an increase in PM emissions;
- (ii) Sealing off defective bags or filter media;
- (iii) Replacing defective bags or filter media or otherwise repairing the control device;
- (iv) Sealing off a defective fabric filter compartment;
- (v) Cleaning the bag leak detection system probe or otherwise repairing the bag leak detection system; or
- (vi) Shutting down the process producing the PM emissions.

[40 C.F.R. §§60.674(c) and (d); 45CSR16] [EU52, EU53]

4.3. Testing Requirements

4.3.1. Within 90 days of reaching nominal production capacity but not later than 180 days from initial startup of the board line, the permittee shall complete the following performance testing:

4.3.1.1 The permittee shall perform EPA approved stack tests to determine emissions of NO_x, CO, and PM_{2.5} on the board dryer (EU36), one calcining kettle (either EU12 or EU13) and the cage mill DSG dryer (EU 05). CO testing of the calcining kettle (EU12 or EU13) shall be performed while the recycle rate is at 7.7% or as close as practical. Additionally, PM_{2.5} testing of the board dryer shall be performed while the dryer is processing moisture resistant board and again while the dryer is processing regular board.

4.3.1.2 The permittee shall perform EPA approved stack tests to determine emissions of PM_{2.5} from the end saw dust collector (FF02) which controls the waste/recycle system (EU02).

[45CSR13, R13-2656, 4.3.1.]

Note: The initial testing was performed in the week of August 25, 2008.

4.3.2 After initial testing, ongoing compliance shall be demonstrated by repeating the above testing according to the following schedule:

Test	Test Results	Testing Frequency
Initial	≤50% of limits	Once/5 years
Initial	Between 50% and 90% limits	Once/3 years
Initial	≥90% of limits	Annual
Annual	After two successive tests indicate emission rates ≤50% of limits	Once/5 years
Annual	After two successive tests indicate emission rates <90% of limits	Once/3 years
Annual	≥90% of limits	Annual
Once/3 years	After two successive tests indicate emission rates ≤50% of limits	Once/5 years
Once/3 years	< 90% of limits	Once/3 years
Once/3 years	≥90% of limits	Annual
Once/5 years	≤50% of limits	Once/5 years
Once/5 years	< 90% of limits	Once/3 years
Once/5 years	≥90% of limits	Annual

[45CSR13, R13-2656, 4.3.2.]

Note: The testing was conducted in August 2013 and 2014. According to the testing results, the following test schedule shall be followed:

EU12 or EU13 shall be tested for NO_x and CO by August 6, 2016.

EU36 shall be tested for PM_{2.5}, NO_x and CO by August 6, 2016.

EU12 or EU13 shall be tested for PM_{2.5} by August 6, 2018.

EU05 shall be tested for PM_{2.5}, NO_x and CO by August 6, 2018.

FF02 (EU02) shall be tested for PM_{2.5} by August 6, 2018.

- 4.3.3. (a) In conducting the performance tests required in 40 C.F.R. §60.8, the owner or operator shall use as reference methods and procedures the test methods in appendices A–1 through A–7 of 40CFR60 or other methods and procedures as specified in this section, except as provided in 40 C.F.R. §60.8(b). Acceptable alternative methods and procedures are given in paragraph (e) of this section.
- (b) The owner or operator shall determine compliance with the PM standards in Section 4.1.10(a) in accordance with 40 C.F.R. §60.675(b).
- (c) (1) In determining compliance with the particulate matter standards in Section 4.1.10(b) or Section 4.1.10(e)(1), the owner or operator shall use Methods and procedures specified in 40 C.F.R. §60.675(c)(1).
- (2) (i) In determining compliance with the opacity of stack emissions from any baghouse that controls emissions only from an individual enclosed storage bin under 4.1.10(f), using Method 9 (40 CFR part 60, Appendix A-4), the duration of the Method 9 (40 CFR part 60, Appendix A-4) observations shall be 1 hour (ten 6-minute averages).
- (ii) The duration of the Method 9 (40 CFR part 60, Appendix A-4) observations may be reduced to the duration the affected facility operates (but not less than 30 minutes) for baghouses that control storage bins or enclosed truck or railcar loading stations that operate for less than 1 hour at a time.
- (3) When determining compliance with the fugitive emissions standard for any affected facility described under Section 4.1.10(b) or Section 4.1.10(e)(1), the duration of the Method 9 (40 CFR part 60, Appendix A–4) observations must be 30 minutes (five 6-minute averages). Compliance with the applicable fugitive emission limits in Table 3 of 40 C.F.R.60 Subpart OOO must be based on the average of the five 6-minute averages.
- (d) To demonstrate compliance with the fugitive emission limits for buildings specified in Section 4.1.10(e)(1), the owner or operator must complete the testing specified in 40 C.F.R. §60.675(d). Performance tests must be conducted while all affected facilities inside the building are operating.
- (e) The owner or operator may use the methods and procedures specified in 40 C.F.R. §60.675(e) as alternatives to the reference methods and procedures specified in this section:
- (g) For performance tests involving only Method 9 (40 CFR part 60 Appendix A–4) testing, the owner or operator may reduce the 30-day advance notification of performance test in 40 C.F.R. §§60.7(a)(6) and 60.8(d) to a 7-day advance notification.

[40 C.F.R. §60.675; 45CSR16] [EU05, EU06, ~~EU07~~, EU08, EU16, EU18, EU52, EU53, [DSG Conveying Equipment](#)]

Note: EU05, EU06, ~~EU07~~, EU08, EU16 & EU18 have been tested.

- 4.3.4. (a) In conducting the performance tests required in 40 C.F.R. §60.8, the owner or operator shall use the test methods in appendix A of this part or other methods and procedures as specified in this section, except as provided in 40 C.F.R. §60.8(b).
- (b) The owner or operator shall determine compliance with the particulate matter standards in 40 C.F.R. §60.732 as follows:
- (1) Method 5 shall be used to determine the particulate matter concentration. The sampling time and volume for each test run shall be at least 2 hours and 1.70 dscm.
- (2) Method 9 and the procedures in 40 C.F.R. §60.11 shall be used to determine opacity from stack emissions.

[40 C.F.R. §60.736; 45CSR16] [EU12, EU13]

4.4. Recordkeeping Requirements

- 4.4.1. See Section 4.2.

4.4.2. (b)(1) Owners or operators of affected facilities (as defined in §§ 60.670 and 60.671) for which construction, modification, or reconstruction commenced on or after April 22, 2008, must record each periodic inspection required under § 60.674(b) or (c), including dates and any corrective actions taken, in a logbook (in written or electronic format). The owner or operator must keep the logbook onsite and make hard or electronic copies (whichever is requested) of the logbook available to the Administrator upon request.

(2) For each bag leak detection system installed and operated according to §60.674(d), the owner or operator must keep the records specified in paragraphs (b)(2)(i) through (iii) of §60.676.

(i) Records of the bag leak detection system output;

(ii) Records of bag leak detection system adjustments, including the date and time of the adjustment, the initial bag leak detection system settings, and the final bag leak detection system settings; and

(iii) The date and time of all bag leak detection system alarms, the time that procedures to determine the cause of the alarm were initiated, the cause of the alarm, an explanation of the actions taken, the date and time the cause of the alarm was alleviated, and whether the cause of the alarm was alleviated within 3 hours of the alarm.

[40 C.F.R. §60.676(b); 45CSR16] [EU52, EU53]

4.5. Reporting Requirements

4.5.1. Each owner or operator seeking to comply with 40 C.F.R. §60.670(d) shall submit to the Administrator the information according to 40 C.F.R. §60.676(a) about the existing facility being replaced and the replacement piece of equipment.

[40 C.F.R. §60.676(a); 45CSR16] [EU05, EU06, ~~EU07~~, EU08, EU16, EU18, EU52, EU53, [DSG Conveying Equipment](#)]

4.5.2. The owner or operator of any affected facility shall submit written reports of the results of all performance tests conducted to demonstrate compliance with the standards set forth in 40 C.F.R. §60.672, including reports of opacity observations made using Method 9 (40 CFR part 60, Appendix A-4) to demonstrate compliance with 40 C.F.R. §60.672(b), (e) and (f).

[40 C.F.R. §60.676(f); 45CSR16] [EU05, EU06, ~~EU07~~, EU08, EU16, EU18, EU52, EU53, [DSG Conveying Equipment](#)]

4.5.3. A notification of the actual date of initial startup of each affected facility shall be submitted to the Administrator.

(1) For a combination of affected facilities in a production line that begin actual initial startup on the same day, a single notification of startup may be submitted by the owner or operator to the Administrator. The notification shall be postmarked within 15 days after such date and shall include a description of each affected facility, equipment manufacturer, and serial number of the equipment, if available.

[40 C.F.R. §60.676(i); 45CSR16] [EU05, EU06, ~~EU07~~, EU08, EU16, EU18, EU52, EU53, [DSG Conveying Equipment](#)]

4.6. Compliance Plan

4.6.1. Reserved.