

BOX 385 GRANTSVILLE, WV 26147 304-354-9516 DrilcoOilGas.com

December 22, 2020

ANDREW L. LOCKWOOD GEOLOGIST III WV DEP OFFICE OF OIL & GAS 304-719-9802 Andrew.L.Lockwood@wv.gov RECEIVED Office of Oil and Gas

DEC 28 2020

WV Department of Environmental Protection

Hello Andrew,
Attached is the entire PERMIT APPLICATION RENEWAL for UIC WELL 2D08701623 (SUMMERS 7)

I believe everything is complete, and as accurate, as possible.

If you have any questions, please contact me at 304-354-9516, or hugh@drifcooilgas.com.

Thank you,

Hugh D. Dale, Jr., President

Drilco Oil & Gas Corporation



by Dec 28, 2020

west virginia department of environmental protection

Office of Oil and Gas 601 57th Street Charleston, WV 25304 (304) 926-0450 fax: (304) 926-0452

Austin Caperton, Cabinet Secretary www.dep.wv.gov

By Email Transmission

October 1, 2020

Mr. Hugh Dale David Dale, DBA DD Oil Company P.O. Box 406. Spencer, WV 25276

RECEIVED
Office of Oil and Gas

DEC 28 2020

WV Department of Environmental Protection

RE: Reapplication for UIC Permit 2D08701623 (Summers 7)

Mr. Dale:

This letter is being sent to you as a courtesy to inform you that your current UIC permit for the Summers 7 injection well in Roane County will expire June 28, 2021. If you wish to reapply for this permit, you must submit your application documents 180 days prior to the permit expiration date which is December 30, 2020. The permit application package can be downloaded from the WVDEP website. Please contact us if you have questions or need assistance.

Sincerely,

Andrew L. Lockwood

Géologist III

Office of Oil and Gas Phone: 304-719-9802

Andrew.L.Lockwood@wy.gov

Cc: Joe Taylor (Inspector)-(by email)



UNDERGROUND INJECTION CONTROL (UIC) PERMIT APPLICATION PACKAGE CLASS 2 & 3

RECEIVED
Office of Oil and Gas

DEC 28 2020

WV Department of Environmental Protection

Office of Oil and Gas

601 57th Street, SE Charleston, WV 25304 Phone: (304) 926-0450

"Promoting a healthy environment"

INSTRUCTIONS/GUIDANCE TO COMPLETE A CLASS 2 and CLASS 3 UNDERGROUND INJECTION CONTROL (UIC) PERMIT APPLICATION

A. GENERAL INSTRUCTIONS

The Office of Oil and Gas (OOG) has developed a comprehensive permit package and instruction/guidance document to assist in the preparation of a UIC permit application. Where possible, standardized forms have been created and identified as Appendices to the UIC application package. NOTE the instruction/guidance document identifies additional requirements to be submitted with the application.

B. FEES

The application fee for a UIC permit is \$500.00. There will be an additional \$50.00 fee for a groundwater protection plan (GPP).

C. SUBMITTAL

Please submit an original and a complete copy of the UIC permit application package along with the application fee of \$550.00 to:

West Virginia Department of Environmental Protection Office of Oil and Gas Underground Injection Control (UIC) 601 57th Street, SE Charleston, WV 25304

RECEIVED
Office of Oil and Gas

DEC 28 2020

WV Department of Environmental Protection



CHECKLIST FOR FILING A UIC PERMIT APPLICATION

Please utilize this checklist to ensure you have prepared, completed, and enclosed all required documentation and payment to ensure a timely review of your submittal.

Operator		
Existing	UIC	C Well
UIC Permit	API	I
ID Number	Nur	mber

Office of Oil and Gas Office Use Only				
Permit Reviewer				
Date Received				
Administratively Complete Date				
Approved Date				
Permit Issued				

Please check the fees and payment included.

Fees	Payment Type		
UIC Permit Fee: \$500		Check	
Groundwater Protection Plan		Electronic	
(GPP) Fee: \$50.00		Other	

Please check the items completed and enclosed.

Checklist
UIC-1
Section 1 – Facility Information
Section 2 – Operator Information
Section 3 – Application Information
Section 4 – Applicant/Activity Request and Type
Section 5 – Brief description of the Nature of the Business
CERTIFICATION
Section 6 – Construction
Appendix A Injection Well Form
Appendix B Storage Tank Inventory
Section 7 – Area of Review
Appendix C Wells Within the Area of Review



Appendix D Public Service District Affidavit
Appendix E Water Sources
Appendix F Area Permit Wells
Section 8 – Geological Data on Injection and Confining Zones
Section 9 – Operating Requirements / Data
Appendix G Wells Serviced by Injection Well
Section 10 – Monitoring
Section 11 – Groundwater Protection Plan (GPP)
Appendix H Groundwater Protection Plan (GPP)
Section 12 – Plugging and Abandonment
Section 13 – Additional Bonding
Section 14 – Financial Responsibility
Appendix I Financial Responsibility
Section 15 – Site Security Plan
Appendix J Site Security for Commercial Wells
Section 16 – Additional Information
Appendix K Other Permit Approvals

*NOTE: For all 2D wells an additional bond in the amount of \$5,000 is required.

Reviewed by (Print Name): Hugh Dale - DD Oil Company

Reviewed by (Sign):

Date Reviewed:

1-24-2024

dep

Section 1 – 5 UIC-1 Form



WEST VIRGINIA DEPARTMENT OF **ENVIRONMENTAL PROTECTION**

OFFICE OF OIL AND GAS

601 57th Street, SE Charleston, WV 25304 (304) 926-0450

www.dep.wv.gov/oil-and-gas

UNDERGROUND INJECTION CONTROL (UIC) PERMIT APPLICATION

UIC PERMIT ID # 200871623

API # 47-087-01623

WELL# SUMMERS #7

Section I. Facility Information

Facility Name: DD OIL WALTON DISPOSAL

Address: 7845 Charleston Road (Rt 119)

City: SPENCER

State: WV

Zip: 25286

County: WALTON

District: Walton

Location description:

OFF ROUTE 119. TAKE EXISTING ROAD THRU ONE GATE 2.2 MILES TO WELL. TANK BATTERY 100' OFF ROUTE 119. EXISTING TANKS AT MOUTH OF McKOWNS CREEK. ALL WATER PUMPED TO WELL ABOVE.

Location of well(s) or approximate center of field/project in UTM NAD 83 (meters):

Easting: 466837.7

Latitude: 38.640116 Longitude: -81.38105

Environmental Contact Information:

Name: DAVID DALE

Northing: 4276910

OWNER Title:

Phone: 304-927-1147 (O) 304-532-1147 (M) Email: ddoilcompany@suddenlink.net

RECEIVED
Office of Oil and Gas

DEC 28 2020

Section 2. Operator Information

Operator Name: DAVID DALE DBA DD OIL CO

WV Department of Environmental Protection

Operator ID:

308509

Address: PO BOX 406

City: SPENCER

State: WV

Zip: 25276

County: ROANE

Contact Name: HUGH D DALE DRILCO OIL CORP Contact Title: OPERATOR

Contact Phone: 304-354-9516 (O) 304-550-0978 Contact Email: hugh@drilcooilgas.com

pplicant Information
■ PRIVATE □ PUBLIC □ FEDERAL □ STATE □ OTHER (explain):
(2D, 2H, 2R)
Applicant / Activity Request and Type:
new UIC Permit:
riefly describe the nature of business and the activities to be conducted:
PRODUCING OIL WELLS AND ONE INJECTION WELL. RODUCES @15 bbls PER DAY OIL. AND 57 barrels OF WATER PER DAY. S RE-INJECTED IN THE SAME FORMATION / BIG INJUN FORMATION.
Office of Oil and Gas DEC 2 8 2020 WV Department of Environmental Protection
(Z i ii t ly L 3



APPLICATION CERTIFICATION

In accordance with WV Code 47CSR13.13.11, all UIC permit applications must be signed by one of the following:

- 1. For a corporation: by a principle corporate officer of at least the level of vice-president;
- 2. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively;
- 3. For a municipality, State, Federal, or other public agency: by either a principle executive officer or ranking elected official;
- 4. Or a duly authorized representative in accordance with 47CSR13.13.11.b. (A person may be duly authorized by one of the primary entities (1-3) listed above by submitting a written authorization to the Chief of the WVDEP Office of Oil and Gas designating an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of plant manager, operator of a well or a well field, superintendent, or position of equivalent responsibility. A duly authorized representative may thus be either a named individual or any individual occupying a named position.)

DD Oil Company	
(Company Name)	
2D08701623	
(IIIC Permit Number)	

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this document and all attachments and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment. (47CSR13.13.11.d)

Hugh Dale

(Print Name)

(Print Title)


(Signature)

(Date)

Section 6

Construction

David Dale DBA DD Oil Company Summers No. 7 47-087-01623



Office of Oll and Gas Environmental Protection

Environmental Protection

WALTON FIELD ROANE CO,WV

4708701623

APPENDIX A Injection Well Form

DIC IN ILIN CAND
1) GEOLOGIC TARGET FORMATION BIG INJUN SAND
Depth 2077' Feet (top) 2115' Feet (bottom)
2) Estimated Depth of Completed Well, (or actual depth of existing well): 2150' Feet
3) Approximate water strata depths: Fresh 120' Feet Salt 1650' Feet
4) Approximate coal seam depths: NONE
5) Is coal being mined in the area? Yes No
6) Virgin reservoir pressure in target formation 500 psig Source WV GEO SURVEY BLUE BOOK CIN 1909
7) Estimated reservoir fracture pressure 2000 PS LB psig (BHFP)
8) MAXIMUM PROPOSED INJECTION OPERATIONS:
Injection rate (bbl/hour) 2.375 BBL/HOUR
Injection volume (bbl/day) 57 BBL/DAY
Injection pressure (psig) 475-500 PSI832
Bottom hole pressure (psig) 8.32 THRU 4.5 BUT THROUGH 2 7/8 ' TUBING - 416 PSI
9) DETAILED IDENTIFICATION OF MATERIALS TO BE INJECTED, INCLUDING ADDITIVES:
PRODUCED SW ACID STICK TO KEEP IRON DOWN LO
RECEIVED Office of Oil and Gas
DEC 2 8 2020
Temperature of injected fluid (OF)
10) FILTERS (IF ANY) WV Department of Environmental Protection
10 MICROS 30 INCHES LONG (7 OF THEM) NO WATER FILTERS
11) SPECIFICATIONS FOR CATHODIC PROTECTION AND OTHER CORROSION CONTROL
CHANGED TO STAINLESS STEEL AND FIBERSPOR 2011 - NOV 23 FINISHED
THE PROPERTY OF STREET



4708701623 APPENDIX A (cont.)

12. Casing and Tubing Program

TYPE	Size	New or Used	<u>Grade</u>	Weight per ft. (lb/ft)	FOOTAGE: For Drilling	INTERVALS: Left in Well	CEMENT: Fill-up (Cu.
Conductor					 	<u> </u>	<u>Ft.)</u>
Fresh Water	8 5/8	NEW		20 LB FT	160'	160'	CTS
Coal						100	013
Intermediate 1				 			
Intermediate 2							
Production	4.5	NEW	J55	9.5 LB FT	2160'	2160'	CTS
Tubing	2 7/8	NEW	EUE	7.3 LB FT	1970'	1970'	013
Liners					1.070	1070	

TYPE	Wellbore Diameter	Casing Size	Wall Thickness	Burst Pressure	Cement Type	Cement Yield (cu.	Cement to Surface ?
Conductor						ft./sk)	(Y or N)
Fresh Water	11'	8 5/8			CLASS A	CTS	CTS
Coal					JE/100/1		
Intermediate 1		1				Office	RECEIVED of Oil and Gas
Intermediate 2	 					DE	C 2 8 2020
Production	7 7/8	4.5			CLASS A	WV Environ	Department of mental Protection
Tubing					OLAGO A		CIS
Liners							

PACKERS	Packer #1	Packer #2	Packer #3	Packer #4
Kind:	TENSION 2 3/8 X 4 1/2	20-30 C 20 C		
Sizes:				
Depths Set:	1970 KB			






4708701623

STATE OF WEST VIRGINIA
DEPARTMENT OF MINES
OIL AND GAS DIVISION

Rotary	2
Spudder	
Cable Tools	

Quadrangle. W	alton		OIL AND	GAS DIVISION		Cable Tools				
Permit No. RO.			WELL	RECORD		Storage Oil or Gas	well Injection			
Company Jos	seph S. G x 471, Sp	russ encer, W.	Va.	Casing and Tubing	Used in Drilling	Left in Well	(KIND)			
	B. Summe	rs	Acres 105		-					
Location (waters)		n			l		Kind of Packer			
Well No.	7		Blev936				Kind of Packer			
District Walt	con	County R	oane	10			Size of			
The surface of tr			e Moffatt	. 814	150	150				
Minaral Jaka	. T	Address Walto	n, w. va.	. 644			Depth set			
Mineral rights ar	e owned by	. B. Summe	rs, et al er, W. Va.							
Drilling commen		20_67					······································			
Drilling complete	7-	29-67		2		i	Perf. top			
Date Shot	From		Го	Liners Used.			Perf. bottom			
With							Perf. top			
Open Flow			Inch				Perf. bottom			
WELL FRACTU RESULT AFTER	RED (DETAIL TREATMENT	(Initial open Flow	or bbls.)Injac	FEE FEE 1 and 30,00	T INCI T INCI O Gallons	HES F Gelled S				
						Feet				
Sand					Depth 2077	-2095 and	2111-2115			
Formation	Color	Hard or Bott	Тор	Bottom	Off, Gas or Water	-2095 and	2111-2115			



4708701623

PRALABLA LOS

14

Joseph S. Gruss Attm: Mr. Hickox Spencer, West Virginia

I. B. SUMMERS #7 -	ROAME COUNTIS	WEST VIRGINIA
0 To 75 To 152 To 165 To 400 To 490 To 540 To 657 To 1020 To 1020 To 1175 To 1244 To 1555 To 1635 To 1637 To 1	75 152 165 400 490 540 657 667 870 1020 1020 1350 1555 1620 1635 1885 1927 1933 1965 2009 2054 2066 2092 2110 2117 2150	shaley sand shells shale shale, sandy shale & shells sand shale sandy shale lime sandy shale & shale sand; shale & lime shells sand; shale & lime shells sand, shaley and sand shaley sand shaley sand shaley sand shaley sand shaley sand shale sand salt sand shale

ALLARAXAI

STATE OF WEST VIRGINIA)

Office of Oil and Gas

I hereby certify that the Driller's Log is correct decording to the Daily Drilling Report.

MITCHELL & MITCHELL DRILLING GOSTRACTORS

1. 1 D-W/ to 1. en



Select County: (087) Roane Enter Permit #: 1623 Get Data Reset

Location Production Plugging Sample ✓ Owner/Completion Stratigraphy Pay/Show/Water Logs

<u>Disclaimer</u> WVGES Main ☑ Btm Hole Loc "Pipeline-Plus

WV Geological & Economic Survey:

Well: County = 087 Permit = 1623 Link to all digital records for well

Report Time: Monday, September 18, 2023 4:48:22 PM

Location Information:

API COUN 4708701623 Roane

There is no Bottom Hole Location data for this well

Owner Information:

API CMP_DT SUFFIX STATUS SURFACE_OW 4708701623 7/29/1967 Original Loc Completed George Moffatt SURFACE_OWNER WELL_NUM CO_NUM LEASE LEASE_NUM MINERAL_OWN OPERATOR_AT_COMPLETION PROP_VD PROP_TRGT_FM TFM_EST_PR I B Summers et al Gruss, Joseph S I B Summers

Completion Information

ELEV DATUM FIELD DEEPEST_FM DEEPEST_FMT INITIAL_CLASS FINAL_CLASS TYPE
936 Ground Level Walton(Rock Ck) Undf PRICE blw INJN Big Injun (Price&eq) Service Well Unsuccessful Salt W API CMP_DT SPUD_DT ELEV DATUM 4708701623 7/29/1967 7/20/1967 936 Ground RIG CMP MTHD TVD TMD NEW FTG KOD G E Salt Water Disp Rotary Fractured

Pay/Show/Water Information:

DEPTH_BOT FM_BOT 2095 Big Injun (Price&eq) G BEF G AFT O BEF O AFT WATER QNTY 2115 Big Injun (Price&eq

There is no Production Gas data for this well

There is no Production Oil data for this well ** some operators may have reported NGL under Oil

There is no Production NGL data for this well ** some operators may have reported NGL under Oil

There is no Production Water data for this well

Stratigraphy Information:

API	SUFFIX	FM	FM_QUALITY	DEPTH_TOP	DEPTH_QUALITY	THICKNESS	THICKNESS_QUALITY	ELEV	DATUM
4708701623	Original Loc	1st Salt Sand	Well Record	1620	Reasonable	15	Reasonable	936	Ground Level
4708701623	Original Loc	2nd Salt Sand	Well Record	1635	Reasonable	250	Reasonable	936	Ground Level
4708701623	Original Loc	Big Lime	Past WVGES Staff Geologst	1933	Reasonable	133	Reasonable	936	Ground Level
4708701623	Original Loc	Big Injun (Price&eq)	Well Record	2066	Reasonable	26	Reasonable	936	Ground Level

Wireline (E-Log) Information:

* Scanned/Raster Log Information:

API	STATUS	LOG_TOP	LOG_BOT	DEEPEST_FML	LOGS_AVAI	L SCAN	GR_TOP	GR_BO	r D_top	D_BOT	N_TOP N_B	OT I_TOP	I_BOT	T_TOP	T_BOT	S_TOP	S_BOT	O_TOP	O_BOT INCH2
4708701	1623 Regular Entry	0	2150	Big Injun (Price&eq) G,I	Υ	0	215)			1600	2150						Y

^{*} There is no Digitized/LAS Log data for this well

Downloadable Log Images/Data: We advise you to save the scanned log or digitized log file(s) to your PC for viewing. To do so, right-click the file of interest and select the save option. Then you can direct the file to a location of your choice. Please note the scanned log images vary in size and some may take several minutes to download.

Scanned/Raster

Logs FILENAME 08701623gi.tif 08701623go.ti geologic log types:
d density (includes bulk density, compensated density, density, density porosity, grain density, matrix density, etc.)
e photoelectric adsorption (PE or Pe, etc.)

Quick Reference Guide for Log File Names For more info about WVGES scanned logs click here

g gamma ray i induction (includes dual induction, medium induction, deep induction, etc.)

I laterolog m dipmeter

n neutron (includes neutron porosity, sidewall neutron--SWN, etc.)

o other¹ s sonic or velocity

z spontaneous potential or potential mechanical log types:

b cement bond

c caliper o other¹

p perforation depth control or perforate

¹other logs may include, but are not limited to, such curves as audio, bit size, CCL--casing collar locator, continuous meter, directional survey, gas detector, guard, NCTL--Nuclear Cement Top Locator, radioactive tracer, tension

There is no Plugging data for this well

There is no Sample data for this well

Tank Registration Numbers

APPENDIX B

Storage Tank Inventory
044-00000431
5 044-00000 437

Office of Oil and Gas

API#	Tank ID	(UTM NAI	ocation 9 83 Meters) Easting	Installation Date	Tank Age (Months)	Construction Material (Steel,	Capacity (gallons)	Type of Fluid Stored	Volume of Fluid Stored	Tank Type Single/Double Wall
PLASTIC	_	1101111115	Lusting			plastic, etc.)	1 (8)	7 tata storea	(gallons)	Wall
PLASTIC TANKS	1+2	(See atta	ched)	2011	9405	Plastic	8,400	BRINE		
1.49,10								77 		VIII - VI

			**************************************	_						
				-			2			
					-					NAME OF THE PARTY



Operator:

DD Oil Company

UIC Permit No.:

2D08701623

Secondary Containment Calculations Earth Berm Containment

(Input Measurements In Blue Cells)

Tank	Tank Dim	ensions	Capacity					
TOTAL	Height (Ft)	Dia (Ft)	Barrels	Gallons	Cu Ft			
1	14.55	9.917	200.2	8407.1	1123.9			
2	14.55	9.917	200.2	8407.1	1123.9			
3			0.0	0.0	0.0			
4			0.0	0.0	0.0			
5			0.0	0.0	0.0			
6			0.0	0.0	0.0			
7			0.0	0.0	0.0			
8			0.0	0.0	0.0			
9			0.0	0.0	0.0			
10			0.0	0.0	0.0			
		Total	400.3	16,814.1	2,247.7			

Enter	largest	tank	as	Tank	1.
		COLLIN	43	1 WIIIX	

Tank	Tank Base Exclusions						
I allk	Dia (Ft)	Depth (Ft)	Vol (CuFt)				
1	0	4.00	0.0				
2	9.917	4.00	309.0				
3	0	4.00	0.0				
4	0	4.00	0.0				
5	0	4.00	0.0				
6	0	4.00	0.0				
7	0	4.00	0.0				
8	0	4.00	0.0				
9	0	4.00	0.0				
10	0	4.00	0.0				
Т	otal Tank Base	Exclusions	309.0				

	Tank 1 entered as "0" diameter to exclude it from
ı	the tank base exclusion calculations.

Containment Dimensions					
Top Interior F	Perimeter				
Length (Ft)	Width (Ft)				
90.00	25.00				
Bottom Interio	r Perimeter				
Length (Ft)	Width (Ft)				
82.00	17.00				
Depth (Ft)					
4.00	18.1				
Total Containment Volume (CuFt)	7220.0				
All containment measureme	ents must be interior				

volume (curt)	
All containment measurements must be interior	Ī
dimensions.	

Tank Containment Volume (CuFt)	7220.0
Minus Tank Base Exclusions (CuFt)	309.0
Net Containment Volume (CuFt)	6911.1
Largest Tank Volume (CuFt)	1123.9
Available Containment Volume (CuFt)	614.9%

25ft

17ft

4 ft depth

90ft


82ft

Section 7 Area of Review

Iffice of Oil & Gas

NOV 2 0 2015

WV Department of



[:] intalloand discharge structures, Storage, ground water supply sources, pump, Valves, tank, Secondary containment Well

º D. 0 1-00









APPENDIX C

Wells within the Area of Review

API#	Well Type	Well Status (Active, Abandoned, Shut-in, Plugged)	Northing (UTM NAD 83 Meters)	Easting (UTM NAD 83 Meters)	Penetrate Injection Zone (Y or N)	Penetrate Confining Zone (Y or N)	Total Vertical Depth	Surface Elevation
					_			
3.6.1			1' 1 1 1	• ,				

Make as many copies as necessary and include page numbers as appropriate.



Form OG-10	Ciroli Lause	10.00	in them than colony and a			ı. Zi.						
			0 10		16 93		70 inc		.	5 5.	93.	汉
			94		, aver		,					uni.l
				:) !	VIRGINIA		λ	1	otarý pudde		<u> </u>	บกุลรัฐ
			DEPARTM	1	OF MINES	1.			able 1			ુ. સ્વતંત્રી
Quadrangle Val			1.0		CORD				orage	as Well	กรากเ	
Permit No. ROA				7.70						Mell.	(KIND)	1
Company JOS Address 30	Broad St.	ALIV. AL.	Y. T.	- 1	Casing and Tubing	Ue Del	ed in Ulfog	Left Wel			Packers	
Farm I B Su Location (waters)	mmers 't		Acres 105		Size	7				Kind	of Packer	
Well No 6			Elev. 948	13		254 245		in the state of	- (-)	1		* (. 2)
District Walton The surface of trace		County Robo		10 8	/4	1:	55	155		Size o		
		ddress	1.		3/16	-3* } -3* }				Depth	sct	·
Mineral rights are	A	ddress	Hairs			11			1 12 1 25			
Drilling commence	10-15	5-66		3 2							bottom	
Date Shot			To Allahar	Li	ners Used				**,		bottom	
Open Flow	/10ths Water	r in :	in		tach copy of c				140	-	•	
Voleme		in	In		SING CEME		ed (bags)	700		.No. Ft.	, rn-T2-0	Date
Bock Pressure		lbs	bbls., 1st 24 h	rs. Na	me of Service	Co-	How	CO		FEET		
WELL ACIDIZE) (DETAILS)				FEE	<u>r ' </u>	INC	HES		FEBT_	n	ICHES.
WELL FRACTUI	RED (DETAILS					. 13 gd ·	INC	HBS		FEBT	•	
RESULT AFTER	TREATMENT	(Initial open Flow	or bbls.)	1 5	BBIs.	? ; j.					i de.	
ROCK PRESSUR	E AFTER TRE	EATMENT		<i>F</i> H	OURS	() ()				•		
Fresh Water Producing Sand	Big Injur				t Water	Dep	th	: .	Feet_]	
Formation	Color	Hard or Soft	Top		Bottom	(Oil, Gas r Water		Depti		Remark	
)surface			0		5					. g		
rock & cle			5		75							\ · · ·
shale & ro			75		135		>					
shale & ro			135		160	•						
red bed ro		[清]	160		213						0	
rock & san			213	ં ધ	534							
shale & sa			504	1.	B15							
sand shale			815		067						•	
			1 1 1 1 1 1 1 1 1			1.33			165	3117	45	•
sand with	SIIHT B		1067		322	· · ·		1 /	$\mathscr{Q}_{\mathcal{P}_{J_{j}}}$		450	
sand			1322		535			5263	7 01	HOV !	VED 9	31
sand,			1535	•	616	à		160	5 \ 5 \	Nest Vir	Wincs W	
أومشاروا ويراوا الرساف			1616		690			\\		י ואבות '	arding	
salt sala		the second		1 -				10.77	~~	CALUIL		
salt sand		0	1690	$\frac{1}{10}$	855			1		SOLO L	١	
salt sand		7.76	1855	10 25,7	855 ·					2018 L	VED Binia Mines	
salt sand		2.22	111,	10 25,7						2018		•

Formation	Color	Hard 4r Soft	Top 3/	Bettem	Oil, Gas or Water	Depth Found	93 Remarks
limey sand			1875	1896			
lime	-11		1896	1955			
ime	r San da		1955	2051			
njun sand		\int_{Γ}	2051	2090			STANT AND
.njun	Hell out to p					(12) مارین مصنعور در	=1.000 Service
hale	基础		2090	2 0 93			ing and the
11978			2093	2143		2.2.1. 2020	ing Francis
						noroda	er (noest lides
		rates billions.			inimana		ua: Tali i-pi
مربع اور مساور المساور					dia Alansue	estan andrew	Liver'ly positive
					eed tafatta	. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	क राज शरी विका
					And the second	PHILIPPINE	Essassinas Sail
						19-11-01	Serolamov gast
	ing design					Pićani.	1
-M-25-14-0	-77.75 L	ing record, Control	Society year doc	A STATE OF STATE		10da Mese him	·wo!4
TIME AND THE PARTY.		101.120.31				The state of the s	2000
erioni i di		Lavegaraw	of similar in				Shows
יאכיים!	A Second Control of the Control of t					221LATES	i.i. acrotzen'
2. 17.	TO A CONTRACT					againa a	arundari ale
			A. N.			المراجعة والمواجعة المراجعة ا	12. 19.2.
				1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		SOUTH THE WINE	ता है उस्तर रहिता संप्रधानक स्ट
			S. F. A. L. C. L. L. C. St. C. L.			The state of the s	The sections of the section of the s
rinari			c 3a			1002	nonana.
							· · · · · · · · · · · · · · · · · · ·
							don A. S.
							inour less to
							6599
							vina - i 51.
							sclaire by
							ति त्रिकार वर्ष
	[4] (A)						
					LETT .		
					Date Octol	er ogs	10.6
				Appoun	Joseph 5.	34. 188. E	and much sign
	.				Vn	Fest D	, O x
	A CONTRACTOR		A STATE OF THE STA	2. (2		(Title)	
	Almen !				がりがた かんじょう		


4708701493CEII STATE OF WEST VIRGINIA DEPARTMENT OF MINES OIL AND GAS DIVISION OIL & GAS DI OIL

APR 1 5 1971

AFFIDAVIT OF PLUGGING AND FILLING WELLDEFT. OF WINES

		MAREVE OIL CORP.	-	
COAL OP	ERATOR OR OWNER	P. O. Box .1228		* (1.25. 3%)
	ADDRESS	Parkersburg, W. Va. 2	6101	
		April 13.	RESS	1971.``
OAL OF	ERATOR OR OWNER	WELL AND LO	CATION	181
	ADD CONTROL OF THE PROPERTY OF	Walton		District
		Roane		
LEASE OR		CHARLES STORY		County
	W. W.	Vell. No. 6		· · · · · · · · · · · · · · · · · · ·
	ADDRESS	I. B. Summers		
		**	• • • • •	Farm
FATE INSPECTOR S	UPERVISING PLUGGING Fred B	Burdette, Sisso	nville,	W.Va. 2518
	AFFIDAV	47		
TATE OF WEST V				
county of Roane				
		W. C. Weske		
eing first duly swo	I. A. Poya and and rn according to law depose and	we Us Weske	nood in th	
mig mat duly swo	in according to law depose and	way that they are experie	nced in the	e work of
ugging and filling o	oil and gas wells and were employ articipated in the work of pluggin	ed by Mareve 011	Corp.	
en operator, and pa	b. Oth Annil!	g and iming the above v	ven, that a	ald work
as commenced on the following	he 9th day of April -	$\frac{19.7\pm}{1}$, and that the	ne well wa	s plugged
D OR ZONE RECORD	FILLING MATERIAL		 	
PORMATION .	FILLING MAILRIAL	PLUGS USED	#	ASING
PORMATION		SIZE & KIND	PULLED	LEFT IN
	1050 : 1550	Noment	-0-	85/8" 15
				丹子" 1090'
	1750 - 1550 1550 - 1000	Cement	10501	112 1070
	1550 - 1000	fud Laden Flu		/ 1070
•	1550 - 1000	fud Laden Flu	d	, 1070
	1550 - 1000 1000 - 950	fud Laden Flu Cement fud Laden Flu	d	, 1070
•	1550 - 1000 1000 - 950 950 - 180	fud Laden Flu Cement fud Laden Flu	d d	12 1070
	1550 - 1000 1000 - 950 950 - 180 180 - 130	Mud Laden Flu Cement Mud Laden Flu Cement	d d	, 12 1070
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20	fud Laden Flu Cement fud Laden Flu Cement fud Laden Flu	d d	12 1070
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20	fud Laden Flu Cement fud Laden Flu Cement fud Laden Flu	d d	12 1070
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20	fud Laden Flu Cement fud Laden Flu Cement fud Laden Flu	d d	12 1070
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement	d d	12 1070
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	fud Laden Flu Cement fud Laden Flu Cement fud Laden Flu	d d	
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement	d d	
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement	d d	
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement Cement Cement	d d	ENT
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement Cement DESCRIPTION 1-1-11 30" above	d d d	inscribed
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flucement Mud Laden Flucement Mud Laden Flucement Cement Cement	d d d	inscribed
	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement Cement DESCRIPTION 4½" 30" above Mareve 0: ROA-1493	d d d	inscribed
COAL SEAMS	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement Cement DESCRIPTION 1-2" 30" above Mareve 0: ROA-1-1-93 P & A:	d d d N OF MONUM 7e G.L. 11 Corp	ENT
COAL SEAMS	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement Cement DESCRIPTION 1-2" 30" above Mareve 0: ROA-1-1-93 P & A:	d d d d d d d d d d d d d d d d d d d	inscribed
COAL SEAMS d that the work of April	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement Cement DESCRIPTION 1-2" 30" above Mareve 0: ROA-1-1-93 P & A:	d d d N OF MONUM 7e G.L. 11 Corp	inscribed day of
COAL SEAMS	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement Cement DESCRIPTION 1-2" 30" above Mareve 0: ROA-1-1-93 P & A:	d d d N OF MONUM 7e G.L. 11 Corp	ent inscribed
COAL SEAMS d that the work of April	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement Cement DESCRIPTION 1-2" 30" above Mareve 0: ROA-1-1-93 P & A:	d d d N OF MONUM 7e G.L. 11 Corp	inscribed day of
d that the work of April And further depo	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement DESCRIPTION 142" 30" above Mareve 0: ROA-1493 P & A: Was completed on the	d d d N OF MONUM 7e G.L. 11 Corp	day of
d that the work of April And further depo	1550 - 1000 1000 - 950 950 - 180 180 - 130 130 - 20 20 - 0	Mud Laden Flux Cement Mud Laden Flux Cement Mud Laden Flux Cement DESCRIPTION 142" 30" above Mareve 0: ROA-1493 P & A: Was completed on the	d d d N OF MONUM 7e G.L. 11 Corp	day of (L.A.Po (W.C.We

APPENDIX C



APPENDIX C RECEIVED Office of Oil and Gas 18 Summers 7 **(1)** John Pell 2-G1 1372 IB Summers 6 **1493** C W Vineyard 7 SUMMERS_7 1861 Geor J Gandee 1 C W Vineyard 5-i IB Summers 4 1B Summmers 1 I B Summers 5 1282 1520 1279 0 C Vineyard 6-G Moffalt Moffat 1495 Adro 1283 1628 G Moffatt 1 C W Vineyan G W Canterbury 11 G W Canterbul & Bixin 1266 G Moffatt 3 G Moffatt 2 C E Canterbury 1254 118 1267 1257 1602 C E Canterbury & Canterbury 8 HHI Mara Dall O 1337 AMPIN D D OIL COMPANY 0 500 1000 1500 ft I B SUMMERS CROSS SECTION LOCATION WALTON DISTRICT, ROANE COUNTY, W.VA. Author: MCB Date: 34 July, 2014 Siente: See scatebar

N

P.G Cunningham 1

70080

SUMMERS_7

1461Marks Heirs 1268


1317

500

C Moore 1

1323

WV Oil & Gas Wells (WVOG)



APPENDIX D

Public Service District Affidavit

Underground Injection Control Permit applicants must identify all publically recorded drinking water sources within a one (1) mile radius of the proposed injection well facility. If no drinking water sources are present within this radius a written affidavit shall be supplied by the local Public Service District (PSD) as ample verification.

"I certify under penalty of law that (state name of business)

DD OIL COMPANY

has verified with the public service district (state name of PSD)

Bellevisor

Walton PSD - Field Supervisor

that there are no such publically recorded sources.

(Signature of Authorized Representative)

Sworn and subscribed to before me this 23 cday of Penalty 20 2020

my commission expires 10 19 2023

(Notary Signature)

Walton PSD - Field Supervisor

(Signature of Authorized Representative)

RECEIVED
Office of Cil and Gas

OFFICIAL SEAL NOTARY PUBLIC STATE OF WEST VIRGINIA

DEC 28 2020

WV Department of Environmental Protection



APPENDIX E

Water Sources

Operator: DD Oil Companyear 2023 UIC Permit # 2D08701623

		Source #	Source #	Source #	Source #
Water Source, Name					
Northing	and the second				
Easting					
Parameter	Units			_	_
TPH - GRO	mg/L	100	Thorog	are no de	amactic
TPH - DRO	mg/L	Tip y		are no a	Dille Suc
TPH - ORO	mg/L				
BTEX	mg/L		Water c	ources	within
Chloride	mg/L		Walti 3	Oui CC3	W I L I I I I I
Sodium	mg/L		_		
Total Dissolved Solids	/T		tho 1/1	mile AC	D
(TDS)	mg/L		IIIE 1/4	IIIIIE AC	
Aluminum	mg/L				
Arsenic	mg/L				
Barium	mg/L				
Iron	mg/L		t.		
Manganese	mg/L				
pН	SU				
Calcium	mg/L				
Sulfate	mg/L				
MBAS	mg/L				
Dissolved Methane	mg/L				
Dissolved Ethane	mg/L				
Dissolved Butane	mg/L				
Dissolved Propane	mg/L				
Bacteria	c/100m				
(Total Coliform)	L				



APPENDIX F Area Permit Wells

API#	Well Type (Injection, Production, Observation, Monitoring)	Well Status (Active, Abandoned, Shut-in, Plugged)	Northing (UTM NAD 83 Meters)	Easting (UTM NAD 83 Meters)
	NI.			
	IVOI	. Ap	plica	DIE
				Office of Oil and o
				DEC 2 8 202 WV Department of Environmental Protes

Make as many copies as necessary and include page numbers as appropriate.




APPENDIX G

Wells Serviced by Injection Wells

API#	Operator	Producing Formation
47-087-1300	DD OIL CO	BIG INJUN SAND
47-087-1219	DD OIL CO	BIG INJUN SAND
47-087-1183	DD OIL CO	BIG INJUN SAND
47-087-1245	DD OIL CO	BIG INJUN SAND
47-087-1422	DD OIL CO	BIG INJUN SAND
47-087-1860	DD OIL CO	BIG INJUN SAND
47-087-1382	DD OIL CO	BIG INJUN SAND
47-087-1307	DD OIL CO	BIG INJUN SAND
47-087-1309	DD OIL CO	BIG INJUN SAND
47-087-1310	DD OIL CO	BIG INJUN SAND RECEIVED Office of Oil and Gas
47-087-1558	DD OIL CO	BIG INJUN SAND DEC 2 8 2020
47-087-1857	DD OIL CO	
47-087-1311	DD OIL CO	BIG INJUN SAND W Department of BIG INJUN SAND Protection
47-087-1859	DD OIL CO	BIG INJUN SAND
47-087-1421	DD OIL CO	BIG INJUN SAND
47-087-1420	DD OIL CO	BIG INJUN SAND
47-087-1520	DD OIL CO	BIG INJUN SAND
47-087-1861	DD OIL CO	BIG INJUN SAND
47-087-1283	DD OIL CO	BIG INJUN SAND
47-087-1284	DD OIL CO	BIG INJUN SAND
47-087-1552	DD OIL CO	BIG INJUN SAND
47-087-1242	DD OIL CO	BIG INJUN SAND
47-087-1243	DD OIL CO	BIG INJUN SAND
47-087-1259	DD OIL CO	BIG INJUN SAND
47-087-1847	DD OIL CO	BIG INJUN SAND
47-087-1848	DD OIL CO	BIG INJUN SAND
47-087-4048	DD OIL CO	BIG INJUN SAND

Make as many copies as necessary and include page numbers as appropriate.






APPENDIX G

Wells Serviced by Injection Wells

API#	Operator	Producing Formation	
47-087-1516	DD OIL CO	BIG INJUN SAND	
47-087-1517	DD OIL CO	BIG INJUN SAND	
47-087-3969	DD OIL CO	BIG INJUN SAND	
47-087-1227	DD OIL CO	BIG INJUN SAND	
47-087-1228	DD OIL CO	BIG INJUN SAND	
47-087-1229	DD OIL CO	BIG INJUN SAND	
47-087-1234	DD OIL CO	BIG INJUN SAND	
47-087-1263	DD OIL CO	BIG INJUN SAND	
47-087-1856	DD OIL CO	BIG INJUN SAND	
47-087-1862	DD OIL CO	BIG INJUN SAND	
47-087-1264	DD OIL CO	BIG INJUN SAND	ECEIVED of Oil and Ga
47-087-1247	DD OIL CO	BIG INJUN SAND	Of Oil and Ga
47-087-1248	DD OIL CO	1 (1)(7 (1)(1)(1)(1)(1)(1)(1)(1)	2 8 2020
47-087-1244	DD OIL CO	BIG INJUN SAND TON	partment of ntal Protection
47-087-1246	DD OIL CO	BIG INJUN SAND	
47-087-1277	DD OIL CO	BIG INJUN SAND	
47-087-1845	DD OIL CO	BIG INJUN SAND	
47-087-1515	DD OIL CO	BIG INJUN SAND	
47-087-1846	DD OIL CO	BIG INJUN SAND	
47-087-4077	DD OIL CO	BIG INJUN SAND	
47-087-1372	DD OIL CO	BIG INJUN SAND	
47-087-1380	DD OIL CO	BIG INJUN SAND	
47-087-1269	DD OIL CO	BIG INJUN SAND	
47-087-1397	DD OIL CO	BIG INJUN SAND	

Make as many copies as necessary and include page numbers as appropriate.





APPENDIX B

Office

Project

10 November 2015

INPUT Geographic, NAD83

OUTPUT

UTM, NAD83 17 - 84W to 78W, Meters

WELL

SUMMERS 7

Latitude: 38 38.407

Longitude: 81 22.863

1/2

Northing/Y: 4276910.036

Easting/X: 466837.664

Convergence: -0 14 16.58378

Scale Factor: 0.999613542

TANKS

MCKOWN CREEK

Latitude: 38 37.232

Longitude: 81 23.329

2/2

Northing/Y: 4274739.814

Easting/X: 466152.531

Convergence: -0 14 33.66949

Scale Factor: 0.999614108


RECEIVED
Office of Oil 8. Gas
NOV 2 0 2015

VVV Department of
Environmental Protection

Office of Oil and Gar

DEC 28 2020

WV Department of Environmental Prote 13



Section 8

Geological Data Injection and Confining Zones To Gene Smith W.V DEP

2-12-2016

D&D Oil Well Summers 7

API Number 2D0871623

Section 8 Geological Data and Confining Zones.

Section 8 Continued

Deficiency C

The Big Lime confining layer is covering the Big Injun Sand so fluid with not migrate vertically. The Big Lime & depth is 1943'-2070', 127 Feet, See Brannock Resources attached dated 7-24-2014 complete geological description of Walton oil field.

Deficiency D attached is contour map of the Big Lime formation in the Walton oil field.

Deficiency E, All residents rely on city water and the Walton public service district no water wells used in the area.

RECEIVED
Office of Oil and Gas

FEB 1 2 2016

WV Department of Environmental Protection

BRANNOCK RESOURCES

Michael C. Brannock
Petroleum Geologist
A.A.P.G. Cert. #2878

July 24, 2014

Mr. Hugh Dale, Vice President D D Oil Company P.O. Box 406 Spencer, West Virginia

Re: [. B. Summers #7

Dear Hugh:

I have marked the location of your I. B. Summers #7 well on the maps that you emailed to me. Those maps are part of Bulletin 43 that covers the Rock Creek Field located in Roane County. Comparing the well spot maps with the digital data from the West Virginia Geological Survey, I feel very confident of the location of your well with regards to those shown on Figure 17, page 25. I am enclosing a map generated from the data in the survey's data base for comparison. The pattern of the well spots and well types from the bulletin maps and my digitally derived map match up very well.

I downloaded log copies from the survey's library and constructed a cross section through the Summers #7 well to show the formations directly above the Big Injun sandstone per your request. Only a gamma ray/induction open hole log was run on the Summers #7. Comparing this log with 2 other gamma ray/density logs adjacent to your well (see attached map), the log tops for the Summers #7 are:

Little Lime: 1891'-1938' (47') Pencil Cave: 1938'-1943' (5') Big Lime: 1943'-2070' (127') Big Injun: 2070'-2124' (54')

The Little Lime, Blg Lime and Big Injun appear to be very consistent in thickness and lithology in this area with a few minor changes at the formation contacts. The Pencil Cave sometimes does not show up very well due to pinchouts between wells. Based upon this cross section it would be reasonable to assume that there is sufficient barrier between the Big Injun and overlying formations to prevent the migration of fluids provided there is good mechanical integrity of the well and proper operational practices are followed.

If you need additional information, please feel free to call me at my office.

Sincerely yours,

Michael C. Brannock, Owner BRANNOCK RESOURCES

P.O. Box 1764

Parkersburg, WV 26102

V: 304-485-2878

E: brannockres@suddenlink.net

RECEIVED Gas

JUL 2 5 2014

Environmental Protection

To Gene Smith W.V. DEP

2-12-2016

API Number 2D0871623

Section 8 Geological Data and Confining Zones.

Deficiency F

The Hydrostatic Fluid Level is at 2077 Feet.

RECEIVED
Office of Oil and Gas

FEB 1 2 2016


WV Department of Environmental Protection

MV Danarhmant

Office of Oil & Gas

Fig. 2

Structure and Isopach map on Big Injun sand



Primary reserves will justify the development and investment, and a good possibility that secondary may contribute as much as primary.

To be successful in finding reserves of more than 5 million bbl, investigation of known blanket sands is essential, and then the method of determination of the new production limits must be established.

4. A reliable and economical method for determining relative permeabilities within Blue Creek was developed and used to great success.

 Good production practices and methods are a must, and contribute in every way to the ultimate success of the program.

Walton field. Walton field is located in Harper, Walton, and Smithfield districts, Roane County, W.Va.

The field was discovered in 1907, and approximately 9,000 acres had been developed up until 1966. Since 1966, approximately 300 wells have been drilled on 5,500 acres for an erage spacing of 18 acres per well.

Almost all the production in this field is from the Big Injun at an average depth of 1,940 ft. Fig. 1 shows this trend, old and new development, and its relation to Blue Creek field.

Blue Creek. Blue Creek field is located in Big Sandy and Elk districts of Kanawha County, W.Va.

There were eight to 10 producing wells drilled about 1920, three or four of which were still producing in the Big Injun sand in 1967.

There have been 78 wells drilled since the spring of 1967 to the summer of 1969. There now have been 67 leases validated which comprise 5,200 acres. All production from this field is from Big Injun sand at an average depth of 1,870 ft.

There is presently room for approximately 250 additional wells to be drilled on 20-acre spacing.

Reservoir and structural condition. The field is basically a syncline laying between the intersection of two major anticlines.

One anticline trending northeastsouthwest known as the Arches Fork and the other trending north-south known as the Milliken.


The trap is formed by a lithology change on the north side of the field where the Big Injun sand thickness grades from 20 to 0 ft over a distance of less than 800 ft.

Within the syncline, the sand characteristics are such that shale content within the sand is less than 10% of the pore space, with permeabilities averaging 20 md, porosity 21%, and thickness greater than 35 ft.

On the other three sides of the syncline, sand thickness remains essentially constant, (about 35 ft) but as structure approaches -950 ft subsea, shale content reaches 25% of the pore space and reduces the permeability to less than 5 md., thereby effecting a permeability trap for the nonmovement of oil beyond that point of permeability reduction. The proven producible area of this field has now been determined to be 7,200 acres.

As a result of this development, application of the disposal systems, hydraulic fracturing, the concept that movable oil can be produced downdip from nonmovable oil—provided that a dispersed clay system is available to effectively reduce permeability—major reservoirs can now be found whenever reevaluation in these areas are made.

The ability, through logging-coring analysis, to determine where permeability reduction occurs can set the limits of a producible oil reserve located structurally below and connected directly to an updip movable



RECEIVED
Office of Oil and Gas FEB 1 8 2015





Figure 20b

WV Department of Environmental Protection

RECEIVED
Office of Oil and Gas








Figure 16. Geologic structure map for Rock Creek field. Detum is the top of the Loyalhanna limestone (ac identified by drillers). Distribution of wells that produce oil and water parallel the field structure. Cutiliers may represent wells drilled into former oil-bearing strata into which water has encroached. Absence of wells reporting oil and water production in north-center of field is probably due to incomplete drillers' records. Wells in this area have produced significant amounts of water (M. Brannock, Quaker State, personal communication, 1993). Contour internal is 50 feet. field structure. Outliers may represent wells drilled into former oil-bearing strain into which

Stratigraphic Cross Section "SUMMERS_7" : Equally Spaced Logs Datum = BIG INJUN

Vertical Scale = 1 in per 100 ft SUMMERS_7.xsd; 07/23/14



TD=1974.00




Environmental Protection





PERFORATING

Control of the last of the las	-		
	COMPA	NY JOSEP	H S. GRU
	WELL_	I. B.	SUMMERS
	FIELD_	WALTO	N
	COUNT	Y ROANE	
FIELD or LOCATION WELL COMPANY	Location	WALTO	N DIST.
COUL FIELD LOCA WELL COM	Sec	Twp	Rge
Permanent Datu Log Measured Fr Drilling Measure	m:k omk	ROUND LEVE	L; Ele Ft. Above
Date		8/5/67	
Run No.		ONE	
Type Log		PDC-GR	
Depth — Driller		2150	
Depth - Logger		2141	
Bottom logged	interval	2138	
Top logged inte		1850	
Type fluid in ho		FRESH WAT	ER
Salinity, PPM	Cl.	-	
Density			
Level	45 E	FULL	
Max. rec. temp.,		1 /2 110110	
Operating rig t	ime	1/2 HOUR	
Recorded By Witnessed By		MALONE WESHE	
Willessed by		MESILE	
ROI	RE-HOLE REC	ORD	1
Bit Size	From	To	Size V
7 7/8	N/A	T.D.	4 1/2

DEPTH CONTROL SS #7 TATE WEST VIRGINIA Other Services: SCH-H Elev.: K.B. N/A D.F G.L. 936 EST COPY BEST COPY BY B	and borehole reference data were furnished by the customer.				WELL PERFORATED FROM 2077'-2095' 19 SHOTS	2111'-2115'	PERFORATED WITH 3 3/8" HYPER-JETS.							LEVEL WAS NOT AVAILABLE FROM OPEN HOLE LOG.						
	The well name, location	EQUIPMENT DATA	ONE	9	3 5/8	ا ن ن و	8".		General	3016	2016	HNTG.		* K.B. TO GROUND	E .	AMA RAY	1			
CASING RECORD It. From To SURF. T.D.	FOLD HERE	FOL	Run No.	Tool Model No.		Derr Model No.	Length		14 : 4 T	HOIST ITUCK NO.	Tool Serial No.		Remarks:			GAMMA RADIOACTIVITY				







WALTON

FIELD_

B. SUMMERS

WELL

ROANE COUNTY

STATE WEST VIRGINIA

Elev:



PERMIT #
ROA.1623

COMPANY.

WELL

FIELD_

COUNTY_

SEC.


PERMANENT DATUM GROUNE LOG MEASURED FROM K.B. DRILLING MEASURED FROM 7-29-6 DATE RUN NO. DEPTH - DRILLER 2150 DEPTH-LOGGER 21531 BTM. LOG INTER. 21101 TOP LOG INTER. CASING-DRILLER CASING-LOGGER BIT SIZE TYPE FLUID IN HOLE DENS. VISC. PH FLUID LOSS SOURCE OF SAMPLE Rm @ MEAS. TEMP. Rmf@MEAS.TEMP. (a Rmc@MEAS.TEMP. SOURCE Ref Rec Rm @ B. H. T. æ TIME SINCE CIRC. | HOURS MAX. REC. TEMP. EQUIP. LOCATION 1911 RECORDED BY RUGH


PERRIN


WITNESSED BY


	3i:	r	dw	Į (ell	
	GR	9,	nduction	ł.	_	
	JOSEPH	s.	GRUSS	_		
	1.B. S	UMME	RS #7			
	WALTON					
_	ROANE		STAT	E_W	.VA.	
	TWB		***	01	THER SERVICE	i\$:
=	LEVEL	E	RGE	+	EV: K.B	
<u>.</u>	FT. A	BOVE	PERM. DATU		D.F. G.L. 93	
	7-29-6	7		I	OPY	
_	21501 21531			ST C aila	ble	
_	2150' 2153' 2140' 1600'	112.0			ble -	
	21501 21531 21/101 16001		e v		-	
	2150: 2153: 2140: 1600: @ N/A MUD	cc	e v		-	СС
٥F	2150: 2153: 21/10: 1600: @ N/A 7 7/8: MUD	CC CC	e v	∂ila CC °F	-	٥F
o F	2150 1 2153 1 21/10 1 1600 1 @ N/A 7 7/8 1 MUD N/A	o F CC	@ @ @ @ @	op op	@	°F
٥F	21501 21531 21/101 16001 @ N/A MUD N/A	CC CC	@ @ @	∂ila CC °F	@	٥F
o F	2150 1 2153 1 21/10 1 1600 1 @ N/A 7 7/8 1 MUD N/A	o F CC	@ @ @ @ @	op op	@	°F
of of of	2153: 2153: 2140: 1600: @ N/A 7 7/8: MUD N/A	ok ok cc	@ @ @ @ @	or o	(Q) (Q) (Q) (Q)	or or


REMARKS NA.	NA.NOT AVAILABLE					
ES IN MUD	CHANGES IN MUD TYPE OF ADDITIONAL SAMPLES	NAI CAMPIEC			,	
DATE CAMBIE NO		29 July 2011			SCALE CHANGES	
DEBTE DELLED			TYPE LOG	OG DEPTH	SCALE UP HOLE	SCALE DOWN HOLE
TYPE FILLIN IN						
HOLE						
VISC.						
PH FLUID LOSS	9	35				
SOURCE OF SAMPLE		3			- 11	
Rm (" MEAS.TEMP.	d o (i)	10 (b)	07 7110		EQUIPMENT DATA	
Rmt (# MEAS.TEMP.			-	TOOL TYPE	IOOL POSITION	OTHER
				GAMMA RAY	77. 17. 17. 17. 17. 17. 17. 17. 17. 17.	
KINC (MEAS. IEMY.	d o (1)	10 W		INDUCTION	FREE	
SOURCE Rant Rinc						
Rm (/ B. H.T.	d o (a)	30 W				
Rmf @ B. H. T.	do (i)	do . w				
Rmc @ B.H.T.	do (d)					
TWY	GAMMA DAV	_		200		





























COMPANY JOSEPH S. GRUSS

WELL 1.B. SUMMERS #7

FIELD WALTON

LOCATION

COUNTY ROANE

STATE W.VA.

RGE

TWP.

SEC.

5\$C-108

NOV 2 0 2015

AS 03531 AM		=	MAX. REC. TEMP.	TWE SINCE CIRC	Ray @ B. W. T.	SOURCE Rand Ranc	RING MEAS. TEMP.	RMPAMEAS. TEMP.	-	-	-	_		Z		-	CASING - DRILLER	TOP LOG INTER	TM LOG INTRO		DROTM DOMES	SUN NO	DAYE	DRILLING MEASURED FROM	WATER GAMES BY BOT		Ēnv	iror	De nme	ye Mi	al	Pr	Commence of the Control of the Contr	3	DERMIT #		SS
D TOTAL	t	10101 1 117	No CHO OF		6 02		PERMIT	and the state of the state of	do of	N/A	22	NVA		1	7/7/08	1	9	2140		2020		10001		R	T CON	CMICOO	SEC.	LOCATION:	COUNTY	4 000000		WELL	Control of the Contro		COMPANY		
-		40.	OR O	4.5 50		A C. A.		TARREST CO.	- 6	N/N	- 5	N/A	MUUD	1/0	2/2		16001	21101	2 53 5	2150		1-69-67		B . FT. ABOVE PERM.	FRVEF	A Property	AMP		ROANE	The state of the s	WALTON	1.8. SUMMERS	Wilder Charles Street, Color		JOSEPH S.	GR 9	Bir
	The second secon	slo		do ®		40 60	-	-	None and Associated to the Party of the Part	William to the state of the sta		4	17	1	The state of the s	(B)	The state of the s	The state of the s	elderreas	0000			and the state of t	PERM. DATUM	770'	0.2%	a a		STATE	and and the statement of the statement o		RS #7			GRUSS	nduction	dw
Philipping of the Party of the		do		30 og		30 A)	(h)	(5)	And the same of th	66	-			The state of the s		0	Particular and project description of the second	410000000	9010	10py			6.1. 936		REC. R.B.			OTMER SURVICES:	V. VA.	-	DE	REC of C	8	20	Gas 20 of		ell


CANADALA	ges in m	ud type or	ADDITIO	DNAL SAN	PLES				SCALE CHANGES	
DATESA	imple no.				1000	TYPE	LOG	DEPTH		T =====
Depth —	DRILLER								SCALE UP HOLE	SCALE DOWN HOLI
TYPE FLI			_							
DENS.	VISC.		-+		-					
PH FL	UID LOSS		cc		cc					
SOURCE (of Sample					_			AMENIA SA	
Ren (ri ME	AS. TEMP.	Œ	96	(a)	0g	RUN NO.	TOOL		QUIPMENT DATA	
Rent & M	EAS.TEMP.	<u> </u>	og	(ar	0 F			The state of the s	TOOL POSITION	OTHER
Ranc (1 M	EAS.TEMP.	(u)	OF	(4)	OF			A RAY	FREE	
SOURCE	Rent Renc			1		-	INDU	CTION	FREE	
R ₁₀₀ (/ 8.	. 10. 7.	(a·	op	e	o _F					
Rand (i' 8	LH.T.	(e)	OF	a ·	o _F		·			The second secon
Rose (it t	B. H. T.	6	op	(p)	OF					

Office of Oil & Gas

NOV 2 0 2015

WV Department of Environmental Protection Recorded By Witnessed By Type Log
Depth — Driller
Depth — Logger
Depth — Logged interval
Top logged interval
Type fluid in hole
Salinity, PPM CI. Max. rec. temp., dog F. Operating rig time COUNTY Recorded Drilling Measured From Log Measured From Permanent Datum: 7/8 978 FIELD or. LOCATION WELL BORE-HOLE COMPANY From Sec. Location FIELD ALMOOD S MELL COMPANY RECORD 77 00 00 GROUND MALONE FULL PDC:-GR 2150 2141 2138 1850 FRESH 1 8/5/67 0 Eg Twp. WALTON DIST LEVE JOSEPH S. WATER Fr. Above Perm. Datum SUMMERS Size J Elev.: 936 Wg. STATE CASING IN. BEST COPY available SURF MEST VIRGINIA RECORD Elev.: K.B._N/A Other Services 50 õ 936 FOLD HERE The well name, location and borehole reference data were furnished by the customer. EQUIPMENT DATA Gamma Ray Run No. ONE Tool Madel No Diameter PERFORATED FROM 2077 '-2095' SHOTS 19 Det'r Model No G 2111'-2115' SHOTS Type SCINT RECEIVED Office of Oil and Gas PERFORATED WITH 3/8" HYPER-JETS 3 Length 811 DEC 28 2020 General Hoist Truck No. 3016 WV Department of Environmental Protection inst. Truck No. Tool Serial No. 3016 240 Location HNTG Remarks: TO GROUND LEVEL WAS NOT AVAILABLE FROM OPEN HOLE LOG

Office of Oil & Gas



WV Department of Environmental Protection

DEC 3 8 5050

RECEIVED Office of Oil and Gas


RECEIVED
Office of Oil & Gas

WV Department of Department of Protection

4708701623 GAMMA RAY HOACTIVITY INCREASES 19 Shots 5 2115 GAMMA RAY SCHL TD 2141 DBLR TD 2150 10_3/A 0F = 1 GL 936 STATE WEST VIRGINIA

Office of Oil & Gas

Structure and Isopach map on Big Injun sand



- Primary reserves will justify the development and investment, and a good possibility that secondary may contribute as much as primary.
- 3. To be successful in finding reserves of more than 5 million bbl, investigation of known blanket sands is essential, and then the method of determination of the new production limits must be established.
- 4. A reliable and economical method for determining relative permeabilities within Blue Creek was developed and used to great success.
- Good production practices and methods are a must, and contribute in every way to the ultimate success of the program.

Walton field. Walton field is located in Harper, Walton, and Smithfield districts. Roane County, W.Va.

The field was discovered in 1907, and approximately 9,000 acres had been developed up until 1966. Since 1966, approximately 300 wells have been drilled on 5,500 acres for an erage spacing of 18 acres per well.

Almost all the production in this field is from the Big Injun at an average depth of 1,940 ft. Fig. 1 shows this trend, old and new development, and its relation to Blue Creek field.

Blue Creek. Blue Creek field is located in Big Sandy and Elk districts of Kanawha County, W.Va.

There were eight to 10 producing wells drilled about 1920, three or four of which were still producing in the Big Injun sand in 1967.

There have been 78 wells drilled since the spring of 1967 to the summer of 1969. There now have been 67 leases validated which comprise 5,200 acres. All production from this field is from Big Injun sand at an average depth of 1,870 ft.

There is presently room for approximately 250 additional wells to be drilled on 20-acre spacing.

Reservoir and structural condition. The field is basically a syncline laying between the intersection of two major anticlines.

One anticline trending northeastsouthwest known as the Arches Fork and the other trending north-south known as the Milliken.

The trap is formed by a lithology change on the north side of the field where the Big Injun sand thickness grades from 20 to 0 ft over a distance of less than 800 ft.


Within the syncline, the sand characteristics are such that shale content

within the sand is less than 10% of the pore space, with permeabilities averaging 20 md, porosity 21%, and thickness greater than 35 ft.

On the other three sides of the syncline, sand thickness remains essentially constant, (about 35 ft) but as structure approaches -950 ft subsea, shale content reaches 25% of the pore space and reduces the permeability to less than 5 md., thereby effecting a permeability trap for the nonmovement of oil beyond that point of permeability reduction. The proven producible area of this field has now been determined to be 7,200 acres.


As a result of this development, application of the disposal systems, hydraulic fracturing, the concept that movable oil can be produced downdip from nonmovable oil—provided that a dispersed clay system is available to effectively reduce permeability—major reservoirs can now be found whenever reevaluation in these areas are made.

The ability, through logging-coring analysis, to determine where permeability reduction occurs can set the limits of a producible oil reserve located structurally below and connected directly to an updip movable



Stratigraphic Cross Section "SUMMERS_7" : Equally Spaced Logs Datum = BIG INJUN

Vertical Scale = 1 in per 100 ft SUMMERS_7.xsd; 07/23/14



Section 9

Operating Requirements

To Gene Smith W.V DEP

2-12-2016

D&D Well Summers 7

API Number 2D0871623

D&D Oil

Deficiency 2D0871623

Section 9

Operating Requirements Data

Section A

The fluid between in the 4 ½ casing annulus and tubing is filled with fresh water to conduct the mechanical integrity test.

Section B

D&D Oil is operating this well and fully intend to continue operating this well in compliance with rules, regulations and with the permit. Will continue to daily monitor the injection pressure, annulus pressure and record the volume. Data will be recorded on form wr-40 and continue to be submitted to the Office of Oil and Gas monthly.

RECEIVED
Office of Oil and Gas

FEB 1 2 2016

WV Department of Environmental Protection





INJECTATE

November 10, 2023

Mr. Hugh Dale Drilco Oil and Gas Corp PO Box 385 Grantsville, WV 26147

RE:

Project: DW 47 - 87 - 1623
Pace Project No.: 30632478

Dear Mr. Dale:

Enclosed are the analytical results for sample(s) received by the laboratory on October 19, 2023. The results relate only to the samples included in this report. Results reported herein conform to the applicable TNI/NELAC Standards and the laboratory's Quality Manual, where applicable, unless otherwise noted in the body of the report.

Some analyses were subcontracted outside of the Pace Network. The test report from the external subcontractor is attached to this report in its entirety.

The test results provided in this final report were generated by each of the following laboratories within the Pace Network:

- · Pace Analytical Services Beaver
- Pace Analytical Services Greensburg

If you have any questions concerning this report, please feel free to contact me.

Sincerely,

Skyler C. Richmond

skyler.richmond@pacelabs.com

Rich

(724)850-5600

Project Manager

Enclosures

Office of Oil and Gas

DEC 01 2023







CERTIFICATIONS

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

Pace Analytical Services Pennsylvania

1638 Roseytown Rd Suites 2,3&4, Greensburg, PA 15601

ANAB DOD-ELAP Rad Accreditation #: L2417 ANABISO/IEC 17025:2017 Rad Cert#: L24170

Alabama Certification #: 41590 Arizona Certification #: AZ0734 Arkansas Certification

California Certification #: 2950
Colorado Certification #: PA01547
Connecticut Certification #: PH-0694

EPA Region 4 DW Rad

Florida/TNI Certification #: E87683

Georgia Certification #: C040

Guam Certification
Hawaii Certification
Idaho Certification
Illinois Certification
Indiana Certification
Iowa Certification #: 391
Kansas Certification #: E-10358
Kentucky Certification #: KY90133
KY WW Permit #: KY0098221

...ouisiana DHH/TNI Certification #: LA010 Louisiana DEQ/TNI Certification #: 04086

Maine Certification #: 2023021 Maryland Certification #: 308

Y WW Permit #: KY0000221

Massachusetts Certification #: M-PA1457 Michigan/PADEP Certification #: 9991

Pace Analytical Services Beaver

225 Industrial Park Road, Beaver, WV 25813 Virginia VELAP 460148 West Virginia DEP 060 West Virginia DHHR 00412CM Missouri Certification #: 235
Montana Certification #: Cert0082
Nebraska Certification #: NE-OS-29-14
Nevada Certification #: PA014572023-03
New Hampshire/TNI Certification #: 297622
New Jersey/TNI Certification #: PA051
New Mexico Certification #: PA01457
New York/TNI Certification #: 10888
North Carolina Certification #: 42706
North Dakota Certification #: R-190
Ohio EPA Rad Approval: #41249

Oregon/TNI Certification #: PA200002-015 Pennsylvania/TNI Certification #: 65-00282 Puerto Rico Certification #: PA01457 Rhode Island Certification #: 65-00282

South Dakota Certification

Tennessee Certification #: TN02867

Texas/TNI Certification #: T104704188-22-18
Utah/TNI Certification #: PA01457223-14
USDA Soil Permit #: 525-23-67-77263
Vermont Dept. of Health: ID# VT-0282
Virgin Island/PADEP Certification
Virginia/VELAP Certification #: 460198
Washington Certification #: C868
West Virginia DEP Certification #: 143
West Virginia DHHR Certification #: 9964C
Wisconsin Approve List for Rad

North Carolina DEQ 466 Kentucky Wastewater Certification KY90039 Pennsylvania DEP 68-00839







SAMPLE SUMMARY

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

Lab ID	Sample ID	Matrix	Date Collected	Date Received
30632478001	WELL	Water	10/19/23 08:00	10/19/23 14:35

RECEIVED Office of Oil and Gas

DEC 01 2023

WV Department of Environmental Protection



SAMPLE ANALYTE COUNT

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

				Analytes	
Lab ID	Sample ID	Method	Analysts	Reported	Laboratory
30632478001	WELL	EPA 200.7	MFC	8	PASI-BV
		EPA 300.0, Rev 2.1	SMG	3	PASI-BV
		SM 4500-H+ B-11	KLD	1	PASI-BV
		EPA 900.0	REH1	2	PASI-PA
		EPA 903.1	MAR1	1	PASI-PA
		EPA 904.0	JJS1	1	PASI-PA

PASI-BV = Pace Analytical Services - Beaver PASI-PA = Pace Analytical Services - Greensburg

RECEIVED
Office of Oil and Gas

DEC 01 2023

Wv Department of Environmental Protection



ANALYTICAL RESULTS

Proiect:

DW 47 - 87 - 1623

Pace Project No.:

30632478

Sample: WELL	L	ab ID:	30632478001	Collected	10/19/2	3 08:00	Received: 10/	19/23 14:35 Ma	ıtrix: Water	
Parameters R	esults	Units	Report Limit	MDL	Reg. Limit	DF	Prepared	Analyzed	CAS No.	Qual
BVR 200.7 Metals Total	An	alvtical	Method: EPA 2	00.7 Prepar	ration Meth	od: EP/	\ 200.2			
BVK 200.7 Metals (Otal		-	ytical Services							
				0.92		100	10/30/23 13:45	11/03/23 17:38	7429-90-5	
Aluminum	1.2J	mg/L	2.0			100	10/30/23 13:45	11/03/23 17:38	7440-38-2	
Arsenic	ND	mg/L	2.0	0.52			10/30/23 13:45	11/03/23 17:38	7440-39-3	
Barium	313	mg/L	0.50	0.18		100	10/30/23 13:45	11/03/23 17:38	7440-70-2	
Calcium	20100	mg/L	50.0	8.6		100		11/03/23 17:38	7439-89-6	
Iron	84.8	mg/L	5.0	0.65		100	10/30/23 13:45		7439-96-5	
Manganese	3.1	mg/L	0.50	0.15		100	10/30/23 13:45	11/03/23 17:38	7440-23-5	
Sodium	58400	mg/L	500	476		1000	10/30/23 13:45	11/03/23 17:40		NO
Strontium	329	mg/L	1.0	0.16		100	10/30/23 13:45	11/03/23 17:38	1440-24-0	N2
BVR 300.0 IC Anions	An	alytical	Method: EPA 3	00.0, Rev 2.	1					
	Pa	ce Anal	ytical Services	- Beaver						
Bromide	1300	mg/L	500	155		5000		11/09/23 12:25	24959-67-9	
	130000	mg/L	5000	1000		5000		11/09/23 12:25	16887-00-6	
Chloride Sulfate	ND	mg/L	25000	5000		5000		11/09/23 12:25	14808-79-8	D3
		-		-00 II. D 44						
VR 4500H+ pH, Electrometric		-	Method: SM 45							
	Pa	ce Anal	lytical Services	- Beaver						
pH at 25 Degrees C	5.5	Std. Uni	its			1		11/03/23 11:22		H6,N2

RECEIVED
Office of Oil and Gas

DEC 01 2023

Wir Departmen U Environmental Protect



Pace Analytical Services, LLC 225 Industrial Park RD Beaver, WV 25813 (800)999-0105

Office of Oil and Gas

DEC 01 2023

Environmental Protection

QUALITY CONTROL DATA

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

QC Batch:

625739

QC Batch Method:

EPA 200.2

Analysis Method:

Analysis Description:

LIA

Laboratory:

EPA 200.7 BVR 200.7 Metals, Total

Pace Analytical Services - Beaver

Associated Lab Samples:

Date: 11/10/2023 03:29 PM

30632478001

METHOD BLANK: 3050005

Associated Lab Samples:

30632478001

Matrix: Water

		Blank	Reporting			
Parameter	Units	Result	Limit	MDL.	Analyzed	Qualifiers
Aluminum	mg/L	ND	0.020	0.0092	11/02/23 15:37	
Arsenic	mg/L	ND	0.020	0.0052	11/02/23 15:37	
Barium	mg/L	ND	0.0050	0.0018	11/02/23 15:37	
Calcium	mg/L	ND	0.50	0.086	11/02/23 15:37	
Iron	mg/L	ND	0.050	0.0065	11/02/23 15:37	
Manganese	mg/L	ND	0.0050	0.0015	11/02/23 15:37	
Sodium	mg/L	ND	0.50	0.48	11/02/23 15:37	
Strontium	mg/L	ND	0.010	0.0016	11/02/23 15:37	N2

LABORATORY CONTROL SAMPLE:	3050006					
Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Aluminum	mg/L	2	2.0	102	85-115	
Arsenic	mg/L	2	2.2	109	85-115	
Barium	mg/L	2	2.1	105	85-115	
Calcium	mg/L	40	42.1	105	85-115	
iron	mg/L	2	2.2	109	85-115	
Manganese	mg/L	2	2.2	108	85-115	
Sodium	mg/L	20	20.5	102	85-1 15	
Strontium	mg/L	2	2.1	104	85-115 N	12

MATRIX SPIKE & MATRIX	SPIKE DUPL	ICATE: 3050	031		3050032							
Parameter	Units	30633377001 Result	MS Spike Conc.	MSD Spike Conc.	MS Result	MSD Result	MS % Rec	MSD % Rec	% Rec Limits	RPD	Max RPD	Qual
Aluminum	mg/L	0.048	2	2	2.2	2.1	108	105	70-130	2	20	
Arsenic	mg/L	ND	2	2	2.2	2.2	111	109	70-130	2	20	
Barium	mg/L	0.046	2	2	2.2	2.1	105	103	70-130	2	20	
Calcium	mg/L	26.1	40	40	67.3	66.8	103	102	70-130	1	20	
Iron	mg/L	0.74	2	2	2.5	2.5	89	86	70-130	2	20	
Manganese	mg/L	0.053	2	2	2.2	2.2	107	105	70-130	2	20	
Sodium	mg/L	64.7	20	20	84.2	84.8	97	101	70-130	1	20	
Strontium	mg/L	0.27	2	2	2.4	2.3	105	103	70-130	2	20	N2

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.



QUALITY CONTROL DATA

Project:

DW 47 - 87 - 1623

Pace Project No.: 30

30632478

MATRIX SPIKE & MATRIX	SPIKE DUPL	ICATE: 3050	033		3050034							
Parameter	Units	30633755001 Result	MS Spike Conc.	MSD Spike Conc.	MS Result	MSD Result	MS % Rec	MSD % Rec	% Rec Limits	RPD	Max RPD	Qual
Aluminum	mg/L	113 ug/L	2	2	2.3	2.3	109	109	70-130	0	20	
Arsenic	mg/L	ND	2	2	2.3	2.3	113	113	70-130	0	20	
Barium	mg/L	9.8 ug/L.	2	2	2.2	2.2	107	107	70-130	0	20	
Calcium	mg/L	21000 ug/L	40	40	64.2	64.5	108	109	70-130	0	20	
Iron	mg/L	160 ug/L	2	2	2.4	2.4	111	111	70-130	0	20	
	mg/L	26.8 ug/L	2	2	2.2	2.2	110	110	70-130	0	20	
Manganese Sodium	mg/L	53700 ug/L	20	20	76.6	77.8	114	120	70-130	2	20	
Strontium	mg/L	124 ug/L	2	2	2.3	2.3	107	107	70-130	0	20	N2

RECEIVED Office of Oil and Gas

DEC 01 2023

WV Department of Environmental Protection

Page 7 of 33

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.



QUALITY CONTROL DATA

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

QC Batch:

Bromide Chloride Sulfate 628497

QC Batch Method:

EPA 300.0, Rev 2.1

Analysis Method:

EPA 300.0, Rev 2.1

Analysis Description:

BVR 300.0 IC Anions

Laboratory:

Pace Analytical Services - Beaver

Associated Lab Samples:

30632478001

METHOD BLANK: 3063897

7

Matrix: Water

Associated Lab Samples:

Date: 11/10/2023 03:29 PM

30632478001

		Blank	Reporting			
Parameter	Units	Result	Limit	MDL	Analyzed	Qualifiers
3	mg/L	ND	0.10	0.031	11/09/23 22:05	
•	mg/L	ND	1.0	0.20	11/09/23 22:05	
	mg/L	ND	5.0	1.0	11/09/23 22:05	

LABORATORY CONTROL SAMPLE:	3063898	O. ite.	1.00	100	0/ Das	
Parameter	Units	Spike Conc.	LCS Result	LCS % Rec	% Rec Limits	Qualifiers
Bromide	mg/L	1	1.0	103	90-110	
Chloride	mg/L	25	23.9	96	90-110	
Sulfate	mg/L	50	47.3	95	90-110	

MATRIX SPIKE & MATRIX S	PIKE DUPL	ICATE: 3063	902		3063903	3						
Parameter	Units	30633808001 Result	MS Spike Conc.	MSD Spike Conc.	MS Result	MSD Result	MS % Rec	MSD % Rec	% Rec Limits	RPD	Max RPD	Qual
Bromide	mg/L	<0.031	1	1	1.0	1.1	102	107	90-110	5	20	
Chloride	mg/L	0.40J	25	25	24.4	25.0	96	99	90-110	3	20	
Sulfate	mg/L	2.9J	50	50	51.1	51.5	96	97	90-110	1	20	

MATRIX SPIKE & MATRIX S	PIKE DUPL	ICATE: 3063	904		3063905							
Parameter	Units	30633811001 Result	MS Spike Conc.	MSD Spike Conc.	MS Result	MSD Result	MS % Rec	MSD % Rec	% Rec Limits	RPD	Max RPD	Qual
Bromide	mg/L	<0.031	1	1	1.1	1.0	110	103	90-110	7	20	
Chloride	mg/L	0.42J	25	25	25.0	24.3	98	95	90-110	3	20	
Sulfate	mg/L	3.0J	50	50	51.0	50.1	96	94	90-110	2	20	

RECEIVED
Office of Oil and Gas

DEC 01 2023

WV Department of Environmental Protection

Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.



QUALITY CONTROL DATA

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

QC Batch:

626957

QC Batch Method:

SM 4500-H+ B-11

Analysis Method:

SM 4500-H+ B-11

Analysis Description:

4500H+BBV pH, BV

Laboratory:

Pace Analytical Services - Beaver

Associated Lab Samples: SAMPLE DUPLICATE:

30632478001

3056208

30632478001 Result

Dup

Result **RPD** Max RPD

Qualifiers

pH at 25 Degrees C

Units Std. Units

Std. Units

5.5

5.5

0

20 H6,N2

SAMPLE DUPLICATE:

3056209

Parameter

Parameter

30633378003 Result Units

7.7

Dup Result

RPD

Max **RPD**

Qualifiers

pH at 25 Degrees C

Date: 11/10/2023 03:29 PM

7.7

0

20 H6,N2



Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.



ANALYTICAL RESULTS - RADIOCHEMISTRY

Project:

DW 47 - 87 - 1623

30632478

Pace Project No.: 30632478						
Sample: WELL PWS:	Lab ID: 306324 Site ID :	78001 Collected: 10/19/23 08:00 Sample Type:	Received:	10/19/23 14:35	Matrix: Water	
Parameters	Method	Act ± Unc (MDC) Carr Trac	Units	Analyzed	CAS No.	Qual
	Pace Analytical Se	ervices - Greensburg				
Gross Alpha	EPA 900.0	3,116 ± 1,102 (1,379) C:NA T:NA	pCi/L	11/08/23 18:45	12587-46-1	
Gross Beta	EPA 900.0	1,481 ± 703 (1,061) C:NA T:NA	pCi/L	11/08/23 18:45	12587-47-2	
	Pace Analytical So	ervices - Greensburg				
Radium-226	EPA 903.1	968 ± 123 (12.0) C:NA T:92%	pCi/L	10/31/23 12:00	13982-63-3	
	Pace Analytical Se	ervices - Greensburg				
Radium-228	EPA 904.0	896 ± 162 (9.00) C:70% T:81%	pCi/L	10/30/23 16:20	15262-20-1	

RECEIVED
Office of Oil and Gas

DEC 01 2023

W Department of Environmental Protection





QUALITY CONTROL - RADIOCHEMISTRY

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

QC Batch:

624342

Analysis Method:

EPA 903.1

QC Batch Method:

EPA 903.1

Analysis Description:

903.1 Radium-226

Laboratory:

Pace Analytical Services - Greensburg

Associated Lab Samples:

mples: 30632478001

Matrix: Water

METHOD BLANK: 3043621 Associated Lab Samples: 3

Parameter

30632478001

Units

Analyzed

Qualifiers

Radium-226

0.0562 ± 0.291 (0.605) C:NA T:95%

Act ± Unc (MDC) Carr Trac

pCi/L

10/31/23 11:25



Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.





QUALITY CONTROL - RADIOCHEMISTRY

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

QC Batch:

QC Batch Method:

626018

EPA 900.0

Analysis Method:

EPA 900.0

Analysis Description:

900.0 Gross Alpha/Beta

Laboratory:

Pace Analytical Services - Greensburg

Associated Lab Samples:

Matrix: Water

METHOD BLANK: 3051393 Associated Lab Samples:

30632478001

30632478001

Parameter	Act ± Unc (MDC) Carr Trac	Units	Analyzed	Qualifiers
Gross Alpha	-0.059 ± 0.624 (1.75) C:NA T:NA	pCi/L	11/09/23 08:34	
Gross Beta	0.706 ± 0.784 (1.66) C:NA T:NA	pCi/L	11/09/23 08:34	



Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.





QUALITY CONTROL - RADIOCHEMISTRY

Project:

DW 47 - 87 - 1623

Pace Project No.:

QC Batch Method:

30632478

QC Batch:

624343 EPA 904.0

Analysis Method:

EPA 904.0

Analysis Description:

904.0 Radium 228

Laboratory:

Pace Analytical Services - Greensburg

Associated Lab Samples:

nples: 30632478001

Matrix: Water

METHOD BLANK: 3043628 Associated Lab Samples: 3

30632478001

Parameter

Act ± Unc (MDC) Carr Trac

Units

Analyzed

Qualifiers

Radium-228

 0.436 ± 0.406 (0.823) C:71% T:79%

pCi/L

10/30/23 16:22



Results presented on this page are in the units indicated by the "Units" column except where an alternate unit is presented to the right of the result.



QUALIFIERS

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

DEFINITIONS

DF - Dilution Factor, if reported, represents the factor applied to the reported data due to dilution of the sample aliquot.

ND - Not Detected at or above adjusted reporting limit.

TNTC - Too Numerous To Count

J - Estimated concentration above the adjusted method detection limit and below the adjusted reporting limit.

MDL - Adjusted Method Detection Limit.

PQL - Practical Quantitation Limit.

RL - Reporting Limit - The lowest concentration value that meets project requirements for quantitative data with known precision and bias for a specific analyte in a specific matrix.

1,2-Diphenylhydrazine decomposes to and cannot be separated from Azobenzene using Method 8270. The result for each analyte is a combined concentration.

Consistent with EPA guidelines, unrounded data are displayed and have been used to calculate % recovery and RPD values.

LCS(D) - Laboratory Control Sample (Duplicate)

MS(D) - Matrix Spike (Duplicate)

DUP - Sample Duplicate

RPD - Relative Percent Difference

NC - Not Calculable.

SG - Silica Gel - Clean-Up

U - Indicates the compound was analyzed for, but not detected.

N-Nitrosodiphenylamine decomposes and cannot be separated from Diphenylamine using Method 8270. The result reported for each analyte is a combined concentration.

Reported results are not rounded until the final step prior to reporting. Therefore, calculated parameters that are typically reported as "Total" may vary slightly from the sum of the reported component parameters.

Act - Activity

Unc - Uncertainty: For Safe Drinking Water Act (SDWA) analyses, the reported Unc. Is the calculated Count Uncertainty (95% confidence interval) using a coverage factor of 1.96. For all other matrices (non-SDWA), the reported Unc. is the calculated Expanded Uncertainty (aka Combined Standard Uncertainty, CSU), reported at the 95% confidence interval using a coverage factor

Gamma Spec: The Unc. reported for all gamma-spectroscopy analyses (EPA 901.1), is the calculated Expanded Uncertainty (CSU) RECEIVED at the 95.4% confidence interval, using a coverage factor of 2.0. Office of Oil and Gas

(MDC) - Minimum Detectable Concentration

Trac - Tracer Recovery (%)

Carr - Carrier Recovery (%)

Pace Analytical is TNI accredited. Contact your Pace PM for the current list of accredited analytes.

TNI - The NELAC Institute.

DEC 01 2023

WV Department of Environmental Protection

ANALYTE QUALIFIERS

Date: 11/10/2023 03:29 PM

Sample was diluted due to the presence of high levels of non-target analytes or other matrix interference. D3

Н6 Analysis initiated outside of the 15 minute EPA required holding time.

The lab does not hold NELAC/TNI accreditation for this parameter but other accreditations/certifications may apply. A N2

complete list of accreditations/certifications is available upon request.



QUALITY CONTROL DATA CROSS REFERENCE TABLE

Project:

DW 47 - 87 - 1623

Pace Project No.:

30632478

Lab ID	Sample iD	QC Batch Method	QC Batch	Analytical Method	Analytical Batch
30632478001	WELL	EPA 200.2	625739	EPA 200.7	626873
30632478001	WELL	EPA 300.0, Rev 2.1	628497		
30632478001	WELL.	SM 4500-H+ B-11	626957		
30632478001	WELL	EPA 900.0	626018		
30632478001	WELL	EPA 903.1	624342		
30632478001	WELL	EPA 904.0	624343		

Office of Oil and Gas

DEC 0 1 2023

WV Department of Environmental Protection

Analysis: I rection 2 Day 3 Day 1 Day 1 Pes 1 No Includ:
Samples received via: FEDEX UPS Clie Date/Time: Date/Time: 1435 Date/Time: 1435
Sample pH Acceptable Y N NA Sulfide Present Y N NA Lab USE ONLY: Lab Sample # / Comments: Lab USE ONLY: Lab Sample # / Comments: Y N NA Temp Blank Received: Y N N Therm IDH: Cooler 1 Temp Upon Receipt: Cooler 1 Therm Lor: Cooler 1 Therm Corr. Factor: Cooler 1 Temp Upon Receipt: Cool

DC#_Title: ENV-FRM-BEAV-0020 v02_SAMPLE CONTAINER FORM Effective Date: 4/14/2022

12	=======================================	10	9	œ	7	0	ဟ	4	ω	2	>	Sample Line Item	Site 1	Client
												Matrix		
			T	1	T	T	\top	T	\dagger		T	AG1H		
				T	T	T	T	T	T	T	T	AG1U	<u> </u>	
				T	T	T	T	T	T	1		AG2S		
				T	T	T	T	T		T		AG3S		
				T	T	T	T	T	T	T		AG4U		
					T	T		T	T	Т	ع	BP1N		
					T	T	Τ		T	T	-	BP1U		
					T		Г	T	T			BP1Z		
							Ī					BP2N		
					Γ							BP2S		
					Γ							BP2U		
												врзс		
												BP3N	,	
1												BP3S		
											-	BP3U		
												BP4N		
T												CG3H		
T												WGKU		
											1	WGFU		
												CG1U		
				Environmental Protection	§	DE	7	Office				AG74		
				nmen	Dep	בכ	7	9 i	7 1		i	DG9H		
	\perp			a P	artm	Ţ	4		() () ()		1	DG9S	z	Profile #
				otec	⊒ G			ui.			I	OH9U	otes	.# .#
				9				à				/G9A	Notes Log	
												/G9B		
											- 1	/G9H	200	181
1											15	/G9U	E	Q
1												N .	printering	20X52
L	1	_										P5T		2
1	1	_	4	4		_					Z	PLC	20	
+	-	+	+	4	4	4	4	_	4	1	+		Line	
+	+	+	+	-	4	4	4	-	4	+	+		6	
+	+	+	+	+	4	+	+	+	+	+	+			
													1	

	Glass	SS			Plastic		多い。
DG9H	40mL HCl amber voa vial	GBOD	300mL BOD Glass Stopper	BP1N	1L HNO, plastic	- Transfer	
DG9M	40mL MeOH clear vial	WGKU	8oz clear soil jar	BDIA			opwo/adta
nagp	Anni TSD amhor wint		Cot ocal ocal an	0710	it n2504 plastic	SP5T	120mL Coliform Na Thiosulfate
100	Home Tor amper vial	WGFU	4oz clear soil jar	BP1U	1L unpreserved plastic	ZPLC	Ziploc Bag
DG9S	40mL H ₂ SO ₄ amber vial	BJFU	402 unpreserved amber wide	BD17			
TOOT	Anni No This authority		Lor authococi sea author Mide	מיוע	IL NACH, Zn Acetate	Q N	General Unpreserved
	TOTAL ING THE BRIDER VIBI	CG3H	250mL clear glass HCl	BP2A	500mL NaOH, Asc Acid plastic	GNN	General Nitric
DG9U	40mL amber unpreserved	AG1H	1L HCl amber glass	BP2N		ONG	Conord Sulfania
VG9A	40mL Asc Acid glass	AG1S	1L H ₂ SO ₄ amber glass	BP2S		1	Conorm Canada
VG9B	40mL Sodium Bisulfate glass	AG1U	1liter unpres amber glass	BP2U	500ml inpresented plactic		
VG9C	40ml NaOH clear vial	1000			cocuit anjoreserved plastic		
	The state of the s	AGZO	South H2SO4 amper glass	BP2Z	500mL NaOH, Zn Acetate		N. N
MASA	40mt HCl clear viai	AG3S	250mL H ₂ SO ₄ amber glass	врзс	250mL NaOH plastic		Watrix
VG9T	40mL Na Thio, clear vial	AG3U	250mL unpres amber glass	BP3N		TW	Mater
VG9U	40mL unpreserved clear vial	AC74	Somi ombar alaa Nirior	7		94.1	AACICI
	Louis authiosol son oldai stal	AG/4	bumL amber glass NH4Cl	врзи	250mL unpreserved plastic	75	Solid
1		AG4U	100mL unpres amber glass	BP3S	250mL H ₂ SO ₄ plastic	잍	Non-aqueous liquid
Oualtra 👾 62889	RRO			BP4N	125mL HNO ₃ plastic	WP	Wipe Page 17 of 33
					The same of the sa		2000

Qualtra. . . : 62889

Pace® Analyucal Services, LLC

DW WP

Drinking Waterge 1 of 1

Page 17 of 33

DC#_Title: ENV-FRM-BEAV-0058 v03_Pace WV Sample Condition Upon Receipt (SC

Effective Date: 2/8/2023

WO#: 30632478 5 Due Date: 11/10/23

CLIENT: BV-DRILCO LIMS30 Lab Sample Condition Upon Receipt (West Virginia

LIMIOGO Lab Gampie Gomana	•	•		
Courier: Fed Ex UPS USPS Client	3rd Pa	arty Cou	ırier	Pace Other
Tracking #:				
Custody Seal on Cooler/Box/Containers Present: yes	no)	<u></u>	Seals intact: yes ono
	Туре	of Ice:	Wet	
Cooler Temperature Observed Temp 3.	<u>5</u> _	°C		ection Factor: 10 °C Final Temp: 35 °C
Thermal Preservation Requirement Met Yes No			1071	pH paper Lot# Date and Initials of person examining all 3 2 contents: CDW 10-20-3
	Yes	No	N/A	
Chain of Custody Present:	/			1.
Chain of Custody Filled Out:		/		2.Missing Analyses, Pres Type, # C
Chain of Custody Relinquished:	/			3.
Sampler Name & Signature on COC:	/			4.
Sample Labels match COC: -Includes date/time/ID Matrix:	W	7		5.
Samples Arrived within Hold Time:	/			6.
Short Hold Time Analysis (<72hr remaining):	-			7.
Rush Turn Around Time Requested:		/		8.
Sufficient Volume:	/			9.
Correct Containers Used:	4	_		10.
-Pace Containers Used:	4	_	-	(
Containers Intact:	/			13.
Orthophosphate field filtered:	-		/	12.
Hex Cr Aqueous sample field filtered:			/	13.
-pH adjusted within 24 hours? (If yes, indicate acid lot #)	-		/	
Filtered volume received for Dissolved tests:	-	_	/	14.
All containers have been checked for chemical preservation:	/			15.
exceptions: VOA, coliform, O&G, LLMercury, Non-aqueous mat	rix			
All containers meet method/chemical preservation requirements:				Initial when completed COW Date: 10 - 30 - 33
				Tests not preserved:
Headspace in VOA Vials:			/	16.
Trip Blank Present:			/	17.
RECEIVED				Initial when DW Date: 10 - 20 - 23
Office of Oil and Gas				20160
DEC 0 1 2023				
WV Department of Environmental Protection				
The State of the State of the Project Man	aner cir	see the	SREE	Review schedule in LIMS. The status may be reviewed in the Status section

^{*}PM review is documented electronically in LIMS, when the Project Manager closes the SRF Review schedule in LIMS. The status may be reviewed in the Status section of the Workorder Edit Screen.

Rettoykined by/Company; (Signature) Co. J. G. J. Sank 10-15. 2.3	shed by/Company: (Signature) Date. (C)		Relinquished by/Company: (Signature) Date/Time:	Shirt Area)	Customer Remarks / Special Conditions / Possible Hazards:		106 0 108 108 108 108 108 108 108 108 108 1	e i	n in in	PE	7	านฏ			8/2/1		Customer Sample ID Matrix * Grab	* Matrix Codes (Insert in Matrix box below): Drinking Water (DW), Ground Water (GW), Wastewater (WW), Product (P), Soil/Solid (SI), Oil (OL), Wipe (WP), Air (AR), Tissue (TS), Bioassay (B), Vapor (V), Other (OT)	[] Hold: [] 2 Day [] 4 Day [] 4 Day [] 4 Day [] 5 Day [] 5 Day [] 4 Day [] 5	posal: Rush: Same Day	F	enature):	Collected By (print): Purchase Order #: Quote #:	7 //4 / Site/Facility ID #:	5 47-87-1623	nber:		A N NI	6x 406 Speacer till	DOI'l Compa	:AllaiyCal	
Date/Time: Re/E) yed by/Company: (Signature)	Received by Company:	3	Time: パピー Received by/Company: (Signature)	Radchem sample(s) screened (<500 cpm):	Packing Material Used:	Type of ice Used: Wet Blue Dry	22									1/1/4 2005 1/1/4	Date Time Date Time	Collected (or Composite End	W), Ground Water (GW), Wastewater (WW) ue (TS), Bioassay (B), Vapor (V), Other (OT)	rges Apply) Analysis:	, Ag			DW PWS ID #: . DW Location Code:	Compliance Monitoring?	Roane	State: County/City: Time Zone Collected:	- I		<u>ک</u> ن	Billing Information: Company DD 011 Company PO Box 401	Chain-of-Custody is a LEGAL DOCUMENT - Complete all relevent fields	CHAIN-OF-CUSTODY Analytical Request Document
(Signatu)re) Date/Time: 1435	(Signature) Date/Time:	(Date/Time	Y N NA Samples received via:	Lab Tracking #:	None SHORT HOLDS PRESENT (<72 hours):				1 6 6			8				1 to 100	Res #of A A								CT [XLET	-		_	276 Container Preservative Type		fields	Iment LAB USE ONLY- Affix Wo
W W SE		Table	MTJLLA	Client Courier Pace Courier	2774321	NT (<72 hours): Y N N/A	L							2 P P P P P P P P P P P P P P P P P P P	8 25 2			Lab S	Lead		Resid	USDA Res	Samp I.	Correc	Custoc Collec Bottl	Custoc	Analyses Lab Profile/Line:	(C) ammonium hydroxide, (D) TSP, (U) Unpreserved, (O) Other	** Preservative Types: (1) nitric acid, (2) sulfuric acid, (3) hydrochloric acid, (4) sodium hydroxide, (5) zinc acetate, (6) methanol (7) sodium bisulfate (8) sodium thiosulfate, (9) heyane (A) accordic acid (6) ammonium sulfate	ervative Type	3063247		AFFEX WO#: 30632478
Non Conformance(s): Page:	Trip Blank Received: Y N NA HCL MeOH TSP Other	Mon Sous	· ·	Cooler 1 Therm Corr. Factor:oC Cooler 1 Corrected Temp:oC	eceipt:	Lab Sample Temperature Into:		The second secon			0470	No Analysis Pres Tide	NON-CONFORMANCE					Lab Sample # / Comments		bresent fps:	Chloring Fresent Y N	V.A. Requirated Soils Somples in Holding Time V.A.NA Samples in Holding Time V.A.NA	D Ice Y N	મ મ	Custody Signatures Present Y N NA Collector Signature Present Y N NA Bottles Intact		ofile/Line: Sample Receipt Checklist:		sodium hydroxide, (5) zinc acetate, bic acid (A) ammonium sulfate				532478

site e Sample Line Item **Slient** Matrix AG1H Thurshus its. WY Detect AG1U DEC 0 1 50/3 AG2S AG3S REDEIVED AG4U C BP1N BP1U BP1Z BP2N BP2S BP2U BP3C BP3N BP3S BP3U BP4N CG3H WGKU WGFU CG1U AG74 DG9H Profile # DG9S Notes Log eventhing DH9U VG9A VG9B VG9H VG9U GN-SP5T 200 ZPLC MA OO DE

N

DC#_Title: FNV-FRM-BEAV-0020 v02_SAMPLE CONTAINER FORM Effective : 4/14/2022

1

8 9 co 7 တ CT 4 ယ

12

1	Qualtray ID: 62880			VG9U	Ţ	VCoT	Henv	VG9C	Ĭ	Vapp !	VG9A	טפטט	31	DG9T	Deac	313	DG9P	DG9M		DOGE	
	77.73					1															194. St. 40.
Č	RO			40mL unpreserved clear vial	*OTHE NATIONAL CLEAR VIA	On No This all and the state of	40ml HOI clear viol	40mL NaOH clear vial	40TH South Bisultate glass	Anna South Birth	40ml Asc Acid class	40mL amber unpreserved		40mL Na Thio amber vial	40mL H ₂ SO ₄ amber vial	Contract and and	40ml TSD ambervial	40mL MeOH clear vial	FORTIE FICE ATTIONS VOM VINI	Glass	
		7040	À	AG74	AG3U	AGSS	7020	2000	AG1U	AGIO	202	AG1H	Coor	2000	BJFC	WGFO		WGKU	GBOD	88	
Pace® Analytical Services, LLC	1	nume unpres amber glass	000	60mL amber glass NH4CI	250mL unpres amber glass	250mL H ₂ SO ₄ amber glass	occur izeo4 amper glass	SOOT H SO ATTACK	1liter unpres amber glass	IL 12504 amber glass		1L HCI amber glass	Zouthit clear glass HCI	250	4oz unpreserved amber wide	402 clear soil jar	יייייייייייייייייייייייייייייייייייייי	807 clear soil jar	300mL BOD Glass Stopper		
services, LLC	BP4N	BP3S	0.00	בממ	BP3N	BP3C	BPZZ	2	BP2U	BP2S		BDON	BP2A		RP17	BP1U	27 70	0040	BP1N		
	125mL HNO ₃ plastic	250mL H ₂ SO ₄ plastic	DIASTIC		250mL HNO ₃ plastic	250mL NaOH plastic	500mL NaOH, Zn Acetate		500mL unpreserved plastic	500mL H ₂ SO ₄ plastic	Section Carried Carrie	SOOM HNO Places	500mL NaOH, Asc Acid plastic	in Machine	1) NaOH 70 Applied	1L unpreserved plastic	TL H2SO4 plastic		1L HNO ₃ plastic	Plastic	
MG	WP	2	S		TW						GING	2	GNN	GN		ZPLC	SP5T	1	7	. 7.5	
Drinking Waterge 1 of 1	Wipe	Non-aqueous liquid	Solid		Water	Watrix					General Sulturic		General Nitric	General Unpreserved		Ziploc Bag	120mL Coliform Na Thiosulfate	**:pc/Ongo	Wine/Swah	Misc.	

DC#_Title: ENV-FRM-BEAV-0058 v03_Pace WV Sample Condition Upon Receipt (SC'

Effective Date: 2/8/2023

WO#: 30632478

PM: SCR

Due Date: 11/10/23

CLIENT: BY-DRILCO

LIMS30 Lab Sample Condition Upon Receipt (West Virginia

Courier: Fed Ex UPS USPS Client	3rd P	arty Co	urier	Pace Other
Tracking #:				
Custody Seal on Cooler/Box/Containers Present: yes	□ n	9		Seals intact: yes no
Thermometer Used 14	Туре	of Ice:	Wet) Blue None
Cooler Temperature Observed Temp 3	3	° C	Corre	ection Factor: 10 °C Final Temp: 35 °C
Thermal Preservation Requirement Met Yes No				pH paper Lot# Date and Initials of person examining
The final test and the second				224322 contents: COW 10-20-83
	Yes	No	N/A	
Chain of Custody Present:	/			1.
Chain of Custody Filled Out:		/		2. Missing Analyses, Pres Type, Hal Chs.
Chain of Custody Relinquished:	/			3.
Sampler Name & Signature on COC:	/			4.
Sample Labels match COC:		Z		5,
-Includes date/time/ID Matrix:	W	T	-	
Samples Arrived within Hold Time:	_			6.
Short Hold Time Analysis (<72hr remaining):				7.
Rush Turn Around Time Requested:		/		8.
Sufficient Volume:	/			9.
Correct Containers Used:	4			10. Office RECEIVED of Oil Grad Gas
-Pace Containers Used:	/			of Oil Oil Oil
Containers Intact:	/			II. DEC O I
Orthophosphate field filtered:			/	12. 2023
Hex Cr Aqueous sample field filtered:			/	13. Environmental Department of .
-pH adjusted within 24 hours? (If yes, indicate acid lot #)			/	orunental oruneri, or.
Filtered volume received for Dissolved tests:			/	14.
All containers have been checked for chemical preservation:	/			15.
exceptions: VOA, coliform, O&G, LLMercury, Non-aqueous mate	rix			
All containers meet method/chemical preservation requirements:	/			Initial when Dow Date: 10-30-33
				Jests not preserved:
Headspace in VOA Vials:			/	16.
Trip Blank Present:			/	17.
				completed DW Date: 10 - 20 - 23
Comments:				
The second secon				

^{*}PM review is documented electronically in LIMS, when the Project Manager closes the SRF Review schedule in LIMS. The status may be reviewed in the Status section of the Workorder Edit Screen.



2005 N. Center Ave. Somerset, PA 15501

814/443-1671 814/445-6666 FAX: 814/445-6729

Tuesday, October 31, 2023

Skyler Richmond PACE ANALYTICAL 1638 ROSEYTOWN ROAD SUITES 2, 3, & 4 GREENSBURG, PA 15601

Order No.: G2310E26

Dear Skyler Richmond:

Geochemical Testing received 1 sample(s) on 10/24/2023 for the analyses presented in the following report.

There were no problems with sample receipt protocols and analyses met the TNI/NELAC, EPA, and laboratory specifications except where noted in the Case Narrative or Laboratory Results.

If you have any questions regarding these tests results, please feel free to call.

Sincerely,

Joelle Streczywilk

Environmental Laboratory Manager

RECEIVED
Office of Oil and Gas

DEC 01 2023

WAY Department of Environmental Protection

Report(s) To: Penny Westrick



Geochemical Testing

CLIENT:

PACE ANALYTICAL

Project:

Lab Order:

G2310E26

CASE NARRATIVE

Date: 31-Oct-23

No problems were encountered during analysis of this workorder, except if noted in this report.

Under West Virginia's Laboratory Certification Program, Geochemical Testing's Laboratory Certificate I.D. is 141.



Glossary:

 \ensuremath{H} - Method Hold Time exceeded and is not compliant with 40 CFR 136 Table II.

U - The analyte was not detected at or above the listed concentration, which is below the laboratory quantitation limit.

B - Analyte detected in the associated Method Blank

Q1 - See case narrative

ND - Not Detected

MCL - Contaminant Limit

J - Indicates an estimated value.

Q - Qualifier

QL -Quantitation Limit

DF - Dilution Factor

S - Surrogate Recovery outside accepted recovery limits

T - Sample received above required temperature and is not compliant with 40CFR136 Table II.

T1 - Sample received above required temperature

MDA - Minimum Detectable Activity.

** - Value exceeds Action Limit

TICs - Tentatively Identified Compounds.

E - Value above quantitation range



Glossary (continued)

- Spike recovery limits are not applicable when the sample concentration exceeds the spike concentration by a factor of four or greater.
- B Dilution water blank exceeded method criterion.
- C1 CCV recovery above the acceptance limits. Results may be biased high.
- C2 CCV recovery below the acceptance limits. Results may be biased low.
- C3 ICV recovery above the acceptance limits. Results may be biased high.
- C4 ICV recovery below the acceptance limits. Results may be biased low.
- C5 Positive values verified by second column confirmation.
- C6 Confirmation analysis by another detector or chromatographic column was not performed.
- D1 The analysis did not meet the minimum DO depletion of at least 2 mg/L.
- D2 The analysis did not meet the minimum residual DO of at least 1 mg/L.
- D3 Sample required dilution due to a matrix interference.
- D4 Sample was diluted in the extraction steps due to marked matrix interferences.
- D5 Sample required dilution due to a chloride interference.
- D6 Sample was diluted and the reporting limits were raised to achieve method compliant internal standard recovery.
- D7 Sample was digested at a dilution due to the formation of a postdigestion precipitate.
- DP Sample was digested at a dilution to achieve method compliant natrix spike recovery.
- D9 Sample was digested at a dilution to meet method compliant digestion criteria.
- E2 Unable to obtain a stable weight within specified limits due to sample matrix. Value is estimated.
- F1 Fecal sample tested positive for residual chlorine.
- H1 Due to under-depletion from the initial dilutions for BOD, the sample was reanalyzed outside the hold time.
- H2 Due to over-depletion from the initial dilutions for BOD, the sample was reanalyzed outside the hold time.
- H3 Sample was re-analyzed outside of hold time due to error during original analysis.
- H4 The Nitrite result used to report Nitrate was analyzed past the 48-hour holding time.
- Internal standard recovery above method acceptance limits. Results are estimated.
- Internal standard recovery was below method acceptance limits. Results are estimated.
- IP One of the instrument performance checks () did not meet the acceptance criteria.
- L1 LCS above the acceptance limits. Result may be biased high.
- L2 LCS below the acceptance limits. Result may be biased low.
- L3 Analyte was spiked into the LCS, but was not recovered.
- M1 Matrix Spike recovery above the acceptance limits.
- Matrix Spike recovery below the acceptance limits.
- Mi- The matrix spike failed high for the surrogate.
- M5 The matrix spike failed low for the surrogate.
- M6 The reporting limits were raised due to sample matrix interference.

- M7 Recovery for matrix spike could not be quantified due to matrix interference
- M8 Analyte was spiked into the MS, but was not recovered.
- M9 Analyte concentration was determined by the method of standard addition (MSA).
- N1 The lab does not hold accreditation from PA-DEP for this parameter by this method
- N2 PADEP does not accredit labs for this analyte by this method.
- N3 The lab is accredited for this method in West Virginia, but not in PA (its primary accrediting body).
- N4 PADEP does not accredit labs for this analyte by this method in drinking water.
- O1 The flashpoint tester cannot detect below 50 degrees F.
- O2 Result is temperature of the sample when flame observed. No flash observed. Result qualified.
- O3 The reporting limits were raised due to the high concentration of non-target compounds.
- O4 Sample was received with headspace.
- O5 Sample was received in incorrect container and is not compliant with 40CFR136 Table II.
- O6 Insufficient sample volume was received to comply with the method.
- P1 The pH of the sample was >2 and is not compliant with 40CFR136 Table !!.
- P2 Sample contained residual chlorine and is not compliant with 40CFR136 Table II
- P3 The pH of the sample was <10 and is not compliant with 40CFR136 Table II.
- P4 Field preservation does not meet EPA or method recommendations for this analysis.
- P5 Acid preservation may not be appropriate for the analysis of 2-Chloroethylvinyl ether.
- P6 Sample required additional preservative upon receipt.
- P7 The sample was received unpreserved.
- P8 The pH of the sample was < 9 and is not compliant with 40 CFR136 Table II.
- R Relative Percent Difference (RPD) was above the control limit.
- R1 RPD above control limits between matrix spike and MS duplicates.
- R2 RPD above the control limit between duplicates.
- R3 RSD above the control limit between replicates.
- R4 RPD above control limits between Inorganic Carbon check and spike.
- R5 RPD above control limits between control sample and control sample duplicates.
- S2 Surrogate recovery in the blank was below the control limit.
- S3 Surrogate recovery in the blank was above the control limit.
- S4 Surrogate recovery in the LCS is above the control limit.
- S5 Surrogate recovery in the LCS is below the control limit.
- SR Analyte recovery was outside the accepted recovery limits and above the control limit for RPD.
- T3 Target analyte found in trip/field blank.
- TC The MS tune check (tailing factor) did not meet the acceptance criteria.

Laboratory Results

Geochemical Testing

Date: 31-Oct-23

CLIENT:

PACE ANALYTICAL

Lab Order:

G2310E26

Client Sample ID: 30632478001

DF Date Prepared

Well

Project:

Analyses

Collection Date:

10/19/2023 8:00:00 AM

Lab ID:

Specific Gravity

G2310E26-001

Sampled By:

Pace

Matrix: AQUEOUS

DateReceived:

10/24/2023 11:11:46 AM

SPECIFIC GRAVITY

1.156

Result

Q

Analyst: **MAG** 0.3000 0.300

PQL Units

MDL

1

ASTM D1429-08 2011

Date Analyzed

10/30/23 7:45 AM





TESTING TESTING

Environmental and Energy Analysis

Quality Assurance Project Report
Prepared for
PACE ANALYTICAL
10/31/2023

David M. Glessner Quality Assurance Coordinator

Office RECEIVED of Oil and Gas

DEC 01 2023

WV Department of Environmental Protection

Project: WorkOrder: G2310E26 Client: PACE ANALYTICAL

Analytical QC Summary Report

Explanatory Notes

- Spike recovery limits are not applicable when the sample concentration exceeds the spike concentration by a factor of four or greater.
- Matrix Spike and MS Duplicates are sample specific controls and are not used to evaluate the analytical
- ω Laboratory duplicate. If one or both of the values is less than 5 times the PQL, the allowed difference is +/- the PQL
- "R" indicates a relative percent difference (RPD) was above the acceptance limit between duplicate QC samples or sample specific duplicates.

RECEIVED
Office of Oil and Gas DEC 01 2023

三八精编 宝宝

Client: PACE ANALYTICAL WorkOrder: G2310E26

Project:

Analytical QC Summary Report

SampleID: BLANK		SampT	SampType: BLANK		TestNo: ASTM D1429-08	TM D142		Prep Date:			RunNo: 294828	1828
		Batchli	BatchID: R294828	8				Analysis Da	Analysis Date: 10/30/2023)23	SeqNo: 7696790	6790
Analyte	Caic Val	Units	PQL	Spk Val	SPKrefval	REC	Low Limit	High Limit	RPDrefval	RPD	RPDlimit	Qual
Specific Gravity	_		0.3					÷				
SampleID: G2310E26-001ADUP	01ADUP	SampT	SampType: DUP		TestNo: ASTM D1429-08	TM D14;	29-08	Prep Date:			RunNo: 294828	1828
		Batchil	BatchID: R294828	00				Analysis D	Analysis Date: 10/30/2023)23	SeqNo: 7696793)6793
Analyte	Calc Val	Units	PQL	Spk Val	SPKrefval	REC	Low Limit	High Limit	RPDrefval	RPD	RPDlimit	Qual
Specific Gravity	1.156		0.3						1.156		20	
SampleID: LCS		SampT	SampType: LCS		TestNo: ASTM D1429-08	TM D14:	29-08	Prep Date:			RunNo: 294828	4828
		Batchl	BatchID: R294828	œ				Analysis D	Analysis Date: 10/30/2023	023	SeqNo: 7696791	36791
Analyte	Calc Val	Units	PQL	Spk Val	SPKrefval	REC	Low Limit	Low Limit High Limit	RPDrefval	RPD	RPDlimit	Qual
Specific Gravity	1.046		0.3	1.039		100.7%	85	115				

RECEIVED
Office of Oil and Gas
DEC 01 2073

En outside

Analytical QC Summary Report

Project:

Qualifier	Description
	Spike recovery limits are not applicable when the sample concentration exceeds the spike concentration by a factor of four or greater.
8	
R1	Dilution water blank exceeded method criterion

DEC 01 2023

RECEIVED Office of Oil and Gas

WV Department of Environmental Protection

2 S D7 9 又 D3 2 Sample required dilution due to a chloride interference. Sample was diluted in the extraction steps due to marked matrix interferences Sample required dilution due to a matrix interference The analysis did not meet the minimum residual DO of at least 1 mg/L. The analysis did not meet the minimum DO depletion of at least 2 mg/L. Confirmation analysis by another detector or chromatographic column was not performed Sample was digested at a dilution due to the formation of a post-digestion precipitate Sample was diluted and the reporting limits were raised to achieve method compliant internal standard recovery.

G 2

Positive values verified by second column confirmation.

ICV recovery below the acceptance limits. Results may be biased low ICV recovery above the acceptance limits. Results may be biased high ß

CCV recovery below the acceptance limits. Results may be biased low. CCV recovery above the acceptance limits. Results may be biased high.

Value above quantitation range.

Sample was digested at a dilution to meet method compliant digestion criteria Sample was digested at a dilution to achieve method compliant matrix spike recovery

D9

Unable to obtain a stable weight within specified limits due to sample matrix. Value is estimated Fecal sample tested positive for residual chlorine.

Method Hold Time exceeded and is not compliant with 40CFR136 Table II

Due to under-depletion from the initial dilutions for BOD, the sample was reanalyzed outside the hold time

Due to over-depletion from the initial dilutions for BOD, the sample was reanalyzed outside the hold time.

Sample was re-analyzed outside of hold time due to error during original analysis.

The Nitrite result used to report Nitrate was analyzed past the 48-hour holding time

Internal standard recovery above method acceptance limits. Results are estimated

Internal standard recovery was below method acceptance limits. Results are estimated

One of the instrument performance checks () did not meet the acceptance criteria

Indicates an estimated value.

WorkOrder: G2310E26 Client: PACE ANALYTICAL

Project:

Analytical QC Summary Report

5	LCS above the acceptance limits. Result may be biased high.
2	LCS below the acceptance limits. Result may be biased low.
Ü	Analyte was spiked into the LCS, but was not recovered.
3	Matrix Spike recovery above the acceptance limits.
M2	Matrix Spike recovery below the acceptance limits.
M 4	The matrix spike failed high for the surrogate.
M ₅	The matrix spike failed low for the surrogate.
M6	The reporting limits were raised due to sample matrix interferen
M7	Recovery for matrix spike could not be quantified due to matrix
200	Analista was spiked into the NAC but was not specially

RECEIVED
Office of Oil and Gas DEC 01 2023

S Z 4 N Z Z PADEP does not accredit labs for this analyte by this method in drinking water. PADEP does not accredit labs for this analyte by this method The lab does not hold accreditation from PA-DEP for this parameter by this method The flashpoint tester cannot detect below 50 degrees F. Not Detected. The lab is accredited for this method in West Virginia, but not in PA (its primary accrediting body). Analyte concentration was determined by the method of standard addition (MSA) Analyte was spiked into the MS, but was not recovered

interference

9 03 2 2 Sample was received in incorrect container and is not compliant with 40CFR136 Table II. Sample was received with headspace. The reporting limits were raised due to the high concentration of non-target compounds. Result is temperature of the sample when flame observed. No flash observed. Result qualified.

P3 P3 2 Sample contained residual chlorine and is not compliant with 40CFR136 Table II The pH of the sample was >2 and is not compliant with 40CFR136 Table II. Insufficient sample volume was received to comply with the method

90

The pH of the sample was <10 and is not compliant with 40CFR136 Table II.

P5 Acid preservation may not be appropriate for the analysis of 2-Chloroethylvinyl ether Field preservation does not meet EPA or method recommendations for this analysis.

P6 Sample required additional preservative upon receipt.

The sample was received unpreserved.

P7

The pH of the sample was < 9 and is not compliant with 40 CFR136 Table II.

Qualified Data See Case Narrative.

Relative Percent Difference (RPD) was above the control limit.

'D above control limits between matrix spike and MS duplicates.

WV Department Environmenta ornesimon

Client: PACE ANALYTICAL WorkOrder: G2310E26

Project:

2

RPD above the control limit between duplicates.

Analytical QC Summary Report

23	RSD above the control limit between replicates.				
R4	RPD above control limits between Inorganic Carbon check and spike.				
7 5	RPD above control limits between control sample and control sample duplicates.		[ป) i	
W	Recovery for the spiked control sample outside accepted limits.	ganyol	20 2	- 17 M	
S2	Surrogate recovery in the blank was below the control limit.	Otto		192- 3	
S3	Surrogate recovery in the blank was above the control limit.	of (ს (>იი	ma.	
S4	Surrogate recovery in the LCS is above the control limit.	ice		ronr	
SS	Surrogate recovery in the LCS is below the control limit.		V	Envi	
SR	Analyte recovery was outside the accepted recovery limits and above the control limit for RPD.			1	
-1	Sample temperature received outside the regulatory limit and is not compliant with 40CFR Part136 Table II (for NPW samples).				
1	Sample temperature received outside the regulatory limit. (Primarily for SCM samples).				
T3	Target analyte found in trip/field blank			-	
7	The MS tune check (tailing factor) did not meet the acceptance criteria.				
	The analyte was not detected at or above the listed concentration, which is below the laboratory quantitation limit.		;		

Note 2: NA is used in the Laboratory QC report as "Not Applicable."

Chain of Custody

PASI Pittsburgh Laboratory Workorder: 30632478

Workorder Name: DW 47 - 87 - 1623

Results Requested By: 11/10/2023

Coole	ω	2	1-	1	Transfers	Çī	4	ω	2		Item	Send State	Greer Phone Email:	1638 Suites	Skyle
Cooler Temperature on Receipt				neledach Dy		·				WELL	Sample ID	Send Invoice To: invoices@pacelabs.coupahost.com State of Sample Origin: W/	Greensburg, PA 15601 Phone (724)850-5600 Email: skyler.richmond@pacelabs.com	Pace Analytical Pittsburgh 1638 Roseytown Road Suites 2,3,4	Skyler C. Richmond
0 00 10				Date/Time						10/19/2023 08:00	Collect Date/Time	s.coupahost.com		Ç.	aeochemical
Custody Seal				ne Received By						30632478001	Lab ID				aeochemical
Y or N				ed By						Water	Matrix			P.O.	And in case the case of the ca
Rac	ANTI-STEEL STORESTONES CONTRACTOR	NAME OF TAXABLE PARTY O	1.						+		Umpre≃erve	Preserved Containe			Annual Proof of the Samuel Control of the Sa
Page in the last on the	t.		5 4 D A	Date/Time				† 	-	< S	Specific G	3	STM D1429-	08	
		an mailtan	onevilla.												Rec
The second secon					Comments						D	HECEN e of OH EC 01	Burk Chris		Requested Analysis
								22	اره	LAB USE ONLY			Section Control		





west virginia department of environmental protection

Office of Oil and Gas 601 57th Street, SE Charleston, WV 25304 Phone (304) 926-0450 Harold D. Ward, Cabinet Secretary dep.wv.gov

January 23, 2023

DD Oil Company Attn: Hugh Dale P.O. Box 406 Spencer, WV 25276

Re: Mechanical Integrity Test Approval and Authorization for Injection

UIC Permit 2D08701623 (Summers No.7)

Dear Mr. Dale:

The mechanical integrity tests performed August 19, 2022, on well API 47-087-011623 and the associated pump line August 19, 2022, have been approved. Authorization is granted for injection. The maximum permitted injection pressure for this well is set at 500 psi. If you have any questions, please to contact Andrew L. Lockwood via email at Andrew.L.Lockwood@wv.gov or by phone at (304) 926-0499 ext. 41104.

Respectfully,

Jason Harmon Deputy Chief

WVDEP Office of Oil & Gas

WV DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF OIL AND GAS PRE-OPERATION CERTIFICATE FOR LIQUID INJECTION MECHANICAL INTEGRITY TEST RECORD

			MI	T Date: Al	UGUST 1	9, 2022		
				erator's We			MERS #7	
			AP	I#: 47- 087	7	- 01623		
				C Permit #:				
			Fie	eld Name (2	R only):	SUMMERS	S #7	
WELL OPERATOR	DD OIL CO.						IUGH D DALE	
Address:	, 0 307, 100							
	SPENCER, WV 25276							
INJECTION FORM Perforation Interval	2115-2150	UN SAND	De	pth_2070 pen Hole Inte	feet (terval	op) to_212	4 feet (bot	tom)
INJECTION PERMI								
2D Commercial	Disposal 🗾 21) Non-Com	mercial Dis	sposal 📋	2R Area	Permit (E	OR) ∐3SS	Solution Mining
INJECTATE TYPE Produced Water □ Drilling Waste L Additives (ie. biocid WELL CONSTRUCT	Fresh Wate iquids Solu es, inhibitors, etc	r Contion Mining .) Scale Inf	; Waste [nibitors, Bio	Gas (2R)	01	her (Speci	•	
WELL CONSTRUC	TION / CASING I	ROGRAM		T	T	FOOTAGE		
CASING OR TUBING	SIZE	GRADE	WEIGHT	NEW	USED	USED IN	FOOTAGE LEFT	CEMENT USED
TYPE			PER FT.			DRILLING	IN WELL	
CONDUCTOR	11 3/4	H40	42	X		15 FT	NONE	NONE
FRESH WATER	8 5/8	J55	24	X		160 FT	160 FT	CTS
COAL								
INTERMEDIATE								
PRODUCTION	4 1/2	J55	9.5	X		2160 FT	2160 FT	CTS (455 saks)
TUBING	2 7/8	EUE	7.3	X		2068 FT	2068 FT	
LINERS								
PACKER	TYPE: TENSION R4 H	IALLIBURTON	SIZE: N80	2 7/8		DEPTH: 2	268	
MECHANICAL INT Standard Annulus Is Test Annulus Fille Pump Line Test MAXIMUM PERMIT MECHANICAL INT FILLED ANNULUS V WITNESSED TEST. PIPELINE WAS ALS	S Pressure Test d? Yes N Other (Sp FED WELLHEAD EGRITY TEST D WITH WATER. PI CHART WAS GI	lo If Yes, Secify) D INJECTION ESCRIPTION RESSURE TO HI	ON PRESSU ON FESTED TH M, THEN A	HE ANNULU	US TO 75	0 POUND	NE. PRESSUR	75 WE/
(2R Area Permits: If m	ultiple pump lines	are tested tog	ether, please	list wells se	rviced by	the tested p	ump lines.)	

WR-37	
12/23/1	9

API#: 47-_087 _-01623


NOTE:

- If the well and the pump line are tested together the MIT pressure must be 1.5 times the maximum permitted injection pressure held for a minimum of 20 minutes with no more than a 5% loss.
- If the well is tested separately, the MIT pressure must be 1.5 times the maximum permitted injection pressure held for a minimum of 20 minutes with no more than a 5% loss.
- If the pump line is tested separately, the MIT pressure shall be the maximum permitted injection pressure plus 100 psi held for a minimum of 20 minutes with no more than a 5% loss. Multiple pump lines can be tested together.
- All MITs must be witnessed by a state inspector. A valid recording chart containing the inspector's signature must accompany this completed form.
- All MITs that fail must be submitted using this form and chart.


WVDEP-Office of Oil and Gas

- Submit all MIT required documentation to OOG within 30 days of test.
- The mechanical integrity of this well must be demonstrated at least 5 years from this test date and each time work is completed on the well or pump line to continue injection.

The undersigned certify:	
The MIT was performed on AUGUST 19, 2022	
The well and/or pump line:	
demonstrated mechanical integrity or _ failed to demo	onstrate mechanical integrity.
The MIT was witnessed by JOE TAYLOR	, Inspector WVDEP - Office of Oil and Gas.
DD OIL COMPANY	12/15/2022
Permit Holder Company Name	Date
HUGH DALE	
Agent or Responsible Party (Print Name)	
(1//_	
Signature	
, ,	
OPERATOR	
Title	
Office of Oil a	and Gas Use Only:
THIS WELL IS AUTHORIZED FOR INJECTION UP TO A MAXIMUM WELLHEAD INJECTION PRESSUI	RE OF <u>SOO</u> psi
Special Conditions:	
NONE - TETATED	5 PASSED
	`
UIC Program Manager	Date



WEI MIT Sect K 1 Houre
Rotation Sammers of Footbacker 8-14-2022 Strote CM 2:00 bM MINUSSC.C Randy Holbant PONNIE HENNET



PITELINE MIT
8/22/22

Sumers of Consult of the Standard of the

Wixeson son

17.8

Monitoring

To Gene Smith W.V DEP

2-12-2016

D&D Well Summers 7

API Number 2D0871623

D&D Oil

Deficiency 2D0871623

Section 9

Operating Requirements Data

Section A

The fluid between in the 4 ½ casing annulus and tubing is filled with fresh water to conduct the mechanical integrity test.

Section B

D&D Oil is operating this well and fully intend to continue operating this well in compliance with rules, regulations and with the permit. Will continue to daily monitor the injection pressure, annulus pressure and record the volume. Data will be recorded on form wr-40 and continue to be submitted to the Office of Oil and Gas monthly.

RECEIVED
Office of Oil and Gas

FEB 1 2 2016

WV Department of Environmental Protection

Groundwater Protection Plan

APPENDIX H

GROUNDWATER PROTECTION PLAN

Facility N	Jame:_D	D OIL WALTON FIEL	D DISPOSAI		California (California de California de Cali
County:_	ROANE				
Facility L					
Postal Ser	rvice Ad	ldress: PO BOX 406	J. 11550411		
	-1=_0500+47e-11000	SPENCER WV	25276		
Latitude:	81* 2	22' 30"	Longitude:	38* 38' 00"	
Contact I	nformati	ion:	2		
Person:		I D DALE			
Phone Nu		304-550-0978			
E-mail A	ddress:	hugh@drilcooilgas	s.com		
PUMP	of all op S, PIPE	Derations that may conta			RECEIVED Office of Oil and Gas DEC 2 8 2020 WV Department of Environmental Protection
2. A dese	cription potentia	of procedures and facil	ities used to jbove.	protect groundw	rater quality from the
NO EC	UIPME GE AR	TANKS ARE NEW PUENT IS OLDER THAN RE INSIDE DIKES ANI NILY.	10 YEARS.	ALL SOURCE	S OF DIKE AND
3. List p	rocedure	es to be used when desig	gning and add	ing new equipm	ent or operations.

dep

ALL SYSTEMS ARE NEWER. NOTHING PLANNED BUT ALL FLUID IN TANKS/LINES/PUMPS MAY REQUIRE FLUID REMOVAL BY VACUUM

TRUCK.

4. Summarize all activities at your facility that are already regulated for groundwater protection.

ALL ACTIVITIES ARE RAN WITH FULL COMPLIANCE WITH ALL RULE GUIDELINES OF PERMIT OF UIC WELL GUIDELINES

5. Discuss any existing groundwater quality data for your facility or an adjacent property.

ALL WATER SOURCES HAVE BEEN TAKEN FOR ALL CREEKS, RIVERS. ALL GROUND WATER SOURCES ON ADJACENT PROPERTY.

6. Provide a statement that no waste material will be used for deicing or fill material on the property unless allowed by another rule.

THE SUMMERS 7 WELL, DD OIL COMPANY, API 047-087-01623 IS USED ONLY FOR BRINE DISPOSAL OF BRINE PRODUCED FOR DD OIL WELLS IN WALTON FIELD.

 Describe the groundwater protection instruction and training to be provided to the employees. Job procedures shall provide direction on how to prevent groundwater contamination.

ALL EMPLOYEES HAVE RECEIVED TRAINING BY QUALIFIED ENVIRONMENTAL ENGINEERING FIRM.

ALL WERE TRAINED TO FOLLOW RULES/PERMIT CONDITIONS OF UIC PERMIT AND TANK STORAGE, AS WELL AS SPILL TRAINING.

Office of Oil and Gas

DEC 2 8 2020

WV Department of Environmental Protection



8. Include provisions for inspections of all GPP elements and equipment. Inspections must be made quarterly at a minimum.

ALL TANKS/PUMPS/PIPELINE AND DISPOSAL WELL ARE CHECKED DAILY.

Signature:

Date: 12/18/2020

RECEIVED Office of Oil and Gas

DEC 28 2020

WV Department of Environmental Protection



Plugging and Abandonment

To Gene Smith W.V DEP

2-12-2016

API Number 2D0871623

D&D Oil Summons 7

6- Deficiency No. 6

Attached is plugged Schematic plug and adbandment.


Procedure, fist move in service rig and all necessary equipment to preform work. First, rig up on well, and pull all injection string tubing. 2 7/8 in well, set on tension release packer and pull tubing to surface. Remove packer from tubing then run tubing back in well within 100 foot of total depth. Displace bottom plug, on perforations 100 feet at last perforation at 2077 plus A 100 plug above 2077 wait 24 hours for plug to set then pull tubing up and displace Bentonite Gel to elevation to 936 Feet. Then spot a 100 Foot cement plug. Then, pull tubing used to displace Cement Gel, wait 4 hours then set a 100 foot plug to surface set monument attach API number to monument and reclaim land and location to state spec's. Turn in to DEP plugging permit, sign Affidarit to release well from operations bond.

Received

FEB 12 2016

Office of Off and Gas Protection

Office of Office of



Office of Oil and Gas
Office of Oil and Gas
WW Dept. of Environmental Protection

Additional Bonding

This facility has all required bonds including individual well bond and UIC Bond

Financial Responsibility

APPENDIX I

Requirement for Financial Responsibility to Plug/Abandon an Injection Well

То:	WV Department of Environmental Protection Office of Oil and Gas 601 57 th Street, SE Charleston, West Virginia 25304-2345 ATTN: Underground Injection Control Program	
From:	DD OIL CO	
	PO BOX 385	CONTRACTOR AND
	GRANTSVILLE, WV 26147	
Date:	12/18/2020	
Subject:	Underground Injection Control (UIC) Permit Applicati # UIC 2D0871623	on
	Requirement for Financial Responsibility	
	n financial responsibility and resources to close, plug, a injection wells(s) in a manner prescribed by the Chief of	and abandon
Name:	HUGH D DALE	RECEIVED Office of Oil and Gas
Signature:	<i>7</i> 0	DEC 2 8 2020
Date:	12/18/2020	Environmental Protection



Section 15
Site Security Plan

APPENDIX J

Site Security for Commercial Facilities

Provide a detailed description of the method(s) utilized at the facility to restrict or prohibit illegal dumping of unauthorized waste or vandalism at the facility.

- 1. Complete enclosure of all wells, holding tank/pits and manifold assemblies within a chain link or other suitable fencing; and
- 2. Require that all gates and other entry points be locked when the facility is unattended; or
- 3. Providing tamper-proof seals for the master valve on each well (a "lock-out" or chain & padlock system would be more secure; however, these devices could create a potential safety hazard if the well needed to be quickly shut in due to an emergency); and
- 4. Installing locking caps on all valves and connections on holding tanks, unloading racks, and headers.

SUMMERS 7 WELL IS IN COMPLIANCE WITH ALL OF THE ABOVE CRITERIA 1-4.

Office of Oil and Gas
DEC 2 8 2020

WV Department of Environmental Protection



Additional Information

APPENDIX K

Identify permit or construction approvals received or applied for under the following programs:

Permit/approvals	ID Number	
Hazardous Waste Management Program under RCRA	NONE	
NPDES Program	NONE	
Prevention of Significant Deterioration (PSD)	NONE	
Nonattainment Program	NONE	
Dredge or Fill	NONE	
NPDES/NPDES – Stormwater	NONE	
WVDEP – Office of Waste Management (OWM) – Solid Waste Facility	NONE	
WVDEP – OWM – RCRA (Hazardous Waste TSD or Transporter)	NONE	
WVDEP - OWM - UST	NONE	
CERCLA - Superfund	NONE	
WV Voluntary Remediation – Brownfields	NONE	
FIFRA – Federal Insecticide, Fungicide and Rodenticide Act	NONE	
Well Head Protection Program (WHPP)	NONE	
Underground Injection Control (UIC)	#UIC 2D0871623	
Toxic Substances Control Act (TSCA)	NONE	
Best Management Plans	NONE	RECEIVED Office of Oil and Gas
Management of Used Oil	NONE	DEC 28 2020
Other Relevant Permits (Specify):		WV Department of Environmental Protection
N/A		Ivironmental Protection

